



NETWORK CONTROLS

Statewide Term Contract for Audio/Visual # 4400026093
Network Controls
1521 South Buncombe Rd.
Greer, SC 29651



U.S. Reference guide and pricebook

Prices effective January 15, 2022



Powering Business Worldwide

Switch  N to Eaton.

REFERENCE GUIDE AND PRICEBOOK

Table of Contents

Introduction

Input Plug and Output Receptacle Chart	4
--	---

Ordering Information, Parts, Accessories and Current List Pricing

Eaton Power Distribution, Monitoring and Enclosures

ePDU Basic	5
ePDU Metered Input (Monitored)	7
ePDU Metered Outlet	8
ePDU Managed	9
Eaton Automatic Transfer Switches	11
Eaton HotSwap Maintenance Bypass (MBP)	12
REPO Rack PDU	13
ePDU Cables	15
Eclipse Surge Suppressors	16
Eaton MiniRaQ	17
Eaton S-Series Enclosures	19
Eaton B-Line 2 & 4 Post Racks and Accessories	24
Eaton TanLock	26
Branch Circuit Breakers	27

Single-phase (Standby)

Eaton 3S UPS (350–750 VA)	30
---------------------------	----

Single-phase (Line-interactive)

Eaton 5S UPS (550–1500 VA)	31
Eaton 5SC UPS (550–1500 VA)	32
Eaton 5P UPS Rackmount (550–3000 VA)	33
Eaton 5P UPS Tower (750–3000 VA)	35
Eaton 5PX UPS Rack/Tower (1000–3000 VA)	36
Eaton 5PX G2 UPS Rack/Tower (1000–3000 VA)	39

Single-phase (Online)

Eaton 9SX Tower (700-3000VA)	41
Eaton 9PX UPS Rack/Tower (700VA-3KVA)	43
Eaton 9PX UPS Li-Ion (1-3kVA)	47
Eaton 9PX UPS Rack/Tower (5–6 kVA)	50
Eaton 9PX UPS Rack/Tower (8–11 kVA)	52
Eaton 9PX SP UPS Rack/Tower (6-10 kVA)	54
Eaton Single Phase Battery Packs	56
Eaton 9155 UPS (8–15 kVA)	57
Eaton 9PXM UPS Rack/Tower (4–20 kVA)	60

Series FERRUPS

Eaton Ferrups FX UPS	64
----------------------	----

Three-phase (Double-conversion)

REFERENCE GUIDE AND PRICEBOOK

Table of Contents

Eaton BladeUPS (12–60 kW)	66
Eaton 9355 UPS (10–30 kVA)	75
Eaton Emergency Lighting UPS (8-30KVA)	79
Eaton 93E UPS (20–60 kVA)	81
Eaton 93PM UPS (20–50 kW)	85
Power Xpert 9395 UPS	92
Power Xpert 9395P High Performance UPS	94
Power Xpert 9395C UPS	97

REFERENCE GUIDE AND PRICEBOOK

Table of Contents

Additional Products

WaveStar Static Transfer Switch (STS)	98
WaveStar TFA Static Transfer Switch (STS)	99
Ultra-isolator Noise Suppressors	100
Power Conditioners	101
Software Products	107
Connectivity Products	115
Connectivity Chart	115
Surge Protection Products – PSPD Series	116
Single-phase Service Plans Overview	121
Single-phase Service Plans	121

RMA Policy and Product Warranties

Sales Returned Merchandise Authorization (RMA) Policy	125
Product Warranty Statements	126

Notes: Due to continuing product improvement programs, all specifications and prices are subject to change without
With the exception of batteries, any UPS parts or parts kit pricing that is included in this reference guide is based on a concurrent purchase of a new unit(s). Pricing for parts or parts kits purchases made separately from a concurrent unit purchase must be obtained from the Eaton Customer Support Center at 800.356.5737.

RECEPTACLE CHART

Input Plug and Output Receptacle Chart

5-15R	5-15P	5-20R	5-20P
			
L5-20R	L5-20P	L5-30R	L5-30P
			
6-15R	6-15P	L6-20R	L6-20P
			
L6-30R	L6-30P	L14-30R	L14-30P
			
IEC-320-C13 (female)	IEC-320-C14 (male)	IEC-320-C19 (female)	IEC-320-C20 (male)
			
IEC-309, 16A	IEC-309, 32A		
			

R indicates receptacle
P indicates plug
L indicates locking plug or receptacle

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Basic ePDUs

Basic ePDUs are designed for reliable and cost-effective power distribution.

- Available in horizontal and vertical design
- Clearly labeled circuits simplify load balancing
- Cost effective solutions to meet Basic needs



New G3 models feature IEC grip outlets and color-coded outlet sections as well as high-operating temperatures of 60°C (140°F).

Basic PDUs

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Mount Models							
EFLXL1500R-PDU1U	1.44	BA	3	5-15P	(12) 5-15R	1.7 x 17.3 x 2.4	\$134
ePBZ83	1.44	BA	15	5-15P	(12) 5-15R	1.7 x 17.3 x 2.3	\$117
EFLXL2000R-PDU1U	1.92	BA	3	5-20P	(12) 5-20R	1.7 x 17.3 x 2.4	\$146
ePBZ85	1.92	BA	10	5-20P	(12) 5-20R	1.7 x 17.3 x 2.3	\$174
EFLXL2000R-PDU1UL	1.92	BA	3	5-20P	(5) L5-20R	1.7 x 17.3 x 2.4	\$181
ePBZ82	1.92	BA	15	L5-20P/5-20P*	(12) 5-20R	1.7 x 17.3 x 2.3	\$174
ePBZ84	2.88	BA	10	L5-30P	(10) 5-20R	1.7 x 17.0 x 3.5	\$292
ePBZ78	2.88	BA	15	L5-30P	(20) 5-20R	1.7 x 17.0 x 3.5	\$333
ePBZ95	3.33	BA	6	L6-20P	(12) C13, (1) C19	1.7 x 19.0 x 2.4	\$174
ePBZ94	4.99	BA	6	L6-30P	(6) C19	1.7 x 19.0 x 2.4	\$295
ePBZ91	4.99	BA	10	L6-30P	(10) C13	1.7 x 17.0 x 3.5	\$275
ePBZ79	4.99	BA	15	L6-30P	(16) C13, (4) C19	1.7 x 17.0 x 5.1	\$360
EBA332-10	8.64	BA	10	L15-30P	(6) C19	1.7 x 19.0 x 5	\$852
EBAU14-10	8.64	BA	10	L21-30P	(12) C13, (3) C19, (6) 5-20R	3.44 x 19.0 x 8.0	\$883
EBAU28-10	14.44	BA	10	CS8365	(18) C13	3.44 x 19.0 x 8.0	\$1,082
EBAU26-10	17.64	BA	10	IEC60309 532P6W	(18) C13	3.44 x 19.0 x 8.0	\$1,082

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Mount Models - Test and Instrumentation							
T8-A-CB	1.44	BA	9	5-15P	(8) 5-15R	1.72 x 19 x 4.5	\$501
T982A1-F-SS-009	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 7	\$439
T982A1-N-SS-009	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 7	\$454
TPC12-A	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 4.5	\$390
TPC12-A-CB	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 4.5	\$440
TPC12-A-RCB	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 4.5	\$410
TPC12F-A-CB	1.44	BA	9	5-15P	(12) 5-15R	1.72 x 19 x 4.5	\$454
T982A1-3473	1.44	BA	6	L5-15P	(10) 5-15R	1.72 x 19 x 7	\$427
TPC2234-A	1.44	BA	9	(2)5-15P	(8) 5-15R	1.72 x 19 x 4.5	\$678
TPC2234-A-F	1.44	BA	9	(2)5-15P	(8) 5-15R	1.72 x 19 x 4.5	\$740
T982A2-N-SS-009	1.92	BA	9	5-20P	(12) 5-20R	1.72 x 19 x 7	\$438
TPC12-A2	1.92	BA	9	5-20P	(12) 5-20R	1.72 x 19 x 4.5	\$465
TPC12F-A2	1.92	BA	9	L5-20P	(12) 5-20R	1.72 x 19 x 4.5	\$498
T982A2-N-SL-009	1.92	BA	9	L5-20P	(12) 5-20R	1.72 x 19 x 7	\$462
TPC2234-A2	1.92	BA	9	(2)5-20P	(8) 5-20R	1.72 x 19 x 4.5	\$762
TPC2234-A2-F	1.92	BA	9	(2)5-20P	(8) 5-20R	1.72 x 19 x 4.5	\$791
T982C1-F-SL-015	2.88	BA	15	L5-30P	(12) 5-15R	1.72 x 19 x 7	\$572
T982C2-F-SL-015	2.88	BA	15	L5-30P	(12) 5-20R	1.72 x 19 x 7	\$592
T982C2-N-SL-009	2.88	BA	9	L5-30P	(12) 5-20R	1.72 x 19 x 7	\$485
TPC12-C	2.88	BA	15	L5-30P	(12) 5-15R	1.72 x 19 x 4.5	\$642
TPC2105-1-106	2.88	BA	9	L5-30P	(16) C13	1.72 x 19 x 7	\$606
TPC2806	2.88	BA	25	L5-30P	(2) 5-15R, (6) 5-20R	1.72 x 19 x 8	\$2,970
TPC2806-3747R	2.88	BA	12	L5-30P	(2) 5-15R, (6) 5-20R	1.72 x 19 x 8	\$2,327
T8S-3189	3.33	BA	N/A	C20	(8) 5-15R	1.72 x 19 x 7	\$678
T8S-A	3.33	BA	N/A	C20	(8) 5-15R	1.72 x 19 x 7	\$566
T8S-A-CB	3.33	BA	N/A	C20	(8) 5-15R	1.72 x 19 x 7	\$596
T8S-A-CB-SF	3.33	BA	N/A	C20	(8) 5-15R	1.72 x 19 x 7	\$678
T9092B-CB	3.33	BA	N/A	C20	(10) C13	1.72 x 19 x 5	\$580
T9092B-CBSF	3.33	BA	N/A	C20	(10) C13	1.72 x 19 x 5	\$699
PW103BA1U405	3.33	BA	N/A	C20	(16) C13	1.72 x 19 x 7	\$412
LPC208-2P-5606	3.33	BA	6	L6-20P	(3) L6-15R	3 x 10 x 7.75	\$829
TPC2105-1	3.33	BA	N/A	Hardwired	(16) C13	1.72 x 19 x 7	\$531
TPC2105-2	3.33	BA	N/A	Hardwired	(8) C13, (2) C19	1.72 x 19 x 7	\$532
TPC2105-1-107	4.99	BA	9	L6-30P	(16) C13	1.72 x 19 x 7	\$605
TPC2105-1-119	4.99	BA	15	L6-30P	(16) C13	1.72 x 19 x 7	\$609
TPC2105-2-107	4.99	BA	9	L6-30P	(8) C13, (2) C19	1.72 x 19 x 7	\$606
PW105BA2U420	4.99	BA	6	L6-30P	(4) L6-20R	3.44 x 19.0 x 6	\$762

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
PC2715	4.99	BA	20	(2) L6-30P	(2) L6-30R	3.44 x 19 x 8	\$1,864
TPC2105-2-108	5.76	BA	9	IEC60309 332P6W	(8) C13, (2) C19	1.72 x 19 x 7	\$684
TPC4100-A2	8.64	BA	9	L21-20P	(12) 5-20R	1.72 x 19 x 9.5	\$1,217
PC2646-D	8.64	BA	15	L21-30P	(18) 5-15R	3.36 x 19 x 13	\$1,563
TPC4100-C	8.64	BA	9	L21-30P	(12) 5-15R	1.72 x 19 x 9.5	\$1,217
TPC4100-D	8.64	BA	9	L21-30P	(12) 5-20R	1.72 x 19 x 9.5	\$1,294
EBAU14-10	8.64	BA	10	L21-30P	(6) 5-20R, (12) C13, (3) C19	1.72 x 19 x 9.5	\$883
EBAU28-10	14.44	BA	10	CS8365	(18) C13	3.44 x 19 x 8	\$1,082
EBAU26-10	17.64	BA	10	IEC60309 532P6W	(18) C13	3.44 x 19 x 8	\$1,082
T17C19260-3-009	17.64	BA	9	IEC60309 460P9W	(6) C19	1.72 x 19 x 7	\$1,147

Vertical Mount Models

ePBZ75	1.44	BA	15	5-15P	(14) 5-15R	24.0 x 1.5 x 1.5	\$147
ePBZ97	1.92	BA	6	5-20P	(24) 5-20R	60.0 x 1.5 x 1.5	\$244
ePBZ71	1.92	BA	15	5-20P/L5-20P*	(30) 5-20R	72.0 x 1.5 x 1.5	\$341
ePBZ90	2.88	BA	15	L5-30P	(24) 5-20R	40.0 x 1.9 x 2.1	\$354
ePBZ93	3.33	BA	6	L6-20P	(20) C13, (4) C19	42.0 x 2.2 x 1.9	\$305
ePBZ80	4.99	BA	10	L6-30P	(30) C13, (6) C19	52.9 x 1.9 x 2.1	\$375
EBA110-10	4.99	BA	10	L6-30P	(24) C13, (6) C19	63.2 x 2.05 x 2.1	\$992
EBA125-10	4.99	BA	10	L6-30P	(20) C13, (2) C19	35.5 x 2.05 x 2.1	\$934
EBA200-10	5.76	BA	10	L14-30P	(20) C13, (6) C19, (8) 5-20R	66.5 x 2.05 x 2.1	\$1,261
EBA201-10	5.76	BA	10	L14-30P	(24) 5-20R	63.1 x 2.05 x 2.1	\$957
EBA310-10	8.64	BA	10	L21-30P	(30) C13, (6) C19, (1) 5-20R	66.5 x 2.05 x 2.1	\$746
EBA306-10	14.4	BA	10	CS8365	(21) C13, (12) C19	66.5 x 2.05 x 2.1	\$1,460
EBA307-06	17.3	BA	6	IEC60309 460P9	(21) C13, (12) C19	66.5 x 2.05 x 2.1	\$1,469
EBA307-HW	17.3	BA	N/A	Hardwired	(21) C13, (12) C19	66.5 x 2.05 x 2.1	\$1,543

* These units ship with an adapter allowing for 5-20P input plug.

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Metered Input ePDUs

Metered Input models provide input phase and branch circuit monitoring. These ePDUs feature an LED or pixel LCD display that shows current draw for branch circuit loading and phase balancing. All models offer remote monitoring over a network connection.

- Clearly labeled circuits simplify load balancing
- Local current meter display
- Remote monitoring with network connection



Metered Input ePDUs

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Mount Models							
EMIT00-10	1.44	MI	10	5-15P	(12) 5-15R	1.7 x 19 x 8	\$979
EMIT01-10	1.92	MI	10	5-20P	(12) 5-20R	1.7 x 19 x 8	\$979
EMIT02-10	1.92	MI	10	L5-20P	(12) 5-20R	1.7 x 19 x 8	\$979
EMIT03-10	2.88	MI	10	L5-30P	(12) 5-20R	1.7 x 19 x 8	\$1,030
EMIT04-10	5.76	MI	10	L6-30P	(8) C13, (4) C19	1.7 x 19 x 8	\$1,030
EMIT05-10	5.76	MI	10	L6-30P	(16) C13	1.7 x 19 x 8	\$1,082
EMIT06-10	5.76	MI	10	L6-30P	(10) C13, (4) C19	1.7 x 19 x 8	\$922
EMIT07-10	5.76	MI	10	L6-30P	(18) C13	1.7 x 19 x 8	\$934
EMIT08-10	1.44	MI	10	5-15P	(8) 5-15R	1.7 x 19 x 8	\$479
EMIT09-10	1.92	MI	10	L5-20P (5-20P adapter)	(8) 5-20R	1.7 x 19 x 8	\$549
EMIT10-10	3.84	MI	10	C20 (L6-20 adapter)	(8) C13	1.7 x 19 x 8	\$549
EMIU05-10	2.88	MI	10	L5-30P	(16) 5-20R	3.4 x 19 x 8	\$865
EMIU06-10	5.76	MI	10	L6-30P	(12) C13, (4) C19	3.4 x 19 x 8	\$865
EMIU00-10	8.64	MI	10	L21-30p	(12) C13, (6) C19	3.4 x 19 x 8	\$1,459
Vertical Models (ePDU G3)							
EMI100-10	1.44	MI	10	5-15P	(24) 5-15R	66.5 x 2.05 x 2.1	\$656
EMI101-10	1.92	MI	10	5-20P/L5-20P*	(24) 5-20R	66.5 x 2.05 x 2.1	\$701
EMI128-10	1.92	MI	10	L5-20P	(20) 5-20R	2.05 x 2.1 x 52.5	\$1,464
EMI102-10	2.88	MI	10	L5-30P	(30) 5-20R	66.5 x 2.05 x 2.1	\$778
EMI103-10	3.84	MI	10	C20 (L6-20 adapter)	(18) C13, (2) C19	35.5 x 2.05 x 2.1	\$718
EMI104-10	4.99	MI	10	L6-30P	(36) C13, (6) C19	66.5 x 2.05 x 2.1	\$777
EMI109-10	4.99	MI	10	L6-30P	(12) C13, (2) C19	35.5 x 2.05 x 2.1	\$1,305
EMI200-10	5.76	MI	10	L14-30P	(20) C13, (6) C19, (8) 5-20R	66.5 x 2.05 x 2.1	\$1,574
EMI201-10	5.76	MI	10	L14-30P	(24) 5-20R	63.1 x 2.05 x 2.1	\$1,641
EMI318-10	5.76	MI	10	L21-20P	(30) C13, (6) C19, (3) 5-20R	66.5 x 2.05 x 2.1	\$1,043
EMI331-10	8.64	MI	10	L21-30P	(24) C13, (3) C19, (6) 5-20R	66.5 x 2.05 x 2.1	\$1,900
EMI303-10	8.64	MI	10	L15-30P	(30) C13, (6) C19	66.5 x 2.05 x 2.1	\$1,502
EMI310-10	8.64	MI	10	L21-30P	(30) C13, (6) C19, (1) 5-20R	66.5 x 2.05 x 2.1	\$1,209
EMI344-10	8.64	MI	10	L21-30P	(24) 5-20R	66.5 x 2.05 x 2.1	\$1,804
EMI105-06	11.5	MI	6	IEC60309 360P9W	(30) C13, (6) C19	66.5 x 2.05 x 2.1	\$2,146
EMI105-10	11.5	MI	10	IEC60309 360P9W	(30) C13, (6) C19	66.5 x 2.05 x 2.1	\$2,146
EMI143-10	11.5	MI	10	IEC60309 360P9W	(24) C13, (9) C19	66.5 x 2.05 x 2.1	\$2,015

* These models will ship with an adapter allowing for 5-20P input plug

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
EMI305-06	12.48	MI	6	CS8365	(30) C13, (6) C19	66.5 x 2.05 x 2.1	\$1,575
EMI316-10	14.4	MI	10	CS8365	(9) C13, (12) C19	66.5 x 2.05 x 2.1	\$1,874
EMI347-03	14.4	MI	3	CS8365	(48) C13, (12) C19	63.2 x 4.10 x 2.1	\$2,730
EMI413-10	17.3	MI	10	L22-30P	(30) SDG400 - Anderson	69.5 x 2.05 x 2.1	\$2,593
EMI319-10	17.3	MI	10	IEC60309 532P6W	(24) C13, (6) C19	66.5 x 2.05 x 2.1	\$2,106
EMI323-06	17.3	MI	6	IEC60309 460P9W	(38) C13	69.5 x 2.05 x 2.1	\$2,318
EMI338-06	17.3	MI	6	IEC60309 460P9W	(48) C13, (12) C19	63.2 x 4.10 x 2.1	\$2,673
EMI359-06	17.3	MI	6	IEC 60309 460P9	(48)C13, (12) C19	63.1 x 4.09 x 2.1	\$2,255
EMI356-10	17.3	MI	10	309-532P6W	(48)C13, (12) C19	63.2 x 4.10 x 2.1	\$2,135
EMI382-HW	22.2	MI	N/A	Hardwired	(6) L6-30R	63.2 x 4.10 x 2.1	\$2,575

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Metered Outlet ePDUs

Eaton ePDU G3 Metered Outlet models monitor and measure critical factors such as voltage, current and power consumption without the capability to switch outlets. ePDU G3 Metered Outlet models provide the necessary measurements to calculate Level 3 PUE and feature an advanced local display.

- Measurement of outlet-level power consumption
- Ability to deliver Level 3 PUE to increase accuracy and precision of energy analysis
- Remote monitoring of entire environment over the network from a single interface
- Single- and three-phase configurations provide solutions for multiple environment types
- ±1% billing grade accuracy
- Advanced LCD pixel display, hot-swap meter, IEC grip outlets and color-coded circuits
- The ability to daisy chain eight ePDUs to share the same network connection and IP address



Metered Outlet ePDUs

Catalog Number	Max. kW	Function	Cord Length	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Vertical Mount Models							
EMO330-10	17.3	MO	10	IEC60309 460P9W	(12) C13, (12) C19	66.5 x 2.05 x 2.09	\$2,174

Environmental Probes

Catalog Number	Description	List Price
EMP001	Environmental Monitoring Probes for Rack PDU G3	\$258
EM PDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with Rack PDU G3 FW Version 4.0+)	\$291

Environmental Rack Monitors

Description	Part Number	Dimensions (H x W x D, inches)	Shipping Weight (lb)	List Price
Environmental Rack Monitor Water Leak Detector, 3ft	103005780	0.6 x 7.9 x 8.2	0.3	\$163
Environmental Rack Monitor Water Leak Detector, 12ft	103005894	0.6 x 11.2 x 11.4	0.5	\$282
Environmental Rack Monitor Door Contact Sensor	103005781	2.0 x 2.0 x 2.0	0.1	\$33
Environmental Rack Monitor Vibration Sensor	103005782	2.0 x 3.0 x 2.0	0.1	\$44
Environmental Rack Monitor Smoke Detector/Alarm (220V, IEC C13)	103005779	2.4 x 6.3 x 8.8	2.2	\$163
Environmental Rack Monitor Smoke Detector/Alarm (110V, 5-15)	103005890	2.4 x 6.3 x 8.8	2.2	\$163

Accessories

Catalog Number	Description	List Price
010-0029	2-foot C13 to C14 jumper cord	\$12
010-0028	4-foot C13 to C14 jumper cord	\$16
010-0027	6-foot C13 to C14 jumper cord	\$18
010-0025	8-foot C13 to C14 jumper cord	\$20
035-0113	C19 Outlet Cap	\$6
035-0119	C13 Outlet Cap	\$7

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Managed ePDUs

ePDU G3 Managed models include outlet switching and metered outlets. Switching allows you to power cycle (reboot) locked servers or turn off unused outlets. Outlet level monitoring of voltage, current, power and energy (KWH) provides necessary measurements to calculate Level 3 PUE and to run capacity /usage analytics.

- Monitor power consumption in kilowatt hours at the individual outlet level requirement
- Readings available via Ethernet connection over a network (utilizing Eaton's Intelligent Power Manager)
- Power consumption readings allow for Power Usage Effectiveness calculations



Managed ePDUs

Catalog Number	Max.kW	Function	Cord Length	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Mount Models							
EMAT08-10	1.44	MA	10	5-15P	(8) 5-15R	1.7 x 19 x 8	\$704
EMAT09-10	1.92	MA	10	L5-20P (5-20P adapter)	(8) 5-20R	1.7 x 19 x 8	\$821
EMAT10-10	3.84	MA	10	C20 (L6-20 adapter)	(8) C13	1.7 x 19 x 8	\$821
EMAU05-10	2.88	MA	10	L5-30P	(16) 5-20R	3.4 x 19 x 5	\$1,083
EMAU06-10	4.99	MA	10	L6-30P	(10) C13, (4) C19	1.7 x 19 x 11.8	\$1,517
EMAU06-10	4.99	MA	10	L6-30P	(12) C13, (4) C19	3.4 x 19 x 5	\$1,309
EMAU07-10	4.99	MA	10	L6-30P	(16) C13	3.4 x 19 x 5	\$1,083
EMAU13-10	4.99	MA	10	L6-30P	(21) C13, (3) C19	3.44 x 19 x 11.8	\$2,443
EMAU25-10	5.76	MA	10	IEC60309 332P6W	(21) C13, (3) C19	3.44 x 19 x 11.8	\$2,443
Vertical Mount Models							
EMA111-10	1.44	MA	10	5-15P	(8) 5-15R	35.5 x 2.05 x 2.56	\$857
EMA112-10	1.44	MA	10	5-15P	(16) 5-15R	66.5 x 2.05 x 2.56	\$1,055
EMA113-10	1.92	MA	10	5-20P/L5-20P*	(8) 5-20R	35.5 x 2.05 x 2.56	\$920
EMA114-10	1.92	MA	10	5-20P/L5-20P*	(24) 5-20R	66.5 x 2.05 x 2.09	\$1,137
EMA141-10	1.92	MA	10	L5-20P	(24) 5-20R	66.5 x 2.05 x 2.56	\$2,419
EMA108-10	2.88	MA	10	L5-30P	(24) 5-20R	66.5 x 2.05 x 2.56	\$1,421
EMA115-10	3.84	MA	10	C20 (L6-20 adapter)	(21) C13, (3) C19	63.1 x 2.05 x 2.09	\$1,194
EMA107-10	4.99	MA	10	L6-30P	(20) C13, (4) C19	66.5 x 2.05 x 2.10	\$1,690
EMA135-10	4.99	MA	10	L6-30P	(24) C13	69.5 x 2.05 x 2.10	\$2,496
EMA140-10	4.99	MA	10	L6-30P	(24) C13	66.5 x 2.05 x 2.10	\$2,622
EMA142-10	4.99	MA	10	L6-30P	(18) C13, (6) C19	66.5 x 2.05 x 2.56	\$2,637
EMA325-10	5.76	MA	10	L21-20P	(18) C13, (6) C19	66.5 x 2.05 x 2.56	\$1,739
EMA367-06	5.76	MA	6	L21-20P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$1,961
EMA367-10	5.76	MA	10	L21-20P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$1,961
EMA367-15	5.76	MA	15	L21-20P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$1,532
EMA326-10	8.64	MA	10	L15-30P	(18) C13, (6) C19	66.5 x 2.05 x 2.56	\$2,008
EMA327-10	8.64	MA	10	L21-30P	(18) C13, (6) C19	66.5 x 2.05 x 2.56	\$2,078
EMA333-10	8.64	MA	10	L21-30P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$1,750
EMA362-06	8.64	MA	6	L21-30P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$2,711
EMA362-15	8.64	MA	15	L21-30P	(21) C13, (6) C19, 20R	(1) 5- 72.0 x 2.05 x 2.56	\$2,711
EMA375-10	8.64	MA	10	L21-30P	(48) C13	72.0 x 4.10 x 2.10	\$3,973
EMA376-10	8.64	MA	10	L21-30P	(24) C13	66.5 x 2.05 x 2.09	\$2,654
EMA385-10	8.64	MA	10	L21-30P	(21) C13, (3) 5-20R	66.5 x 2.05 x 2.09	\$2,913
EMACPH36JA4A4K2	12.48	MA	6	CS8365	(12) C13, (12) C19	68.1 x 2.05 x 2.09	\$3,346
EMACPH36JA5A5K2	12.48	MA	6	CS8365	(12) C13, (12) C39	68.1 x 2.05 x 2.09	\$3,346
EMACFL36JA4A4K2	17.3	MA	6	IEC 60309 460P9	(12) C13, (12) C19	68.1 x 2.05 x 2.09	\$3,448
EMACFL36JA5A5K2	17.3	MA	6	IEC 60309 460P9	(12) C13, (12) C39	68.1 x 2.05 x 2.09	\$3,448
EMA374-10	17.3	MA	10	IEC60309 532P6W	(48) C13	72.0 x 4.10 x 2.10	\$3,973

Environmental Probes

Catalog Number	Description	
EMP001	Environmental Monitoring Probes for G3	\$258
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with Rack PDU G3 FW Version 4.0+)	\$291

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Managed ePDUs

Environmental Rack Monitors

Description	Part Number	Dimensions (H x W x D, inches)	Shipping Weight (lb)	List Price
Environmental Rack Monitor Water Leak Detector, 3ft	103005780	0.6 x 7.9 x 8.2	0.3	\$163
Environmental Rack Monitor Water Leak Detector, 12ft	103005894	0.6 x 11.2 x 11.4	0.5	\$282
Environmental Rack Monitor Door Contact Sensor	103005781	2.0 x 2.0 x 2.0	0.1	\$33
Environmental Rack Monitor Vibration Sensor	103005782	2.0 x 3.0 x 2.0	0.1	\$44
Environmental Rack Monitor Smoke Detector/Alarm (220V, IEC C-13)	103005779	2.4 x 6.3 x 8.8	2.2	\$163
Environmental Rack Monitor Smoke Detector/Alarm (110V, 5-15)	103005890	2.4 x 6.3 x 8.8	2.2	\$163

Accessories

Catalog Number	Description	List Price
010-0029	2-foot C13 to C14 jumper cord	\$12
010-0028	4-foot C13 to C14 jumper cord	\$16
010-0027	6-foot C13 to C14 jumper cord	\$18
010-0025	8-foot C13 to C14 jumper cord	\$20
035-0113	C19 Outlet Cap	\$6
035-0119	C13 Outlet Cap	\$7

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Eaton Automatic Transfer Switches

eATS (Automatic Transfer Switch)—Designed for switching non-phase synchronized AC power sources, the automatic transfer switch ePDUs' intelligent circuitry monitors both inputs, providing a fast switch transfer from primary to secondary source power critical equipment without interruption. These ePDUs assure the highest level of redundancy to mission-critical applications.

- 1U configurations available
- Custom designs upon request



Eaton Automatic Transfer Switches

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Monitored ATS							
EATS115	1.44	AT	10	(2) 5-15P	(10) 5-15R	1.7 x 17.24 x 9.84	\$1,039
EATS120	1.92	AT	10	(2) 5-20P	(10) 5-20R	1.7 x 17.24 x 9.84	\$1,192
EATS220	3.33	AT	10	C20 (L6-20 adapter)	(8) C13, (1) C19	1.7 x 17.24 x 9.84	\$1,067
EATS30H	5.76	AT	-	Terminal Block	Terminal Block	1.7 x 17.3 x 13.8	\$1,242
EATS30P	5.76	AT	10	(2) L6-30P	(1) L6-30R	1.7 x 17.3 x 13.8	\$1,503
Horizontal Basic ATS - Test and Instrumentation							
T2235-A1-CFB09S	1.44	AT	9	(2) 5-15P	(8) 5-15R	1.72 x 19 x 7	\$965
PWATSS515002	1.44	AT	9	(2) 5-15P	(8) 5-15R	1.7 x 19.0 x 7.0	\$911
TPC2234-A	1.44	AT	9	(2) 5-15P	(8) 5-15R	1.72 x 19 x 4.5	\$678
TPC2234-A-F	1.44	AT	9	(2) 5-15P	(8) 5-15R	1.72 x 19 x 4.5	\$740
T2235-A2-CFB09S	1.92	AT	9	(2) 5-20P	(8) 5-20R	1.72 x 19 x 7	\$999
PWATSS520003	1.92	AT	9	(2) 5-20P	(8) 5-20 R	1.7 x 19.0 x 7.0	\$1,187
TPC2234-A2	1.92	AT	9	(2) 5-20P	(8) 5-20R	1.72 x 19 x 4.5	\$762
TPC2234-A2-F	1.92	AT	9	(2) 5-20P	(8) 5-20R	1.72 x 19 x 4.5	\$791
PWATSL520004	1.92	AT	9	(2) L5-20P	(8) 5-20R	1.7 x 19.0 x 7.0	\$1,062
T2235-A2-CFB09L	1.92	AT	9	(2) L5-20P	(8) 5-20R	1.72 x 19 x 7	\$1,011
PWATSL530005	2.88	AT	9	(2) L5-30P	(8) 5-20R	1.7 x 19.0 x 7.0	\$1,138
T2235-C2-CFB09L	2.88	AT	9	(2) L5-30P	(8) 5-20R	1.72 x 19 x 7	\$1,139
T2235-C2-CNB15L	2.88	AT	15	(2) L5-30P	(8) 5-20R	1.72 x 19 x 7	\$1,138
PWATSL530007	2.88	AT	9	(2) L5-30P	(1) L5-30R	1.7 x 19.0 x 7.0	\$1,087
T2235-5135	2.88	AT	12	(2) L5-30P	(2) L5-30R	1.72 x 19 x 7	\$1,529
PWATSL630006	5.76	AT	9	(2) L6-30P	(12) C13	1.7 x 19.0 x 7.0	\$1,212
PWATSL630008	5.76	AT	9	(2) L6-30P	(1) L6-30R	1.7 x 19.0 x 7.0	\$1,087
T2235-3209	5.76	AT	9	(2) L6-30P	(6) C13, (3) C19	1.72 x 19 x 9.5	\$1,332

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Eaton HotSwap Maintenance Bypass (MBP)

HotSwap MBP—Facilitating hot-swappable UPS replacement from the rack—the HotSwap MBP is also ideal when exchanging a faulty unit or upgrading to a new UPS. The HotSwap MBP offers receptacles in 5-15R and 5-20R.

- Gain additional receptacles on UPSs
- Provide service continuity during battery replacement, UPS maintenance or upgrade
- Ease installation with flexible mounting options (rear panel, the top, on the left or on the right of the UPS (depending on the UPS model)
- Accommodate most space constraints with minimal depth 1U form factor



Eaton HotSwap Maintenance Bypass (MBP)

Catalog Number	Max kW	Function	Cord Length	Input Connection	Output Receptacles	Dimensions	List price
EHBPL1500R-PDU1U	1.44	BA	3'	5-15P	(6) 5-15R	2.1 x 3.8 x 17.3	\$321
EHBPL2000R-PDU1U	1.92	BA	3'	5-20P	(6) 5-20R	2.1 x 3.8 x 17.3	\$384
EHBPL3000R-PDU1U	2.88	BA	3'	L5-30P	(5) 5-20R	2.1 x 3.8 x 17.3	\$557

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Remote Emergency Power Off (REPO) Rack PDUs

Remote emergency power off (REPO) rack PDUs enable immediate and complete power off control from one button.

These PDUs are hardwired and the power off switch can be housed anywhere in the data center for quick and easy access, should the need for immediate shutdown arise.

- EMI/RFI Filter* and Surge Suppression* (*model specific)
- Remote interface capability utilizing remote control panels (RCPs)



Remote Emergency Power Off (REPO) Rack PDUs

Catalog Number	Max. kW	Function	Cord Length (ft)	Input Plug	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Horizontal Mount Models - Test and Instrumentation							
TPC115-10A-LMR	1.44	REPO	10	5-15P	(10) 5-15R	1.72 x 19 x 8	\$984
TPC115-10A-LTR	1.44	REPO	10	5-15P	(10) 5-15R	1.72 x 19 x 8	\$984
TPC115-10A-MTR	1.44	REPO	10	5-15P	(10) 5-15R	1.72 x 19 x 8	\$1,134
TPC115-10A-R	1.44	REPO	10	5-15P	(10) 5-15R	1.72 x 19 x 8	\$1,134
PC125-A2-LTR	1.92	REPO	10	5-20P	(12) 5-20R	3.44 x 19 x 8.5	\$1,119
TPC115-10A2-LMR	1.92	REPO	10	5-20P	(10) 5-20R	1.72 x 19 x 8	\$1,032
TPC115-10A2-LTR	1.92	REPO	10	5-20P	(10) 5-20R	1.72 x 19 x 8	\$1,032
TPC115-10A2-MTR	1.92	REPO	10	5-20P	(10) 5-20R	1.72 x 19 x 8	\$1,229
TPC115-10A2-R	1.92	REPO	10	5-20P	(10) 5-20R	1.72 x 19 x 8	\$1,229
TPC10-A-3060R	1.92	REPO	10	L5-20P	(10) 5-15R	1.72 x 19 x 8	\$1,155
TPC115-10C-LMR	2.88	REPO	15	L5-30P	(10) 5-15R	1.72 x 19 x 8	\$1,067
TPC115-10C-LTR	2.88	REPO	15	L5-30P	(10) 5-15R	1.72 x 19 x 8	\$1,067
TPC115-10C-MTR	2.88	REPO	15	L5-30P	(10) 5-15R	1.72 x 19 x 8	\$1,227
TPC115-10C-R	2.88	REPO	15	L5-30P	(10) 5-15R	1.72 x 19 x 8	\$1,227
TPC115-10D-352R	2.88	REPO	15	L5-30P	(8) 5-20R	1.72 x 19 x 8	\$1,566
TPC115-10D-LMR	2.88	REPO	15	L5-30P	(10) 5-20R	1.72 x 19 x 8	\$1,068
TPC115-10D-LTR	2.88	REPO	15	L5-30P	(10) 5-20R	1.72 x 19 x 8	\$1,068
TPC115-10D-MTR	2.88	REPO	15	L5-30P	(10) 5-20R	1.72 x 19 x 8	\$1,229
TPC115-10D-R	2.88	REPO	15	L5-30P	(10) 5-20R	1.72 x 19 x 8	\$1,332
TPC2653-2R	2.88	REPO	15	L5-30P	(10) 5-15R	1.72 x 19 x 8	\$2,641
PC2651-1R	2.88	REPO	N/A	Hardwired	(4) L5-30R	3.44 x 19 x 11.65	\$3,782
TPC2365-3731	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$997
TPC2365-5403-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$1,191
PC5916-7000R	3.33	REPO	N/A	C20	(8) C13	3.44 x 19 x 7	\$1,646
TPC2365-5902-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$1,305
TPC2365-LTMTD-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$900
TPC2365-LT-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$900
TPC2365-MTD-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$1,115
TPC2365-R	3.33	REPO	N/A	C20	(12) C13	1.72 x 19 x 7	\$1,115
PC125-F-LTR	5.76	REPO	15	L6-30P	(12) 6-150R	3.44 x 19 x 8.5	\$1,316
TPC115-10F-574R	5.76	REPO	6	L6-30P	(10) 6-20R	1.72 x 19 x 8	\$1,416
TPC115-10F-LTR	5.76	REPO	15	L6-30P	(10) 6-15R	1.72 x 19 x 8	\$1,087
TPC2365-3732R	5.76	REPO	15	L6-30P	(12) C13	1.72 x 19 x 9.5	\$1,202
PC2651-2R	5.76	REPO	N/A	Hardwired	(4) L6-30R	3.44 x 19 x 11.65	\$4,101
PC5585-CF1-MTR	5.76	REPO	N/A	Hardwired	(14) C13	3.44 x 19 x 12	\$1,995
PC5585-CF-2654R	5.76	REPO	N/A	Hardwired	(14) C13	3.44 x 19 x 12	\$2,543
PC975-3387-LTR	8.64	REPO	15	L15-30P	(6) 6-20R, (3) L15-30R	3.44 x 19 x 14.5	\$2,866
PC975-3387R	8.64	REPO	15	L15-30P	(6) 6-20R, (3) L15-30R	3.44 x 19 x 14.5	\$2,866
PC2641-D-LMR	8.64	REPO	15	L21-30P	(14) 5-20R	3.44 x 19 x 14.5	\$2,020
PC2641-D-LTR	8.64	REPO	15	L21-30P	(14) 5-20R	3.44 x 19 x 14.5	\$2,020
PC2641-D-MTR	8.64	REPO	15	L21-30P	(14) 5-20R	3.44 x 19 x 14.5	\$2,020
PC2641-D-R	8.64	REPO	15	L21-30P	(14) 5-20R	3.44 x 19 x 14.5	\$2,020
PC6000R	8.64	REPO	6	L21-30P	(23) C13	3.44 x 19 x 16	\$5,333
PC726-D-R	8.64	REPO	15	L21-30P	(18) 5-20R	3.44 x 19 x 14.5	\$2,886
PC975-1969-LTR	8.64	REPO	15	L21-30P	(8) 5-20R, (3) L21-30R	3.44 x 19 x 14.5	\$2,132
PC975-1969R	8.64	REPO	15	L21-30P	(8) 5-20R, (3) L21-30R	3.44 x 19 x 14.5	\$2,132
PC975-2109-LTR	8.64	REPO	15	L21-30P	(8) 5-15R, (6) L5-30R	3.44 x 19 x 14.5	\$2,132
PC975-2109R	8.64	REPO	15	L21-30P	(8) 5-15R, (6) L5-30R	3.44 x 19 x 14.5	\$2,132
PC975-2235R	8.64	REPO	15	L21-30P	(8) 5-20R, (6) L5-30R	3.44 x 19 x 14.5	\$3,039
PC975-LTR	8.64	REPO	15	L21-30P	(8) 5-20R, (3) L6-20R	3.44 x 19 x 14.5	\$2,141
PC975-R	8.64	REPO	15	L21-30P	(8) 5-20R, (3) L6-20R	3.44 x 19 x 14.5	\$2,141
PC2672-5906	8.64	REPO	6	L21-30P	(15) C13, (4) C19	5.19 x 19 x 14	\$4,340
TPC4000-D-LTR	8.64	REPO	15	L21-30P	(10) 5-20R	1.72 x 19 x 8	\$2,713
PC302-I-MTR	8.64	REPO	N/A	Hardwired	(14) C13	3.44 x 19 x 12	\$1,872
TPC2365-5812R	17.3	REPO	15	IEC60309 532P6W	(6) C13, (4) C19	1.72 x 19 x 7	\$1,719
PC2672-1R	17.3	REPO	6	IEC60309 532P6W	(1) 532R6W, (4) C19, (12) C13	5.19 x 19 x 16.50	\$4,058
PC6001R	22.2	REPO	N/A	Hardwired	(3) L15-20R, (15) C13	5.19 x 19 x 20	\$5,621

Remote Control Panels - Test and Instrumentation

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Remote Emergency Power Off (REPO) Rack PDUs

Catalog Number	Remote Type	Switch/EPO	Color	Input Plug	Output Receptacles	Dimensions (Height, inches)	List Price
RCP100-BLK	Standard	2 position/Normally Open	Black	None	None	1.75	\$234
RCP100-BLK-LT	Latching	3 position/Normally Closed	Black	None	None	1.75	\$268
RCP100-GRY	Standard	2 position/Normally Open	Gray	None	None	1.75	\$233
RCP100-GRY-LT	Latching	3 position/Normally Closed	Gray	None	None	1.75	\$268
RCP200-BLK	Standard	2 position/Normally Open	Black	5-15P	(2) 5-15R	3.5	\$420
RCP200-BLK-LT	Latching	3 position/Normally Closed	Black	5-15P	(2) 5-15R	3.5	\$464
RCP200-GRY	Standard	2 position/Normally Open	Gray	5-15P	(2) 5-15R	3.5	\$420
RCP200-GRY-LT	Latching	3 position/Normally Closed	Gray	5-15P	(2) 5-15R	3.5	\$464

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

ePDU Cables

- Adapters to enable equipment with disparate input/output receptacles to work together
- Jumpers to connect two pieces of equipment without cluttering up the cable arrangement
- Splitters to add extra equipment to a UPS or PDU without using up more outlets

All Eaton power cables are tested and certified for use with Eaton products, such as ePDUs, rack power modules (RPMs) and UPSs—proven to deliver the reliability and service life needed for the most rigorous data center applications.

- Choose from adapters, jumpers and splitters for any rack power distribution application
- Select from a broad range of input/output connectors
- Streamline cabling in Enclosures by deploying exactly the cable length needed
- Count on assured performance with pre-tested products that meet UL and Eaton standards

Adapter Cables

Catalog Number	Description	Leads	Input Plug	Output	Length (ft)	List Price
010-0020	10 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	10	\$23
010-0021	7 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	7	\$19
010-0024	15 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	15	\$28
010-0025	8 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	8	\$20
010-0026	8 ft C19 TO Bare Wire Cable	1	Bare Wire	C19	8	\$21
010-0027	6 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	6	\$18
010-0028	4 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	4	\$16
010-0029	2 ft IEC320-C14 to IEC320-C13 Jumper Cable	1	C14	C13	2	\$12
010-0032	1 ft IEC320-C14 to 5-15R Adapter Cable	1	C14	5-15R	1	\$20
010-0034	8 ft IEC320-C19 to Bare Wire Adapter Cable	1	C19	Bare	8	\$42
010-9332	8 ft IEC320-C13 to 5-15P Jumper Cable	1	5-15P	C13	8	\$21
010-9334	8 ft IEC320-C19 to 5-15P Adapter Cable	1	5-15P	C19	8	\$29
010-9335	8 ft IEC320-C19 to 5-20P Adapter Cable	1	5-20P	C19	8	\$35
010-9336	8 ft IEC320-C19 to 6-15P Adapter Cable	1	6-15P	C19	8	\$42
010-9337	8 ft IEC320-C19 to 6-20P Adapter Cable	1	6-20P	C19	8	\$42
010-9338	8 ft IEC320-C19 to L5-15P Adapter Cable	1	L5-15P	C19	8	\$50
010-9339	8 ft IEC320-C19 to L5-20P Adapter Cable	1	L5-20P	C19	8	\$35
010-9341	8 ft IEC320-C19 to L6-20P Adapter Cable	1	L6-20P	C19	8	\$42
010-9342	8 ft IEC320-C19 to IEC320-C20 Adapter Cable	1	C20	C19	8	\$42
010-9343	8 ft SCHUCKO to IEC320-C19 Adapter Cable	1	C19	SCHUCKO	8	\$40
010-9351	8 ft British to IEC320-C19 Adapter Cable	1	C19	British Connector	8	\$35
010-9365	8 ft IEC320-C14 to IEC320-C19 Jumper Cable	1	C19	C14	8	\$44
CBL146	30 ft Power Cord Assembly 10/3 SOOW 2" Pigtails	2	Pigtails	Pigtails	30	\$179
CBL147	Cable Assembly High Volt Cover, 15 ft 10/3 SOOW, L6-30P	1	L6-30P		15	\$191
SUB-PWRCORD-908	8 ft L6-30R to L6-30P Adapter Cable	1	L6-30P	L6-30R	8	\$74

Splitter Cables

Catalog Number	Description	Leads	Input Plug	Output	Length (ft)	List Price
CBL139	Splitter Cable L14-30P to (2) L6-30R (4ft/2ft)	2	L14-30P	L6-30R	4	\$204
CBL143	Splitter Cable L14-30P to (2) L5-30R (4ft/2ft)	2	L14-30P	L5-30R	4	\$204
CBL148	Splitter Cable L14-20P to (2) L5-20R (4ft/2ft)	2	L14-20P	L5-20R	4	\$218
CBL149	Splitter Cable L21-30P to (3) L5-30R (4ft/2ft/1ft)	3	L21-30P	L5-30R	4	\$203
CBL150	Splitter Cable L21-20P to (3) L5-20R (4ft/2ft/1ft)	3	L21-20P	L5-20R	4	\$296

Accessories

Catalog Number	Description	List Price
010-0322	C19 Receptacle Connector	\$19
035-0113	C13 Outlet Cap	\$6
001-0819-1	Mounting Bracket Right	\$27
001-0819-2	Mounting Bracket Left	\$27
001-1393-1	Mounting Bracket Adjustable Black - RoHS Compliant	\$9
001-1928-1	Side Mounting Bracket	\$34
001-1995-1	Bracket	\$41
SUB-HRDWARE-017	VPC Bracket - Standard, Offset	\$16
SUB-HRDWARE-032	Mounting Bracket	\$40
SUB-HRDWARE-038	Toolless Mounting Kit	\$40

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

ECLIPSE SURGE SUPPRESSORS

The Eclipse is Ideal for all uses—computer, peripheral, stereo and video—total protection against power surges, spikes, nearby lightning strikes and line noise.

- Up to 1020 joule rating
- Master on/off switch
- Instantaneous response time
- Visual alarm(s)
- Audible alarm (except personal)
- Circuit breaker and thermal fuse protection
- 360° rotating plug (except personal)



Catalog Number	Style Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price*
ECLL1800-PER	83500	ECLIPSE Personal 120V 1800W (6) 5-15R	2.00 x 1.25 x 11.00	1.0	\$17
ECLL1800-PRO	83501	ECLIPSE Pro 120V 1800W (8) 5-15R	3.88 x 1.31 x 9.75	1.5	\$31
ECLL1800-PROTEL	83502	ECLIPSE ProTel 1800W (8) 5-15R	3.88 x 1.31 x 9.75	1.5	\$34

MiniRaQ by Eaton

Vertical Wallmount Open Frame Rack/Convertible Enclosure

Eaton has partnered with best-in-class wallmount enclosure manufacturer Black Hawk Labs to provide our customers with the most versatile wallmount enclosure in the market. With three options to select from MiniRaQ open, MiniRaQ convertible and MiniRaQ secure, Eaton gives users the options required to secure Edge environment deployments.



Solution highlights:

- 50% smaller footprint in comparison to horizontal wallmount offerings
- Unsurpassed weight capacity allows up to 400lbs of critical equipment to be installed
- Large cable access openings on the top, bottom, and sides of the backplate provide increased cable and conduit routing flexibility
- Modular design guarantees installation can be performed by one technician, which reduces installation costs and time to deploy
- Optional high-velocity, multi-fan module ensures critical networking equipment stays cool, even when fully enclosed
- Optimized for deep rack components, the MiniRaQs vertical equipment mounting orientation allows an equipment depth of 35 inches, exceeding the limitations of traditional horizontal enclosures

MiniRaQ Open- Includes Backplate (2.5" Deep) & Side Panels. Features a 2U Dedicated

Catalog Number	Description	Dimensions (H x W x D Inches)	Weight (lb)	List Price
ETN-MRQ100V06	MiniRaQ Open with 4U Side Panels	19.25 x 19 x 9.75	18 lbs.	\$389
ETN-MRQ100V08	MiniRaQ Open with 6U Side Panels	19.25 x 19 x 13.25	20 lbs.	\$421
ETN-MRQ100V10	MiniRaQ Open with 8U Side Panels	19.25 x 19 x 16.75	22 lbs.	\$470
ETN-MRQ100V12	MiniRaQ Open with 10U Side Panels	19.25 x 19 x 20.25	24 lbs.	\$503

MiniRaQ Convertible- Includes Backplate (4.5" Deep) & Side Panels. Features a 4U Dedicated Space for Patch Panel, Bonus 2U Equipment Space Internal to Backplate, Upgradeable to MiniRaQ Secure Compact.

Catalog Number	Description	Dimensions (H x W x D Inches)	Weight (lb)	List Price
ETN-MRQ351V06	MiniRaQ Convertible - Compact (No Side Panels)	31.0 x 19.6 x 4.5	25 lbs.	\$535
ETN-MRQ351V08	MiniRaQ Convertible - Compact with 2U Side Panels	31.0 x 19.6 x 8.3	34 lbs.	\$681
ETN-MRQ351V10	MiniRaQ Convertible - Compact with 4U Side Panels	31.0 x 19.6 x 11.8	37 lbs.	\$698
ETN-MRQ351V12	MiniRaQ Convertible - Compact with 6U Side Panels	31.0 x 19.6 x 15.3	41 lbs.	\$730
ETN-MRQ351V14	MiniRaQ Convertible - Compact with 8U Side Panels	31.0 x 19.6 x 18.8	44 lbs.	\$763
ETN-MRQ351V16	MiniRaQ Convertible - Compact with 10U Side Panels	31.0 x 19.6 x 22.3	47 lbs.	\$811
ETN-MRQ301V06	MiniRaQ Convertible - Tall (No Side Panels)	38.1 x 19.6 x 4.5	25 lbs.	\$600
ETN-MRQ301V08	MiniRaQ Convertible - Tall with 2U Side Panels	38.1 x 19.6 x 8.3	34 lbs.	\$730
ETN-MRQ301V10	MiniRaQ Convertible - Tall with 4U Side Panels	38.1 x 19.6 x 11.8	37 lbs.	\$763
ETN-MRQ301V12	MiniRaQ Convertible - Tall with 6U Side Panels	38.1 x 19.6 x 15.3	41 lbs.	\$811
ETN-MRQ301V14	MiniRaQ Convertible - Tall with 8U Side Panels	38.1 x 19.6 x 18.8	44 lbs.	\$860
ETN-MRQ301V16	MiniRaQ Convertible - Tall with 10U Side Panels	38.1 x 19.6 x 22.3	47 lbs.	\$925

MiniRaQ Secure- Includes: Backplate (4.5" Deep), Side Panels, Front Panel, Locking Cover & Vented Bottom. Features: 4U Dedicated Space for Patch Panel, Bonus 2U Equipment Space Internal to Backplate. Compact version supports equipment depth of 22" to 28" and tall version supports equipment Depth of 29" to 35".

Catalog Number	Description	Dimensions (H x W x D Inches)	Weight (lb)	List Price
ETN-MRQ351S06	MiniRaQ Secure - Compact (No Side Panels)	31.0 x 19.6 x 4.5	40 lbs.	\$860
ETN-MRQ351S08	MiniRaQ Secure - Compact with 2U Side Panels	31.0 x 19.97 x 8.95	52 lbs.	\$1,250
ETN-MRQ351S10	MiniRaQ Secure - Compact with 4U Side Panels	31.0 x 19.97 x 12.45	58 lbs.	\$1,315
ETN-MRQ351S12	MiniRaQ Secure - Compact with 6U Side Panels	31.0 x 19.97 x 15.95	66 lbs.	\$1,380
ETN-MRQ351S14	MiniRaQ Secure - Compact with 8U Side Panels	31.0 x 19.97 x 19.45	72 lbs.	\$1,461
ETN-MRQ351S16	MiniRaQ Secure - Compact with 10U Side Panels	31.0 x 19.97 x 22.95	78 lbs.	\$1,543

MiniRaQ Enclosure (Cont.)

MiniRaQ Secure (Cont.)

Catalog Number	Description	Dimensions (H x W x D Inches)	Weight (lb)	List Price
ETN-MRQ301S06	MiniRaQ Secure - Tall (No Side Panels)	38.1 x 19.6 x 4.5	48 lbs.	\$958
ETN-MRQ301S08	MiniRaQ Secure - Tall with 2U Side Panels	38.1 x 19.97 x 8.95	60 lbs.	\$1,380
ETN-MRQ301S10	MiniRaQ Secure - Tall with 4U Side Panels	38.1 x 19.97 x 12.45	67 lbs.	\$1,445
ETN-MRQ301S12	MiniRaQ Secure - Tall with 6U Side Panels	38.1 x 19.97 x 15.95	76 lbs.	\$1,543
ETN-MRQ301S14	MiniRaQ Secure - Tall with 8U Side Panels	38.1 x 19.97 x 19.45	83 lbs.	\$1,640
ETN-MRQ301S16	MiniRaQ Secure - Tall with 10U Side Panels	38.1 x 19.97 x 22.95	90 lbs.	\$1,738

Upgrade Kit to convert MiniRaQ Convertible to MiniRaQ Secure- Includes: Front Panel, Locking Cover & Vented Bottom.

Catalog Number	Description	Weight (lb)	List Price
ETN-MRQ351UPG10	10U MiniRaQ Convertible Compact to Secure Upgrade Kit	27 lbs.	\$763
ETN-MRQ351UPG12	12U MiniRaQ Convertible Compact to Secure Upgrade Kit	30 lbs.	\$811
ETN-MRQ351UPG14	14U MiniRaQ Convertible Compact to Secure Upgrade Kit	33 lbs.	\$844
ETN-MRQ351UPG16	16U MiniRaQ Convertible Compact to Secure Upgrade Kit	36 lbs.	\$893
ETN-MRQ301UPG10	10U MiniRaQ Convertible Tall to Secure Upgrade Kit	27 lbs.	\$811
ETN-MRQ301UPG12	12U MiniRaQ Convertible Tall to Secure Upgrade Kit	30 lbs.	\$844
ETN-MRQ301UPG14	14U MiniRaQ Convertible Tall to Secure Upgrade Kit	33 lbs.	\$893
ETN-MRQ301UPG16	16U MiniRaQ Convertible Tall to Secure Upgrade Kit	36 lbs.	\$925

MiniRaQ Accessories

Catalog Number	Description	Weight (lb)	List Price
ETN-BH1001	Hardware Kit (25) 12-24 Panhead Screw Black	2 lbs.	\$23
ETN-BH1002	Hardware Kit (100) 12-24 Panhead Screw Black	3 lbs.	\$80
ETN-BH1003	1U x 3" Risers Bracket Set	2 lbs.	\$57
ETN-BH1004	1U x 6" Risers Bracket Set	2 lbs.	\$57
ETN-BH1005	1U Blanking Panel 19" x 1.75" Black	2 lbs.	\$80
ETN-BH1006	Uniquely Keyed Barrel Lock	1 lbs.	\$113
ETN-BH1007	Additional pair Standard MiniRaQ Keys	1 lbs.	\$48
ETN-BH1008	Toggler® (8) set 1/4" 20 w/ Bolt and Washers	2 lbs.	\$64
ETN-BH1009	TapCon® (10) set 1/4" x 1 1/4" Hex	2 lbs.	\$48
ETN-BH1010	2U x 3" Risers Bracket Set	2 lbs.	\$48
ETN-BH1011	2U x 6" Risers Bracket Set	2 lbs.	\$48
ETN-BH2019	16" X 16" X 3/4" Plywood Insert with Hardware	6 lbs.	\$80
ETN-BH2020	Data/Power Cable Access Plates with Brush Strip	2 lbs.	\$64
ETN-BH2021	Backplate Pouch with Shelf	7 lbs.	\$178
ETN-BH2023	2U x 2" Adapter Kit for Dell/Avigilon ReadyRails	2 lbs.	\$48
ETN-BH2025	MiniRaQ 4G Magnetic Filter Set 10U	2 lbs.	\$113
ETN-BH2026	MiniRaQ 4G Magnetic Filter Set 12U	2 lbs.	\$129
ETN-BH2027	MiniRaQ 4G Magnetic Filter Set 14U	3 lbs.	\$139
ETN-BH2028	MiniRaQ 4G Magnetic Filter Set 16U	3 lbs.	\$145
ETN-BH2029	MiniRaQ Secure Series 10U Fan Tray	6 lbs.	\$373
ETN-BH2029i	MiniRaQ Secure Series 10U Fan Tray (220-240v)	6 lbs.	\$470
ETN-BH2030	MiniRaQ Secure Series 12U Fan Tray	8 lbs.	\$389
ETN-BH2030i	MiniRaQ Secure Series 12U Fan Tray (220-240v)	8 lbs.	\$486
ETN-BH2031	MiniRaQ Secure Series 14U Fan Tray	12 lbs.	\$405
ETN-BH2031i	MiniRaQ Secure Series 14U Fan Tray(220-240v)	12 lbs.	\$503
ETN-BH2032	MiniRaQ Secure Series 16U Fan Tray	14 lbs.	\$421
ETN-BH2032i	MiniRaQ Secure Series 16U Fan Tray(220-240v)	14 lbs.	\$519
ETN-BH2033	3U x 2" Adapter Kit for Dell/Avigilon ReadyRails	2 lbs.	\$57
ETN-BH2034	Seismic Floor Stand for All MiniRaQ Models	48 lbs.	\$811
ETN-BH2037	Patch Panel Hinge Kit	2 lbs.	\$96
ETN-BH2041	2U Shelf Bracket Kit for MRQ301XXX	8 lbs.	\$129
ETN-BH2042	3U Shelf Bracket Kit for MRQ301XXX	10 lbs.	\$145
ETN-BH2043	2U Shelf Bracket Kit for MRQ351XXX	7 lbs.	\$113
ETN-BH2044	3U Shelf Bracket Kit for MRQ351XXX	9 lbs.	\$129

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

S-Series Enclosure

Designed for small and medium-sized businesses, the Eaton S-Series Enclosure supports and protects your critical IT equipment.

These standard configured enclosures are scalable and integrate an array of options including cable management, power distribution and backup power to provide a full network solution.

- Air flow/thermal management options include chimneys, blanking panels, and grommets for the enclosures.
- Split rear doors on most configurations provide easier access and maneuverability in data center environments.
- Guaranteed compatibility with EIA-310 standard size equipment.
- A wide range of cable management options enhance cable routing horizontally and vertically.
- Color: Black



S-Series Enclosure

Part Number	Description	Shipping Dimensions (H x W x D Inches)		Weight (lb)	List Price
		Installed			
ETN-ENC422442SE	Enclosure 42Ux24x42 frame only w/top cover	87 x 38 x 60	81 x 24 x 42	171	\$2,436
ETN-ENC422448SE	Enclosure 42Ux24x48 frame only w/top cover	87 x 38 x 60	81 x 24 x 48	180	\$2,673
ETN-ENC423042SE	Enclosure 42Ux30x42 frame only w/top cover	87 x 38 x 60	81 x 30 x 42	180	\$3,267
ETN-ENC423048SE	Enclosure 42Ux30x48 frame only w/top cover	87 x 38 x 60	81 x 30 x 48	190	\$2,910
ETN-ENC442442SE	Enclosure 44Ux24x42 frame only w/top cover	88 x 38 x 60	84 x 24 x 42	180	\$2,515
ETN-ENC442448SE	Enclosure 44Ux24x48 frame only w/top cover	88 x 38 x 60	84 x 24 x 48	195	\$2,476
ETN-ENC443042SE	Enclosure 44Ux30x42 frame only w/top cover	88 x 38 x 60	84 x 30 x 42	195	\$3,301
ETN-ENC443048SE	Enclosure 44Ux30x48 frame only w/top cover	88 x 38 x 60	84 x 30 x 48	210	\$3,551
ETN-ENC482442SE	Enclosure 48Ux24x42 frame only w/top cover	97 x 38 x 60	91 x 24 x 42	200	\$2,709
ETN-ENC482448SE	Enclosure 48Ux24x48 frame only w/top cover	97 x 38 x 60	91 x 24 x 42	220	\$2,845
ETN-ENC512442SE	Enclosure 51Ux24x42 frame only w/top cover	97 x 38 x 60	91 x 24 x 42	210	\$3,087
ETN-ENC422442S	Enclosure 42Ux24x42 w/doors/top/divider/casters	87 x 38 x 60	81 x 24 x 42	309	\$5,690
ETN-ENC422448S	Enclosure 42Ux24x48 w/doors/top/divider/casters	87 x 38 x 60	81 x 24 x 48	321	\$6,152
ETN-ENC423042S	Enclosure 42Ux30x42 w/doors/top/divider/casters	87 x 38 x 60	81 x 30 x 42	321	\$7,573
ETN-ENC423048S	Enclosure 42Ux30x48 w/doors/top/divider/casters	87 x 38 x 60	81 x 30 x 48	350	\$6,875
ETN-ENC442442S	Enclosure 44Ux24x42 w/doors/top/divider/casters	88 x 38 x 60	84 x 24 x 42	240	\$5,915
ETN-ENC442448S	Enclosure 44Ux24x48 w/doors/top/divider/casters	88 x 38 x 60	84 x 24 x 48	250	\$5,812
ETN-ENC443042S	Enclosure 44Ux30x42 w/doors/top/divider/casters	88 x 38 x 60	84 x 30 x 42	250	\$6,779
ETN-ENC443048S	Enclosure 44Ux30x48 w/doors/top/divider/casters	88 x 38 x 60	84 x 30 x 48	270	\$7,315
ETN-ENC482442S	Enclosure 48Ux24x42 w/doors/top/divider/casters	97 x 38 x 60	91 x 24 x 42	350	\$5,908
ETN-ENC483042S	Enclosure 48Ux30x42 w/doors/top/divider/casters	97 x 38 x 60	91 x 30 x 42	360	\$7,316
ETN-ENC482448S	Enclosure 48Ux24x48 w/doors/top/divider/casters	97 x 38 x 60	91 x 24 x 48	360	\$6,323
ETN-ENC483048S	Enclosure 48Ux30x48 w/doors/top/divider/casters	97 x 38 x 60	91 x 30 x 48	370	\$7,917
ETN-ENC512442S	Enclosure 51Ux24x48 w/doors/top/divider/casters	97 x 38 x 60	91 x 24 x 48	380	\$6,439
ETN-ENC512448S	Enclosure 51Ux24x48 w/doors/top/divider/casters	97 x 38 x 60	91 x 24 x 48	390	\$6,843
ETN-ENC513042S	Enclosure 51Ux30x42 w/doors/top/divider/casters	97 x 38 x 60	91 x 30 x 42	390	\$6,843
ETN-ENC513048S	Enclosure 51Ux30x48 w/doors/top/divider/casters	97 x 38 x 60	91 x 30 x 48	400	\$6,315
ETN-ENC422442SB	Enclosure 42Ux24x42 w/doors/sides/top/levelers/casters	87 x 38 x 60	81 x 24 x 42	347	\$6,603
ETN-ENC423042SB	Enclosure 42Ux30x42 w/doors/sides/top/levelers/casters	87 x 38 x 60	81 x 30 x 42	360	\$8,223
ETN-ENC422448SB	Enclosure 42Ux24x48 w/doors/sides/top/levelers/casters	87 x 38 x 60	81 x 24 x 48	360	\$7,194
ETN-ENC423048SB	Enclosure 42Ux30x48 w/doors/sides/top/levelers/casters	87 x 38 x 60	81 x 30 x 48	375	\$7,823
ETN-ENC422442SC	Enclosure 42Ux24x42 w/doors/sides/top/levelers (no casters)	87 x 38 x 60	81 x 24 x 42	337	\$6,354
ETN-ENC423042SC	Enclosure 42Ux30x42 w/doors/sides/top/levelers (no casters)	87 x 38 x 60	81 x 30 x 42	350	\$7,979
ETN-ENC422448SC	Enclosure 42Ux24x48 w/doors/sides/top/levelers (no casters)	87 x 38 x 60	81 x 24 x 48	350	\$6,982
ETN-ENC423048SC	Enclosure 42Ux30x48 w/doors/sides/top/levelers (no casters)	87 x 38 x 60	81 x 30 x 48	365	\$7,610

S-Series Enclosure

S-Series Enclosure

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-ENC422442SD	Enclosure 42Ux24x42 w/doors/top (no sides/divider/casters)	87 x 38 x 60	81 x 24 x 42	225	\$4,810
ETN-ENC423042SD	Enclosure 42Ux30x42 w/doors/top (no sides/divider/casters)	87 x 38 x 60	81 x 30 x 42	240	\$6,255
ETN-ENC422448SD	Enclosure 42Ux24x48 w/doors/top (no sides/divider/casters)	87 x 38 x 60	81 x 24 x 48	240	\$5,212
ETN-ENC423048SD	Enclosure 42Ux30x48 w/doors/top (no sides/divider/casters)	87 x 38 x 60	81 x 30 x 48	255	\$6,078
ETN-ENC422442SL	Enclosure 42Ux24x42 w/doors/sides/top/casters/combo lock	87 x 38 x 60	81 x 24 x 42	360	\$7,601

Each side panel will add approximately 3/4" to the width of the rack
 Note: Add approximately 65lb to product weight for packaging materials to determine

S-Series Chimney Enclosures and Options

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-ETC422442S	Chimney Enclosure 42Ux24x42 w/doors/top/divider/casters	87 x 38 x 60	81 x 24 x 42	322	\$5,523
ETN-ETC422442SB	Chimney Enclosure 42Ux24x42 w/doors/top/sides/casters	87 x 38 x 60	81 x 24 x 42	320	\$6,568
ETN-ETC422448S	Chimney Enclosure 42Ux24x48 w/doors/top/divider/casters	87 x 38 x 60	81 x 24 x 48	330	\$5,493
ETN-ETC422448SB	Chimney Enclosure 42Ux24x48 w/doors/top/sides/casters	87 x 38 x 60	81 x 24 x 48	335	\$6,425
ETN-ETC423042S	Chimney Enclosure 42Ux30x42 w/doors/top/divider/casters	87 x 38 x 60	81 x 30 x 42	325	\$6,592
ETN-ETC423042SB	Chimney Enclosure 42Ux30x42 w/doors/top/sides/casters	87 x 38 x 60	81 x 30 x 42	330	\$7,709
ETN-ETC423048S	Chimney Enclosure 42Ux30x48 w/doors/top/divider/casters	87 x 38 x 60	81 x 30 x 48	335	\$6,780
ETN-ETC423048SB	Chimney Enclosure 42Ux30x48 w/doors/top/sides/casters	87 x 38 x 60	81 x 30 x 48	340	\$7,823

Notes: Depth of enclosures includes front and rear doors. See the S-Series Enclosures brochure for detailed information.

S-Series Chimneys, pick one with required height for "ETN-ETC" enclosures above

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-EXTTC1219	Telescopic Chimney for enclosure to ceiling heights of 12 to 19in	24 x 24 x 16	H x 23 x 19.5	30	\$638
ETN-EXTTC1728	Telescopic Chimney for enclosure to ceiling heights of 17 to 28in	24 x 24 x 20	H x 23 x 19.5	39	\$756
ETN-EXTTC2645	Telescopic Chimney for enclosure to ceiling heights of 26 to 45in	24 x 24 x 30	H x 23 x 19.5	56	\$877
ETN-EXTTC4376	Telescopic Chimney for enclosure to ceiling heights of 43 to 76in	24 x 24 x 48	H x 23 x 19.5	87	\$1,053

S-Series Seismic Enclosures

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-ENZ422440S	Enclosure Seismic 42Ux24x40 w/doors/divider /lace(no casters)	90 x 38 x 60	84 x 24 x 40	340	\$7,768
ETN-ENZ422440SB	Enclosure Seismic 42Ux24x40 w/doors/sides /lace (no casters)	90 x 38 x 60	84 x 24 x 40	398	\$7,875
ETN-ENZ423040S	Enclosure Seismic 42Ux30x40 w/doors/divider /lace (no casters)	90 x 38 x 60	84 x 30 x 40	381	\$8,709
ETN-ENZ423040SB	Enclosure Seismic 42Ux30x40 w/doors/sides /lace (no casters)	90 x 38 x 60	84 x 30 x 40	437	\$9,390

Note: 1.) Seismic racks tested to NEBS Zone 4 via Telecordia GR-63-CORE specification with 1300 lbs. added load weight, and 50 lbs. top of cabinet cable

S-Series Small/Medium Enterprise Enclosures

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-VS2252440	SME Enclosure 25Ux24x40 with doors/sides/top/casters	60 x 30 x 48	50 x 24 x 40	210	\$3,726

S-Series Enclosure

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

S-SERIES ENCLOSURE OPTIONS/ACCESSORIES

Enclosure Panels and Doors

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-VS2302440	SME Enclosure 30Ux24x40 with doors/sides/top/casters	65 x 30 x 48	59 x 24 x 40	250	\$4,046
ETN-VS2362440	SME Enclosure 36Ux24x40 with doors/sides/top/casters	76 x 30 x 48	70 x 24 x 40	300	\$4,069
ETN-ACC4242DP	S-Series Divider Panel 42U x 42D w/Pass-Thru (Qty-1)	6 x 90 x 50	Side of rack	25	\$438
ETN-ACC4248DP	S-Series Divider Panel 42U x 48D w/Pass-Thru (Qty-1)	6 x 90 x 50	Side of rack	28	\$464
ETN-ACC4842DP	S-Series Divider Panel 48U x 42D w/Pass-Thru (Qty-1)	6 x 90 x 50	Side of rack	28	\$455
ETN-ACC4848DP	S-Series Divider Panel 48U x 48D w/Pass-Thru (Qty-1)	6 x 90 x 50	Side of rack	30	\$484
ETN-ACC4242SP	S-Series Side Panel 42U x 42D (Qty-1)	6 x 90 x 50	Add 3/4" width	45	\$873
ETN-ACC4248SP	S-Series Side Panel 42U x 48D (Qty-1)	6 x 90 x 50	Add 3/4" width	49	\$984
ETN-ACC4442SP	S-Series Side Panel 44U x 42D (Qty-1)	6 x 90 x 50	Add 3/4" width	51	\$642
ETN-ACC4448SP	S-Series Side Panel 44U x 48D (Qty-1)	6 x 90 x 50	Add 3/4" width	51	\$842
ETN-ACC4842SP	S-Series Side Panel 48U x 42D (Qty-1)	6 x 90 x 50	Add 3/4" width	50	\$586
ETN-ACC4848SP	S-Series Side Panel 48U x 48D (Qty-1)	6 x 90 x 50	Add 3/4" width	56	\$849
ETN-ACC2442TP	S-Series Top Panel 24W x 42D	5 x 32 x 51	No height added	21	\$610
ETN-ACC2448TP	S-Series Top Panel 24W x 48D	5 x 32 x 51	No height added	25	\$637
ETN-ACC3042TP	S-Series Top Panel 30W x 42D	5 x 32 x 51	No height added	23	\$648
ETN-ACC3048TP	S-Series Top Panel 30W x 48D	5 x 32 x 51	No height added	28	\$617
ETN-ACC4224FD	S-Series Front Door 42U x 24W	6 x 90 x 50	Add 1" depth	49	\$746
ETN-ACC4224RD	S-Series Rear Door Split 42U x 24W	6 x 90 x 50	Add 1" depth	54	\$1,191
ETN-ACC4230FD	S-Series Front Door 42U x 30W	6 x 90 x 50	Add 1" depth	55	\$801
ETN-ACC4230RD	S-Series Rear Door Split 42U x 30W	6 x 90 x 50	Add 1" depth	62	\$1,134
ETN-ACC4824FD	S-Series Front Door 48U x 24W	6 x 90 x 50	Add 1" depth	55	\$882
ETN-ACC4824RD	S-Series Rear Door Split 48U x 24W	6 x 90 x 50	Add 1" depth	62	\$1,169
ETN-ACC4830FD	S-Series Front Door 48U x 30W	6 x 90 x 50	Add 1" depth	60	\$923
ETN-ACC4830RD	S-Series Rear Door Split 48U x 30W	6 x 90 x 50	Add 1" depth	65	\$1,222
ETN-ACC4224RL	S-Series Rails 42U x 24W	8 x 88 x 5	Internal	22	\$600
ETN-ACC4230RL	S-Series Reducer Rails 42U x 30W	4 x 88 x 8	Internal	42	\$853
ETN-ACC4824RL	S-Series Rails 48U x 24W	8 x 88 x 5	Internal	26	\$705
ETN-ACC4830RL	S-Series Reducer Rails 48U x 30W	4 x 88 x 8	Internal	45	\$1,158
ETN-ACC42VBP	S-Series Vertical Blanking Panels 42U x 30W	5 x 9 x 49	Internal	9	\$468
ETN-ACC48VBP	S-Series Vertical Blanking Panels 48U x 30W	5 x 9 x 49	Internal	10	\$553

Rack and Raised Floor Air Management

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-PBP1U10	Eaton Blanking Panel 19" Tool-less Plastic 1U (Qty-10)	5 x 5 x 20	1U x 19	4	\$89
ETN-PBP1U100	Eaton Blanking Panel 19" Tool-less Plastic 1U (Qty-100)	25 x 10 x 20	1U x 19	40	\$796
ETN-PBP2U10	Eaton Blanking Panel 19" Tool-less Plastic 2U (Qty-10)	5 x 9 x 20	2U x 19	7	\$143
ETN-PBP2U100	Eaton Blanking Panel 19" Tool-less Plastic 2U (Qty-100)	25 x 18 x 20	2U x 19	70	\$1,062
ETN-PBP8U10	Eaton Blanking Panel 19" Tool-less Plastic 8U (Qty-10)	20 x 11 x 15	8U x 19	15	\$381
ETN-PBP8U100	Eaton Blanking Panel 19" Tool-less Plastic 8U (Qty-100)	21 x 50 x 30	8U x 19	150	\$2,864
ETN-JFT12440	Top fan tray kit (4 fans) for S-Series 24" x 42", 120VAC	5 x 32 x 51	Top of rack	45	\$523
ETN-JFT12445	Top fan tray kit (4 fans) for S-Series 24" x 48", 120VAC	5 x 32 x 51	Top of rack	48	\$570

S-Series Enclosure

Rack and Raised Floor Air Management

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-JFT13040	Top fan tray kit (4 fans) for S-Series 30" x 42", 120VAC	5 x 32 x 51	Top of rack	50	\$544
ETN-JFT13045	Top fan tray kit (4 fans) for S-Series 30" x 48", 120VAC	5 x 32 x 51	Top of rack	54	\$590
ETN-FLRGR118	Floor Grommet, 11"W x 8.25"D (Qty-1)	2 x 12 x 17	1 x 11 x 8.25	5	\$189
ETN-FLRGR11810	Floor Grommet, 11"W x 8.25"D (Qty-10)	20 x 12 x 17	1 x 11 x 8.25	50	\$1,770
ETN-FLRGR76	Floor Grommet, 7.5"W x 6.5"D (Qty-1)	2 x 8 x 11	1 x 7.5 x 6.5	4	\$167
ETN-FLRGR7610	Floor Grommet, 7.5"W x 6.5"D (Qty-10)	20 x 8 x 11	1 x 7.5 x 6.5	40	\$1,593
ETN-VF01U100B	1U Steel Screw Attach Blanking Panels - Kit Of 100; Black				\$1,405
ETN-VF01U10B	1U Steel Screw Attach Blanking Panels - Kit Of 10; Black				\$205
ETN-VF01U50B	1U Steel Screw Attach Blanking Panels - Kit Of 50; Black				\$825
ETN-VF02U100B	2U Steel Screw Attach Blanking Panels - Kit Of 100; Black				\$1,631
ETN-VF02U10B	2U Steel Screw Attach Blanking Panels - Kit Of 10; Black				\$234
ETN-VF05U10B	5U Steel Screw Attach Blanking Panels - Kit Of 10; Black				\$277

Network Switch Air Deflectors for Front to Rear Air Flow

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-6509CVK42	Cisco 6509 Conversion Kit for S-Series Enclosures 42U x 30"W	6 x 90 x 50	Internal	90	\$1,566
ETN-6509CVK48	Cisco 6509 Conversion Kit for S-Series Enclosures 48U x 30"W	6 x 90 x 50	Internal	110	\$1,599
ETN-6513CVK42	Cisco 6513 Conversion Kit for S-Series Enclosures 42U x 30"W	6 x 90 x 50	Internal	90	\$1,581
ETN-6513CVK48	Cisco 6513 Conversion Kit for S-Series Enclosures 48U x 30"W	6 x 90 x 50	Internal	115	\$1,614

Rack Shelves

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-FS19201U20	Shelf Fixed 19" 1U x 20"D 200lbs	3 x 22 x 33	1U x 20	15	\$216
ETN-FS19201U40	Shelf Fixed 19" 1U x 20"D 400lbs	3 x 22 x 33	1U x 20	17	\$223
ETN-FS19241U20	Shelf Fixed 19" 1U x 24"D 200lbs	3 x 22 x 33	1U x 24	16	\$216
ETN-FS19241U40	Shelf Fixed 19" 1U x 24"D 400lbs	3 x 22 x 33	1U x 24	18	\$256
ETN-FS19281U20	Shelf Fixed 19" 1U x 28"D 200lbs	3 x 22 x 33	1U x 28	17	\$224
ETN-FS19281U40	Shelf Fixed 19" 1U x 28"D 400lbs	3 x 22 x 33	1U x 28	19	\$247
ETN-RS19241U10	Shelf Roll-Out 19" 1U x 24"D 100lbs	3 x 22 x 33	1U x 24	18	\$868
ETN-RS19242U20	Shelf Roll-Out 19" 2U x 24"D 200lbs	3 x 22 x 33	1U x 24	20	\$717
ETN-RS19281U10	Shelf Roll-Out 19" 1U x 28"D 100lbs	3 x 22 x 33	1U x 28	21	\$759
ETN-RS19282U20	Shelf Roll-Out 19" 2U x 28"D 200lbs	3 x 22 x 33	1U x 28	23	\$785
ETN-CHASBKT2032	Chassis Support Brackets Adj 19" (20"-32") 400 lbs.	6 x 6 x 30	2U x 19	14	\$487
EAUS192U1605	19" Utility Shelf, 2 post mounting, 50 lbs	12x24x9	2U x 30	12	\$191

Rack Cable and PDU Management, Hardware

Part Number	Description	Shipping Dimensions (H x W x D Inches)	Installed	Weight (lb)	List Price
ETN-LACEB42U03	Lacing Bar 42U x 3"W	4 x 3 x 88	42U x 3	7	\$102
ETN-LACEB42U08	Lacing Bar 42U x 8"W	5 x 15 x 88	42U x 8	12	\$269
ETN-LACEB42U12	Lacing Bar 42U x 12"W	5 x 15 x 88	42U x 12	15	\$287
ETN-LACEB48U03	Lacing Bar 48U x 3"W	4 x 3 x 88	48U x 3	8	\$168
ETN-LACEB48U08	Lacing Bar 48U x 8"W	5 x 15 x 88	48U x 8	14	\$273
ETN-LACEB48U12	Lacing Bar 48U x 12"W	5 x 15 x 88	48U x 12	17	\$327
ETN-PWRBAR42U	Power Mounting Bar 42U x 9"W	5 x 15 x 88	42U x 9	15	\$243
ETN-PWRBAR48U	Power Mounting Bar 48U x 9"W	5 x 15 x 88	48U x 9	17	\$270

S-Series Enclosure

Rack Cable and PDU Management, Hardware

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Part Number	Description	Shipping Dimensions	Installed	Weight (lb)	List Price
		(H x W x D Inches)			
ETN-CMDRNR031U	Cable D-Ring Kit 1U (Qty-4)	6 x 4 x 9	1U x .75 x 3.3	3	\$53
ETN-CMDRNR032U	Cable D-Ring Kit 2U (Qty-4)	6 x 4 x 9	2U x .75 x 3.3	4	\$53
ETN-STLDRING	Cable D-Ring Kit, Plastic, (Qty-4)	6 x 4 x 9	1U x .75 x 3.3	3	\$228
ETN-CMTUNR02	Fiber Spool 2.5"H	6 x 9 x 4	4 x 2.75 x 3.8	2	\$115
ETN-CMTUNR05	Fiber Spool 5"H	6 x 9 x 4	4 x 5 x 3.8	3	\$118
ETN-BX45V8	Velcro Strap 8"L, (Qty-50)	5 x 5 x 10	Internal	2	\$154
ETN-BX45V11	Velcro Strap 11"L, (Qty-50)	5 x 5 x 10	Internal	2	\$154
ETN-CMVCKL	Velcro Buckle Strap 9"L, (Qty-10)	6 x 9 x 4	Internal	1	\$148
ETN-CMVCKL12	Velcro Buckle Strap 12"L, (Qty-10)	6 x 9 x 4	Internal	1	\$155
ETN-CMRB19022U	Cable Strain Relief Bar 2"D	3 x 21 x 8	3.5 x 19 x 3	3	\$149
ETN-CMRB19042U	Cable Strain Relief Bar 4"D	3 x 21 x 8	3.5 x 19 x 5	4	\$156

Rack and Raised Floor Air Management

Part Number	Description	Shipping Dimensions	Installed	Weight (lb)	List Price
		(H x W x D Inches)			
ETN-CMRB19082U	Cable Strain Relief Bar 8"D	3 x 21 x 8	3.5 x 19 x 9	6	\$170
ETN-CMPD19031U	Horizontal Ring Manager 1U	3 x 21 x 8	1U x 19 x 4.2	4	\$79
ETN-CMPD19032U	Horizontal Ring Manager 2U	3 x 21 x 8	2U x 19 x 4.2	4	\$85
ETN-CMBPBRSH1U	Cable Pass-Thru Panel 1U w/Brush	6 x 9 x 4	1U x 19 x .5	1	\$94
ETN-CMBPBRSH2U	Cable Pass-Thru Panel 2U w/Brush	6 x 9 x 4	2U x 19 x .5	2	\$100
ETN-CMFD19041U	PatchLink Horizontal Cable Manager 1U	2 x 4 x 22	1U x 19 x 4	2	\$191
ETN-CMFD19042U	PatchLink Horizontal Cable Manager 2U	4 x 4 x 22	2U x 19 x 4	2	\$203
ETN-CMFP19032U	Upper Transition Tray 2U x 3.5"D	9 x 9 x 28	2U x 19 x 4	5	\$192
ETN-CMFP19052U	Upper Transition Tray 2U x 5.0"D	9 x 9 x 28	2U x 19 x 6	6	\$202
ETN-CMLT19032U	Lower Transition Tray 2U x 3.5"D	9 x 9 x 28	2U x 19 x 5	5	\$242
ETN-CMLT19052U	Lower Transition Tray 2U x 5.0"D	9 x 9 x 28	2U x 19 x 6	6	\$243
ETN-CMHD19242U	High Density Cable Organizer, w/rear transition tray 24" cabinet	9 x 9 x 28	2U x 19 x 24	5	\$843
ETN-CMHD19302U	High Density Cable Organizer, w/rear transition tray 30" cabinet	9 x 9 x 28	2U x 19 x 30	7	\$886
ETN-1032CAGE20	Cage Nut #10-32 Hardware Kit(Qty-20)	5 x 5 x 5	Internal	2	\$32
ETN-M6CAGE20	Cage Nut M6 Hardware Kit (Qty-20)	5 x 5 x 5	Internal	2	\$33

Top of Rack Cable Management

Part Number	Description	Shipping Dimensions	Installed	Weight (lb)	List Price
		(H x W x D Inches)			
ETN-LAD1006B	Cable Ladder Rack 6"W x 10'L BLK	2 x 7 x 122	1.5 x 6 x 120	12	\$266
ETN-LAD1012B	Cable Ladder Rack 12"W x 10'L BLK	2 x 13 x 122	1.5 x 12 x 120	24	\$294
ETN-JCMTLDRPD	Ladder Rack Bracket Perpendicular	6 x 10 x 5	Internal	5	\$196
ETN-JCMTLDRPR	Ladder Rack Bracket Parallel	6 x 10 x 5	Internal	5	\$145
ETN-JCMT24SP	Data Cable Partition Panel 24" Solid	6 x 6 x 48	5 x 24 x 2.5	3	\$144
ETN-JCMT24PP	Data Cable Partition Panel 24" Pass-Thru	6 x 6 x 48	5 x 24 x 2.5	3	\$152
ETN-JCMT24PT	Power Cable Trough 24"	3 x 33 x 16	5 x 24 x 10	7	\$266
ETN-JCMT30SP	Data Cable Partition Panel 30" Solid	6 x 6 x 48	5 x 30 x 2.5	4	\$152
ETN-JCMT30PP	Data Cable Partition Panel 30" Pass-Thru	6 x 6 x 48	5 x 30 x 2.5	4	\$171
ETN-JCMT30PT	Power Cable Trough 30"	6 x 6 x 48	5 x 30 x 10	8	\$301

Enclosure shipping and anchoring

Part Number	Description	Shipping Dimensions	Installed	Weight (lb)	List Price
		(H x W x D Inches)			
ETN-JANCHOR1	Floor Anchor Brackets	6 x 10 x 5	2.8 x 7 x 2.8	11	\$254
ETN-ENCMEDRAMP	Eaton Ramp for Medium Duty Pallet (Standard S-Series packaging)				\$370
ETN-ACCJCSTR40	Caster Kit - Qty 4 - for 42" Deep cabinet	10 x 10 x 40	4 x 31 x 6	40	\$450
ETN-ACCJCSTR45	Caster Kit - Qty 4 - for 48" Deep cabinet	10 x 10 x 40	4 x 36 x 6	45	\$503

Note: Call factory for heavy duty packaging options

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Eaton B-Line 2 & 4 Post Racks and Accessories

Maintain your critical applications with the first part of Eaton's Power Solution.

Available in three configurations to meet a variety of application requirements: three-inch upright, six-inch upright and Seismic Rack

- Simple, durable design holds up to repeated relocation
- Full range of accessories simplify cable management
- Flat black powder coat finish complements any data



TWO POST RACKS

Part Number	Description	Height (in./mm)	Width (in./mm)	Mounting width (in./mm)	Inside width (in./mm)	Base anchor spacing (in./mm)	Shipping Weight (lbs)	List Price
SB556084XUFB	Two Post Rack with three-inch uprights (unassembled)	84 / 2133	20.3 / 516	18.3 / 465	17.8 / 451	16 / 406	30	\$321
SB55608419U6FB	Two Post Rack with six-inch uprights (unassembled)	84 / 2133	20.3 / 516	18.8 / 465	17.8 / 451	16 / 406	30	\$541
SB588A	Anchor Kit (Four anchors and hardware)							\$38

TWO POST SEISMIC RACK

SB85219084FB	Two Post Seismic Relay Rack			84 / 2133	20.3 / 516	18.3 / 465	30	\$1,541
--------------	-----------------------------	--	--	-----------	------------	------------	----	---------

FOUR POST RACK

SB838084CFB	Four-post adjustable rack (45U)			84	19	30-36	59.5	\$1,015
-------------	---------------------------------	--	--	----	----	-------	------	---------

WALL MOUNT CABINETS

SB708193025FB	Wall-mounted swing gate rack (13U)	29.2	19	25	25	19.9	39	\$755
---------------	------------------------------------	------	----	----	----	------	----	-------

CABLE MANAGEMENT

Part Number	Description	Fits rack (U)	Height (in./mm)	Depth (in./mm)	Shipping Weight (lbs)	List Price
Cable managers						
SB86083S084FB	Single-sided cable manager for Two Post Rack	84	80.38	3.13	24.2	\$725
SB86083D084FB	Double-sided cable manager for Two Post Rack	84	80.38	3.13	45.3	\$961
Finger bracket						
SB860FSFB	Cable manager finger bracket		11U	4	0.9	\$34
SB860FSKFB	Replacement finger section, 11U, includes hardware				0.6	\$26
Cable Trays						
SB81319TT6FB	Top transition tray, 1 ½ inch high		6	19	4	\$202
SB81319UT6FB	Upper transition tray		6	19	4	\$202
Horizontal rackmount cable managers						
SB87019S1FB	1U horizontal cable manager		1U	19	2.1	\$90
SB87019S2FB	2U horizontal cable manager		2U	19	2.5	\$130
SB87019S3FB	3U horizontal cable manager		3U	19	2.8	\$136

Eaton B-Line 2 & 4 Post Racks and Accessories

Vertical cable managers

Part Number	Description	Height (in./mm)	Depth (in./mm)	Width (in./mm)	Shipping Weight (lbs)	List Price
SB57163S084FB	Single-sided 84-inch cabling	84	6.4	3.6	8	\$562
SB57163D084FB	Double-sided 84-inch cabling	84	12.8	3.6	24	\$623

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

SB571GROMMETKIT	Grommet kit				\$32
SB571BUSHINGKIT	Bushing kit				\$29

ACCESSORIES

ePDU brackets

SB3010	Fixed ePDU support bracket	4.82	1.75	1	\$43
SB3011	Adjustable ePDU support bracket	3.5	1.13	1	\$189

Double shelf

SB596S19103SFB	Steel double-sided shelf for three-inch uprights	4	20	14	\$166
SB596S19106SFB	Steel double-sided shelf for six-inch uprights	4	20	14	\$167

Single solid shelf

SB747S1915SFB	Steel, 15-inch deep single vented shelf	3	15	11	\$115
---------------	---	---	----	----	-------

Single vented shelf

SB747V1915SFB	Steel, 15-inch deep, single vented shelf	3	15	9.2	\$185
---------------	--	---	----	-----	-------

Tanlock by Eaton

Modular Access Control System for Eaton RS Enclosures

Eaton has partnered with best-in-class lock manufacturer Fath Mechatronics to provide our customers with the most versatile module access control system in the market. With two smart lock options available Tanock 3 (PoE) and Tanlock Zero (12V/24V), Tanlock by Eaton gives users the options required to effectively secure their rack enclosure.

Tanlock 3 - Provides Power of Ethernet (PoE) connectability - No peripherals required

Tanlock 0 - Provides connectivity via 5W/12W/24W

Multiple authentication technologies allows users to customize for their specific requirements:

Keypad, RFID, Fingerprint, Hand Vein Scanner, Touch Display, Dual Authentication PIN/RFID and Barcode/QR Code options.

Protocol support: LDAP, SNMP, RESTful API, SysLog

Configurable security by VLAN

Universal rack fit: Retrofit to any enclosure with standard 25mm x 50mm (x2) / 25mm x 150mm universal door cutouts.

Direct integration* with Eaton VPM and VCOM software offerings for simplified remote management, logging and access.

*Tanlock 3 required for VPM/VCOM direct integration



Catalog Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price
TL3-POE-KPAD	TANLock 3, black powder coated, w Keypad	2.25 x 3.25 x 11	2.2	\$1,060
TL3-POE-RFID	TANLock 3, black powder coated, w RFID Reader	2.25 x 3.25 x 11	2.2	\$1,092
TL3-POE-FNGR	TANLock 3, black powder coated, w Fingerprint reader	2.25 x 3.25 x 11	2.2	\$1,101
TL3-POE-PALM	TANLock 3, black powder coated, w Vein scanner (Palmreader)	2.25 x 3.25 x 11	2.2	\$4,186
TL3-POE-TCH	TANLock 3, black powder coated, w Touch display	2.25 x 3.25 x 11	2.2	\$1,099
TL3-POE-DUAL	TANLock 3, black powder coated, w Dual authentication PIN/RFID	2.25 x 3.25 x 11	2.2	\$1,119
TL3-POE-CODE	TANLock 3, black powder coated, for Bar Code / QR Code	2.25 x 3.25 x 11	2.2	\$1,019
TLZ-REMOTE	TANLock Zero, black powder coated, w remote opening	2.25 x 3.25 x 11	2.2	\$687
TLZ-KPAD	TANLock Zero, black powder coated, w Keypad	2.25 x 3.25 x 11	2.2	\$719
TLZ-TCH	TANLock Zero, black powder coated, w Touch Display	2.25 x 3.25 x 11	2.2	\$740
TLZ-RFID	TANLock Zero, black powder coated, w RFID 13.56 Mhz	2.25 x 3.25 x 11	2.2	\$780
TLZ-FNGR	TANLock Zero, black powder coated, w Fingerprint	2.25 x 3.25 x 11	2.2	\$791
TLZ-DUAL	TANLock Zero, black powder coated, w Dual authentication PIN/RFID	2.25 x 3.25 x 11	2.2	\$802

EATON POWER DISTRIBUTION, MONITORING AND ENCLOSURES

Eaton Branch and Subfeed Circuit Breakers MUST be purchased with an Accessory Cabinet

Eaton bolt-on branch circuit breakers can be installed in any 42-pole Eaton panelboard providing over-current and high interrupting current protection. Single-, double- and three-pole breakers can be provided from 10 to 100A trip rating and 10 or 22 kAIC.

Single-pole Breakers

Part Number	Trip Rating	kAIC	List Price
BAB1010	10A	10	\$17
BAB1015	15A	10	\$17
BAB1020	20A	10	\$17
BAB1025	25A	10	\$17
BAB1030	30A	10	\$17
BAB1035	35A	10	\$17
BAB1040	40A	10	\$17
BAB1045	45A	10	\$17
BAB1050	50A	10	\$17
BAB1055	55A	10	\$17
BAB1060	60A	10	\$17
QBHW1015	15A	22	\$28
QBHW1020	20A	22	\$28
QBHW1025	25A	22	\$28
QBHW1030	30A	22	\$28
QBHW1035	35A	22	\$28
QBHW1040	40A	22	\$28
QBHW1045	45A	22	\$28
QBHW1050	50A	22	\$28
QBHW1055	55A	22	\$28
QBHW1060	60A	22	\$28
GHB1010	10A	65	\$80
GHB1015	15A	65	\$80
GHB1020	20A	65	\$80
GHB1025	25A	65	\$80
GHB1030	30A	65	\$80
GHB1035	35A	65	\$80
GHB1040	40A	65	\$80
GHB1045	45A	65	\$80
GHB1050	50A	65	\$80
GHB1060	60A	65	\$80

Double-pole Breakers

Part Number	Trip Rating	kAIC	List Price
BAB2010	10A	10	\$34
BAB2015	15A	10	\$34
BAB2020	20A	10	\$34
BAB2025	25A	10	\$34

BAB2030	30A	10	\$34
BAB2035	35A	10	\$34
BAB2040	40A	10	\$34
BAB2045	45A	10	\$34
BAB2050	50A	10	\$34
BAB2055	55A	10	\$34
BAB2060	60A	10	\$34
BAB2070	70A	10	\$51
BAB2080	80A	10	\$67
BAB2090	90A	10	\$67
BAB2100	100A	10	\$67
QBHW2015	15A	22	\$59
QBHW2020	20A	22	\$59
QBHW2025	25A	22	\$59
QBHW2030	30A	22	\$59
QBHW2035	35A	22	\$59
QBHW2040	40A	22	\$59
QBHW2045	45A	22	\$59
QBHW2050	50A	22	\$59
QBHW2055	55A	22	\$59
QBHW2060	60A	22	\$59
QBHW2070	70A	22	\$82
QBHW2080	80A	22	\$105
QBHW2090	90A	22	\$105
QBHW2100	100A	22	\$105
GHB2015	15A	65	\$116
GHB2020	20A	65	\$116
GHB2030	30A	65	\$116
GHB2035	35A	65	\$116
GHB2040	40A	65	\$116
GHB2050	50A	65	\$116
GHB2060	60A	65	\$116
GHB2070	70A	65	\$191
GHB2080	80A	65	\$191
GHB2090	90A	65	\$191
GHB2100	100A	65	\$191

Three-pole Breakers

Part Number	Trip Rating	kAIC	List Price
BAB3015H	15A	10	\$97
BAB3020H	20A	10	\$97
BAB3025H	25A	10	\$97
BAB3030H	30A	10	\$97
BAB3035H	35A	10	\$97
BAB3040H	40A	10	\$97
BAB3045H	45A	10	\$97
BAB3050H	50A	10	\$97
BAB3055H	55A	10	\$97

BAB3060H	60A	10	\$97
BAB3070H	70A	10	\$107
BAB3080H	80A	10	\$155
BAB3090H	90A	10	\$155
BAB3100H	100A	10	\$155
QBHW3015H	15A	22	\$145
QBHW3020H	20A	22	\$145
QBHW3025H	25A	22	\$145
QBHW3030H	30A	22	\$145
QBHW3035H	35A	22	\$145
QBHW3040H	40A	22	\$145
QBHW3045H	45A	22	\$145
QBHW3050H	50A	22	\$145
QBHW3055H	55A	22	\$145
QBHW3060H	60A	22	\$145
QBHW3070H	70A	22	\$167
QBHW3080H	80A	22	\$224
QBHW3090H	90A	22	\$224
QBHW3100H	100A	22	\$224
GHB3015	15A	65	\$199
GHB3020	20A	65	\$199
GHB3025	25A	65	\$199
GHB3030	30A	65	\$199
GHB3035	35A	65	\$199
GHB3040	40A	65	\$199
GHB3045	45A	65	\$199
GHB3050	50A	65	\$199
GHB3060	60A	65	\$199
GHB3070	70A	65	\$199
GHB3080	80A	65	\$272
GHB3090	90A	65	\$272
GHB3100	100A	65	\$272

Note: Breakers cannot be purchased separately and have to be purchased with the Accessory Cabinets only.

EATON 3S UPS

Eaton series

Now featuring a
3-year warranty with
product registration!

Standby UPS (350–750 VA)

The sleek Eaton 3S delivers high efficiency and energy-saving battery backup and surge protection for your premium home and office equipment —ready to go right out of the box.

- Ease of use: Plug-and-play capability — features HID-compliant USB port for automatic integration with Windows, Mac and Linux (no drivers required)
- EcoControl for 30% greater energy savings than a typical battery backup
- Attractive design and glossy finish make the 3S a perfect fit for the modern office environment
- Up to 10 receptacles — (5) battery backup and surge protection, (5) surge protection only
- Protection for devices connected to telephone, fax and Ethernet lines (10/100 Mbit only)
- User-replaceable battery
- Integrated graceful shutdown capability for connected devices
- Simulated sine wave output on battery
- Warranty (US and Canada): Three-year limited warranty on UPS and Battery (third year of warranty free with online product registration), \$25,000 load protection guarantee



3S NORTH AMERICAN MODELS: 120V, 50/60 Hz

Model	Part Number	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
3S 350	3S350	350/200	5-15P	(8) 5-15R Outlets (4 Battery Backup & 4 Surge Protection only)	3.4 x 5.5 x 13.2	6.6	\$65
3S 550	3S550	550/330	5-15P	(8) 5-15R Outlets (4 Battery Backup & 4 Surge Protection only)	3.4 x 5.5 x 13.2	7.3	\$81
3S 750	3S750	750/450	5-15P	(10) 5-15R Outlets (5 Battery Backup & 5 Surge Protection only)	3.4 x 6.7 x 13.2	9.7	\$116

SOFTWARE

To enable EcoControl functionality on the 750 VA unit, download Eaton UPS Companion software at www.eaton.com/ManageSmarter; the Intelligent Power Software Suite is also available for download free of charge at the link. See the software and connectivity product sections for more detail.

3S BATTERY BACKUP TIMES (in minutes)

3S BATTERY BACKUP TIMES (in minutes)

UPS model	Load	50W	100W	150W	200W	250W	300W	350W	400W	450W
3S350		30	12	7	5					
3S550		42	18	11	6	4				
3S750		61	31	20	13	10	7	6	4	3

Note: Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

Services

For detailed information on service plans, please refer to the Single-phase Service section.

EATON 5S UPS TOWER

Line-interactive UPS (550 – 1500 VA)

120V models not for sale or distribution in CO, VT or WA

Now featuring a
3-year warranty with
product registration!

- Power management: Enhance your power protection capabilities and ensure safe system shutdown with the Eaton UPS Companion software. The 5S interface is auto-recognized when plugged into computers with Windows, Macintosh and Linux environments
- LCD display: Access critical UPS information including battery time and load level in a single screen view with the user-friendly LCD
- Data protection: Safeguard your work and data with the UPS Companion software by gracefully shutting down your equipment during power outages
- Eco-Control: Save up to 30 percent on energy consumption by shutting down non-essential peripherals when the connected computer is turned off
- Convenient form factor: Fit the 5S easily into tight spaces with its slim form factor. The versatile 5S can be used as a tower or as a desktop monitor stand
- Simulated sine wave output on battery
- Warranty (US and Canada): Three-year limited warranty on UPS and Battery (third year of warranty free with online product registration)



5S NORTH AMERICAN MODELS: 120V, 50/60 Hz

Catalog Number	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Net Weight (lb)	LCD	Eco Control	List Price
5S550	550/330	5-15P (6ft)	(8) 5-15R	9.8 x 3.4 x 10.2	12.6	No	No	\$122
5S700	700/420	5-15P (6ft)	(8) 5-15R	9.8 x 3.4 x 10.2	14.7	No	No	\$135
5S700LCD	700/420	5-15P (6ft)	(8) 5-15R	9.8 x 3.4 x 10.2	15.1	Yes	Yes	\$142
5S1000LCD	1000/600	5-15P (6ft)	(10) 5-15R	9.8 x 3.4 x 15.0	21.7	Yes	Yes	\$171
5S1500LCD	1500/900	5-15P (6ft)	(10) 5-15R	9.8 x 3.4 x 15.0	26.1	Yes	Yes	\$229

5S INTERNATIONAL MODELS: 208 or 230V, 50/60 HZ

Catalog Number	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Net Weight (lb)	LCD	Eco Control	List Price
5S700G	700/420	C14	(6) C13	9.8 x 3.4 x 10.2	13.2	No	No	\$176
5S1500G	1500/900	C14	(8) C13	9.8 x 3.4 x 15.0	24.6	No	No	\$313

SOFTWARE

The UPS Companion software is available for download free of charge. See the software and connectivity product sections for more detail.

5S BATTERY BACKUP TIMES (in minutes)

UPS model														
Load	30W	60W	90W	120W	150W	180W	210W	240W	270W	300W	330W	360W	390W	420W
5S550	121	56	31	20	14	10	8	6	5	4	1			
5S700	151	75	37	30	21	14	12	11	9	7	6	5	3	2
5S700G	151	75	37	30	21	14	12	11	9	7	6	5	3	2
5S700LCD	86	67	36	27	20	15	11	9	7	6	5	4	2	2
UPS model														
Load	120W	180W	240W	300W	360W	420W	480W	540W	600W	660W	720W	780W	840W	900W
5S1000LCD	43	26	18	14	10	9	6	4	3					
5S1500G	79	43	30	22	17	13	10	9	8	6	5	4	3	2
5S1500LCD	71	42	31	22	16	13	10	8	7	6	5	4	3	2

Note: Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 5SC UPS

Line-interactive UPS (550 – 1500 VA)

120V models not for sale or distribution in CO, VT or WA

Now featuring a
3-year warranty with
product registration!

The 5SC offers flexible integration with a small form factor and adjustable input waveform sensitivity, making it ideal for protecting tower servers, network-attached storage (NAS), network equipment, ATMs, tickets machines and kiosks.

- LCD display: Enables you to customize UPS settings, view load and power consumption
- Advanced Battery Management (ABM) extends battery life and provides advanced warning of battery failure
- True sine wave output on battery for compatibility with PFC power supplies of computers and servers
- Power management: Integrates with Intelligent Power Manager (IPM) for point-to-point power management (USB/serial) or network-based using server as a proxy
- User-replaceable batteries
- Warranty and service: Protects you with a three-year warranty, which includes the battery, \$150,000 load protection guarantee
- Reliable power protection: Corrects a wide range of input voltage variations with AVR; provides high quality, pure sine wave output on battery and ensures consistent voltage is provided to any sensitive connected equipment
- Convenient form factor: Fits easily into small spaces, making the 5SC ideal for protecting tower servers, Network-attached storage (NAS), network equipment, ATMs, ticket machines and kiosks



5SC NORTH AMERICAN MODELS: 120V, 50/60 Hz

Catalog Number	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5SC500	500/350	5-15P (6 ft)	(4) 5-15R	8.2 x 5.9 x 9.4	15.2	\$220
5SC750	750/525	5-15P (6 ft)	(6) 5-15R	8.2 x 5.9 x 13.4	23.1	\$320
5SC1000	1000/700	5-15P (6 ft)	(8) 5-15R	8.2 x 5.9 x 13.4	25.6	\$365
5SC1500	1440/1080	5-15P (6 ft)	(8) 5-15R	8.2 x 5.9 x 16.1	34	\$471

5SC INTERNATIONAL MODELS: 208 or 230V, 50/60 Hz

Catalog Number	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5SC750G	750/525	C14	(6) C13	8.2 x 5.9 x 13.4	23.1	\$459
5SC1500G	1500/1050	C14	(8) C13	8.2 x 5.9 x 16.1	33.5	\$676

SOFTWARE

The Intelligent Power Software Suite is available for download free of charge. See the software and connectivity product sections for more detail.

5SC BATTERY BACKUP TIMES (in minutes)

UPS model												
Wattage	18	28	35	70	105	140	175	210	245	280	315	350
5SC500	118	89	64	29	19.6	16.3	12.1	10.4	8.9	7.1	5.3	4.7
Wattage	26	42	53	105	158	210	263	315	368	420	473	525
5SC750	120	89	71	36	24	16.6	12.6	10.6	8.7	7	6	5
5SC750G	124	100	74	38	23	16.5	12.6	10.7	8.8	7	6	4.9
Wattage	35	56	70	140	210	280	350	420	490	560	630	700
5SC1000	111	85	66	35.5	23	17	12.7	10.6	8.7	7	5.9	4.8
Wattage	54	86	108	216	324	432	540	648	756	864	972	1080
5SC1500	136	111	90	40.7	24.9	17.5	12.8	10.5	8.6	6.9	5.9	5
5SC1500G	144	109	90	41	24.7	17.3	12.7	10.4	8.4	6.8	5.8	4.8

Note: Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 5P UPS RACKMOUNT

Line-interactive UPS (550–3000 VA)

≤1.5 kVA 120V and below models not for sale or distribution in CO, VT or WA

Now featuring a
3-year warranty with
product registration!

The Eaton 5P Rackmount UPS provides enhanced power conditioning with line-interactive topology and pure sinewave output for distributed IT equipment

- Compatible with the UL 2900-2-2 compliant Eaton Gigabit Network Card (Network-M2)
- Advanced Battery Management (ABM) extends battery life and provides advanced warning of battery failure
- Lithium-ion batteries (LFP chemistry) available in select 5P 1U rackmount models
- Fully integrates with Intelligent Power Software Suite for monitoring and management of servers and graceful shutdown of virtualized environments
- Provides more real power (watts) to protect more equipment for expanding IT systems
- Warranty (US and Canada) - Lead acid UPS: Three-year limited warranty on UPS and batteries free with online product registration, five-year extended warranty plans available.
- Warranty (US and Canada) - Lithium-ion UPS: Five-year limited warranty on UPS and batteries standard
- \$150,000 load protection guarantee



5P RACKMOUNT COMPACT 2U MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P750RC	5P 750 VA 120V Rack Compact 2U	750/600	5-15P (6 ft)	(10) 5-15R	3.4 (2U) x 17.4 x 16.0	31	\$555
5P1000RC	5P 1000 VA 120V Rack Compact 2U	1000/770	5-15P (6 ft)	(10) 5-15R	3.4 (2U) x 17.4 x 16.0	33	\$708
5P1500RC	5P 1500 VA 120V Rack Compact 2U	1440/1100	5-15P (6 ft)	(10) 5-15R	3.4 (2U) x 17.4 x 16.0	41	\$904

5P RACKMOUNT 1U MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P550R	5P 550 VA 120V Rackmount 1U	550/420	5-15P (6 ft)	(5) 5-15R	1.7 (1U) x 17.2 x 14.3	20	\$467
5P750R	5P 750 VA 120V Rackmount 1U	750/600	5-15P (6 ft)	(5) 5-15R	1.7 (1U) x 17.2 x 20.0	31	\$692
5P1000R	5P 1000 VA 120V Rackmount 1U	1000/770	5-15P (6 ft)	(5) 5-15R	1.7 (1U) x 17.2 x 20.0	33	\$880
5P1500R	5P 1500 VA 120V Rackmount 1U	1440/1100	5-15P (6 ft)	(5) 5-15R	1.7 (1U) x 17.2 x 21.8	44	\$1,073
5P1500R-L	5P 1500 VA 120V RM 1U Lithium-ion	1440/1100	5-15P (6 ft)	(5) 5-15R	1.7 (1U) x 17.2 x 21.8	35	\$1,942

5P RACKMOUNT 1U MODELS: 200-240V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P850GR	5P 850 VA 208V Rackmount 1U	850/600	C14	(4) C13	1.7 (1U) x 17.2 x 20.0	30	\$866
5P1550GR	5P 1550 VA 208V Rackmount 1U	1550/1100	C14	(6) C13	1.7 (1U) x 17.2 x 21.8	43	\$1,130
5P1550GR-L	5P 1550 VA 208V RM 1U Lithium-ion	1550/1100	C14	(6) C13	1.7 (1U) x 17.2 x 21.8	35	\$2,113

5P RACKMOUNT 2U MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P1500RT	5P 1500 VA 120V Rack / Tower 2U	1440/1440	5-15P	(8) 5-15R	3.4 (2U) x 17.4 x 20.6	72	\$1,008
5P2200RT	5P 2200 VA 120V Rack / Tower 2U	1950/1920	5-20P	(8) 5-15/20R	3.4 (2U) x 17.4 x 20.6	73	\$1,478
5P3000RT	5P 3000 VA 120V Rack / Tower 2U	3000/2700	L5-30P	(6) 5-15/20R, (1) L5-30R	3.4 (2U) x 17.4 x 25.5	95	\$1,770

EATON 5P UPS RACKMOUNT

Line-interactive UPS (550–3000 VA)

5P OPTIONS

Catalog Number	Description	Rating (VA)	For use with 5PX model	Note	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Two-post rail kit							
RK2PA	2-post rack mounting kit 1U		All Models except 5P550R*	*5P550R uses ears only			\$101
103007018-5591	2-post rack mounting kit RT		All RT Models				\$101

*See user's manual for more detail on 2-post rack mounting

Catalog Number	Description	For use with 5P model	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
Power distribution and maintenance bypass						
EHBPL1500R-PDU1U	HotSwap Maintenance Bypass (MBP)	5P1500RT	5-15P	(6) 5-15R	2.1 x 17.3 x 3.8	\$321
EHBPL2000R-PDU1U	HotSwap Maintenance Bypass (MBP)	5P2200RT	5-20P	(6) 5-20R	2.1 x 17.3 x 3.8	\$384
EHBPL3000R-PDU1U	HotSwap Maintenance Bypass (MBP)	5P3000RT	L5-30P	(5) 5-20R	2.1 x 17.3 x 3.8	\$557

SOFTWARE AND CONNECTIVITY OPTIONS

NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
RELAY-MS	Relay / Serial Interface Card	\$139
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with Network-M2 only)	\$291

See software and connectivity product sections for more detail.

5P RACKMOUNT BATTERY BACKUP TIMES (in minutes)

UPS model										
Load (watts)	50	100	200	400	600	700	800	1000	1500	2500
5P550R	37	19	9	3						
5P750R		40	19	8	4					
5P850GR		45	20	8	4					
5P1000R		51	25	11	7	6				
5P1500R			47	20	12	10	8	5		
5P1550GR			50	20	12	10	7	5		
5P1500RT			56	26	15	11	9	7	3	
5P2200RT			59	33	20	16	13	8	4	
5P3000RT				41	27	22	18	14	9	4
5P750RC	60	45	20	8	5					
5P1000RC		52	26	11	7	6				
5P1500RC			50	21	12	10	8	6		
Load (watts)	110	220	330	440	550	660	770	880	990	1100
5P1500R-L	70	34	21	15	11	9	7	6	5	4
5P1550GR-L	70	34	21	15	11	9	7	6	5	4

Note: Runtimes are displayed in minutes. Runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive graphs at www.eaton.com/5Pm.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 5P UPS TOWER

Line-interactive UPS (750–3000 VA)

≤1.5 kVA 120V and below models not for sale or distribution in CO, VT or WA

Now featuring a
3-year warranty with
product registration!

The Eaton 5P Tower UPS provides enhanced power conditioning with line-interactive topology and pure sinewave output for distributed IT equipment

- Compatible with the UL 2900-2-2 compliant Eaton Gigabit Network Card (Network-M2)
- Advanced Battery Management (ABM) extends battery life and provides advanced warning of battery failure
- Customize UPS settings, view load and power consumption through the graphical interactive LCD screen interface
- Fully integrates with Intelligent Power Software Suite for monitoring and management of servers and graceful shutdown of virtualized environments
- Provides more real power (watts) to protect more equipment for expanding IT systems
- Warranty (US and Canada): Three-year limited warranty (third year of warranty free with online product registration), five-year extended warranty plans available, \$150,000 load protection guarantee



5P TOWER MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P750	5P 750 120V Tower	750/600	5-15P (6ft)	(8) 5-15R	9.1 x 5.9 x 13.6	24	\$414
5P1000	5P 1000 120V Tower	1000/770	5-15P (6ft)	(8) 5-15R	9.1 x 5.9 x 13.6	25	\$555
5P1500	5P 1500 120V Tower	1440/1100	5-15P (6ft)	(8) 5-15R	9.1 x 5.9 x 17.5	36	\$677
5P2200	5P 2200 120V Tower	1950/1920	5-20P (6ft)	(8) 5-15/20R	3.4 (2U) x 17.4 x 20.6	73	\$1,150
5P3000	5P 3000 120V Tower	3000/2700	L5-30P (10 ft)	(6) 5-15/20R, (1) L5-30R	3.4 (2U) x 17.4 x 25.5	81	\$1,564

5P TOWER MODELS: 200-240V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5P850G	5P 850 VA 208V Tower	850/600	C14	(6) C13	9.1 x 5.9 x 13.6	23	\$458
5P1550G	5P 1550 VA 208V Tower	1550/1100	C14	(8) C13	9.1 x 5.9 x 17.5	34	\$803

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
RELAY-MS	Relay / Serial Interface Card	\$139
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with Network-M2 only)	\$291

See software and connectivity product sections for more detail.

5P TOWER BATTERY BACKUP TIMES (in minutes)

UPS model	50	100	200	400	600	700	800	1000	1500	2500
5P750		40	19	8	4					
5P850G										
5P1000		51	25	11	7	6				
5P1500			47	20	12	10	8	5		
5P1550G										
5P3000				41	27	22	18	14	9	4

Note: Runtimes are displayed in minutes. Runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive runtime graphs at www.eaton.com/5P.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 5PX UPS RACK/TOWER

Extended Run Capable

\$1.5 kVA 120V and below models not for sale or distribution in CO, VT or WA



Now featuring a
3-year warranty with
product registration!

Line-interactive UPS (1000–3000 VA)

The Eaton 5PX UPS provides enhanced power conditioning with line-interactive topology and pure sinewave output for distributed IT equipment with extended runtime options

- Extended runtime available by adding up to 4 External Battery Modules (EBMs)
- Compatible with the UL 2900-2-2 compliant Eaton Gigabit Network Card (Network-M2) for enhanced cybersecurity
- Advanced Battery Management (ABM) extends battery life and provides advanced warning of battery failure
- Meters energy consumption down to the outlet segments/groups
- Displays critical UPS information in a next-generation graphical LCD
- TAA-compliant models available
- Comes with free monitoring and management software, perfect for virtualized environments
- Hot-swappable batteries allow you to replace batteries while the UPS stays on
- Load segments enable shutdown of connected devices for increased runtime via load shedding
- 4-post rail kit included (2-post rail kit optional)
- Warranty (US and Canada): Three-year limited warranty (third year of warranty free with online product registration), five-year extended warranty plans available, \$150,000 load protection guarantee



5PX NORTH AMERICAN MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5PX1000RT	Eaton 5PX 1000 VA 120V Rack Tower 2U	1000/1000	5-15P (8ft)	(8) 5-15R	3.4 (2U) x 17.4 x 20.6	62	\$778
5PX1500RT	Eaton 5PX 1500 VA 120V Rack Tower 2U	1440/1440	5-15P (8ft)	(8) 5-15R	3.4 (2U) x 17.4 x 20.6	65	\$1,008
5PX1500RTN	Eaton 5PX 1500 VA with Network Card-M2	1440/1440	5-15P (8ft)	(8) 5-15R	3.4 (2U) x 17.4 x 20.6	65	\$1,389
5PX2200RT	Eaton 5PX 2200 VA 120V Rack Tower 2U	1950/1920	5-20P (8ft)	(8) 5-15/20R	3.4 (2U) x 17.4 x 20.6	65	\$1,748
5PX2200RTN	Eaton 5PX 2200 VA with Network Card-M2	1950/1920	5-20P (8ft)	(8) 5-15/20R	3.4 (2U) x 17.4 x 20.6	65	\$2,129
5PX3000RT2U	Eaton 5PX 3000 VA 120V Rack Tower 2U	3000/2700	L5-30P (10ft)	(6) 5-15/20R, (1) L5-30R	3.4 (2U) x 17.4 x 25.4	87	\$2,092
5PX3000RTN	Eaton 5PX 3000 VA with Network Card-M2	3000/2700	L5-30P (10ft)	(6) 5-15/20R, (1) L5-30R	3.4 (2U) x 17.4 x 25.4	87	\$2,473
5PX3000RT3U	Eaton 5PX 3000 VA 120V Rack Tower 3U	3000/2700	L5-30P (10ft)	(6) 5-15/20R, (1) L5-30R	5.1 (3U) x 17.4 x 19.6	86	\$2,173

5PX TAA COMPLIANT MODELS*

Number	Description	(VA/Watts)	Connection	Receptacles	(H x W x D, inches)	(lb)	Price
5PX1500RTUS	Eaton 5PX 1500 VA 120V Rack / Tower 2U	1440/1440	5-15P (8ft)	(8) 5-15R	3.4 (2U) x 17.4 x 20.6	65	\$1,398
5PX2200RTUS	Eaton 5PX 2200 VA 120V Rack / Tower 2U	1950/1920	5-20P (8ft)	(8) 5-15/20R	3.4 (2U) x 17.4 x 20.6	65	\$2,010
5PX3000RT2US	Eaton 5PX 3000 VA 120V Rack / Tower 2U	3000/2700	L5-30P (10ft)	(6) 5-15/20R, (1) L5-30R	3.4 (2U) x 17.4 x 25.4	87	\$2,443

*Note: 5PX TAA EBM models are listed under 5PX options

5PX INTERNATIONAL MODELS: 208/230V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5PX1500IRT	Eaton 5PX 1500 VA 208/230V Rack / Tower 2U	1500/1350	C14	(8) C13	3.4 (2U) x 17.4 x 20.6	61	\$1,170
5PX2200IRT	Eaton 5PX 2200 VA 208/230V Rack / Tower 2U	2200/1980	C20	(1) C19, (8) C13	3.4 (2U) x 17.4 x 20.6	63	\$2,048
5PX3000IRT2U	Eaton 5PX 3000 VA 208/230V Rack / Tower 2U	3000/2700	C20	(1) C19, (8) C13	3.4 (2U) x 17.4 x 25.4	84	\$2,396

5PX OPTIONS

Catalog Number	Description	Rating (VA)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
5PX3000IRTN	Eaton 5PX 3000 VA with Network Card-M2	3000/2700	C20 (1) C19, (8) C13	84	\$2,777

Extended Battery Modules			For Use With Model			
5PXEBM48RT	Eaton 5PX 48V EBM Rack / Tower 2U	48V	5PX1000RT, 5PX1500RT, 5PX2200RT	3.4 (2U) x 17.4 x 20.0	72	\$675
5PXEBM72RT2U	Eaton 5PX 72V EBM Rack / Tower 2U	72V	5PX3000RT2U	3.4 (2U) x 17.4 x 25.5	102	\$954
5PXEBM72RT3U	Eaton 5PX 72V EBM Rack / Tower 3U, short depth	72V	5PX3000RT3U	5.1 (3U) x 17.4 x 19.6	98	\$1,010
5PXEBM48RTUS	Eaton 5PX 48V EBM TAA Rack / Tower 2U	48V	5PX1000RT, 5PX1500RT, 5PX2200RT	3.4 (2U) x 17.4 x 20.0	72	\$980
5PXEBM72RT2US	Eaton 5PX 72V EBM TAA Rack / Tower 2U	72V	5PX3000RT2U	3.4 (2U) x 17.4 x 25.5	102	\$1,191
						List Price
Two-post rail kit						
103007018-5591	Two-post rack mounting rail kit (supports 2U models only)					\$101

Power distribution and maintenance bypass

Catalog Number	Description	For use with 5PX model	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
EHBPL1500R-PDU1U	HotSwap Maintenance Bypass (MBP)	5PX1000RT, 5PX1500RT	5-15P	(6) 5-15R	2.1 x 17.3 x 3.8	\$321
EHBPL2000R-PDU1U	HotSwap Maintenance Bypass (MBP)	5PX2200RT	5-20P	(6) 5-15/20R	2.1 x 17.3 x 3.8	\$384
EHBPL3000R-PDU1U	HotSwap Maintenance Bypass (MBP)	5PX3000RT2U	L5-30P	(5) 5-15/20R	2.1 x 17.3 x 3.8	\$557

For detailed information on FlexPDU and HotSwap Maintenance Bypass products, please refer to the Eaton Power Distribution and Enclosures section.

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
RELAY-MS	Relay / Serial Interface Card	\$139
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with Network-M2 only)	\$291

See software and connectivity product sections for more detail.

Extended Run Capable

5PX BATTERY BACKUP TIMES (in minutes) ¹					
Load (VA/Watts)	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
5PX1000RT (with 5PXEBM48RT)					
100/70	120	462	796	1131	1466
250/175	69	286	490	695	899
500/350	30	145	254	364	473
750/525	17	83	151	219	286
1000/700	11	59	108	156	204
1000/1000 ²	7	39	71	103	135
5PX1500RT (with 5PXEBM48RT)					
150/105	81	334	550	765	981
375/262	43	187	315	442	569
750/525	18	87	150	214	277
1125/787	9	50	89	129	169
1440/1050	6	35	66	96	126
1440/1440 ²	3	21	41	62	82
5PX2200RT (with 5PXEBM48RT)					
195/136	71	274	465	656	847
488/341	39	154	270	385	501
975/682	16	67	123	179	236
1463/1045	8	36	67	93	128
1950/1365	5	26	48	65	93
2200/1920 ²	3	15	29	36	57
5PX3000RT2U or 5PX3000RT3U (with 5PXEBM72RT2U or 5PXEBM72RT3U)					
300/210	63	273	470	667	864
750/525	31	148	254	360	465

View interactive runtime graphs at www.eaton.com/5PX

1500/1050	13	64	111	158	206
2250/1575	8	35	64	94	123
3000/2100	6	26	48	70	91
3000/2700 ²	4	19	35	52	68

1. Battery backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc. International model runtimes are available; please visit www.eaton.com/5PX for details. 2. Runtimes shown at full load with maximum power factor.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.


EATON 5PX G2 UPS RACK/TOWER

Extended runtime capable, Next-generation UPS

Line-interactive UPS (1000–3000 VA)

The Eaton 5PX G2 UPS provides secure, connected power protection with extended runtime capability for distributed IT

- Extended runtime available by adding up to (4) Extended Battery Modules (EBMs)
- 5PX G2 models use lead-acid batteries only at this time
- Up to 25% or more standard runtime with only the internal batteries for 1.5 kVA and 2 kVA models compared to legacy 5PX
- Compatible with the optional UL 2900-1 and IEC 62443-4-2 compliant Eaton Gigabit Network Card (NETWORK-M2) and Industrial Gateway Card (INDGW-M2) for enhanced cybersecurity
- Network Bundle models (with "RTN" in the part number) include a factory pre-installed Gigabit Network Card
- Advanced Battery Management (ABM) extends battery life and provides advanced warning of battery failure
- Pure sinewave output in battery mode
- Displays critical UPS information in a next-generation graphical LCD and new LED light bar for easy UPS status identification
- Protects more devices with the highest possible watt output per VA rating (unity output PF)
- Compatible with Eaton Intelligent Power Manager (IPM) and Visual Power Manager (VPM) software
- Hot-swappable batteries (by qualified persons) allow you to replace batteries while the UPS stays on
- Load segments enable shutdown of connected devices for increased runtime via load shedding
- 4-post rail kit included (2-post rail kit optional); optional 4-post "ship-in-rack" rail kit available (RK4PRS)
- For TAA applications, see legacy 5PX TAA models; 5PX G2 does not offer TAA-compliant models at this time
- Warranty (US and Canada): Three-year limited warranty on the UPS and batteries, five-year extended warranty plans available, plus a \$150,000 load protection guarantee



5PX G2 NORTH AMERICAN MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	MSRP Price
5PX1000RTG2	Eaton 5PX G2 1000 VA 120V 2U Rack/Tower	1000/1000	5-15P (10ft)	(8) 5-15R	3.4 (2U) x 17.2 x 17.6	44.5	\$778
5PX1000RTNG2	Eaton 5PX G2 1000 VA 120V 2U Rack/Tower w/ NETWORK-M2 card	1000/1000	5-20P (10ft)	(8) 5-15R	3.4 (2U) x 17.2 x 17.6	44.5	\$1,159
5PX1500RTG2	Eaton 5PX G2 1440 VA 120V 2U Rack/Tower	1440/1440	5-20P (10ft)	(8) 5-15R	3.4 (2U) x 17.2 x 17.6	50.7	\$1,036
5PX1500RTNG2	Eaton 5PX G2 1440 VA 120V 2U Rack/Tower w/ NETWORK-M2 card	1440/1440	5-20P (10ft)	(8) 5-15R	3.4 (2U) x 17.2 x 17.6	50.7	\$1,417
5PX2000RTG2	Eaton 5PX G2 2000 VA 120V 2U Rack/Tower 2U	1950/1950	5-20P (10ft)	(1) L5-20R (6) 5-15/20R	3.4 (2U) x 17.2 x 23.7	65.3	\$1,781
5PX2000RTNG2	Eaton 5PX G2 2000 VA 120V 2U Rack/Tower w/ NETWORK-M2 card	1950/1950	5-20P (10ft)	(1) L5-20R (6) 5-15/20R	3.4 (2U) x 17.2 x 23.7	65.3	\$2,162
5PX2000RT3UNG2	Eaton 5PX G2 2000 VA 120V 3U Rack/Tower w/ NETWORK-M2 card, Short Depth	1950/1950	5-20P (10ft)	(1) L5-20R (6) 5-15/20R	5.1 (3U) x 17.2 x 19.0	64.2	\$2,090
5PX3000RTG2	Eaton 5PX G2 3000 VA 120V 2U Rack/Tower	3000/3000	L5-30P (10ft)	(1) L5-30R (6) 5-15/20R	3.4 (2U) x 17.2 x 23.7	74.5	\$2,132
5PX3000RTNG2	Eaton 5PX G2 3000 VA 120V 2U RT w/ NETWORK-M2 card	3000/3000	L5-30P (10ft)	(1) L5-30R (6) 5-15/20R	3.4 (2U) x 17.2 x 23.7	74.5	\$2,513
5PX3000RT3UNG2	Eaton 5PX G2 3000 VA 120V 3U Rack/Tower w/ NETWORK-M2 card, Short Depth	3000/3000	L5-30P (10ft)	(1) L5-30R (6) 5-15/20R	5.1 (3U) x 17.2 x 19.0	72.8	\$2,405

5PX G2 GLOBAL MODELS: 208/230V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	MSRP Price
5PX1500HRTG2	Eaton 5PX G2 1500 VA 200-240V 2U Rack/Tower	1500/1500	C14	(8) C13	3.4 (2U) x 17.2 x 17.6	49.4	\$1,204
5PX2200HRTG2	Eaton 5PX G2 2200 VA 200-240V 2U Rack/Tower	2200/2200	L6-20P (6ft Detachable) or C20	(2) C19 (8) C13	3.4 (2U) x 17.2 x 23.7	62.2	\$2,087
5PX3000HRTG2	Eaton 5PX G2 3000 VA 200-240V 2U Rack/Tower	3000/3000	L6-20P (6ft Detachable) or C20	(2) C19	3.4 (2U) x 17.2 x 23.7	69.9	\$2,465
5PX3000HRTNG2	Eaton 5PX G2 3000 VA 200-240V 2U Rack/Tower w/ NETWORK-M2 card	3000/3000	L6-20P (6ft Detachable) or C20	(2) C19 (8) C13	3.4 (2U) x 17.2 x 23.7	69.9	\$2,846

SPX OPTIONS

Extended Battery Modules (EBMs)		DC Voltage	For Use With Models	Dimensions (H x W x D, inches)	Weight (lb)	MSRP Price
5PXEBM48RTG2	Eaton 5PX 48V EBM 2U Rack/Tower	48 Vdc	All 5PX G2 2U UPS models rated at 1 kVA and 1.5 kVA only	3.4 (2U) x 17.2 x 17.6	61.3	\$688
5PXEBM72RTG2	Eaton 5PX 72V EBM 2U Rack/Tower	72 Vdc	All 5PX G2 2U UPS models rated at 2 kVA , 2.2 kVA or 3 kVA only	3.4 (2U) x 17.2 x 23.7	89.1	\$981
5PXEBM72RT3UAG2	Eaton 5PX 72V EBM 3U Rack/Tower	72 Vdc	5PX G2 3U UPS models rated at 2 kVA or 3 kVA only	5.1 (3U) x 17.2 x 19.0	87.5	\$981

Accessory Rack Mounting Kit Options						List Price
103007018-5591	Two-post rack mounting rail kit (designed for 2U models only)					
RK4PRS	4-post ship-in-rack rail kit (required to ship 5PX G2 UPS or EBMs while mounted in a rack on a shock pallet)					\$101

Power Distribution and Maintenance Bypass

Catalog Number	Description	For use with 5PX G2 models	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
EHBPL1500R-PDU1U	HotSwap Maintenance Bypass (MBP)	1-1.5 kVA 120V models	5-15P	(6) 5-15R	2.1 x 17.3 x 3.8	\$321
EHBPL2000R-PDU1U	HotSwap Maintenance Bypass (MBP)	2 kVA 120V models	5-20P	(6) 5-20R	2.1 x 17.3 x 3.8	\$384
EHBPL3000R-PDU1U	HotSwap Maintenance Bypass (MBP)	3 kVA 120V models	L5-30P	(5) 5-20R	2.1 x 17.3 x 3.8	\$557

For detailed information on FlexPDU and HotSwap Maintenance Bypass products, please refer to the Eaton Power Distribution and Enclosures section.

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
RELAY-MS	Relay / Serial Interface Card	\$139
EM PDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

For battery runtime charts of each model, see www.eaton.com/SPXG2 and view the specs for the model in question after launch.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

Eaton 9SX UPS Tower

Online UPS (700–3000 VA)

The Eaton 9SX UPS is ideal for critical applications with harsh electrical environments including IT, industrial automation and control, and healthcare. It's built for scalable deployment with a graphical LCD interface that enables local access to configurations and settings, history, diagnostics, energy consumption and load segment control.

- 5-button graphical LCD menu provide access to settings, alerts and history for quick unit setup and first time issue resolution
- True tower form factor, perfect for OEM and industrial applications
- More real power (watts) to protect more equipment
- Increases battery service life and system uptime up to 50% with ABM battery-charging technology and user-replaceable batteries
- Maximizes runtimes with optional extended battery modules (available for all units except the 700 VA tower models)
- Ships with free monitoring and management software, perfect for virtualized environments
- Warranty (US and Canada): Two-year limited warranty, three and five-year extended warranty plans available, \$250,000 load protection guarantee



9SX NORTH AMERICAN TOWER MODELS: 120V, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection ¹	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9SX700 ²	9SX 700 120V TOWER	700/630	5-15P	(6) 5-15R	9.9 x 6.3 x 13.9	26.5	\$1,118
9SX1000	9SX 1000 120V TOWER	1000/900	5-15P	(6) 5-15R	9.9 x 6.3 x 15.1	30.9	\$1,404
9SX1500	9SX 1500 120V TOWER	1500/1350	5-15P	(6) 5-15R	9.9 x 6.3 x 17.0	41.9	\$1,951
9SX2000	9SX 2000 120V TOWER	1960/1770	5-20P	(1) L5-20, (6) 5-20R	13.6 x 8.4 x 16.2	77.2	\$2,534
9SX3000	9SX 3000 120V TOWER	3000/2700	L5-30P	(1) L5-30R, (4) 5-20R	13.6 x 8.4 x 16.2	77.2	\$4,136
9SX3000HW	9SX 3000 120V TOWER	3000/2700	Hardwired	Hardwired	13.6 x 8.4 x 16.2	77.2	\$4,136

1. Input cord length is 8 ft
2. 9SX700 does not have a compatible EBM

9SX GLOBAL TOWER MODELS: 208V⁶, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9SX1000G	9SX 1000 208V TOWER	1000/900	C14 ³	(6) C13	9.1 x 6.3 x 15.1	30.9	\$1,404
9SX1500G	9SX 1500 208V TOWER	1500/1350	C14 ³	(6) C13	9.1 x 6.3 x 17.0	41.9	\$1,951
9SX2000G	9SX 2000 208V TOWER	2000/1800	L6-20P ⁴	(8) C13	13.6 x 8.4 x 16.2	77.2	\$2,534
9SX3000G	9SX 3000 208V TOWER	3000/2700	L6-20P ⁵	(8) C13, (1) C19	13.6 x 8.4 x 16.2	77.2	\$4,136
9SX3000GL	9SX 3000 208V GL TOWER	3000/2700	L6-20P ⁵	(1) L6-30R, (1) L6-20R, (2) 6-20R	13.6 x 8.4 x 16.2	77.2	\$4,136

3. Customer input cord required C14, UPS comes with (2) C13/C14 jumpers
4. Detachable C13 to L6-20P 8ft cord
5. Detachable C19 to L6-20P 8ft cord
6. 9SX "G" global models operate at 200, 208 (default), 220, 230, and 240V

9SX TOWER OPTIONS

Catalog Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended Battery Modules				
9SXEBM36 ¹	Eaton 9SX 1000 Tower EBM	9.9 x 6.3 x 13.9	41.8	\$899
9SXEBM48 ²	Eaton 9SX 1500 Tower EBM	9.9 x 6.3 x 17.0	52.9	\$1,007
9SXEBM96 ³	Eaton 9SX 2000/3000 Tower EBM	13.6 x 8.4 x 16.2	110.2	\$1,281
EBMCBL36T	9SX 1000 EBM 6ft extension cable			\$144
EBMCBL48T	9SX 1500 EBM 6ft extension cable			\$144
EBMCBL96T	9SX 3000 EBM 6ft extension cable			\$144
CBLADAPT36T	Adapter cable from Eaton 9SX UPS/EBM to Eaton 9130 1000VA UPS/EBM models			\$133
CBLADAPT48T	Adapter cable from Eaton 9SX UPS/EBM to Eaton 9130 1500VA UPS/EBM models			\$133
CBLADAPT96T	Adapter cable from Eaton 9SX UPS/EBM to Eaton 9130 2/3 kVA UPS/EBM models			\$133

1. This EBM works with 1000 VA models (9SX700 does not have an EBM)
2. This EBM works with 1500 VA models
3. This EBM works with 2000/3000 VA models

9SX Accessory Options

Catalog Number	Description	List Price
SMKITA	Seismic Kit	\$751
**All 9SX units(except 9SX3000HW) tested and approved for OSHPD certification		

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410

Eaton 9SX UPS Tower

Online UPS (700–3000 VA)

INDGW-M2	Industrial Gateway Card	\$464
EM PDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

RUNTIME CHARTS

9SX TOWER MODELS BATTERY BACKUP TIMES (in minutes)

View interactive runtime graphs
at www.eaton.com/9SX

Factor*

Load (VA/Watts)	Internal Batteries	+1 EBM	+2 EBM	+3 EBM	+4 EBM
9SX700					
700 / 630	5.8	N/A	N/A	N/A	N/A
525 / 473	9.4	N/A	N/A	N/A	N/A
350 / 315	16.6	N/A	N/A	N/A	N/A
175 / 158	35.8	N/A	N/A	N/A	N/A
9SX1000					
1000 / 900	6.7	32	58	88	113
750 / 675	10.5	44	82	122	165
500 / 450	18.5	70	1289	191	269
250 / 225	38.5	141	263	-	-
9SX1000G					
1000 / 900	5.9	29	53	83	108
750 / 675	9.3	40	74	108	147
500 / 450	16.2	62	115	168	232
250 / 225	32.0	120	216	338	-
9SX1500					
1500 / 1350	5.9	29	53	81	105
1125 / 1013	9.1	39	73	109	146
750 / 675	16.5	64	117	171	239
375 / 338	36.7	135	249	380	-
9SX1500G					
1500 / 1350	5.3	28	51	79	104
1125 / 1013	8.9	39	72	108	144
750 / 675	16.2	62	115	168	234
375 / 338	34.7	130	233	363	-
9SX2000					
2000 / 1770	10.4	44	81	117	160
1500 / 1350	15.8	61	112	167	228
1000 / 900	26.2	97	175	274	363
500 / 450	53.8	199	374	-	-
9SX2000G					
2000 / 1770	10.5	44	83	115	160
1500 / 1350	16.1	62	114	172	234
1000 / 900	27.5	102	184	288	378
500 / 450	55.7	206	390	-	-
9SX3000 & 9SX3000HW					
3000 / 2700	5.7	28	54	80	102
2250 / 2025	9.2	40	71	109	147
1500 / 1350	16.7	64	116	172	241
750 / 675	37.7	138	261	389	-
9SX3000G					
3000 / 2700	5.8	29	52	77	104
2250 / 2025	8.7	39	72	108	142
1500 / 1350	15.7	61	114	167	231
750 / 675	35.3	131	235	366	-

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 9PX UPS RACK/TOWER (700-3000VA)

As a stand-alone, online double-conversion UPS, the Eaton 9PX 700-3000 VA rack/tower models can withstand harsh electrical environments for a variety of critical applications including IT, edge networks, industrial automation, healthcare and K-12. It's built for scalable deployment and features a graphical LCD interface that enables local access to configurations and settings, history and diagnostics, energy consumption and load segment control.



- Graphical LCD screen lets you customize settings, diagnose UPS alarms and view load and power consumption locally
- Remote power off, remote on/off and output relay ports provide increased control capabilities
- Load segments allow for prioritized shutdown and automated restart protocols, daily or weekly reboot schedules and remote power cycling
- Up to 94% efficiency in online mode cuts energy usage and costs
- ABM charging technology keeps batteries cool and stretches their lifetime by up to 50 percent
- Seamlessly integrates with Intelligent Power Manager to monitor, manage and control physical and virtual environments
- PredictPulse remote monitoring service can be added to increase reliability and peace of mind—Eaton monitors your UPS, notifies you when there's an alarm and takes appropriate action
- Four-post rail kit is included (two-post rail kit is optional)
- Warranty (US and Canada): Two-year limited warranty, five-year extended warranty plans available, \$250,000 load protection guarantee

9PX 700-3000 VA RACK/TOWER: 120/110/100V¹ OUTPUT, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection ²	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX700RT	9PX 700 120V RT	700/630	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	36	\$1,216
9PX1000RT	9PX 1000 120V RT	1000/900	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	36	\$1,521
9PX1500RT	9PX 1500 120V RT	1500/1350	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	43	\$2,135
9PX1500RTN	9PX 1500 120V RT w/ NMC	1500/1350	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	43	\$2,648
9PX2000RT	9PX 2000 120V RT	2000/1800	5-20P	(6) 5-20R, (1) L5-20R	3.4 (2U) x 17.3 x 23.8	62	\$2,676
9PX2000RTN	9PX 2000 120V RT w/ NMC	2000/1800	5-20P	(6) 5-20R, (1) L5-20R	3.4 (2U) x 17.3 x 23.8	62	\$3,189
9PX3000RT	9PX 3000 120V RT	3000/2700	L5-30P	(6) 5-20R, (1) L5-30R	3.4 (2U) x 17.3 x 23.8	63	\$4,505
9PX3000RTN	9PX 3000 120V RT w/ NMC	3000/2700	L5-30P	(6) 5-20R, (1) L5-30R	3.4 (2U) x 17.3 x 23.8	63	\$5,018

1. Model voltages: 120V, 125V, 110V (20% output derating), 100V (20% output derating). The default nominal voltage is 120V.

2. Input linecords are 8ft long

9PX 700-3000 VA RACK/TOWER: 208/230/240V³ OUTPUT, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX1000GRT	9PX 1000G 208V RT	1000/900	C14	(8) C13	3.4 (2U) x 17.3 x 17.7	40	\$1,521
9PX1500GRT	9PX 1500G 208V RT	1500/1350 ₃	C14	(8) C13	3.4 (2U) x 17.3 x 17.7	44	\$2,135
9PX2200GRT	9PX 2000G 208V RT	2200/2000 ₄	C20 / L6-20P ⁵	(8) C13, (2) C19	3.4 (2U) x 17.3 x 23.8	60	\$2,676
9PX3000GRT	9PX 3000G 208V RT	3000/2700 ₆	C20 / L6-20P ⁵	(8) C13, (2) C19	3.4 (2U) x 17.3 x 23.8	60	\$4,505
9PX3000GLRT	9PX 3000GL 208V RT	3000/2700 ₆	C20 / L6-20P ⁵	(1) L6-30R, (2) L6-20R	3.4 (2U) x 17.3 x 23.8	60	\$4,505
9PX3K3UN	9PX 3000 3U 208V RT w/NMC	3000/3000	Terminal Block with L6-30P	(2) L6-30R, (2) L6-20R	5.1 (3U) x 17.3 x 28.4	106	\$5,265

3. 2U Global model voltages: 208V, 200V (derated to 1350W). The default nominal voltage is 208V.

4. 2U Global model voltages: 208V, 200V (derated to 2000W). The default nominal voltage is 208V.

6. 2U Global model voltages: 208V, 200V (derated to 2700W). The default nominal voltage is 208V.

5. Detachable L6-20P to C19 input linecords are 6ft long.

9PX 3 kVA RACK/TOWER: 208/240V to 120V⁶ OUTPUT, 50/60 Hz BUNDLES

Catalog Number	Description	Rating (VA/Watts)	Input Connection ⁷	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX3K3UNTF5	9PX 3K 3U 208V RT UPS and 5kVA Transformer w/NMC	3000/3000	Terminal Block with L6-30P	(2) L6-20R, (1) L6-30R (18) 5-20R	10.2 (6U) x 17.3 x 28.4	201	\$6,420

EATON 9PX UPS RACK/TOWER (700-3000VA)

9PX3K3UNP1	9PX 3K 3U 208V RT UPS and PPDM1 w/NMC	3000/3000	L6-30P	(1) L14-30R, (1) L6-30R, (6) 5-20R	10.2 (6U) x 17.3 x 28.4	203	\$6,698
------------	---	-----------	--------	---------------------------------------	-------------------------	-----	---------

9PX 3 kVA RACK/TOWER: 208/240V to 120V6 OUTPUT, 50/60 Hz BUNDLES

Catalog Number	Description	Rating (VA/Watts)	Input Connection ⁷	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX3K3UNP2	9PX 3K 3U 208V RT UPS and PPDM2 w/NMC	3000/3000	Hardwired	Hardwired	10.2 (6U) x 17.3 x 28.4	201	\$6,698

6. See 9PX 5-6kVA page for transformer and PPDM individual listings.

7. L6-30P input cords are 6ft long.

9PX OPTIONS

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended runtime							
9PXEBM36RT	9PX 700-1K RT EBM	Use with 9PX700RT, 9PX1000RT			3.4 (2U) x 17.3 x 17.7	49	\$978
9PXEBM48RT	9PX 1.5K RT EBM	Use with 9PX1000GRT, 9PX1500RT, 9PX15000GRT			3.4 (2U) x 17.3 x 17.7	62	\$1,056
9PXEBM72RT	9PX 2-3K RT EBM	Use with 9PX 2-3K 2U UPS (excludes 9PX3K3UN Models)			3.4 (2U) x 17.3 x 23.8	86	\$1,084
9PXEBM180RT	9PX 3K RT EBM	Use with 9PX 9PX3K3UN Models			5.1 (3U) x 17.3 x 25.4	150	\$1,959

Catalog Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price
RK2PC	2-post rack mounting rail kit (one kit required for each UPS and EBM)			\$141
BINTSYS	Battery integration system- vertical mounting platform with wheels	7.9 x 20.5 x 31.5	30	\$639
SMKITA	Seismic Kit*			\$751

*Only 9PX3000GLRT and EBMs tested and approved for OSHPD certification

Power distribution (PDU) and maintenance bypass (MBP) options

Catalog Number	Description	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
EHBPL1500R-PDU1U	HotSwap MBP for use with 9PX1500RT	5-15P	(6) 5-15R	2.1 (2U) x 17.3 x 3.8	\$321
EHBPL2000R-PDU1U	HotSwap MBP for use with 9PX2000RT	5-20P	(6) 5-20R	2.1 (2U) x 17.3 x 3.8	\$384
EHBPL3000R-PDU1U	HotSwap MBP for use with 9PX3000RT	L5-30P	(5) 5-20R	2.1 (2U) x 17.3 x 3.8	\$557

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

9PX 700-3000VA BATTERY BACKUP TIMES (in minutes)**

Load (Watts)	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
9PX700RT					
200	44.5	138	248	370	501
300	29.4	89	161	239	324
400	21.1	65	116	172	233
500	15.8	49.5	89	132	178
600	12.1	39.7	71	106	143
630	11.5	37.5	67	100	135
9PX1000RT					
200	44.5	138	248	370	501
300	29.4	89	161	239	324
400	21.1	65	116	172	233
500	15.8	49.5	89	132	178
600	12.1	39.7	71	106	143
700	9.5	32.8	59	87	118
800	7.7	27.2	50	74	100

EATON 9PX UPS RACK/TOWER (700-3000VA)

800	7.7	27.8	50	74	100
900	6.3	24.1	43	64	86
9PX1000GRT					
200	41.5	200	384	583	794
300	27.7	134	258	392	534
400	20.4	100	192	293	399
500	15.8	79	152	232	316
600	12.6	65	125	190	259
700	10.3	54	105	160	218
800	8.6	46.7	90	138	188
900	7.3	41	79	121	165
9PX1500RT					
300	41.9	157	290	432	584
450	26.8	100	185	276	373
600	19.2	72	133	199	268
750	14.4	55.3	102	153	206
900	11.2	44.2	82	122	165
1050	8.8	36.5	68	101	137
1200	7.1	30.9	57	86	116
1350	5.8	26.7	49.5	74	100
9PX1500GRT					
300	38.3	143	263	393	530
450	25.8	95.7	176	263	356
600	18.5	71	131	195	264
750	13.9	55.6	102	153	207
900	10.7	45.2	83	124	168
1050	8.5	37.7	70	104	140
1200	6.9	32.2	60	89	120
1350	5.8	28.2	52	78	105
9PX2000RT					
360	56	209	384	573	772
540	36	136	249	373	503
720	25.9	98	181	270	364
900	19.9	76	139	208	281
1080	16.6	61	113	168	227
1260	13.2	51	94	141	190
1440	10.8	43	80	120	162
1620	9.0	38	70	104	141
1800	7.7	33	61	91	123
9PX2200GRT					
400	46	170	312	467	631
600	30	112	206	308	416
800	22	82	151	226	305
1000	16.6	64	118	176	238
1200	12.8	52	96	144	194
1400	10.3	44	81	121	163
1600	8.4	38	69	104	140
1800	7.0	33	60	90	121
2000	6.0	28.7	53	79	107
9PX3000RT					
600	35	132	242	362	489
900	22.2	84	156	232	314
1200	16.4	61	112	167	225
1500	11.8	47	86	129	174
1800	9.0	38	69	104	140
2100	7.2	31	58	87	117
2400	5.8	27	49	74	100
2700	4.8	23	43	64	86
3000	4.1	20.2	37	56	76
9PX3000GRT, 9PX3000GLRT					
600	34	125	231	345	466
900	21.9	82	150	225	304
1200	14.9	59	109	162	219
1500	10.8	46	84	125	170
1800	8.3	37	68	102	138
2100	6.6	31	57	86	116

EATON 9PX UPS RACK/TOWER (700-3000VA)

2400	5.4	27	49	73	99
2700	4.5	23	42	63	85
3000	3.8	19.9	37	55	74

** Runtimes shown at full load with maximum power factor, are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive runtime graphs at www.eaton.com/9PX

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 9PX LITHIUM ION UPS RACK/TOWER (1-3kVA)



The 9PX lithium ion UPS has the same incredible features as the lead acid UPS with the additional value add of 8-10 years life expectancy for batteries, allowing peace of mind, also increased runtime vs VRLA 9PX, lighter UPS and EBM, and a smaller footprint with the 1U EBM. It can withstand harsh electrical environments for a variety of critical applications including IT, edge networks, industrial automation, healthcare and K-12. It's built for scalable deployment and features a graphical LCD interface that enables local access to configurations and settings, history and diagnostics, energy consumption and load segment control.

- 8-10 year life expectancy for batteries and UPS allowing a set it and forget deployment
- Add up to 4 EBMs for additional runtime
- BMS(Battery Management System)improves reliability and performance by actively monitoring temperature and charge cycles
- Remote power off, remote on/off and output relay ports provide increased control capabilities
- Load segments allow for prioritized shutdown and automated restart protocols, daily or weekly reboot schedules and remote power cycling
- Up to 94% efficiency in online mode cuts energy usage and costs
- Seamlessly integrates with Intelligent Power Manager to monitor, manage and control physical and virtual environments
- PredictPulse remote monitoring service can be added to increase reliability and peace of mind—Eaton monitors your UPS, notifies you when there's an alarm and takes appropriate action
- Four-post rail kit is included (two-post rail kit is optional)
- Warranty (US and Canada) - Lithium-ion UPS: Five-year limited warranty on UPS and batteries standard

9PX 1500-3000 VA RACK/TOWER: 120/110/100V1 OUTPUT, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection ²	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX1500RT-L	9PX 1500 120V RT	1500/1350	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	36	\$4,063
9PX1500RTN-L	9PX 1500 120V RT w/ NMC	1500/1350	5-15P	(8) 5-15R	3.4 (2U) x 17.3 x 17.7	37	\$4,576
9PX2000RT-L	9PX 2000 120V RT	2000/1800	5-20P	(6) 5-20R, (1) L5-20R	3.4 (2U) x 17.3 x 23.8	51	\$4,988
9PX2000RTN-L	9PX 2000 120V RT w/ NMC	2000/1800	5-20P	(6) 5-20R, (1) L5-20R	3.4 (2U) x 17.3 x 23.8	52	\$5,501
9PX3000RT-L	9PX 3000 120V RT	3000/2400*	L5-30P	(6) 5-20R, (1) L5-30R	3.4 (2U) x 17.3 x 23.8	53	\$7,926
9PX3000RTN-L	9PX 3000 120V RT w/ NMC	3000/2400*	L5-30P	(6) 5-20R, (1) L5-30R	3.4 (2U) x 17.3 x 23.8	54	\$8,439

1. Model voltages: 120V, 125V, 110V (20% output derating), 100V (20% output derating). The default nominal voltage is 120V.

2. Input linecords are 8ft long

*2400W at 100% full load for UPS only, 2700W at 100% load for UPS + EBMs

9PX 700-3000 VA RACK/TOWER: 208/230/240V³ OUTPUT, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX1500GRT-L	9PX 1500G 208V RT	1500/1350 ³	C14	(8) C13	3.4 (2U) x 17.3 x 17.7	35	\$4,063
9PX2200GRT-L	9PX 2000G 208V RT	2200/2000 ⁴	C20 / L6-20P	(8) C13, (2) C19	3.4 (2U) x 17.3 x 23.8	49	\$4,988
9PX3000GRT-L	9PX 3000G 208V RT	3000/2400 ^{5*}	C20 / L6-20P ⁵	(8) C13, (2) C19	3.4 (2U) x 17.3 x 23.8	50	\$7,926

3. 2U Global model voltages: 208V, 200V (derated to 1350W). The default nominal voltage is 208V.

4. 2U Global model voltages: 208V, 200V (derated to 2000W). The default nominal voltage is 208V.

5. 2U Global model voltages: 208V, 200V (derated to 2400W). The default nominal voltage is 208V.

6. Detachable L6-20P to C19 input linecords are 6ft long.

*2400W at 100% full load for UPS only, 2700W at 100% load for UPS + EBMs

9PX OPTIONS

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended runtime							
9PXEBM48RT-L	9PX 1.5K RT EBM	Use with 9PX1500RT-L, 9PX1500GRT-L			1.7 (1U) x 17.2 x 17.6	37	\$2,463
9PXEBM72RT-L	9PX 2-3K RT EBM	Use with 9PX 2-3K 2U UPS			1.7 (1U) x 17.2 x 23.7	47	\$3,125

Mounting Hardware (all modules include 4-post rail kits)

Catalog Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price
RK2PC	2-post rack mounting rail kit (one kit required for each 2U UPS)			\$141
RK2PA	2-post rack mounting rail kit (one kit required for each 1U EBM)			\$101
BINTSYS	Battery integration system- vertical mounting platform with wheels	7.9 x 20.5 x 31.5	30	\$639

Power distribution (PDU) and maintenance bypass (MBP) options

Catalog Number	Description	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	List Price
EHBPL1500R-PDU1U	HotSwap MBP for use with 9PX1500RT	5-15P	(6) 5-15R	2.1 (2U) x 17.3 x 3.8	\$321
EHBPL2000R-PDU1U	HotSwap MBP for use with 9PX2000RT	5-20P	(6) 5-20R	2.1 (2U) x 17.3 x 3.8	\$384

EATON 9PX LITHIUM ION UPS RACK/TOWER (1-3kVA)

EHBPL3000R-PDU1U	HotSwap MBP for use with 9PX3000RT	L5-30P	(5) 5-20R	2.1 (2U) x 17.3 x 3.8	\$557
ePBZ78	Basic 3kVA, 120V, 0U ePDU	L5-30P	(20) 5-20R	1.7 (1U) x 17.0 x 5.1	\$333
ePBZ93	Basic 3kVA, 208V, 0U ePDU	L6-20P	(20) C13, (4) C19	35 (0U) x 1.9 x 2.4	\$305
ePBZ79	Basic 3-6kVA, 208V, 1U ePDU	L6-30P	(16) C13, (4) C19	1.7 (1U) x 17.0 x 5.1	\$360

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
EMPD1H1C2	Environmental Monitoring Probe	\$291

See software and connectivity product sections for more detail.

9PX Li-Ion 1-3kVA Battery Backup Times (in minutes)**

Load(Watts)	Internal batteries	+1 EBM	+2 EBM's	+3 EBM's	+4 EBM's
9PX1500RT-L					
1350	11.2	30.0	47.1	64.3	81.4
1215	12.6	33.5	52.7	71.9	91.0
1080	14.2	38.0	59.7	81.4	103.0
945	16.3	43.5	68.4	93.3	118.1
810	19.1	50.8	79.8	108.9	137.9
675	22.9	61.0	95.9	130.7	165.6
540	28.1	74.8	117.6	160.3	203.1
405	37.0	98.6	154.9	211.2	267.5
270	54.4	145.2	228.1	311.0	394.0
9PX1500GRT-L					
1350	12.0	31.9	50.2	68.4	86.7
1215	13.3	35.5	55.8	76.0	96.3
1080	15.0	39.9	62.7	85.4	108.2
945	17.0	45.2	71.0	96.9	122.7
810	19.7	52.5	82.5	112.5	142.5
675	23.4	62.5	98.2	133.9	169.6
540	28.7	76.4	120.1	163.8	207.5
405	37.1	99.0	155.6	212.1	268.7
270	52.0	138.7	218.0	297.3	376.6
9PX2000RT-L					
1800	13.6	36.3	57.0	77.8	98.5
1620	15.2	40.4	63.5	86.6	109.7
1440	17.1	45.5	71.6	97.6	123.6
1260	19.5	52.0	81.7	111.4	141.1
1080	22.6	60.3	94.8	129.3	163.8
900	27.1	72.3	113.6	154.8	196.1
720	33.5	89.3	140.3	191.4	242.4
540	43.8	116.7	183.4	250.1	316.8
360	62.6	167.0	262.4	357.8	453.2
9PX2200GRT-L					
2000	12.3	32.8	51.5	70.2	88.9
1800	13.6	36.3	57.1	77.8	98.6
1600	15.2	40.6	63.8	87.0	110.2
1400	17.3	46.2	72.6	99.0	125.4
1200	20.2	53.8	84.5	115.3	146.0
1000	23.9	63.8	100.3	136.7	173.2
800	29.4	78.4	123.1	167.9	212.7
600	38.2	101.8	159.9	218.1	276.2
400	54.3	144.7	227.4	310.1	392.9
9PX3000RT-L (UPS + EBM's)					
2700	-	24.1	37.9	51.7	65.5
2400	10.2	26.9	42.2	57.6	72.9
2160	11.3	30.3	47.7	65.0	82.3
1890	12.9	34.7	54.5	74.3	94.1
1620	14.8	40.4	63.5	86.5	109.6
1350	18.0	48.3	75.9	103.5	131.1
1080	23.0	59.9	94.2	128.4	162.6
810	28.0	79.1	124.3	169.5	214.7
540	43.0	114.3	179.5	244.8	310.1
9PX3000GRT-L(UPS+EBM's)					
2700	-	24.2	38.0	51.8	65.6
2430	10.5	26.9	42.2	57.5	72.9
2160	11.3	30.2	47.5	64.7	82.0
1890	12.8	34.6	54.4	74.2	94.0

EATON 9PX LITHIUM ION UPS RACK/TOWER (1-3kVA)

1620	14.9	40.3	63.3	86.3	109.4
1350	18.0	47.9	75.3	102.7	130.0
1080	23.0	59.4	93.4	127.4	161.4
810	30.0	77.6	121.9	166.3	210.6

****Runtimes shown at full load with maximum power factor, are approximate and may vary with equipment, configuration, battery age, temperature, etc.
View interactive graphs at www.eaton.com/9PX**

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 9PX

5-6 kVA Bundles

Delivering premium backup power and scalable battery runtimes for servers, voice/data networks and storage systems, the Eaton 9PX UPS is the ideal solution for both rack and stand-alone installations. With an advanced LCD screen interface and robust power management software, managing a UPS has never been easier with the 9PX—even in virtualized environments.

- Graphical LCD screen enables you to customize UPS settings, diagnose UPS alarms and view load and power consumption
- Provides more real power (watts) to protect more equipment and leave room for expanding IT systems
- Delivers added runtime with extended battery modules and extends battery service life by 50% with ABM Technology
- Virtualization-ready UPS includes connectivity card
- Cuts energy usage and costs with 93% efficiency rating in default, online mode
- Maximizes availability with extended battery runtime options, hot-swappable batteries, internal bypass and optional maintenance bypass
- Fully integrates with Intelligent Power Software Suite for continuous up time of servers and virtual machines.
- 4-post rail kit included (2-post rail kit optional)
- Warranty (US and Canada): Two-year limited warranty, five-year extended warranty plans available, \$250,000 load protection guarantee



9PX 5-6 kVA RACK/TOWER: 208/230V¹ OUTPUT, 50/60 Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX5K	5 kVA 9PX UPS	5000/4500	Terminal block with L6-30P cord	Hardwired + (2) L6-30R, (2) L6-20R	5.1 (3U) x 17.3 x 28.4	106	\$6,792
9PX6K	6 kVA 9PX UPS	6000/5400 ²	Terminal block with L6-30P cord	Hardwired + (2) L6-30R, (2) L6-20R	5.1 (3U) x 17.3 x 28.4	106	\$7,329
9PX6K-10	6 kVA 9PX UPS w/ 10ft input cord	6000/5400 ²	Terminal block with 10ft L6-30P cord	Hardwired + (2) L6-30R, (2) L6-20R	5.1 (3U) x 17.3 x 28.4	106	\$7,618

1. 9PX 5K, 6K operate at 200, 208 (default), 220, 230, 240V
2. 6K models derated at 200, 208, 220V (see technical specs)

5-6 kVA Bundles

9PX 5-6 kVA RACK/TOWER: 120/240V³ OUTPUT, 50/60⁶ Hz

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX5KTF5 ⁶	5 kVA 9PX UPS w/ 5 kVA Transformer	5000/4500	Terminal block with L6-30P cord	(1) L6-30R, (2) L6-20R, (18) 5-20R	10.2 (6U) x 17.3 x 28.4	201	\$7,940
9PX5KP1	5 kVA 9PX UPS w/ 6 kVA PPD ⁴	5000/4500	L6-30P	(1) L14-30R, (1) L6-30R, (6) 5-20R	10.2 (6U) x 17.3 x 28.4	203	\$8,217
9PX5KP2	5 kVA 9PX UPS w/ 6 kVA PPD ⁴	5000/4500	Hardwired	Hardwired	10.2 (6U) x 17.3 x 28.4	201	\$8,217
9PX6KTF5 ⁶	6 kVA 9PX UPS w/ 5 kVA Transformer	6000/5400 ⁵	Terminal block with L6-30P cord	(1) L6-30R, (2) L6-20R, (18) 5-20R	10.2 (6U) x 17.3 x 28.4	201	\$8,474
9PX6KP1	6 kVA 9PX UPS w/ 6 kVA PPD ⁴	6000/5400 ⁵	L6-30P	(1) L14-30R, (1) L6-30R, (6) 5-20R	10.2 (6U) x 17.3 x 28.4	203	\$8,752
9PX6KP2	6 kVA 9PX UPS w/ 6 kVA PPD ⁴	6000/5400 ⁵	Hardwired	Hardwired	10.2 (6U) x 17.3 x 28.4	201	\$8,752

3. 9PX 5K, 6K operates at 200, 208 (default), 220, 230, 240V - See manuals for output voltage details
4. PPD provides external, wrap-around maintenance bypass
5. 6K models derated at 200, 208, 220V (see technical specs)
6. Bundles with 9PXTFMR5 have output frequency of 60 Hz only

9PX TAA COMPLIANT MODELS⁶

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
----------------	-------------	-------------------	------------------	--------------------	--------------------------------	-------------	------------

EATON 9PX

9PX6KUS	6 kVA 9PX UPS	6000/5400 ²	Terminal block with L6-30P cord	Hardwired + (2) L6-30R, (2) L6-20R	5.1 (3U) x 17.3 x 28.4	106	\$8,434
---------	---------------	------------------------	---------------------------------	------------------------------------	------------------------	-----	---------

6. Note: 9PX TAA EBM models listed under 9PX options

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended runtime							
9PXEBM180RT	5/6 kVA EBM (add up to 4 EBMs). Cable is 18" in length.				5.1 (3U) x 17.3 x 25.4	150	\$1,959
9PXEBM180RTUS	5/6 kVA TAA EBM (add up to 4 EBMs). Cable is 18" in length, TAA-compliant				5.1 (3U) x 17.3 x 25.4	150	\$2,443
EBMCBL180	9PX 5/6 kVA 6ft EBM extension cable						\$216
CBLADAPT180	Adapter cable from Eaton 9135/MX UPS or EBM to 5/6 kVA 9PX UPS models						\$159
Mounting Hardware (all modules include 4-post rail kits)							
RK2PC	2-post rack mounting rail kit (one kit required for each UPS, EBM, PPDM, or transformer)						\$141
BINTSYS	Battery integration system - vertical mounting platform with wheels				7.9 x 20.5 x 31.5	30	\$639
SMKITA	Seismic Kit*						\$751

*Only 9PX5K, 9PX6K and 9PXEBM180RT tested and approved for OSHPD certification

Power distribution and maintenance bypass

MBP6K208	Rear-mount 3U, 208V maintenance bypass for 5 and 6 kVA 9PX UPS models		Hardwired	Hardwired + (2) L6-30R			\$698
EMI200-10	Monitored Ethernet ePDU output receptacles. 0U form factor.		L14-30P	(8) 5-20R, (20) C13, (6) C19	66.5 (0U) x 2.05 x 2.1		\$1,574

Transformer accessories⁷

9PXTFMR5	9PX 5 kVA stepdown transformer	5000	L6-30P	(18) 5-20R	5.1 (3U) x 17.3 x 25.4	95	\$1,187
9XPPDM1	9PX PowerPass Distribution Module (plug-and-play)	6000	L6-30P	(1) L14-30R, (1) L6-30R, (6) 5-20R	5.1 (3U) x 17.3 x 25.4	97	\$1,466
9XPPDM2	9PX PowerPass Distribution Module (Hardwired)	6000	Hardwired	Hardwired	5.1 (3U) x 17.3 x 25.4	95	\$1,466

7. These transformer accessories may be ordered a la cart but for best pricing they should be purchased as bundled solution.

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

9PX BATTERY BACKUP TIMES (in minutes)**

Load (Watts)	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
5400	3.0	16	28	47	58
4050	4.5	24	45	62	90
2700	8.5	38	71	104	133
1350	22.0	85	147	214	287
540	57.0	203	399	554	755

** Runtimes shown at full load with maximum power factor, are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive runtime graphs at www.eaton.com/9PX

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

Eaton 9PX UPS Rack/Tower

8-11 kVA Bundles

Delivering premium backup power and scalable battery runtimes for servers, voice/data networks and storage systems, the Eaton 9PX UPS is the ideal solution for both rack and stand-alone installations. With an advanced LCD screen interface and robust power management software, managing a UPS has never been easier with the 9PX—even in virtualized environments.



- Graphical LCD screen enables you to customize UPS settings, diagnose UPS alarms and view load and power consumption
- Provides more real power (watts) to protect more equipment and leave room for expanding IT systems
- Delivers added runtime with extended battery modules and extends battery service life by 50% with ABM Technology
- Virtualization-ready UPS includes connectivity card
- Cuts energy usage and costs with 94% efficiency rating in default, online mode
- Maximizes availability with extended battery runtime options, hot-swappable batteries, internal bypass and optional maintenance bypass
- Fully integrates with Intelligent Power Software Suite for continuous up time of servers and virtual machines. (Included)
- 4-post rail kit included
- Warranty (US and Canada): Two-year limited warranty, five-year extended warranty plans available, \$250,000 load protection guarantee

9PX RACK/TOWER: 208/230V¹ OUTPUT, 50/60 Hz BUNDLES

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX8KHW	8 kVA 9PX UPS power module and 11 kVA EBM	8000/7200	Hardwired	Hardwired	10.2 (6U) x 17.3 x 27.6	190	\$8,673
9PX8K	8 kVA 9PX UPS power module, 11 kVA EBM and 11 kVA MBP	8000/7200	Hardwired	Hardwired + (3) L6-30R	10.2 (6U) x 17.3 x 30.0	205	\$9,779
9PX11KHW ²	11 kVA 9PX UPS power module and 11 kVA EBM	11000/10000	Hardwired	Hardwired	10.2 (6U) x 17.3 x 27.6	190	\$10,437
9PX11K ²	11 kVA 9PX UPS power module, 11 kVA EBM and 11 kVA MBP	11000/10000	Hardwired	Hardwired + (3) L6-30R	10.2 (6U) x 17.3 x 30.0	205	\$11,543

1. 9PX 8K, 11K operate at 200, 208 (default), 220, 230, 240, 250V
2. 11K models derated at 200, 208, 220, 250V (see technical specs)

9PX RACK/TOWER: 120/240V³ OUTPUT, 50/60⁵ Hz BUNDLES

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX8KTF5	8 kVA 9PX UPS power module, 11 kVA EBM, 11 kVA MBP and 5 kVA Transformer ⁵	8000/7200	Hardwired	(2) L6-30R, (18) 5-20R	15.3 (9U) x 17.3 x 30.0	300	\$10,960
9PX11KTF5 ³	11 kVA 9PX UPS power module, 11 kVA EBM, 11 kVA MBP and 5 kVA Transformer ⁵	11000/10000	Hardwired	(2) L6-30R, (18) 5-20R	15.3 (9U) x 17.3 x 30.0	300	\$12,725
9PX11KTF11 ³	11 kVA 9PX UPS power module, 11 kVA EBM and 10 kW Transformer	11000/10000	Hardwired	Hardwired + (2) L14-30R, (8) 5-20R	15.3 (9U) x 17.3 x 27.6	377	\$13,881
9PX11KTF11M ³	11 kVA 9PX UPS power module, 11 kVA EBM, 11kVA MBP and 10 kW Transformer	11000/10000	Hardwired	Hardwired + (3) L6-30R, (2) L14-30R, (8) 5-20R	15.3 (9U) x 17.3 x 27.6	392	\$14,987

3. 11K models
5. Bundles with

9PX OPTIONS

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended runtime							
9PXE240RT	8/11 kVA EBM (add up to 5 EBMs). Cable is 18" in length.				5.1 (3U) x 17.3 x 26.8	143	\$1,998
EBMCBL240	9PX 8/11 kVA 6ft EBM extension cable						\$233

8-11 kVA Bundles

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
CBLADAPT180	Adapter cable from Eaton EX RT UPS or EBM to 5/6 kVA 9PX UPS models						\$159
BINTSYS	Battery integration system - vertical mounting platform with wheels				7.9 x 20.5 x 31.5	30	\$639
SC240RT	240V supercharger module to add up to 12 EBMs to 8 /11 kVA 9PX UPS models.				5.1 (3U) x 17.3 x 26.8	34	\$1,107
SMKITA	Seismic Kit*						\$751

Eaton 9PX UPS Rack/Tower

*Only 9PX8K, 9PX11K and 9PXEBM180RT tested and approved for OSHPD certification

Power distribution and maintenance bypass

MBP11K208	Rear-mount 3U, 208V maintenance bypass for 8/11	Hardwired	Hardwired + (3) L6-30R		\$1,112
ePBZ79	Basic ePDU for additional output receptacles. 1U form factor.	L6-30P	(16) C13, (4) C19	1.7 (1U) x 17.0 x 5.1	\$360
EBA201-10	Basic ePDU for additional output receptacles. 0U form factor.	L14-30P	(24) 5-20R	66.5 (0U) x 2.05 x 2.1	\$957
EMI200-10	Monitored Ethernet ePDU output receptacles. 0U form factor.	L14-30P	(8) 5-20R, (20) C13, (6) C19	66.5 (0U) x 2.05 x 2.1	\$1,574

Additional modules

9PXTFMR5	9PX 5 kVA stepdown transformer	5000/5000	L6-30P	(18) 5-20R	5.1 (3U) x 17.3 x 25.4	95	\$1,187
9PXTFMR11	9PX 10 kW stepdown transformer	10000/10000	Hardwired	Hardwired + (2) L14-30R, (8) 5-20R	5.1 (3U) x 17.3 x 25.4	187	\$3,461
9PX8KPM ⁴	9PX 8 kVA power module	8000/7200	Hardwired	Hardwired	5.1 (3U) x 17.3 x 27.6	46	\$6,718
9PX11KPM ⁴	9PX 11 kVA power module	11000/10000	Hardwired	Hardwired	5.1 (3U) x 17.3 x 27.6	46	\$8,491

4. These transformer accessories may be ordered a la cart but for best pricing they should be purchased as bundled solution.

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

9PX BATTERY BACKUP TIMES (in minutes)**

Load (Watts)	With Bundled EBM	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs	+5 EBMs
10000	3	10	18	25	34	42
7500	5.5	15	25	37	48	61
5000	10	25	42	61	80	98
2500	25	60	97	136	163	184

** Runtimes shown at full load with maximum power factor, are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive runtime graphs at www.eaton.com/9PX

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 9PX SP UPS RACK/TOWER SPLIT-PHASE

6-10 kVA Split-phase

Delivering premium backup power and scalable battery runtimes for servers, voice/data networks and storage systems, the Eaton 9PX SP UPS is the ideal solution for both rack and stand-alone installations. With an advanced LCD screen interface and robust power management software, managing a UPS has never been easier with the 9PX—even in virtualized environments.



- SP models offer both 120 and 208 output without a transformer saving, u space, weight and cost
- Graphical LCD screen enables you to customize UPS settings, diagnose UPS alarms and view load and power consumption
- Provides more real power (watts) to protect more equipment and leave room for expanding IT systems
- Delivers added runtime with extended battery modules and extends battery service life by 50% with ABM Technology
- Virtualization-ready UPS includes connectivity card
- Cuts energy usage and costs with 93% efficiency rating in default, online mode
- Maximizes availability with extended battery runtime options, hot-swappable batteries, internal bypass and optional maintenance bypass
- Fully integrates with Intelligent Power Software Suite for continuous up time of servers and virtual machines. (Included)
- 4-post rail kit included (2-post rail kit optional for 9PX6KSP)
- Warranty (US and Canada): Two-year limited warranty, five-year extended warranty plans available, \$250,000 load protection guarantee

9PX SP 6-10 kVA RACK/TOWER¹: 120/208V or 120/240V OUTPUT, 50/60 Hz, SPLIT-PHASE

Catalog Number	Description	Rating (VA/Watts)	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PX6KSP	6kVA 9PX SP UPS	5500/4900 ²	Terminal block with L14-30P cord	(1) L14-30R, (1) L6-30R, (6) 5-20R, Hardwired	6.8 (4U) x 17.3 x 26.7	157	\$8,248
9PX8KSP	8kVA 9PX SP UPS	8000/7200	Hardwired	(2) L14-30R, (1) L6-30R, Hardwired	10.3 (6U) x 17.3 x 32.0	225	\$10,243
9PX10KSP	10kVA 9PX SP UPS	10000/9000 ²	Hardwired	(2) L14-30R, (1) L6-30R, Hardwired	10.3 (6U) x 17.3 x 32.0	225	\$12,951

1. UPS and EBM ship with a 4-post rail kit, 9RK

2. 9PX SP models derated at 100/200, 120/208, 110/220V (see technical specs)

9PX SPLIT-PHASE OPTIONS

Catalog Number	Description	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Extended runtime						
9PXEBM240SP	6K SP EBM (add up to 4 EBMs), Use with 9PX6KSP UPS			5.1 (3U) x 17.3 x 26.6	132	\$2,022
EBMCBL240SP	9PX EBM Cable Extension 6kVA Split-Phase, 6ft					\$418
9PXEBM360SP	8/10K EBM (add up to 4 EBMs) Use with 9PX8KSP, 9PX10KSP UPS			5.1 (3U) x 17.3 x 25.4	163	\$2,022
EBMCBL360SP	9PX EBM Cable Extension 8/10kVA Split-Phase, 6ft					\$418

BYPASS POWER MODULE: Maintenance Bypass for Rackmount or Wall-Mount*

BPM125HW	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$2,461
BPM125AR	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(6) L14-30R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627
BPM125BR	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(3) L14-30R + (3) L6-20R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627
BPM125CR	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(3) L14-30R + (6) C19 + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627
BPM125DR	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(3) L14-30R + (6) 5-20R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627
BPM125ER	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(3) L6-30R, (6) 5-20R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627
BPM125FR	BPM for 9PX6K**, 9PX8KSP, 9PX10K SP	Hardwired	(6) L6-30R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,627

*"R" models include 4-post rail kit, 125A "HW" model does not include 9RK 4-post rail kit

**9PX6KSP is compatible with bypass modules. They are limited to current output of the UPS and cannot be loaded beyond 30A total.

Power distribution

ePBZ79	Basic ePDU for additional output receptacles. 1U form factor	L6-30P	(16) C13, (4) C19	1.7 (1U) x 17.0 x 5.1		\$360
--------	--	--------	-------------------	-----------------------	--	-------

EATON 9PX SP UPS RACK/TOWER SPLIT-PHASE

EBA201-10	Basic ePDU for additional output receptacles. 0U form factor	L14-30P	(24) 5-20R	66.5 (0U) x 2.05 x 2.1	\$957
EMI200-10	Monitored Ethernet ePDU output receptacles. 0U form factor	L14-30P	(8) 5-20R, (20) C13, (6) C19	66.5 (0U) x 2.05 x 2.1	\$1,574
CBL139	Splitter Cable L14-30P to (2) L6-30R (4ft/2ft)	L14-30P	(2) L6-30R		\$204
CBL143	Splitter Cable L14-30P to (2) L5-30R (4ft/2ft)	L14-30P	(2) L5-30R		\$204
RK2PC	2-post rack mounting rail kit, works with 9PX6K UPS ONLY				\$141
9RK	4-post rail kit for BPM125HW (included with 9PX UPS and EBM)				\$141
BINTSYS	Battery integration system - vertical mounting platform with wheels			7.9 x 20.5 x 31.5 30	\$639

SOFTWARE AND CONNECTIVITY OPTIONS

Catalog Number	Description	List Price
NETWORK-M2	Eaton Gigabit Network Card	\$410
INDGW-M2	Industrial Gateway Card	\$464
EMPDT1H1C2	Environmental Monitoring Probe Gen 2 (Compatible with NETWORK-M2 only)	\$291

See software and connectivity product sections for more detail.

9PX 6 kVA BATTERY BACKUP TIMES (in minutes)**

Load (Watts)	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
5400	6	16	29	44	61
4860	7	18	32	48	68
4320	8	21	38	56	78
3780	10	25	44	66	90
3240	12	31	53	79	109
2700	15	38	66	96	133
2160	20	49	82	124	195
1620	27	68	113	198	259

9PX 8/10 kVA BATTERY BACKUP TIMES (in minutes)**

Load (Watts)	Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
9000	5	13	22	33	47
8100	6	15	25	38	52
7200	7	17	30	44	61
6300	8	20	35	51	71
5400	9	24	43	62	86
4500	12	30	53	77	105
3600	16	40	68	99	135
2700	23	55	95	148	193

** Runtimes shown at full load with maximum power factor, are approximate and may vary with equipment, configuration, battery age, temperature, etc. View interactive runtime graphs at www.eaton.com/9PX

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON BATTERY PACKS

Use this UPS battery selector tool to find replacement batteries for your backup power devices and avoid bu interruptions.



<http://upsselector.eaton.com/Replace>

Part Number	Description	List Price
112-01097	3S350 LV Replacement Battery	\$52
58700033	3S550 LV Replacement Battery	\$52
112-00955-00	3S750 LV Replacement Battery	\$72
744-A2091	5S550 Replacement Battery Pack	\$54
744-A2093	5S700, 5S700LCD, 5S700G, 5SC500 Replacement Battery Pack	\$62
744-A2165	5S1000LCD Replacement Battery Pack	\$109
744-A2166	5S1500LCD, 5S1500G Replacement Battery Pack	\$125
EBP-0690	5115 500 Tower LV&HV Replacement Battery Pack	\$108
EBP-0691	5115 750 Tower LV&HV Replacement Battery Pack	\$154
EBP-0693	5115 1400 Tower LV&HV Replacement Battery Pack	\$199
744-A2277	5SC750, 5SC750G Replacement Battery Pack	\$128
744-A2278	5SC1000 Replacement Battery Pack	\$149
744-A2279	5SC1500, 5SC1500G Replacement Battery Pack	\$208
744-A2218	5P750, 5P850G Replacement Battery Pack	\$143
744-A2219	5P1000 Replacement Battery Pack	\$165
744-A2223	5P1500, 5P1550G Replacement Battery Pack	\$240
744-A2217	5P550R Replacement Battery Pack	\$209
744-A2220	5P750R, 5P850GR Replacement Battery Pack	\$280
744-A2221	5P1000R Replacement Battery Pack	\$332
EBP-0807	5P1500R/5P1550GR 1U Rackmount Replacement Battery Pack	\$396
744-A4058	5P750RC Replacement Battery Pack	\$258
744-A4059	5P1000RC Replacement Battery Pack	\$306
744-A4060	5P1500RC Replacement Battery Pack	\$366
EBP-1001	5P1500RT, 5PX1000, 5PX1500, 5PX1500i 2U Rackmount Replacement Battery Pack	\$318
EBP-1002	5PX 2200 2U Rackmount Replacement Battery Pack	\$633
EBP-1003	5PX 3000 2U Rackmount Replacement Battery Pack	\$684
FSBR-00200	5PX 3000 3U Replacement Battery Pack	\$684
EBP-1601	PW9130 700 120V Tower Replacement Battery Pack	\$366
EBP-1602	PW9130 1000 120V Tower Replacement Battery Pack	\$416
EBP-1603	PW9130 1500 120V Tower Replacement Battery Pack	\$481
EBP-1604	PW9130 2000/3000 120V TowerReplacement Battery Pack	\$651
744-A4310	9SX 700 120V Tower Replacement Battery Pack	\$366
744-A4311	9SX 1000 120V Tower Replacement Battery Pack	\$416
744-A4312	9SX 1500 120V Tower Replacement Battery Pack	\$493
744-A4313	9SX 2000/3000 120V Tower Replacement Battery Pack	\$608
EBP-1605	PW9130 700/1000 Rackmount Replacement Battery Pack	\$366
EBP-1606	PW9130 1500 Rackmount Replacement Battery Pack	\$441
EBP-1607	PW9130 2000/3000 Rackmount Replacement Battery Pack	\$596
744-A0687	PW9130 2000/3000 EBM Replacement Battery Pack (Qty 2 per EBM)	\$299
744-A3960	9PX700RT, 9PX1000RT Replacement Battery Pack	\$416
744-A3296	9PX1000GRT Replacement Battery Pack	\$416
744-A3959	9PXEBM36RT Replacement Battery Pack	\$408
744-A3297	9PX1500RT, 9PX1500GRT, 9PXEBM48RT Replacement Battery Pack	\$507
744-A3121	9PX2000RT, 9PX2200GRT, 9PXEBM72RT Replacement Battery Pack	\$639
744-A3122	9PX3000RT, 9PX3000GRT, 9PX3000GLRT Replacement Battery Pack	\$657
744-A1974	9PX3K3UN, 9PX5K, 9PX6K, 9SX5000, 9PXEBM180RT (Qty 2 per EBM), 9PXEBM360SP (Qty 2 per EBM), 9SX5000EBM (Qty 2 per EBM) Replacement Battery Pack	\$646
744-A1976	9PXEBM240RT Replacement Battery Pack (Qty 2 per EBM)	\$646
744-A2517	9PX6KSP Replacement Battery Pack	\$646
744-A2523	9PXEBM240SP Replacement Battery Pack	\$646
744-A2519	9PX8KSP, 9PX10KSP Replacement Battery Pack	\$790
ASY-0529	PW9170+ Battery Pack	\$705

EATON 9155 UPS & ACCESSORIES



9155-8kVA, 9155-10kVA, 9155-12kVA, 9155-15kVA MODELS

Industry proven design delivers a robust system that performs above expectations year after year

- True double-conversion topology protects equipment from all nine of the most common power problems
- Output Power factor rated at 0.9 to deliver what today's high power loads require
- Flexible voltages with split-phase design for 100/200, 110/220, 120/240, 120/208 and 127/220V applications
- Use Eaton's patented Hot Sync paralleling technology to parallel up to 4 similar sized UPSs (4 x 15kVA)
- Optional rear-mounted maintenance bypass switch can be ordered with the UPS or installed in the field
- 8 to 15kVA available with configurable rear power distribution modules (PDMs) allowing 15 different output receptacle types
- Internal batteries to keep the UPS footprint smaller to allow customers to install more revenue generating equipment
- Different product heights allow for additional battery runtime in the same footprint
- Includes on-site 5x8 startup and operator training by Eaton field technician
- Includes one year of PredictPulse remote monitoring service (requires connectivity parts and self installation)
- Eaton startup is required all 9155 UPS systems



9155 UPS MODELS

Catalog Number ⁵	Description ⁽¹⁾	Rating ² (kVA/kW)	Input Connection	Output Receptacles	Dimensions (H x W x D in) ³	Weight ³ (lb.)	List Price
K40811000000000	9155 8 kVA 32 Battery (2-high)	8/7.2	Hardwired	See Chart	32.2 x 12.0 x 33.7	352	\$14,000
K40812000000000	9155 8 kVA 64 Battery (3-high)	8/7.2	Hardwired	See Chart	47.8 x 12.0 x 33.7	590	\$16,670
K40813000000000	9155 8 kVA 32 Battery w/Trans. Mod. (3-high)	8/7.2	Hardwired	See Chart	47.8 x 12.0 x 33.7	558	\$19,300
K41011000000000	9155 10 kVA 32 Battery (2-high)	10/9	Hardwired	See Chart	32.2 x 12.0 x 33.7	352	\$16,120
K41012000000000	9155 10 kVA 64 Battery (3-high)	10/9	Hardwired	See Chart	47.8 x 12.0 x 33.7	590	\$19,190
K41013000000000	9155 10 kVA 32 Battery w/Trans. Mod. (3-high)	10/9	Hardwired	See Chart	47.8 x 12.0 x 33.7	558	\$22,060
K41211000000000	9155 12 kVA 32 Battery (2-high)	12/10.8	Hardwired	See Chart	32.2 x 12.0 x 33.7	352	\$16,900
K41212000000000	9155 12 kVA 64 Battery (3-high)	12/10.8	Hardwired	See Chart	47.8 x 12.0 x 33.7	590	\$20,020
K41213000000000	9155 12 kVA 32 Battery w/Trans. Mod. (3-high)	12/10.8	Hardwired	See Chart	47.8 x 12.0 x 33.7	558	\$22,780
K41511000000000	9155 15 kVA 32 Battery (2-high)	15/13.5	Hardwired	See Chart	32.2 x 12.0 x 33.7	352	\$18,430
K41512000000000	9155 15 kVA 64 Battery (3-high)	15/13.5	Hardwired	See Chart	47.8 x 12.0 x 33.7	590	\$21,920
K41513000000000	9155 15 kVA 32 Battery w/Trans. Mod. (3-high)	15/13.5	Hardwired	See Chart	47.8 x 12.0 x 33.7	558	\$24,780

1. 50/60 Hz auto-sensing. All models can be used for frequency/phase conversion with derated 80% load, please refer to manual for details. (Neutral required all models)
2. Input voltage 100/200, 110/220, 120/240, Vac 180° phase displacement, 120/208, 127/220 Vac 120° phase displacement.
Output voltages are user-selectable 100/200, 110/220, 120/240 Vac 180° phase displacement.
3. Weight is installed weight, add 47 lb. (2-modules high) or 50 lb. (3-modules high) to determine shipping weight. Add 6" to height for shipping. Pallet size 32"W x 44" L
4. For parallel systems, change CTO digit #5 to a "2". A hotsync parallel card is included, order a Parallel Tie Cabinet if needed.
5. 9155 models with transformers can use an attached PDM for bypassing the electronics and battery sections.
You can also use an external bypass, (BPM or wall mount panelboard) which will also bypass **ONLY** the electronics and battery sections of the UPS.
If you order a 9155 without a PDM it will arrive without any wiring between the transformer, and electronics module.
Without the PDM, the customers electrician will be responsible for connecting the transformer to the UPS electronics section.

CONNECTIVITY OPTIONS (factory added or to be ordered separately)

Available X-Slot card options: The UPS has two X-Slot bays available; one X-Slot card can be factory installed.

If a second X-Slot card is required, it can be ordered separately and user-installed.

Catalog Number if ordered separately	Value for UPS catalog # Digit 8	Description	Material number	Weight (lb)	List Price
	0	NONE (No Pre-installed X-Slot card)	-	0	\$0
INDGW-X2	3	(NEW) Industrial Gateway Card (X-Slot)	744-07538	2	\$524
103003055	6	Industrial Relay Card	103003055	2	\$460

Note: Parallel UPS systems use one of the two X-Slots for the HotSync paralleling card.

When adding cards as factory option: add card list price to UPS list price

9155 UPS (8–15 kVA)

OUTPUT RECEPTACLES AND MAINTENANCE BYPASS

Catalog Number	Description	Dimensions (H x W x D, inches)	Weight (lb.)	List Price
See worksheet	Power Distribution Module (PDM) with Mechanical Bypass Switch, mounted to rear of the UPS	16.5 x 12.0 x 7.0	25	\$1,100

Receptacle Codes Use code letters below in digits 9–12 in the Catalog number

PDM Worksheet codes	Description (Qty) NEMA Type	Voltage	Phase	Price adder for bypass and for each receptacle code chosen
S	Mechanical Bypass Module only			\$1,100

EATON 9155 UPS & ACCESSORIES



A	(4) 5-15R	120	Single	\$235
B	(4) 5-20R UL	120	Single	\$235
D	(4) 6-15R	208/240	Single HV	\$235
E	(4) 6-20R	208/240	Single HV	\$235
F	(4) L5-15R	120	Single	\$235
G	(2) L5-20R*	120	Single	\$235
H	(2) L5-30R*	120	Single	\$235
I	(2) L6-15R	208/240	Single HV	\$235
J	(2) L6-20R*	208/240	Single HV	\$235
K	(2) L6-30R*	208/240	Single HV	\$235
L	(2) L14-20R*	120/208 or 120/240	Split	\$235
M	(2) L14-30R*	120/208 or 120/240	Split	\$235
X	Blank Plate	-	-	\$20
0 (Zero) Use with PDM when no receptacles are needed		-	-	

Notes: If any output receptacles are chosen, the Maintenance Bypass module will be included and will add to the list price. Maximum 4 within CTO part number (digits 9-12).

The combined quantities of LOCKING receptacles (denoted with a *) must not exceed four.

If only a mechanical bypass is chosen, remaining three slots should be populated with "0".

If choosing any receptacle please use the "X" designation for any of the other slots (4 total) not populated. Please contact factory for custom configuration availability.

9155 OPTIONS

Catalog Number	Description	Dimensions (H x W x D in)	Weight (lb.)	List Price
103004194-5501	Seismic/OSHPD mounting kit for UPS and battery cabinets	4" added to UPS	136.0	\$2,670
124100017-001	9155 Parallel Tie Cabinet	24.0 x 20.3 x 2.2	80	\$2,250
103004336	CAN Bridge Card	-	-	\$730
P-103003557	Remote Monitoring Device Kit w/ PXGX Card and 1 ft. network cable	15 x 13 x 12 (Ship)	5	\$2,620
103006244	Wall-mount REPO switch	6 x 7 x 8 (Ship)		\$570
CTD9155	Certified test data 9155			\$300

Catalog Number	Description	Input Connection	Output Receptacles	Dimensions (H x W x D, inches)	Weight (lb.)	List Price
External Bypass Accessories*						
BPM125HW	Bypass Power Module	Hardwired	Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$2,343
BPM125AR	Bypass Power Module	Hardwired	(6) L14-30R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,454
BPM125BR	Bypass Power Module	Hardwired	(3) L14-30R +	5.1 (3U) x 17.3 x 25.6	35	\$3,454
BPM125CR	Bypass Power Module	Hardwired	(3) L14-30R +	5.1 (3U) x 17.3 x 25.6	35	\$3,454
BPM125DR	Bypass Power Module	Hardwired	(3) L14-30R +	5.1 (3U) x 17.3 x 25.6	35	\$3,454
BPM125ER	Bypass Power Module	Hardwired	(3) L6-30R,	5.1 (3U) x 17.3 x 25.6	35	\$3,454
BPM125FR	Bypass Power Module	Hardwired	(6) L6-30R + Hardwired	5.1 (3U) x 17.3 x 25.6	35	\$3,454

*Notes: BPMs will not wrap around 9155 models equipped with transformers. Input to BPM will come from transformer output therefore bypassing electronics section only

BPM can be installed in both rackmount and wall mount form factors

"R" models include 4-post rail kit, 125A "HW" model does not include rail kit

9155 UPS (8-15 kVA)

Extended Battery Modules

Catalog Number	Description	Rating	Voltage	Dimensions (H x W x D in)	Weight (lb.) ¹	List Price
103004192-5501	9355 10-15 kVA 2-High Line-up (EBM)	15kVA	192 vdc	64 Batteries	32.2 x 12.0 x 30.2	480
103004193-5501	9355 10-15 kVA 3-High Line-up (EBM)	15kVA	192 vdc	96 Batteries	47.8 x 12.0 x 30.2	710

1. Weight is installed weight, add 47 lb. (2-modules high) or 50 lb. (3-modules high) to determine shipping weight. Add 6" to height for shipping. Pallet size 32"W x 44" L

Note: Up to (4) EBM 64 battery or (3) EBM 96 battery can be added for additional runtime.

9155 BATTERY BACKUP TIMES (in minutes) @ 0.9 POWER FACTOR

Load (VA/Watts)	UPS + Internal					UPS + Internal		+1 EBM	
	32 Battery	+1 EBM 64	+2 EBM 64	+3 EBM 64	+4 EBM 64	64 Battery	96	+2 EBM 96	+3 EBM 96
15000/13500	4.6	23.0	43.0	65.1	88.6	13.3	43.0	76.7	113.0
14500/13050	4.9	24.1	45.2	68.3	93.0	14.1	45.2	80.5	119.0
14000/12600	5.2	25.2	47.3	71.5	97.4	14.9	47.3	84.2	125.0
13500/12150	5.5	26.4	49.4	74.7	102.0	15.8	49.4	88.1	130.0
13000/11700	5.8	27.6	51.6	78.1	106.0	16.7	51.6	92.0	136.0
12500/11250	6.1	28.8	54.0	81.6	111.0	17.6	54.0	96.2	142.0
12000/10800	6.5	30.2	56.5	85.5	116.0	18.6	56.5	101.0	149.0
11500/10350	6.9	31.6	59.3	89.7	122.0	19.2	59.3	106.0	156.0
11000/9900	7.3	33.3	62.4	94.4	129.0	20.2	62.4	111.0	164.0
10500/9450	7.8	35.1	65.9	99.6	136.0	21.4	65.9	117.0	174.0
10000/9000	8.4	37.2	69.8	106.0	144.0	22.6	69.8	124.0	184.0
9500/8550	9.1	39.6	74.2	112.0	153.0	24.1	74.2	132.0	196.0
9000/8100	9.9	42.3	79.4	120.0	163.0	25.7	79.4	141.0	209.0

EATON 9155 UPS & ACCESSORIES



8500/7650	10.8	45.5	85.2	129.0	175.0	27.6	85.2	152.0	225.0
8000/7200	11.9	49.1	91.9	139.0	189.0	29.8	91.9	164.0	242.0
7500/6750	13.1	53.2	99.7	151.0	205.0	32.3	99.7	178.0	263.0
7000/6300	14.6	58.0	109.0	164.0	224.0	35.2	109.0	194.0	286.0
6500/5850	16.3	63.5	119.0	180.0	245.0	38.6	119.0	212.0	314.0
6000/5400	18.4	70.0	131.0	198.0	270.0	42.5	131.0	234.0	346.0
5500/4950	20.1	77.6	145.0	220.0	300.0	47.2	145.0	259.0	383.0
5000/4500	22.4	86.6	162.0	245.0	334.0	52.6	162.0	289.0	428.0
4500/4050	25.2	97.4	182.0	276.0	376.0	59.2	182.0	325.0	-
4000/3600	28.6	110.0	207.0	313.0	426.0	67.1	207.0	369.0	-
3500/3150	32.8	127.0	238.0	359.0	-	77.0	238.0	423.0	-
3000/2700	38.3	148.0	277.0	418.0	-	89.7	277.0	-	-
2500/2250	45.6	176.0	329.0	-	-	107.0	329.0	-	-

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SERVICES

For detailed information on service plans, please contact your Eaton Service Sales Representative

EATON 9PXM UPS RACK/TOWER

Online double-conversion UPS (4–20 kVA)



Reliable online, high-frequency, double-conversion power protection that provides flexible solutions for mission-critical applications.

- N + X power and logic redundancy eliminating all system level single point-of-failure
- Easily scalable to adapt to changing IT environments by simply adding power and/or battery modules
- Double-conversion, online design delivers the highest level of protection
- ABM technology significantly increases battery service life
- Hot-swappable battery and power modules, each weighing less than 30 pounds for easy handling and replacement
- Configurable output
- Warranty (US and Canada): Two-year limited warranty and \$250,000 load protection guarantee; optional service plans available

9PXM MODELS

Model	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PXM Modules				
Split-phase Power Module (120/208, 127/220, 110/220, 120/240V In & Out)	9PXMSPPM	6.00 x 8.50 x 23.00	26.5	\$3,605
Battery Module (two required per slot/string)	9PXMBAT	3.00 x 8.50 x 23.00	22.5	\$611
Optional 20 Amp Charger Module (same form factor as 4 kVA power modules)	9PXMCHGR	6.00 x 8.50 x 23.00	22.5	\$3,470
Note: For 9PXM replacement modules, contact our Service Group at 800.356.5737 for pricing.				
UPS Enclosures				
8-slot enclosure (4, 8, 12 or 16 kVA), Hardwired Input/Output	9PXM08AAXXX	25.00 x 17.50 x 34.50	125	\$5,747
12-slot enclosure (4, 8, 12, 16 or 20 kVA), Hardwired Input/Output	9PXM12AAAAA	36.50 x 17.50 x 34.50	170	\$6,390
External Options				
Rack Kit (same for 8 and 12-slot UPS's & EBC's)	9PXM RK	6.00 x 19.50 x 23.00	34.5	\$643
Floor Anchoring kit	9PXMFAK	5.00 x 3.00 x 5.00	8	\$373
8-slot Standard External Battery Enclosure: black	9PXM08SEBM	25.00 x 17.50 x 34.50	118	\$4,855
12-slot Standard External Battery Enclosure: black	9PXM12SEBM	36.50 x 17.50 x 34.50	162	\$5,680
8-slot Connected External Battery Enclosure: black	9PXM08SEBM-C	25.00 x 17.50 x 34.50	118	\$6,136
12-slot Connected External Battery Enclosure: black	9PXM12SEBM-C	36.50 x 17.50 x 34.50	162	\$6,961
Network-M2 Network Card	Network-M2			\$410
Relay-MS Relay Card	Relay-MS			\$139
Bypass Power Module - Hardwired Input/Output	BPM125HW	5.1(3U) x 17.3 x 25.6	35	\$2,461
Bypass Power Module - Hardwired Input/(6) L14-30R + Hardwired	BPM125AR	5.1(3U) x 17.3 x 25.6	35	\$3,627
Bypass Power Module - Hardwired Input/(3) L14-30R + (3) L6-20R +	BPM125BR	5.1(3U) x 17.3 x 25.6	35	\$3,627
Bypass Power Module - Hardwired Input/(3) L14-30R + (6) C19 + Hardwired	BPM125CR	5.1(3U) x 17.3 x 25.6	35	\$3,627
Bypass Power Module - Hardwired Input/(3) L14-30R + (6) 5-20R + Hardwired	BPM125DR	5.1(3U) x 17.3 x 25.6	35	\$3,627
Bypass Power Module - Hardwired Input/(3) L6-30R + (6) 5-20R + Hardwired	BPM125ER	5.1(3U) x 17.3 x 25.6	35	\$3,627
Bypass Power Module - Hardwired Input/(6) L6-30R + Hardwired	BPM125FR	5.1(3U) x 17.3 x 25.6	35	\$3,627
*BPM Notes: Not for use with 9155 models equipped with transformers				
BPM can be installed in both rackmount and wallmount form factors				
"R" models include 4-post rail kit, 125A "HW" model does not include rail kit				

PRE-CONFIGURED SYSTEMS: Hardwire Input and Output Options

The Controlled System: Hardware Input and Output Options					Dimensions	Weight	List
Model Number		Input Connection		(H x W x D, inches)	(lb)	Price	
9PXM8S4K	4 kVA	Hardwired	Hardwired	25.00 x 17.50 x 34.50	229.0	\$11,142	
Includes:		expandable					
(1) 8-slot enclosure		to 16 kVA					
(1) power module							
(2) battery modules							
(1) network card							
9PXM8S8K	8 kVA	Hardwired	Hardwired	25.00 x 17.50 x 34.50	229.0	\$15,969	
Includes:		expandable					
(1) 8-slot enclosure		to 16 kVA					
(2) power modules							
(4) battery modules							
(1) network card							

EATON 9PXM UPS RACK/TOWER

Online double-conversion UPS (4–20 kVA)

9PXM8S12K	12 kVA expandable to 16 kVA	Hardwired	Hardwired	25.00 x 17.50 x 34.50	229.0	\$20,796
Includes: (1) 8-slot enclosure (3) power module (6) battery modules (1) network card						

PRE-CONFIGURED SYSTEMS: Hardwire Input and Output Options

Model Number		Input Connection		Dimensions (H x W x D, inches)	Weight (lb)	List Price
9PXM8S16K	16 kVA	Hardwired	Hardwired	25.00 x 17.50 x 34.50	229.0	\$24,393
Includes: (1) 8-slot enclosure (4) power module (8) battery modules (1) network card						
9PXM12S8K	8 kVA expandable to 20 kVA (N+1)	Hardwired	Hardwired	36.50 x 17.50 x 34.50	378.0	\$16,612
Includes: (1) 12-slot enclosure (2) power modules (4) battery modules (1) network card						
9PXM12S12K	12 kVA expandable to 20 kVA (N+1)	Hardwired	Hardwired	36.50 x 17.50 x 34.50	482.0	\$21,439
Includes: (1) 12-slot enclosure (3) power module (6) battery modules (1) network card						
9PXM12S16K	16 kVA expandable to 20 kVA (N+1)	Hardwired	Hardwired	36.50 x 17.50 x 34.50	586.0	\$26,266
Includes: (1) 12-slot enclosure (4) power module (8) battery modules (1) network card						
9PXM12S20K	20 kVA expandable to 20 kVA (N+1)	Hardwired	Hardwired	36.50 x 17.50 x 34.50	690.0	\$31,093
Includes: (1) 12-slot enclosure (5) power module (10) battery modules (1) network card						

PRE-CONFIGURED SYSTEMS WITH HARDWIRE INPUT AND OUTPUT RECEPTACLE OPTIONS

9PXM8S4K-PD	4 kVA expandable to 16 kVA	Hardwired	(4) 5-20 (2) L6-30	25.00 x 17.50 x 34.50	229.0	\$11,377
Includes: (1) 8-slot enclosure (1) power module (2) battery modules (1) network card						
9PXM8S8K-PD	8 kVA expandable to 16 kVA	Hardwired	(4) 5-20 (2) L6-30	25.00 x 17.50 x 34.50	229.0	\$16,204
Includes: (1) 8-slot enclosure (2) power modules (4) battery modules (1) network card						
9PXM12S8K-PD	8 kVA expandable to 20 kVA (N+1)	Hardwired	(8) 5-20 (2) L6-20 (2) L6-30 (2) L14-30	36.50 x 17.50 x 34.50	378.0	\$17,147
Includes: (1) 12-slot enclosure (2) power modules (4) battery modules (1) network card						

PRE-CONFIGURED SYSTEMS WITH HARDWIRE INPUT AND OUTPUT RECEPTACLE OPTIONS

Model Number		Input Connection		Dimensions (H x W x D, inches)	Weight (lb)	List Price
--------------	--	------------------	--	-----------------------------------	----------------	---------------

EATON 9PXM UPS RACK/TOWER

Online double-conversion UPS (4–20 kVA)

9PXM12S12K-PD Includes: (1) 12-slot enclosure (3) power module (6) battery modules (1) network card	12 kVA expandable to 20 kVA (N+1)	Hardwired	(8) 5-20 (2) L6-20 (2) L6-30 (2) L14-30	36.50 x 17.50 x 34.50	482.0	\$21,974
9PXM12S16K-PD Includes: (1) 12-slot enclosure (4) power module (8) battery modules (1) network card	16 kVA expandable to 20 kVA (N+1)	Hardwired	(8) 5-20 (2) L6-20 (2) L6-30 (2) L14-30	36.50 x 17.50 x 34.50	586.0	\$26,801
9PXM12S20K-PD Includes: (1) 12-slot enclosure (5) power module (10) battery modules (1) network card	20 kVA expandable to 20 kVA (N+1)	Hardwired	(8) 5-20 (2) L6-20 (2) L6-30 (2) L14-30	36.50 x 17.50 x 34.50	690.0	\$31,628

Notes: 60 Hz automatic frequency selection. Input/output voltages: 208–240 Vac or 110/220, 120/208, 120/240 and 127/220 Vac. All enclosures include a caster kit. Each pre-configured system includes a 6.5-minute runtime. Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc. Split-phase Power Modules included.

Customizable Receptacle Options

Network-M2	# of outlets	# of Bays	CTO Digit	Maximum of two different types of receptacles for 8-slot enclosures and five different types for 12-slot enclosures Bays available per enclosure: 8-slot has (2) bays 12-slot has (5) bays	List Price
Blank	0	1	A		\$0
5-20R	4	1	B		\$85
C13	8	1	C		\$100
C19	4	1	D		\$100
L5-20R	2	1	E		\$100
L6-20R	2	1	F		\$135
L5-30R	2	1	G		\$130
L6-30R	2	1	H		\$150
L14-30R	2	1	J		\$135
IEC309	1	1	K		\$80

SOFTWARE AND CONNECTIVITY OPTIONS

See software and connectivity product sections for more detail.

EATON 9PXM UPS RACK/TOWER

Online double-conversion UPS (4–20 kVA)

9PXM battery backup times (in minutes)

Load		Battery modules (part number 9PXMBAT). You must order two battery modules to occupy one slot.											
kVA	kW	2	4	6	8	10	12	14	16	18	20	22	24
4 kVA	3.6 kW	6	17	28	39	52	65	78	92	107	121	136	152
8 kVA	7.2 kW		6	11	17	22	28	33	39	45	52	58	65
12 kVA	10.8 kW			6	9	13	17	20	24	28	31	35	39
16 kVA	14.4 kW				6	8	11	14	17	19	22	25	28
20 kVA	18.0 kW					6	8	10	12	14	17	19	21
kVA	kW	26	28	30	32	34	36	38	40	42	44	46	48
4 kVA	3.6 kW	167	183	200	216	233	250	267	284	302	320	338	356
8 kVA	7.2 kW	71	78	85	92	99	107	114	121	129	136	144	152
12 kVA	10.8 kW	43	48	52	56	60	65	69	74	78	83	87	92
16 kVA	14.4 kW	30	33	36	39	42	45	49	52	55	58	61	65
20 kVA	18.0 kW	23	25	28	30	32	35	37	39	42	44	47	49
kVA	kW	50	52	54	56	58	60	62	64	66	68	70	72
4 kVA	3.6 kW	374	393	411	430	449	468	487					
8 kVA	7.2 kW	160	167	175	183.4	192	200	208	216	224	233	241	250
12 kVA	10.8 kW	97	102	107	111	116	121	126	131	136	141	147	152
16 kVA	14.4 kW	68	71	75	78	82	85	89	92	96	99	103	107
20 kVA	18.0 kW	52	54	57	59	62	65	67	70	73	75	78	81
kVA	kW	74	76	78	80	82	84	86	88	90	92	94	96
4 kVA	3.6 kW												
8 kVA	7.2 kW	258	267	276	284	293	302	311	320	329	338	347	356
12 kVA	10.8 kW	157	162	16	173	178	183	189	194	200	205	211	216
16 kVA	14.4 kW	110	114	118	121	125	129	133	136	140	144	148	152
20 kVA	18.0 kW	84	87	89	92	95	98	101	104	107	109	112	115
kVA	kW	98	100	102	104	106	108	110	112	114	116		
4 kVA	3.6 kW												
8 kVA	7.2 kW	365	374	383	393	402	411	421	430	440	449		
12 kVA	10.8 kW	222	227	233	238	244	250	256	261				
16 kVA	14.4 kW	156	160	163	167	171	175	179					
20 kVA	18.0 kW	118	121	124	127	130	133						

Battery runtimes are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON Ferrups FX Connected Industrial UPS

Ferrups series

Ferroresonant UPS (1100–18,000 VA)

- Bulletproof power integrity and management for telecommunications, computer, and industrial applications
- Special configurations and options available—call sales support for details: 800.356.5794
- Added connectivity options provide guaranteed communications and security in mission critical industrial and manufacturing settings
- Warranty (US and Canada): Two-year limited warranty and \$250,000 load protection guarantee; optional service plans available



FERRUPS FE 60 Hz MODELS

Model	CTO Part Number	Input/Output Voltage	Runtimes Full/Half Load	Input Plug	Output Receptacles	List Price
FX1100	Coming Soon!	120/120	14/35 Min	Hardwired	HW	N/A
FX3100	FX310000AAA1	120/120	14/35 Min	Hardwired	HW	\$11,460
FX5300	Coming Soon!	120/120, 208,240	14/35 Min	Hardwired	HW	N/A
FX7000	Coming Soon!	120/120, 208,240	14/35 Min	Hardwired	HW	N/A
FX12K5	Coming Soon!	240/120,208,240	14/35 Min	Hardwired	HW	N/A
FX18K0	Coming Soon!	240/120,208,240	14/35 Min	Hardwired	HW	N/A

Extendend Battery Modules	Description	
FXEBM01	Ferrups FX 48VDC EBM	\$9,265
FXEBM03	Ferrups FX 48VDC EBM	\$11,655
FXEBM04	Ferrups FX 48VDC EBM	\$13,897
FXEBM06	Ferrups FX 48VDC EBM	\$15,999

Maintenance Bypass Modules

BPEFXMBB02		\$1,578
BPEFXMBB04		\$1,529
BPEFXMBB05		\$1,735
BPEFMBBM02		\$1,323

EATON Ferrups FX Connected Industrial UPS

Connectivity Options

NETWORK-M2	\$410
RELAY-MS	\$139
INDRELAY-MS	\$709
INDGW-M2	\$464

Configurable Outlet Panel

Outlet Type	Quantity per Panel	CTO Digit	List Price
Hardwired/Not Available	N/A	A	\$0
5-15R	4	B	\$70
5-20R	4	C	\$90
L5-15R	4	D	\$100
L5-20R	4	E	\$100
L5-30R	2	G	\$130
6-15R (HIGH VOLT ONLY)	2	H	\$95
L6-20R (HIGH VOLT ONLY)	4	I	\$135
L6-30R (HIGH VOLT ONLY)	2	J	\$150
L14-30R (HIGH VOLT ONLY)	2	K	\$135
L14-20R (HIGH VOLT ONLY)	2	L	\$125
L6-15R	2	M	\$110
6-20R	2	N	\$115
C13	2	P	\$100
C19	2	Q	\$100
TB w/15A 1P CB	1	R	\$65
TB w/20A 1P CB	1	S	\$70
TB w/30A 1P CB	1	T	\$75
TB w/15A 2P CB	1	U	\$65
TB w/20A 2P CB	1	V	\$70
TB w/30A 2P CB	1	X	\$75

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

Eaton BladeUPS

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

The Eaton BladeUPS is a revolutionary power quality solution, expanding power protection from 5 kW to 60 kW in a single industry standard 19-inch rack, and, most significantly, providing this robust, compact solution without generating the additional heat associated with legacy end-of-row, modular UPS products.



- Up to three (3) busbar sizes available, six (6), four (4) and three (3) module configurations
- Preassembled systems NOW available in either black or white racks
- Achieves the highest power density in the marketplace
- Requires only six rack units (6U) per unit
- Reduces single points of failure with an intelligent bypass design that eliminates human error
- Provides the ultimate in reliability through a peer-to-peer paralleling relationship



BLADEUPS (12 kW) MODELS: 208V

Model	Part Number	Rating	Input/Output Voltage	Dimensions (H x W x D, inches)	Weight ¹ (lb)	List Price
BladeUPS 12 kW 208V HW in/HW out Terminal Block	ZC121TB00100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	380.0	\$13,900
BladeUPS 12 kW 208V w/60A 5W in/5W out	ZC1212200100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	322.0	\$13,900
BladeUPS 12 kW 208V w/60A 5W in/4W out	ZC1212600100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	321.0	\$13,900
BladeUPS 12 kW 208V w/60A 5W in/RPM ONLY	ZC1212000100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	321.0	\$13,700
BladeUPS 12 kW 208V w/parallel cord	ZC121P060100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	311.0	\$13,700
BladeUPS 12 kW 208V w/60A 5W in/5W out w/ INDGW-X2 SNMP/ModBus	ZC1212208100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	322.0	\$14,400
BladeUPS 12 kW 208V w/60A 5W in/4W out w/ INDGW-X2 SNMP/ModBus	ZC1212608100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	321.0	\$14,500
BladeUPS 12 kW 208V w/60A 5W in/RPM ONLY w/ INDGW-X2 SNMP/ModBus	ZC1212008100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	321.0	\$14,300
BladeUPS 12 kW 208V w/parallel cord w/ INDGW-X2 SNMP/ModBus	ZC121P068100000	12 kVA (12 kW)	208/208	10.5 (6U) x 17.3 x 28.0	311.0	\$14,900
BladeUPS 8 kW 208V w/ NEMA L21-30P in/ L21-30R out	ZC0811100100000	8kVA (8kW)	208/208	10.5 (6U) x 17.3 x 28.0	311.0	\$10,200
BladeUPS 8 kW 208V w/ NEMA L21-30P in/ L21-30R out w/ INDGW-X2 SNMP/ModBus	ZC0811108100000	8kVA (8kW)	208/208	10.5 (6U) x 17.3 x 28.0	311.0	\$10,700
BladeUPS 5kW 208V w/NEMA L21-20P in/L21-20R out, 1 Int batt string	ZC0517700110000	5kVA (5kW)	208/208	10.5 (6U) x 17.3 x 28.0	218.0	\$8,600
BladeUPS 5kW 208V w/NEMA L21-20P in/L21-20R out, 1 Int batt string w/ INDGW-X2 SNMP/ModBus	ZC0517708110000	5kVA (5kW)	208/208	10.5 (6U) x 17.3 x 28.0	218.0	\$9,100
BladeUPS 5kW 208V w/NEMA L21-20P in/L21-20R out, 2 Int batt string	ZC0517700100000	5kVA (5kW)	208/208	10.5 (6U) x 17.3 x 28.0	308.0	\$9,300
BladeUPS 5kW 208V w/NEMA L21-20P in/L21-20R out, 2 Int batt string w/ INDGW-X2 SNMP/ModBus	ZC0517708100000	5kVA (5kW)	208/208	10.5 (6U) x 17.3 x 28.0	308.0	\$9,800

1. All weights are installed weight, add 80 lb to determine shipping weight.
2. 5W in (wired input plug) is model IEC309-60 CH560P9W or similar
3. 5W out (output connector) is model IEC309-60 CH560C9W or similar
4. 4W out (output connector) is model IEC309-60 CH460C9W or similar

BLADEUPS (12 kW) MODELS: 400V

Model	Part Number	Rating	Input/Output Voltage	Dimensions (H x W x D, inches)	Weight ¹ (lb)	List Price
BladeUPS 12kW 400V w/IEC 309-32A 5W in/5W out	ZC1224400100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	318.0	\$13,900
BladeUPS 12kW 400V w/IEC 309-32A 5W in/5W out w/ INDGW-X2 SNMP/ModBus	ZC1224408100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	314.0	\$14,400
BladeUPS 12kW 400V w/IEC 309-32A 5W in/ RPM ONLY out	ZC1224000100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	317.0	\$13,700
BladeUPS 12kW 400V w/ IEC 309-32A 5W in/ RPM ONLY out w/ INDGW-X2 SNMP/ModBus	ZC1224008100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	318.0	\$14,200

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

BLADEUPS (12 kW) MODELS: 400V

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS 12kW 400V w/parallel cord	ZC122P060100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	314.0	\$13,900
BladeUPS 12kW 400V w/parallel cord w/ INDGW-X2 SNMP/ModBus	ZC122P068100000	12 kVA (12 kW)	400/400	10.5 (6U) x 17.3 x 28.0	317.0	\$15,100

1. All weights are installed weight, add 80 lb to determine shipping weight.

Eaton BladeUPS

2. 5W in (wired input plug) is model IEC309-32 CH532P6W or similar
 3. 5W out (output connector) in model IEC309-32 CH532C6W or similar
 Note: BladeUPS EBM's are not TAA Compliant

BUILT-IN CONNECTIVITY OPTIONS

Option	Select digit "8" in the Style Number	Value for Style Number digit 8	Price Adder
X-Slot 2	Industrial Relay Card (5A @ 250 Vac)	4	\$452
	Hot Sync CAN Bridge Card	6	\$714
Option	Select digit "9" in the Style Number	Value for Style Number digit 9	Price Adder
X-Slot 1	Industrial Relay Card (5A @ 250 Vac)	4	\$452
	Industrial Gateway Card (X-Slot) INDGW-X2	8	\$524

Note: All parallel configured systems include a Hot Sync CAN Bridge card in the standard part number

BLADEUPS (12-60 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models
Factory Installed and Tested UPS Systems in 42U Rack. System capable of expansion to maximum of 60kW N+1 (6 modules)

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP21110XXXXX000 208V (Max config 60kW N+1)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	683	\$20,500
BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP21115XXXXX000 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	683	\$21,000
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP212100XXXX000 208V (Max config 60kW N+1)	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	994	\$33,600
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP212150XXXX000 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	994	\$34,200
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2131000XXXX000 208V (Max config 60kW N+1)	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1316	\$45,700
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2131500XXXX000 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1316	\$46,200
BladeUPS Pre-Assembled Bottom Entry 48 kW, ZP21410000XX000 208V (Max config 60kW N+1)	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1638	\$56,000
BladeUPS Pre-Assembled Bottom Entry 48 kW, ZP21415000XX000 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1638	\$56,400
BladeUPS Pre-Assembled Bottom Entry 60 kW, ZP215100000X000 208V (Max config 60kW N+1)	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	1960	\$69,800
BladeUPS Pre-Assembled Bottom Entry 60 kW, ZP215150000X000 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	1960	\$70,300
BladeUPS Pre-Assembled Bottom Entry 60 kW ZP21610000000000 N+1, 208V (Max config 60kW N+1)	60 kVA (60 kW) N+1	208/208	81.0 x 24.0 x 42.0	2282	\$84,300
BladeUPS Pre-Assembled Bottom Entry 60 kW ZP21615000000000 N+1, 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW N+1)	60 kVA (60 kW) N+1	208/208	81.0 x 24.0 x 42.0	2282	\$84,800

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

Top Entry

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS Pre-Assembled Top Entry 12 kW, 208V (Max config 60kW N+1)	ZP22110XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	683	\$20,500
BladeUPS Pre-Assembled Top Entry 12 kW, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP22115XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	683	\$21,000
BladeUPS Pre-Assembled Top Entry 24 kW, 208V (Max config 60kW N+1)	ZP222100XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	994	\$33,600
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP222150XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	994	\$34,200
BladeUPS Pre-Assembled Top Entry 36 kW, 208V (Max config 60kW N+1)	ZP2231000XXXX000	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1316	\$45,700
BladeUPS Pre-Assembled Top Entry 36 kW, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP2231500XXXX000	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1316	\$46,200
BladeUPS Pre-Assembled Top Entry 48 kW, 208V (Max config 60kW N+1)	ZP22410000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1638	\$56,000

Eaton BladeUPS

BladeUPS Pre-Assembled Top Entry 48 kW, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP22415000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1638	\$56,500
BladeUPS Pre-Assembled Top Entry 60 kW, 208V (Max config 60kW N+1)	ZP225100000X000	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	1960	\$69,800
BladeUPS Pre-Assembled Top Entry 60 kW, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP225150000X000	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	1960	\$70,300
BladeUPS Pre-Assembled Top Entry 60 kW N+1, 208V (Max config 60kW N+1)	ZP2261000000000	60 kVA (60 kW) N+1	208/208	81.0 x 24.0 x 42.0	2282	\$84,300
BladeUPS Pre-Assembled Top Entry 60 kW N+1, 208V, w/ INDGW-X2 (Max config 60kW N+1)	ZP2261500000000	60 kVA (60 kW) N+1	208/208	81.0 x 24.0 x 42.0	2282	\$84,800

BLADEUPS (12-60 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models

Factory Installed and Tested UPS System. Systems with Maintenance Bypass included in the rack will NOT include factory wiring to MBM, and will require customer to install wiring between the UPS busbar and the MBM. System capable of expansion to maximum of 60kW (5 modules)

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, 208V, MBM in rack (Max config 60kW)	ZP21110XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	759	\$26,700
BladeUPS Pre-Assembled Bottom Entry 12 kW, 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW)	ZP21115XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	759	\$27,200
BladeUPS Pre-Assembled Bottom Entry 24 kW, 208V, MBM in rack (Max config 60kW)	ZP212100XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1070	\$39,900
BladeUPS Pre-Assembled Bottom Entry 24 kW, 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW)	ZP212150XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1070	\$40,500
BladeUPS Pre-Assembled Bottom Entry 36 kW, 208V, MBM in rack (Max config 60kW)	ZP2131000XXX100	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1392	\$52,000
BladeUPS Pre-Assembled Bottom Entry 36 kW, 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW)	ZP2131500XXX100	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1392	\$52,500
BladeUPS Pre-Assembled Bottom Entry 48 kW, 208V, MBM in rack (Max config 60kW)	ZP21410000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1714	\$62,200
BladeUPS Pre-Assembled Bottom Entry 48 kW, 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW)	ZP21415000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1714	\$62,800

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

Bottom Entry

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS Pre-Assembled Bottom Entry 60 kW, 208V, MBM in rack (Max config 60kW)	ZP215100000X100	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	2036	\$76,200
BladeUPS Pre-Assembled Bottom Entry 60 kW, 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 60kW)	ZP215150000X100	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	2036	\$76,700

Top Entry

BladeUPS Pre-Assembled Top Entry 12 kW, 208V, MBM in rack (Max config 60kW)	ZP22110XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	759	\$26,700
BladeUPS Pre-Assembled Top Entry 12 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 60kW)	ZP22115XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	759	\$27,200
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, MBM in rack (Max config 60kW)	ZP222100XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1070	\$39,900
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 60kW)	ZP222150XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1070	\$40,500
BladeUPS Pre-Assembled Top Entry 36 kW, 208V, MBM in rack (Max config 60kW)	ZP2231000XXX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1392	\$52,000

Eaton BladeUPS

BladeUPS Pre-Assembled Top Entry 36 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 60kW)	ZP22315000XX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1392	\$52,500
BladeUPS Pre-Assembled Top Entry 48 kW, 208V, MBM in rack (Max config 60kW)	ZP22410000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1714	\$62,200
BladeUPS Pre-Assembled Top Entry 48 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 60kW)	ZP22415000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1714	\$62,800
BladeUPS Pre-Assembled Top Entry 60 kW, 208V, MBM in rack (Max config 60kW)	ZP225100000X100	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	2036	\$76,200
BladeUPS Pre-Assembled Top Entry 60 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 60kW)	ZP225150000X100	60 kVA (60 kW)	208/208	81.0 x 24.0 x 42.0	2036	\$76,700

Note: Maintenance Bypass does NOT include factory wiring to the UPS busbar, which must be completed by others before startup is scheduled or completed. MBM installed next to wireway in open UPS slot (Top entry MBM below wireway. Bottom entry MBM above wireway)

BLADEUPS (12-48 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models Factory Installed and Tested UPS Systems in 42U Rack. System capable of expansion to maximum of 48kW

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, 208V (Max config 48kW)	ZP23110XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	661	\$19,200
BladeUPS Pre-Assembled Bottom Entry 12 kW, 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	ZP23115XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	661	\$19,800
BladeUPS Pre-Assembled Bottom Entry 24 kW, 208V (Max config 48kW)	ZP232100XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	972	\$32,500
BladeUPS Pre-Assembled Bottom Entry 24 kW, 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	ZP232150XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	972	\$33,000
BladeUPS Pre-Assembled Bottom Entry 36 kW, 208V (Max config 48kW)	ZP23310000XX000	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1294	\$44,500
BladeUPS Pre-Assembled Bottom Entry 36 kW, 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	ZP23315000XX000	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1294	\$45,000
BladeUPS Pre-Assembled Bottom Entry 48 kW, 208V (Max config 48kW)	ZP23410000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1616	\$54,900

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

Bottom Entry

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS Pre-Assembled Bottom Entry 48 kW, 208V w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	ZP23415000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1616	\$55,500

Top Entry

BladeUPS Pre-Assembled Top Entry 12 kW, 208V (Max config 48kW)	ZP24110XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	661	\$19,200
BladeUPS Pre-Assembled Top Entry 12 kW, 208V, w/ INDGW-X2 (Max config 48kW)	ZP24115XXXXX000	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	661	\$19,800
BladeUPS Pre-Assembled Top Entry 24 kW, 208V (Max config 48kW)	ZP242100XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	972	\$32,500
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, w/ INDGW-X2 (Max config 48kW)	ZP242150XXXX000	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	972	\$33,000
BladeUPS Pre-Assembled Top Entry 36 kW, 208V (Max config 48kW)	ZP24310000XX000	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1294	\$44,500
BladeUPS Pre-Assembled Top Entry 36 kW, 208V, w/ INDGW-X2 (Max config 48kW)	ZP24315000XX000	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1294	\$45,000
BladeUPS Pre-Assembled Top Entry 48 kW, 208V (Max config 48kW)	ZP24410000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1616	\$54,900
BladeUPS Pre-Assembled Top Entry 48 kW, 208V, w/ INDGW-X2 (Max config 48kW)	ZP24415000XX000	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1616	\$55,500

BLADEUPS (12-48 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models

Eaton BladeUPS

Factory Installed and Tested UPS System. Systems with Maintenance Bypass included in the rack will **NOT** include factory wiring to MBM, and will require customer to install wiring between the UPS busbar and the MBM. System capable of expansion to maximum of 48kW

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP23110XXXXX100 208V, MBM in rack (Max config 48kW)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	737	\$25,600
BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP23115XXXXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	737	\$26,200
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP232100XXXX100 208V, MBM in rack (Max config 48kW)	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1048	\$38,800
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP232150XXXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1048	\$39,300
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2331000XXXX100 208V, MBM in rack (Max config 48kW)	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1370	\$50,900
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2331500XXXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1370	\$51,400
BladeUPS Pre-Assembled Bottom Entry 48 kW, ZP23410000XX100 208V, MBM in rack (Max config 48kW)	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1692	\$61,200
BladeUPS Pre-Assembled Bottom Entry 48 kW, ZP23415000XX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus (Max config 48kW)	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1692	\$61,700
BladeUPS Pre-Assembled Top Entry 12 kW, ZP24110XXXXX100 208V, MBM in rack (Max config 48kW)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	737	\$25,600
BladeUPS Pre-Assembled Top Entry 12 kW, ZP24115XXXXX100 208V, MBM in rack, w/ INDGW-X2 (Max config 48kW)	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	737	\$26,100

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

Top Entry

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, MBM in rack (Max config 48kW)	ZP242100XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1048	\$38,800
BladeUPS Pre-Assembled Top Entry 24 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 48kW)	ZP242150XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1048	\$39,300
BladeUPS Pre-Assembled Top Entry 36 kW, 208V, MBM in rack (Max config 48kW)	ZP2431000XXXX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1370	\$50,900
BladeUPS Pre-Assembled Top Entry 36 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 48kW)	ZP2431500XXXX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1370	\$51,400
BladeUPS Pre-Assembled Top Entry 48 kW, 208V, MBM in rack (Max config 48kW)	ZP24410000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1692	\$61,200
BladeUPS Pre-Assembled Top Entry 48 kW, 208V, MBM in rack, w/ INDGW-X2 (Max config 48kW)	ZP24415000XX100	48 kVA (48 kW)	208/208	81.0 x 24.0 x 42.0	1692	\$61,700

BLADEUPS (12-36 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models

Factory Installed and Tested UPS Systems in 42U Rack. System capable of expansion to maximum of 36 kW

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP25110XXXXX000 208V	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	651	\$18,700
BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP25115XXXXX000 208V w/(1) INDGW-X2 SNMP/ModBus	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	651	\$19,300
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP252100XXXX000 208V	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	962	\$32,100
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP252150XXXX000 208V w/(1) INDGW-X2 SNMP/ModBus	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	962	\$32,700

Eaton BladeUPS

BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2531000XXX000 208V	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1284	\$44,100
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2531500XXX000 208V w/(1) INDGW-X2 SNMP/ModBus	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1284	\$44,700

Top Entry

BladeUPS Pre-Assembled Top Entry 12 kW, ZP26110XXXXX000 208V	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	651	\$18,700
BladeUPS Pre-Assembled Top Entry 12 kW, ZP26115XXXXX000 208V, w/ INDGW-X2	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	651	\$19,300
BladeUPS Pre-Assembled Top Entry 24 kW, ZP262100XXXX000 208V	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	962	\$32,500
BladeUPS Pre-Assembled Top Entry 24 kW, ZP262150XXXX000 208V, w/ INDGW-X2	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	962	\$33,000
BladeUPS Pre-Assembled Top Entry 36 kW, ZP2631000XXX000 208V	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1284	\$44,500
BladeUPS Pre-Assembled Top Entry 36 kW, ZP2631500XXX000 208V, w/ INDGW-X2	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1284	\$45,000

BLADEUPS (12-36 kW) MODELS: PRE-ASSEMBLED SYSTEMS IN S-SERIES RACK, Available in 208vac or 400vac models

Factory Installed and Tested UPS System. Systems with Maintenance Bypass included in the rack will **NOT include factory wiring to MBM, and will require customer to install wiring between the UPS busbar and the MBM. System capable of expansion to maximum of 48kW**

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP25110XXXXX100 208V, MBM in rack	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	727	\$25,200
BladeUPS Pre-Assembled Bottom Entry 12 kW, ZP25115XXXXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	727	\$25,800

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

Bottom Entry

BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP252100XXXX100 208V, MBM in rack	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1038	\$38,800
BladeUPS Pre-Assembled Bottom Entry 24 kW, ZP252150XXXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1038	\$39,300
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2531000XXX100 208V, MBM in rack	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1360	\$50,900
BladeUPS Pre-Assembled Bottom Entry 36 kW, ZP2531500XXX100 208V, MBM in rack w/(1) INDGW-X2 SNMP/ModBus	36 kVA (36 kW)	208/208	81.0 x 24.0 x 42.0	1360	\$51,400

Top Entry

Model	Part Number	Rating	Input/Output Voltage	Dimensions ¹ (H x W x D, inches)	Weight ² (lb)	List Price
BladeUPS Pre-Assembled Top Entry 12 kW, ZP26110XXXXX100 208V, MBM in rack	ZP26110XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	727	\$25,200
BladeUPS Pre-Assembled Top Entry 12 kW, ZP26115XXXXX100 208V, MBM in rack, w/ INDGW-X2	ZP26115XXXXX100	12 kVA (12 kW)	208/208	81.0 x 24.0 x 42.0	727	\$25,800
BladeUPS Pre-Assembled Top Entry 24 kW, ZP262100XXXX100 208V, MBM in rack	ZP262100XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1038	\$38,800
BladeUPS Pre-Assembled Top Entry 24 kW, ZP262150XXXX100 208V, MBM in rack, w/ INDGW-X2	ZP262150XXXX100	24 kVA (24 kW)	208/208	81.0 x 24.0 x 42.0	1038	\$39,300
BladeUPS Pre-Assembled Top Entry 36 kW, ZP2631000XXX100 208V, MBM in rack	ZP2631000XXX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1360	\$50,900
BladeUPS Pre-Assembled Top Entry 36 kW, ZP2631500XXX100 208V, MBM in rack, w/ INDGW-X2	ZP2631500XXX100	36 kVA (36 kW)	208/208	80.0 x 24.0 x 42.0	1360	\$51,400

Wireway and busbar will be shifted down 6U (Top) or up 6U (bottom) to allow the MBM to be installed to the top or the bottom of the enclosure. Maintenance Bypass is installed next to wireway for easier wiring. Factory wiring NOT provided between MBM and UPS busbar, which is the customers or electrical contractors responsibility.

- Shipping dimensions are 87"H x 37"W x 60"D. If more than 4 units are installed batteries for 5th and 6th units will ship on a separate pallet maximum 15"H x 32"W x 48"D. Total shipping weight for configurations of 4 UPS modules or less is installed weight plus 345 lbs. For configurations of 5 or 6 UPS modules add 391 lbs. to installed weight.
- All weights are installed weight. To determine shipping weight of pre-assembled systems add 368 lbs.
- For 400vac configurations, change digit six (6) in the part number from number "1" to number "2". If a maintenance bypass is in the configuration, also change digit 13 from number "1" to number "2". List price remains the same for either voltage.
- For configuration in built in WHITE S-Series rack change digit "3" in above Preassembled part numbers to a number 3. Cost is the same as systems with black racks.

Eaton BladeUPS

Additional notes: Factory-installed connectivity for Pre-Assembled Systems:

Style Number digit 7 represents the communication card installed in the system.

0 = No connectivity, 2 = ModBus RTU, 3 = Standard relay card, 4 = Industrial relay card, 5 = Industrial Gateway Card (X-Slot)

For systems with more than one UPS module, additional cards are required. Please visit the Connectivity Products section for card information, including pricing.

BladeUPS ASSEMBLIES

Description	Style Number	Part Number	Nominal Voltage	Dimensions (H x W x D, inches)	Weight (lb)	List Price
S-Series Enclosure with 48kW BladeUPS Parallel bar Top w/wireway	P-103000505	ETN- BLADERACK4T	208V or 400V	81.0 x 24.0 x 42.0	452	\$6,697
S-Series Enclosure with 48kW BladeUPS Parallel bar Bottom w/wireway	P-103000506	ETN- BLADERACK4B	208V or 400V	81.0 x 24.0 x 42.0	452	\$6,697
S-Series Enclosure with 60kW BladeUPS Parallel bar Top w/wireway	P-103000503	ETN- BLADERACK6T	208V or 400V	81.0 x 24.0 x 42.0	466	\$7,392
S-Series Enclosure with 60kW BladeUPS Parallel bar Bottom w/wireway	P-103000504	ETN- BLADERACK6B	208V or 400V	81.0 x 24.0 x 42.0	466	\$7,392
BladeUPS OPTIONS						
Extended Battery Modules						
Eaton BladeUPS 3U EBM ¹	103005747-6591			5.2 (3U) x 17.2 x 26.0	170	\$2,302
S-Series Enclosure (Used to install extra EBMs or MBM)						
S-Series 42Ux24"x42" w/Side Panels, Castors	ETN-ENC422442SB			80.5 (42U) x 24 x 42	2,200	See S-Series Enclosure page for pricing

Multi-mode three-phase rack mount UPS (5 to 60kW N+1)

BladeUPS ASSEMBLIES

Description	Style Number	Part Number	Nominal Voltage	Dimensions (H x W x D, inches)	Weight (lb)	List Price
S-Series 42Ux24"x42" w/divider, Castors	ETN-ENC422442S			80.5 (42U) x 24 x 42	2200	See S-Series Enclosure page for pricing
Extension Cable						
BladeUPS 3 Ft EBM Extension Cable	103006348-001			2.4 x 8.5 x 9.7	2.0	\$299
1. Shipped on pallet with dimensions of 5x40x48. Up to 8 EBMS can be shipped stacked on the same pallet. Contact Customer Care for more information						
2. BladeUPS EBMs are not TAA Compliant						
Maintenance Bypass						
BladeUPS Maintenance Bypass Module, 208V	103007415-5208			10.5 (6U) x 17.3 x 29.6	76.0	\$7,029
BladeUPS Maintenance Bypass Module, 400V	103007415-5400			10.5 (6U) x 17.3 x 29.6	76.0	\$7,029
UPS Paralleling						
BladeUPS 60 kW Bus Bar, Bottom Entry	103007571-5591 ^{1,2}			71.9 x 6.0 x 5.7	54.0	\$4,247
BladeUPS 60 kW Bus Bar, Top Entry	103007573-5591 ^{1,2}			71.9 x 6.0 x 5.7	54.0	\$4,247
BladeUPS 60 kW Universal Wireway	103007569-5591 ^{1,2}			10.4 (6U) x 19.0 x 34.0	45.0	\$1,413
BladeUPS 48 kW BusBar, Top Entry	103007828-5591 ^{1,2}			51.0 x 6.0 x 5.7	40.0	\$3,538
BladeUPS 48 kW BusBar, Bottom Entry	103007830-5591 ^{1,2}			51.0 x 6.0 x 5.7	40.0	\$3,538
BladeUPS 36 kW BusBar, Top Entry	P-103002755-591 ^{1,2}			41.0 x 6.0 x 5.7	32.0	\$3,195
BladeUPS 36 kW BusBar, Bottom Entry	P-103002756-591 ^{1,2}			41.0 x 6.0 x 5.7	32.0	\$3,195

1. Additional assembly services (Part Number AS00N00-Wire) required for field installation of busbar assemblies. Contact Eaton service for pricing

2. Please consult Application Engineering for correct rack sizing when purchasing above items.

3. All bus bar assemblies are rated for 208 or 400V installations.

4. Add 15 lbs for shipping material

5. Busbars and wireways designed to fit into various manufacturers racks including Eaton RS series, 48U, 42U and smaller racks

RPM TOPSELLERS

Topseller RPMs are the most popular configurations.

Part Number	Input Cable	Recep 1	Recep 2	Metering	List Price
Y03113011100000	BladeUPS 208V 15'	L21-20 (2)	L21-20 (2)	Power Equalizer	\$3,195
Y03113022100000	BladeUPS 208V 15'	L21-30 (2)	L21-30 (2)	Power Equalizer	\$3,285
Y03114022100000	BladeUPS 208V 20'	L21-30 (2)	L21-30 (2)	Power Equalizer	\$3,360
Y03113055100000	BladeUPS 208V 15'	L6-30 (3)	L6-30 (3)	Power Equalizer	\$3,095
Y03113047100000	BladeUPS 208V 15'	L6-20 (3)	5-20 (6)	Power Equalizer	\$3,095
Y03113017100000	BladeUPS 208V 15'	L21-20 (2)	5-20 (6)	Power Equalizer	\$3,145
Y03113027100000	BladeUPS 208V 15'	L21-30 (2)	5-20 (6)	Power Equalizer	\$3,190

Eaton BladeUPS

Y031220AA300000	IEC309-60 (60A) 10'	IEC C13 (12)	IEC C13 (12)	Energy Management	\$4,450
Y03100044100000	Hardwire (208V)	L6-20 (3)	L6-20 (3)	Power Equalizer	\$2,995
Y03100077100000	Hardwire (208V)	5-20 (6)	5-20 (6)	Power Equalizer	\$2,995
Y032420CD100000	BladeUPS 400V 10'	IEC C13 (12)	IEC C19 (6)	Power Equalizer	\$3,010
Y032440CD100000	BladeUPS 400V 20'	IEC C13 (12)	IEC C19 (6)	Power Equalizer	\$3,170
Y032000CC300000	Hardwire (400V)	IEC C13 (12)	IEC C13 (12)	Energy Management	\$4,020

RPM ACCESSORIES

Part Number	Description	List Price
103006226	RPM wall-mount bracket kit	\$227

RACK POWER MODULE CONFIGURATOR

Description	Quantity	Part Number Digit	Value	List Price
Base 3U RPM Distribution Box	-	1	Y	
		2	0	
		3	3	
Input Voltage	208V	4	1	\$2,080
	400V		2	\$2,080
Input Cords: Connection	Hardwired	5	0	
	BladeUPS Unit 208V		1	
	IEC309-60 5 wire		2	
	NEMA L21-30P		3	
	BladeUPS Unit 400V		4	
Input Cords: Length	Hardwired	6	0	\$215
	6 feet		1	BladeUPS Unit 208V IEC309-60 5 wire NEMA L21-30P BladeUPS Unit 400V \$170
	10 feet		2	BladeUPS Unit 208V IEC309-60 5 wire NEMA L21-30P BladeUPS Unit 400V \$230
	15 feet		3	BladeUPS Unit 208V IEC309-60 5 wire NEMA L21-30P BladeUPS Unit 400V \$315
	20 feet		4	BladeUPS Unit 208V IEC309-60 5 wire NEMA L21-30P BladeUPS Unit 400V \$390
Future Option	-	7	0	-
Output Receptacle Plate #1 & Output Receptacle Plate #2	L21-20R	2	8 & 9	\$400
	L21-30R	2		\$445
	L6-15R	3		\$350
	L6-20R	3		\$350
	L6-30R	3		\$350
	5-15R	6		\$350
	5-20R	6		\$350
	L14-20R	3		\$350
	L14-30R	3		\$350
	IEC320-C13 (208V)	12		\$350
	IEC320-C19 (208V)	6		\$350
	IEC320-C13 (230V)	12		\$350
	IEC320-C19 (230V)	6		\$350

Eaton BladeUPS

	L15-20	2		E	\$400
	L15-30	2		F	\$445
Metering Choices	Power Equalizer	-	10	1	0
	Energy Management System, NO card	-		2	\$695
	Energy Management System, with card	-		3	\$1,025
Future Option		-	11	0	-
		-	12	0	0
	None	-	13	0	-
		-	14	0	-
		-	15	0	-

How to order: 1. Select base model voltage (208V or 400V), 2. Select input connector option, 3. Select input cord length (corded units only), 4. Select first receptacle plate
Example of configured model part number: Y03111022300000

SOFTWARE AND CONNECTIVITY OPTIONS

Bundled with Intelligent Power Software Suite CD and communication cable. See the software and connectivity product sections for more detail.

BLADEUPS 12 kW BATTERY BACKUP TIMES (in minutes)

Load (kW)	%	Internal Battery	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
2	17	44.0	85	137	199	258
3	25	30.4	56	89	128	165
4	33	23.0	42	66	94	120
5	42	18.5	33	51	73	94
6	50	13.6	27	42	60	76
7	58	10.7	23	32	50	64
8	67	8.7	18	28	43	55
9	75	7.3	15	24	38	48
10	83	6.2	13	22	33	42
11	92	5.4	10.9	20	30	38
12	100	4.7	9.5	17	27	34

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

BLADEUPS 8 kW BATTERY BACKUP TIMES (in minutes)

Load (kW)	%	Internal Battery	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
2	25	44.0	85	137	199	258
3	38	30.4	56	89	128	165
4	50	23.0	42	66	94	120
5	63	18.5	33	51	73	94
6	75	13.6	27	42	60	76
7	88	10.7	23	32	50	64
8	100	8.7	18	28	43	55

BLADEUPS 5 kW BATTERY BACKUP TIMES (2 INTERNAL STRINGS) (in minutes)

Load (kW)	%	Internal 2 String	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
2.5	50	36.0	85	137	199	258
3	60	30.4	56	89	128	165
4	80	23.0	42	66	94	120
5	100	18.5	33	51	73	94

BLADEUPS 5 kW BATTERY BACKUP TIMES (1 INTERNAL STRING) (in minutes)

Load (kW)	%	Internal 1 String	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
2.5	50	16.5	47	82	124	166
3	60					
4	80					
5	100	6.1	22	38	57	76

BLADEUPS BATTERY BACKUP TIMES (Parallel UPS, in minutes)

Number of UPS Modules	Total Load (kW)	Internal Battery	+1 EBM per UPS		+2 EBMs per UPS		+3 EBMs per UPS		+4 EBMs per UPS		Configuration	
			Min	EBMs	Min	EBMs	Min	EBMs	Min	EBMs	Load %	kW per UPS
2	12	14	27	2	42	4	60	6	76	8	N+1	50%
3	24	8.7	18	3	28	6	43	9	55	12	N+1	67%
4	36	7.3	15	4	24	8	38	12	48	16	N+1	75%
5	48	6.7	13	5	23	10	35	15	44	20	N+1	80%
6	60	6.2	13	6	22	12	33	18	42	24	N+1	83%

SERVICES

For detailed information on service plans, please refer to the Single-phase Service section tab.

EATON 9355 UPS & ACCESSORIES



9355-10kVA, 9355-15kVA, 9355-20kVA, 9355-30kVA MODELS

Industry proven design delivers a robust system that performs above expectations year after year

- True double-conversion topology protects equipment from all nine of the most common power problems
- Output Power factor rated at 0.9 to deliver what todays high power loads require
- Inherently scalable from 10 to 15kVA or from 20 to 30 kVA, allowing you to pay as you grow with no additional hardware
- Use Eaton's patented Hot Sync paralleling technology to parallel up to 4 similar sized UPSs (4 x 15kVA or 4 x 30kVA)
- Includes rear-mounted (10 & 15kVA) or internal (20 & 30kVA) maintenance bypass switch
- 10 to 15kVA available with configurable rear power distribution modules (PDMs) allowing 15 different output receptacle types
- 20 and 30kVA available with optional total system rated output breaker to connect direct to load panel
- Internal batteries to keep the UPS footprint smaller to allow customers to install more revenue generating equipment
- Different product heights allow for additional battery runtime in the same footprint
- Includes on-site 5x8 startup and operator training by Eaton field technician
- Includes one year of PredictPulse remote monitoring service (requires connectivity parts and self installation)
- Eaton startup is required all 9355 UPS systems



9355 (10-30 kVA) MODELS

Catalog Number	Description ^(1,4)	kVA/kW Rating	Input/ Output Voltage ²	Base Runtime (min)	Dimensions (H x W x D, inches) ³	Weight (lb) ³	List Price
KA1011100000010	9355 10 kVA with 32-Battery (2-high) ⁴	10 kVA/9 kW	208/208	8	32.2 x 12.0 x 33.7	373	\$21,550
KA1012100000010	9355 10 kVA with 64-Battery (3-high) ⁴	10 kVA/9 kW	208/208	22	47.8 x 12.0 x 33.7	609	\$24,000
KA1011200000010	9355 10 kVA with 32-Battery (2-high) ⁴	10 kVA/9 kW	220/220	8	32.2 x 12.0 x 33.7	373	\$21,550
KA1012200000010	9355 10 kVA with 64-Battery (3-high) ⁴	10 kVA/9 kW	220/220	22	47.8 x 12.0 x 33.7	609	\$24,000
KA1013400000010	9355 10 kVA with 32-Battery and input isolation XFMR (3-high)	10 kVA/9 kW	480/208	8	47.8 x 12.0 x 33.7	577	\$27,440
KA1013600000010	9355 10 kVA with 32-Battery and input isolation XFMR (3-high)	10 kVA/9 kW	600/208	8	47.8 x 12.0 x 33.7	577	\$27,440
KA1511100000010	9355 15 kVA with 32-Battery (2-high) ⁴	15 kVA/13.5 kW	208/208	4	32.2 x 12.0 x 33.7	373	\$23,410
KA1512100000010	9355 15 kVA with 64-Battery (3-high) ⁴	15 kVA/13.5 kW	208/208	13	47.8 x 12.0 x 33.7	609	\$25,890
KA1512200000010	9355 15 kVA with 32-Battery (2-high) ⁴	15 kVA/13.5 kW	220/220	4	32.2 x 12.0 x 33.7	373	\$23,410
KA1512200000010	9355 15 kVA with 64-Battery (3-high) ⁴	15 kVA/13.5 kW	220/220	13	47.8 x 12.0 x 33.7	609	\$25,890
KA1513400000010	9355 15 kVA with 32-Battery and input isolation XFMR (3-high)	15 kVA/13.5 kW	480/208	4	47.8 x 12.0 x 33.7	577	\$28,950
KA1513600000010	9355 15 kVA with 32-Battery and input isolation XFMR (3-high)	15 kVA/13.5 kW	600/208	4	47.8 x 12.0 x 33.7	577	\$28,950
KB2013100000010	9355 20 kVA with Internal Batteries	20 kVA/18 kW	208/208	18	66.0 x 20.0 x 34.1	1160	\$32,640
KB2013200000010	9355 20 kVA with Internal Batteries	20 kVA/18 kW	220/220 ²	18	66.0 x 20.0 x 34.1	1160	\$32,640
KB3013100000010	9355 30 kVA with Internal Batteries	30 kVA/27 kW	208/208	11	66.0 x 20.0 x 34.1	1160	\$34,390
KB3013200000010	9355 30 kVA with Internal Batteries	30 kVA/27 kW	220/220 ²	11	66.0 x 20.0 x 34.1	1160	\$34,390
KB2033100000010	9355 20 kVA with Internal Batteries & Output Breaker	20 kVA/18 kW	208/208	18	66.0 x 20.0 x 34.1	1175	\$32,960
KB2033200000010	9355 20 kVA with Internal Batteries & Output Breaker	20 kVA/18 kW	220/220 ²	18	66.0 x 20.0 x 34.1	1175	\$32,960
KB3033100000010	9355 30 kVA with Internal Batteries & Output Breaker	30 kVA/27 kW	208/208	11	66.0 x 20.0 x 34.1	1175	\$34,710
KB3033200000010	9355 30 kVA with Internal Batteries & Output Breaker	30 kVA/27 kW	220/220 ²	11	66.0 x 20.0 x 34.1	1175	\$34,710
KB2023100000010	9355 20 kVA parallel system with Internal Batteries	20 kVA/18 kW	208/208	18	66.0 x 20.0 x 34.1	1160	\$33,270
KB2023200000010	9355 20 kVA parallel system with Internal Batteries	20 kVA/18 kW	220/220 ²	18	66.0 x 20.0 x 34.1	1160	\$33,270
KB3023100000010	9355 30 kVA parallel system with Internal Batteries	30 kVA/27 kW	208/208	11	66.0 x 20.0 x 34.1	1160	\$35,020
KB3023200000010	9355 30 kVA parallel system with Internal Batteries	30 kVA/27 kW	220/220 ²	11	66.0 x 20.0 x 34.1	1160	\$35,020
KB2043100000010	9355 20 kVA parallel system with Internal Batteries & breaker	20 kVA/18 kW	208/208	18	66.0 x 20.0 x 34.1	1176	\$33,580
KB2043200000010	9355 20 kVA parallel system with Internal Batteries & breaker	20 kVA/18 kW	220/220 ²	18	66.0 x 20.0 x 34.1	1176	\$33,580
KB3043100000010	9355 30 kVA parallel system with Internal Batteries & breaker	30 kVA/27 kW	208/208	11	66.0 x 20.0 x 34.1	1176	\$35,320
KB3043200000010	9355 30 kVA parallel system with Internal Batteries & breaker	30 kVA/27 kW	220/220 ²	11	66.0 x 20.0 x 34.1	1176	\$35,320

1. 50/60 Hz auto-sensing.

2. A center balanced input neutral is required for all configurations. 208V units are wye connected 208Y/120V - 220V units 220Y/127V, three-phase, 4-wire plus ground.

If not available order unit with an input isolation delta/wye transformer, or have the customer supply the correct transformer

3. For 9355-10 and 15kVA models: add 47 lbs for 2-high configurations or 50 lbs for 3-high configurations to determine shipping weight. Add 6" to height for pallet. Pallet size 32"W x 44"L

For 9355-20 and 30kVA models: add 60 lbs to determine shipping weight. Add 6" for pallet height. Pallet size 34" W x 40" L

4. For 9355-10 and 15kVA models: to order parallel setup system, change CTO digit #5 to a "2" (add \$680) includes HotSync card. Order a Parallel Tie Cabinet if required

CONNECTIVITY OPTIONS (factory added or to be ordered separately)

Available X-Slot card options: The UPS has two X-Slot bays available; one X-Slot card can be factory installed.

If a second X-Slot card is required, it can be ordered separately and user-installed.

Catalog Number if ordered separately	Value for UPS catalog # Digit 8	Description	Material number	Weight (lb)	List Price
	0	NONE (No Pre-installed X-Slot card)	-	0	\$0
INDGW-X2	3	(NEW) Industrial Gateway Card (X-Slot)	744-07538	2	\$524
103003055	6	Industrial Relay Card	103003055	2	\$460

Note: Parallel UPS systems use one of the two X-Slots for the HotSync paralleling card.

When adding cards as factory option: add card list price to UPS list price

9355-10kVA and 15kVA ONLY - OUTPUT RECEPTACLES

Receptacle Codes	(QTY) NEMA Type	Enter "Receptacle Code" into CTO DIGIT #	List Price Adder for EACH Receptacle Code Chosen
2	(1) L15-30R	9, 10 or 11 only	\$235
3	(1) L21-20R	9, 10 or 11 only	\$235
4	(1) L21-30R	9, 10 or 11 only	\$235
A	(2) 5-15R	9, 10, 11, 12	\$235
B	(2) 5-20R UL	9, 10, 11, 12	\$235

EATON 9355 UPS & ACCESSORIES



D	(2) 6-15R	9, 10, 11, 12	\$235
E	(2) 6-20R	9, 10, 11, 12	\$235
F	(2) L5-15R	9, 10, 11, 12	\$235
G	(1) L5-20R*	9, 10, 11, 12	\$235
H	(1) L5-30R*	9, 10, 11, 12	\$235
I	(2) L6-15R*	9, 10, 11, 12	\$235
J	(1) L6-20R*	9, 10, 11, 12	\$235
K	(1) L6-30R*	9, 10, 11, 12	\$235
L	(1) L14-20R*	9, 10, 11, 12	\$235
M	(1) L14-30R*	9, 10, 11, 12	\$235
X	Blank Panel	9, 10, 11, 12	\$20
N	(2) IEC 320 C13 120V	9, 10, 11, 12	\$235
P	(2) IEC 320 C19 120V	9, 10, 11, 12	\$235

Note: Arrange receptacle codes in numerical-alphabetical order in digits 9 through 12 of the CTO number

Example 1: a PDM with an L21-20, an L14-30, and Qty 2 IEC320-C19 would have digits 9 through 12 of the CTO arranged as "3MPP"

Example 2: a PDM with a 5-15R, and an L6-30, and an L14-30 would have digits 9 through 12 of the CTO arranged as "AKMX"

The combined quantities of LOCKING receptacles (denoted by *) must not exceed 4 per unit.

Please be sure to utilize the "X" designation for any of the 4 total slots not populated.

9355-15kVA and 30kVA MISC OPTIONS

Catalog Number	Description	Dimensions (H x W x D In)	Weight (lb)	List Price
103004194-5501	9355 10-15 kVA Seismic Mounting Kit for UPS or EBM UPS Wrap	4" added to UPS	136	\$2,670
103004896	9355 20-30 kVA Seismic Mounting Kit for UPS and Options Cabinets (not compatible with battery cabinets)		40	\$750
103006244	Wall-mount REPO switch	6 x 7 x 8 (Ship)	6	\$570
P-103003557	Remote Monitoring Display Panel w/ PXGX Card and 1 ft. network cable	15 x 13 x 12	5	\$2,620
103004336	CAN Bridge Parallel Card	2 x 8 x 8	2	\$730
CTD9355	Certified test data 9355			\$300

9355-15kVA WALL MOUNT BYPASS PANELS (Non matching)

Catalog Number	Description	Input/ Output Voltage	Dimensions (H x W x D, inches)	Weight (lb) ¹	List Price
124100027-001	9355 15 kVA 3-breaker Maintenance Bypass Panel (100A Bus, 200A Neutral, & 60A MBP, MIB, MIS, 65kAIC Rated)	208V/208V	48.0 x 20.0 x 5.8	120	\$4,980
124100027-002	9355 15 kVA 3-breaker Maintenance Bypass Panel with integrated 120kA SPD (100A Bus, 200A Neutral, & 60A MBP, MIB, MIS, 65kAIC)	208V/208V	60.0 x 20.0 x 5.8	120	\$9,410
124100027-003	9355 15 kVA 3-breaker Maintenance Bypass Panel with 36-Pole Distribution panel (Eaton GHB 65kAIC)	208V/208V	72.0 x 20.0 x 5.8	210	\$5,540
124100027-004	9355 15 kVA 3-breaker Maintenance Bypass Panel with Integrated 120kA SPD & 36-Pole Distribution Provisions (Eaton GHB 65kAIC)	208V/208V	90.0 x 20.0 x 5.8	225	\$10,200
124100027-006	9355 15 kVA 3-breaker Maintenance Bypass Panel with 36-Pole Distribution Provisions (Eaton QHBW 22kAIC)	208V/208V	72.0 x 20.0 x 5.8	210	\$5,540
124100027-007	9355 15 kVA 3-breaker Maintenance Bypass Panel with 36-Pole Distribution Provisions (Eaton BAB 10kAIC)	208V/208V	72.0 x 20.0 x 5.8	210	\$5,540
124100027-008	9355 15 kVA 3-breaker Maintenance Bypass Panel with Integrated 120kA SPD and 36-Pole Distribution Provisions (Eaton QBHW 22kAIC)	208V/208V	90.0 x 20.0 x 5.8	225	\$9,710
124100027-009	9355 15 kVA 3-breaker Maintenance Bypass Panel with Integrated 120kA SPD and 36-Pole Distribution Provisions (Eaton BAB 10kAIC)	208V/208V	90.0 x 20.0 x 5.8	225	\$9,710
124100020-001	9355 Wall Mount Parallel Tie Cabinet, 1-Breaker MBP (225A Bus, 225A Neutral, (1) 225A MBP, & (4) 80A MOBs) Does not include single maintenance isolation switch MIS ²	208V/208V	36.0 x 20.0 x 5.75	68	\$2,490
124100020-002	9355 Wall Mount Parallel Tie Cabinet With MIS Breaker (225A MBP, 225A MIS, & (4) 80A MOBs) ²	208V/208V	60 x 20.0 x 5.75	140	\$5,350

1. This is a net weight; please add 40 lb for the shipping weight of the panels and 50 lb for panels with panelboard provisions.

2. Parallel tie cabinet can be installed as single unit two (2) breaker bypass until additional UPS systems are added.

9355-20kVA and 9355-30kVA MATCHING BYPASS AND TRANSFORMER CABINETS

Catalog Number	Description	XFMR/ QTY	Rotary Bypass Included	Rating	Input/ Output Voltage	Dimensions (H x W x D, inches)	Weight (lbs)	List Price
KBT000000000010	9355-30kVA bypass switch in match cabinet	NO / 0	YES	30kVA	208/208	67.0 x 20.0 x 34.1	205	\$4,480
KBT001100000010	9355-30kVA single feed or bypass input isolation	YES / 1	YES	30kVA	208/208	66.0 x 20.0 x 34.1	535	\$8,030
KBT002100000010	9355-30kVA dual feed - rectifier input isolation	YES / 1	NO	30kVA	208/208	66.0 x 20.0 x 34.1	535	\$7,560
KBT001200000010	9355-30kVA single feed or bypass input isolation	YES / 1	YES	30kVA	480/208	66.0 x 20.0 x 34.1	535	\$8,030
KBT002200000010	9355-30kVA dual feed rectifier input isolation	YES / 1	NO	30kVA	480/208	66.0 x 20.0 x 34.1	535	\$7,560
KBT001300000010	9355-30kVA single feed or bypass input isolation	YES / 1	YES	30kVA	600/208	66.0 x 20.0 x 34.1	535	\$7,560
KBT002300000010	9355-30kVA dual feed rectifier input isolation	YES / 1	NO	30kVA	600/208	66.0 x 20.0 x 34.1	535	\$7,560
KBT003200000010	9355-30kVA output transformer only	YES / 1	NO	30kVA	208/480	66.0 x 20.0 x 34.1	535	\$7,330
KBT004200000010	9355-30kVA single feed input-output isolation	YES / 2	YES	30kVA	480/480	66.0 x 20.0 x 34.1	792	\$16,040

EATON 9355 UPS & ACCESSORIES



Dual feed applications require 2 transformer cabinets, one for the rectifier and one for the bypass

9355 20 & 30kVA WALL MOUNT MAINTENANCE BYPASS PANELS (Non matching)

Catalog Number	Description	Input/ Output Voltage	Dimensions (H x W x D, inches)	Weight (lbs) ¹	List Price
124100026-001	9355 30 kVA Wall-mount Parallel Tie Cabinet 2-Breaker MBP (400A Bus, 200A Neutral, (1) 350A MBP, & 4 110A MOB's)	208/208	48.0 x 20.0 x 5.8	300	\$4,590
124100026-002	9355 30 kVA Wall Mount Parallel Tie Cabinet With MIS Breaker (350A MBP, 350A MIS, & (4) 110A MOB's)	208/208	57.0 x 24.0 x 11.3	400	\$11,500
124100028-001	9355 20 & 30 kVA 3-breaker Maintenance Bypass Panel (225A Bus, 225A Neutral, & 125A MIB, 110A MIS and MBP, 65kAIC)	208/208	48.0 x 20.0 x 5.8	300	\$5,780
124100028-002	9355 20 & 30 kVA 3-breaker Maintenance Bypass Panel with integrated 120KA SPD (225A Bus, 225A Neutral, & 125A MIB, 110A MIS and MBP, 65kAIC)	208/208	60.0 x 20.0 x 5.8	350	\$10,970
124100028-003	9355 20 & 30kVA 3-Breaker Maintenance Bypass Panel with 36-pole Distribution Panel (Eaton GHB 65kAIC)	208/208	72.0 x 20.0 x 5.8	450	\$6,670
124100028-004	9355 20 & 30 kVA 3-Breaker Maintenance Bypass Panel with Integrated 120kA SPD and 36-pole Distribution Panel (Eaton GHB 65kAIC)	208/208	90.0 x 20.0 x 5.8	500	\$11,460
124100028-006	9355 20 & 30kVA 3-Breaker Maintenance Bypass Panel with 36-pole Distribution Panel (Eaton QBHW 22kAIC)	208/208	72.0 x 20.0 x 5.8	450	\$6,670
124100028-007	9355 20 & 30kVA 3-Breaker Maintenance Bypass Panel with 36-pole Distribution Panel (Eaton BAB 10 kAIC)	208/208	72.0 x 20.0 x 5.8	450	\$6,670
124100028-008	9355 20 & 30 kVA 3-Breaker Maintenance Bypass Panel with Integrated 120kA SPD and 36-pole Distribution Panel (Eaton QBHW 22kAIC)	208/208	90.0 x 20.0 x 5.8	500	\$11,460
124100028-009	9355 20 & 30 kVA 3-Breaker Maintenance Bypass Panel with Integrated 120kA SPD and 36-pole Distribution Panel (Eaton BAB 10kAIC)	208/208	90.0 x 20.0 x 5.8	500	\$11,460

1. This is a net weight; please add 40 lb for the shipping weight of the panels and 50 lb for panels with panelboard provisions.

Note: Please specify preference for breakers.

9355-10 & 15kVA EXTENDED BATTERY BACKUP OPTIONS

Catalog Number	Description	Rating	Voltage		Dimensions (H x W x D in)	Weight (lb) ¹	List Price
103004192-5501	9355 10-15 kVA 2-High Line-up Extended Battery (EBM)	15kVA	192 vdc	64 Batteries	32.2 x 12.0 x 30.2	480	\$9,040
103004193-5501	9355 10-15 kVA 3-High Line-up Extended Battery (EBM)	15kVA	192 vdc	96 Batteries	47.8 x 12.0 x 30.2	710	\$12,920

9355-10 & 15kVA BATTERY BACKUP TIMES (in minutes) @ 0.9 POWER FACTOR

Load (VA/Watts)	UPS with Internal 32 Battery	+1 EBM 64	+2 EBM 64	+3 EBM 64	+4 EBM 64	UPS with Internal 64 Battery	+1 EBM 96	+2 EBM 96	+3 EBM 96
15000/13500	4.6	23.0	43.0	65.1	88.6	13.3	43.0	76.7	113.0
14500/13050	4.9	24.1	45.2	68.3	93.0	14.1	45.2	80.5	119.0
14000/12600	5.2	25.2	47.3	71.5	97.4	14.9	47.3	84.2	125.0
13500/12150	5.5	26.4	49.4	74.7	102.0	15.8	49.4	88.1	130.0
13000/11700	5.8	27.6	51.6	78.1	106.0	16.7	51.6	92.0	136.0
12500/11250	6.1	28.8	54.0	81.6	111.0	17.6	54.0	96.2	142.0
12000/10800	6.5	30.2	56.5	85.5	116.0	18.6	56.5	101.0	149.0
11500/10350	6.9	31.6	59.3	89.7	122.0	19.2	59.3	106.0	156.0
11000/9900	7.3	33.3	62.4	94.4	129.0	20.2	62.4	111.0	164.0
10500/9450	7.8	35.1	65.9	99.6	136.0	21.4	65.9	117.0	174.0
10000/9000	8.4	37.2	69.8	106.0	144.0	22.6	69.8	124.0	184.0
9500/8550	9.1	39.6	74.2	112.0	153.0	24.1	74.2	132.0	196.0
9000/8100	9.9	42.3	79.4	120.0	163.0	25.7	79.4	141.0	209.0
8500/7650	10.8	45.5	85.2	129.0	175.0	27.6	85.2	152.0	225.0
8000/7200	11.9	49.1	91.9	139.0	189.0	29.8	91.9	164.0	242.0
7500/6750	13.1	53.2	99.7	151.0	205.0	32.3	99.7	178.0	263.0
7000/6300	14.6	58.0	109.0	164.0	224.0	35.2	109.0	194.0	286.0
6500/5850	16.3	63.5	119.0	180.0	245.0	38.6	119.0	212.0	314.0
6000/5400	18.4	70.0	131.0	198.0	270.0	42.5	131.0	234.0	346.0
5500/4950	20.1	77.6	145.0	220.0	300.0	47.2	145.0	259.0	383.0
5000/4500	22.4	86.6	162.0	245.0	334.0	52.6	162.0	289.0	428.0
4500/4050	25.2	97.4	182.0	276.0	376.0	59.2	182.0	325.0	-
4000/3600	28.6	110.0	207.0	313.0	426.0	67.1	207.0	369.0	-
3500/3150	32.8	127.0	238.0	359.0	-	77.0	238.0	423.0	-
3000/2700	38.3	148.0	277.0	418.0	-	89.7	277.0	-	-
2500/2250	45.6	176.0	329.0	-	-	107.0	329.0	-	-

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

EATON 9355 UPS & ACCESSORIES



9355-20 & 30kVA EXTENDED BATTERY BACKUP OPTIONS

Catalog Number	Description	Rating	Voltage		Dimensions (H x W x D, inches)	Weight (lbs)	List Price
103005183	9355 20 & 30 kVA 2 String Line & Match Extended Battery Cabinet	30kVA	216 vdc	36 batteries	66.0 x 20.0 x 34.1	1160	\$12,770
103004868	9355 20 & 30 kVA 4 String Line & Match Extended Battery Cabinet	30kVA	216 vdc	72 batteries	66.0 x 20.0 x 34.1	2060	\$19,480

9355 BATTERY BACKUP TIMES (in minutes) @ 0.9 POWER FACTOR

Load (VA/Watts)	UPS with Internal Battery	Internal Battery +EBC 36	Internal Battery +EBC 72	Internal Battery +2 EBC 72	Internal Battery +3 EBC 72
30000/27000	11	31	56	89	108
29000/26100	11	33	58	90	109
28000/25200	12	35	60	93	111
27000/24300	12	38	62	95	114
26000/23400	13	40	65	98	118
25000/22500	14	43	68	101	124
24000/21600	14	46	71	103	129
23000/20700	15	48	74	106	134
22000/19800	16	51	76	109	144
21000/18900	17	53	79	111	152
20000/18000	18	56	82	114	160
19000/17100	19	58	85	117	175
18000/16200	20	62	88	120	189
17000/15300	22	66	92	130	204
16000/14400	24	71	96	142	219
15000/13500	26	75	101	154	234
14000/12600	28	79	105	166	249
13000/11700	31	84	110	178	265
12000/10800	35	88	114	201	280
11000/9900	38	94	119	226	319
10000/9000	42	101	134	251	355
7500/6750	58	117	188	347	471
5000/4500	90	118	294	543	610

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

SERVICES

For detailed information on service plans, please contact your Eaton Service Sales Representative or use online service configurator

EATON EMERGENCY LIGHTING UPS



5.7kW to 27kW

Emergency Lighting product line offers a UPS system with matching battery cabinets to achieve UL 924 required 90 minutes of runtime.

The Eaton Emergency Lighting UPS line combines high capacity and a small footprint, making it a cost-effective solution to comply with Emergency Lighting requirements.

All solutions are fully tested to comply with UL 924.

- 90 minutes of runtime
- Allows for a manually operated and protected test switch
- 5.7-27KW
- 208, 240, 277 and 480V options



9155 SINGLE-PHASE EMERGENCY LIGHTING

Catalog Number	Description	QTY Needed	System Description	Rating (kVA/kW)	Input - Output Voltage	Dimensions (HxWxD, inches)	Weight (lb)	List Price Ea.	System List Price
BH8KEL2081P100	5.7 kW UL 924 UPS	1	9155 Emergency Lighting Single-phase 5.7 kW UPS	5.7/5.7	120/208-120/208 120/240-120/240	47.8 x 24.0 x 33.7	1,350	\$19,010	\$32,820
BHEBM96EL600	UL 924 Battery Cabinet	1						\$13,810	
BH10KEL2081P100	6.8 kW UL 924 UPS	1	9155 Emergency Lighting Single-phase 6.8 kW UPS	6.8/6.8	120/208-120/208 120/240-120/240	47.8 x 36.0 x 33.7	2,060	\$21,580	\$49,200
BHEBM96EL600	UL 924 Battery Cabinet	2						\$13,810	
BH15KEL2081P100	10.7 kW UL 924 UPS	1	9155 Emergency Lighting Single-phase 10.7 kW UPS	10.7/10.7	120/208-120/208 120/240-120/240	47.8 x 48.0 x 33.7	2,770	\$24,490	\$65,920
BHEBM96EL600	UL 924 Battery Cabinet	3						\$13,810	
BH10KEL2081P100	6.8 kW UL 924 UPS	1	9155 Emergency Lighting Single-phase 6.8 kW UPS	6.8/6.8	277 - 277	47.8 x 36.0 x 33.7	2,060	\$21,580	\$56,100
BHEBM96EL600	UL 924 Battery Cabinet	2				\$13,810			
S27N11S15N	277V to 240/120V input transformer	1				19 x 13.4 x 10.6	180	\$3,330	
S24N27S15	240V to 277V output transformer	1				19 x 13.4 x 10.6	180	\$3,570	
BH15KEL2081P10T	9 kW UL 924 UPS	1	9155 Emergency Lighting Single-phase 9 kW UPS	9/9	277 - 277	47.8 x 48.0 x 33.7	2,770	\$23,320	\$71,650
BHEBM96EL600	UL 924 Battery Cabinet	3				\$13,810			
S27N11S15N	277V to 240/120V input transformer	1				19 x 13.4 x 10.6	180	\$3,330	
S24N27S15	240V to 277V output transformer	1				19 x 13.4 x 10.6	180	\$3,570	

9355 THREE-PHASE EMERGENCY LIGHTING

Catalog Number	Description	QTY Needed	System Description	Rating (kVA/kW)	Input - Output Voltage	Dimensions (HxWxD, inches)	Weight (lb)	List Price Ea.	System List Price
BH10KEL2083P100	8.5 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 8.5 kW UPS	8.5/8.5	120/208-120/208	47.8 x 36.0 x 33.7	2,029	\$26,820	\$54,440
BHEBM96EL600	UL 924 Battery Cabinet	2						\$13,810	
BH15KEL2083P100	13.1 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 13.1 kW UPS	13.1/13.1	120/208-120/208	47.8 x 48.0 x 33.7	2,739	\$29,150	\$70,580
BHEBM96EL600	UL 924 Battery Cabinet	3						\$13,810	
BH20KEL2083P100	18 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 18 kW UPS	18/18	120/208-120/208	66.0 x 60.0 x 34.1	5,280	\$35,570	\$78,430
BHEBC72EL600	UL 924 Battery Cabinet	2						\$21,430	
BH30KEL208SF100	24 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 24 kW UPS	24/24	120/208-120/208	66.0 x 60.0 x 34.1	5,280	\$36,730	\$79,590
BHEBC72EL600	UL 924 Battery Cabinet	2						\$21,430	
BH30KEL2083P100	27 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 27 kW UPS	27/27	120/208-120/208	66.0 x 80.0 x 34.1	7,340	\$37,320	\$101,610
BHEBC72EL600	UL 924 Battery Cabinet	3						\$21,430	
BH20KEL2083P100	18 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 18 kW UPS	18/18	480/277-480/277	66.0 x 80.0 x 34.1	6,072	\$35,570	\$94,760
BHEBC72EL600	UL 924 Battery Cabinet	2						\$21,430	
BHKBTO04200	480/480V Transformer	1						\$16,330	
BH30KEL208SF100	24 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 24 kW UPS	24/24	480/277-480/277	66.0 x 80.0 x 34.1	6,072	\$36,730	\$95,920
BHEBC72EL600	UL 924 Battery Cabinet	2						\$21,430	
BHKBTO04200	480/480V Transformer	1						\$16,330	
BH30KEL2083P100	27 kW UL 924 UPS	1	9355 Emergency Lighting Three-phase 27 kW UPS	27/27	480/277-480/277	66.0 x 100 x 34.1	8,132	\$37,320	\$117,940
BHEBC72EL600	UL 924 Battery Cabinet	3						\$21,430	
BHKBTO04200	480/480V Transformer	1						\$16,330	

For 9155 and 9355 models up to 13.1kVA: add 47 lbs for 2-high configurations or 50 lbs for 3-high configurations to determine shipping weight.

Add 6" to height for pallet. Pallet size 32"W x 44"L

For 9355-20 and 30kVA models: add 60 lbs to determine shipping weight. Add 6" for pallet height. Pallet size 34" W x 40" L

EATON EMERGENCY LIGHTING UPS



9155 & 9355 EMERGENCY LIGHTING ACCESSORIES AND OPTIONS

Catalog Number	Quantity	Seismic Kits Description	List Price
103004194-5501	Order 1 kit per cabinet	Seismic/OSHDP kit, 9155 - UPS and battery cabinets only	\$2,670
103004194-5501	Order 1 kit per cabinet	Seismic/OSHDP kit, 9355 8-13.1 kW - UPS and battery cabinets	\$2,670
103004896	Order 1 kit per cabinet	Seismic/OSHDP kit, 9355 18-27 kW - UPS and options cabinets only	\$750

Notes:

1. 9155 seismic/OSHDP kits mount to UPS and battery cabinets only.
2. 9355 8.5-13.1 kW seismic/OSHDP kits mount to UPS and battery cabinets.
3. 9355 18-27 kW seismic/OSHDP kits mount to UPS only. Not compatible with battery cabinets.

CONNECTIVITY OPTIONS (ordered separately)

Available X-Slot card options: The UPS has two X-Slot bays available

Catalog Number	Description	Material number	Weight (lb)	List Price
INDGW-X2	(NEW) Industrial Gateway Card (X-Slot)	744-07538	2	\$524
103003055	Industrial Relay Card	103003055	2	\$460

SERVICES

For detailed information on service plans, please contact your Eaton Service Sales Representative or use online service configurator

EATON 93E UPS & ACCESSORIES

93E-20kVA, 93E-30kVA, 93E-40kVA, 93E-60kVA MODELS

The Eaton 93E UPS delivers three key benefits that drive a lower total cost of ownership (TCO):

- 1.) Internal batteries
- 2.) Compact footprint
- 3.) High energy-efficiency

ASSEMBLED IN THE USA, Subassemblies manufactured in ROC (Taiwan)

- Up to 98% efficiency in ESS mode, double conversion supported by proven two level IGBT power converter design
- All ratings available with internal batteries to save on floor space and reduce installation costs
- Wide variety of matching accessory cabinets to build a full system to meet the customers requirements
- Small footprint allows installation in areas without a lot of space
- Designed to allow more floor space to be dedicated to revenue-producing equipment
- Standard units without additional cabinets can be started by the customer
- All UPS's ordered with EBC's or ordered as a parallel UPS MUST have factory startup



93E 20 to 60 KVA UPS MODELS (Single Utility Feed - 50/60 Hz)

Catalog Number	Description	Input/Output Voltage	kVA Upgradable	EBM Capable	Internal Runtime (min) Load 100%/50%	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EF02GG03001003	20 kVA UPS Single Feed with Internal Batteries	208/208 or 220/220	No	No	12 / 28	53.5 x 20.9 x 31.5	831	\$25,190
9EA02GG05001003	20 kVA UPS Single Feed with Internal Batteries ²	208/208 or 220/220	Yes	Yes	21 / 47	53.5 x 20.9 x 31.5	1049	\$27,170
9EA03GG05001003	30 kVA UPS Single Feed with Internal Batteries ²	208/208 or 220/220	No	Yes	12 / 30	53.5 x 20.9 x 31.5	1049	\$29,220
9EG04GG03001003	40 kVA UPS Single Feed with Internal Batteries	208/208 or 220/220	No	No	7 / 20	74.0 x 23.6 x 31.5	1301	\$44,310
9EB04GG05001003	40 kVA UPS Single Feed with Internal Batteries ²	208/208 or 220/220	Yes	Yes	12 / 29	74.0 x 23.6 x 31.5	1499	\$47,690
9EB06GG05001003	60 kVA UPS Single Feed with Internal Batteries ²	208/208 or 220/220	No	Yes	6.6 / 18	74.0 x 23.6 x 31.5	1499	\$53,120

93E 20 to 60 KVA UPS MODELS (Dual Utility Feed - 50/60 Hz)

Catalog Number	Description	Input/Output Voltage	kVA Upgradable	EBM Capable	Internal Runtime (min) Load 100%/50%	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EF02GG03002003	20 kVA UPS Dual Feed with Internal Batteries	208/208 or 220/220	No	No	12 / 28	53.5 x 20.9 x 31.5	840	\$25,310
9EA02GG05002003	20 kVA UPS Dual Feed with Internal Batteries ²	208/208 or 220/220	Yes	Yes	21 / 47	53.5 x 20.9 x 31.5	1058	\$27,290
9EA03GG05002003	30 kVA UPS Dual Feed with Internal Batteries ²	208/208 or 220/220	No	Yes	12 / 30	53.5 x 20.9 x 31.5	1058	\$29,340
9EG04GG03002003	40 kVA UPS Dual Feed with Internal Batteries	208/208 or 220/220	No	No	7 / 20	74.0 x 23.6 x 31.5	1315	\$44,430
9EB04GG05002003	40 kVA UPS Dual Feed with Internal Batteries ²	208/208 or 220/220	Yes	Yes	12 / 29	74.0 x 23.6 x 31.5	1513	\$47,810
9EB06GG05002003	60 kVA UPS Dual Feed with Internal Batteries ²	208/208 or 220/220	No	Yes	6.6 / 18	74.0 x 23.6 x 31.5	1513	\$53,240

CONNECTIVITY OPTIONS (factory added or to be ordered separately)

Available MS-Slot card options: The UPS has two MS-Slot bays available; one MS-Slot card can be factory installed.

If a second MS-Slot card is required, it can be ordered separately and user-installed.

Catalog Number if ordered separately	Value for UPS catalog # Digit 11	Description	Material number	Weight (lb)	List Price
	0	NONE (No Pre-installed MS-Slot card)	-	0	\$0
RELAY-MS	1	Relay Card-MS	744-98067	2	\$139
INDGW-M2	9	(NEW) Industrial Gateway Card (MS-Slot)	744-07774	2	\$464
INDRELAY-MS	-	Industrial Relay Card	P-116000059	2	\$709

When adding cards as factory option: add card list price to UPS list price

93E (20-60 KVA) EXTENDED RUNTIME OPTIONS:

Catalog Number	Description	UPS Model	Number of Batteries	DC Voltage	Number of Strings	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZAAB000000000	93E 20-30 kVA Extended Battery Cabinet ⁶	20 or 30	36	216V	2	53.5 x 20.9 x 31.5	1182	\$14,650
9EZAAC000000000	93E 20-30 kVA Extended Battery Cabinet ⁶	20 or 30	54	216V	3	53.5 x 20.9 x 31.5	1585	\$19,250
9EZABB000000000	93E 40-60 kVA Extended Battery Cabinet ⁶	40 or 60	72	216V	4	74.0 x 31.3 x 31.5	2713	\$28,130
9EZABC000000000	93E 40-60 kVA Extended Battery Cabinet ⁶	40 or 60	108	216V	6	74.0 x 31.3 x 31.5	3117	\$36,540

EATON 93E UPS & ACCESSORIES

93E OTHER OPTIONS

Catalog Number	Description	ListPrice
CTD93E	Certified Test Data 93E	\$300

93E (20-60 KVA) MAINTENANCE BYPASS OPTIONS: INTEGRATED ACCESSORY CABINETS - SIAC-B, IAC-B and WALL MOUNT BYPASS CABINETS

Catalog Number	Description	Input/Output Voltage	Input Feed	Installation Location	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZHA1010000000	93E 20-30 kVA SIAC-B - Slim line Bypass for Single Feed Units (right)	208/208 or 220/220	Single	Right	53.5 x 8.0 x 31.5	165	\$4,380
9EZHA1020000000	93E 20-30 kVA SIAC-B - Slim line Bypass for Single Feed Units (left) ³	208/208 or 220/220	Single ³	Left	53.5 x 8.0 x 31.5	165	\$4,380
9EZBA1000000000	93E 20-30 kVA IAC-B - Maintenance Bypass for Single Feed Units (full width)	208/208 or 220/220	Single	Either	53.5 x 20.9 x 31.5	237	\$8,630
M1BAAX0X1XXXXXX	93E 20-30 kVA Wall Mount Maintenance Bypass Panel ⁴	208/208 or 220/220	Single ⁴	Wall	57.0 x 24.0 x 11.3	400	\$6,530
M9EZGA1100000000	93E 20-30 kVA Wall Mount Maintenance Bypass Panel With 36 Pole Distribution ⁷	208/208 or 220/220	Single ⁴	Wall	73.5 x 24.0 x 11.3	400	\$7,000
9EZHA2010000000	93E 20-30 kVA SIAC-B - Slim line Bypass for Dual Feed Units (right)	208/208 or 220/220	Dual	Right	53.5 x 8.0 x 31.5	178	\$4,900
9EZHA2020000000	93E 20-30 kVA SIAC-B - Slim line Bypass for Dual Feed Units (left) ³	208/208 or 220/220	Dual	Left	53.5 x 8.0 x 31.5	178	\$4,900
9EZBA2000000000	93E 20-30 kVA IAC-B - Maintenance Bypass for Dual Feed Units (full width)	208/208 or 220/220	Dual	Either	53.5 x 20.9 x 31.5	237	\$8,870
9EZHB1010000000	93E 40-60 kVA SIAC-B - Slim line Bypass for Single Feed Units (right)	208/208 or 220/220	Single	Right	74.0 x 8.0 x 31.5	252	\$5,950
9EZHB1020000000	93E 40-60 kVA SIAC-B - Slim line Bypass for Single Feed Units (left) ³	208/208 or 220/220	Single ³	Left	74.0 x 8.0 x 31.5	252	\$5,950
9EZBB1000000000	93E 40-60 kVA IAC-B - Maintenance Bypass for Single Feed Units (full width)	208/208 or 220/220	Single	Either	74.0 x 20.9 x 31.5	334	\$11,550
M1BFFX0X1XXXXXX	93E 40-60 kVA Wall Mount Maintenance Bypass Panel ⁴	208/208 or 220/220	Single ⁴	Wall	57.0 x 24.0 x 11.3	700	\$9,680
M9EZGB1100000000	93E 40-60 kVA Wall Mount Maintenance Bypass Panel With 36 Pole Distribution ⁷	208/208 or 220/220	Single ⁴	Wall	90.0 x 24.0 x 11.3	725	\$10,850
9EZHB2010000000	93E 40-60 kVA SIAC-B - Slim line Bypass for Dual Feed Units (right)	208/208 or 220/220	Dual	Right	74.0 x 8.0 x 31.5	277	\$6,650
9EZHB2020000000	93E 40-60 kVA SIAC-B - Slim line Bypass for Dual Feed Units (left) ³	208/208 or 220/220	Dual	Left	74.0 x 8.0 x 31.5	277	\$6,650
9EZBB2000000000	93E 40-60 kVA IAC-B - Maintenance Bypass for Dual Feed Units (full width)	208/208 or 220/220	Dual	Either	74.0 x 20.9 x 31.5	364	\$12,010

93E (20-60 KVA) TRANSFORMER & POWER DISTRIBUTION OPTIONS: ITC and IAC-D

Catalog Number	Description	Input/Output Voltage	Transformer	Input Feed	Installation Location	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZFAA0000000000	93E 20-30 kVA IAC - 480V input transformer, Single Transformer ⁵	480/208	Yes	Single	Line and match	53.5 x 20.9 x 31.5	496	\$8,980
9EZFAB0000000000	93E 20-30 kVA IAC - 480V input, 480V output, Dual Transformers ⁵	480/480	Yes	Single	Line and match	53.5 x 20.9 x 31.5	834	\$12,010
9EZFBA0000000000	93E 40-60 kVA ITC - 480V input transformer, Single Transformer ⁵	480/208	Yes	Single	Line and match	74.0 x 31.3 x 31.5	918	\$13,830
9EZFBB0000000000	93E 40-60 kVA ITC - 480V input, 480V output, Dual Transformers ⁵	480/480	Yes	Single	Line and match	74.0 x 31.3 x 31.5	1446	\$17,440

Catalog Number	Description	Input/Output Voltage	Subfeed #1 Rating	Subfeed #2 Rating	Subfeed #3 Rating	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZDA0000000000	93E 20-30 kVA IAC-D - W/42-pole Dist Panelboard and No Subfeed Breakers ^{5 7}	208/208 or 220/220	None	None	None	53.5 x 20.9 x 31.5	238	\$9,680
9EZDAA0000000000	93E 20-30 kVA IAC-D - W/42-pole Dist Panelboard, 1-125A Subfeed BRKR ^{5 7}	208/208 or 220/220	125A	None	None	53.5 x 20.9 x 31.5	258	\$10,330
9EZDAAA0000000000	93E 20-30 kVA IAC-D - W/42-pole Dist Panelboard, 2-125A Subfeed BRKR ^{5 7}	208/208 or 220/220	125A	125A	None	53.5 x 20.9 x 31.5	278	\$10,910
9EZDAAAA0000000000	93E 20-30 kVA IAC-D - W/42-pole Dist Panelboard, 3-125A Subfeed BRKR ^{5 7}	208/208 or 220/220	125A	125A	125A	53.5 x 20.9 x 31.5	298	\$11,550

EATON 93E UPS & ACCESSORIES

Subfeed Breaker Options	Breaker Trip Changes	Original	New	Pricing change
Subfeed breakers are also available in 60A and 40A ratings	From 125A to 60A	A	B	None
Subfeed #1 = Part number digit 6 (9EZDA"A"000000000): Subfeed #2 = Part number digit 7 (9EZDAA"A"000000000): Subfeed #3 = Part number digit 8 (9EZDAAA"A"000000000)	From 125A to 40A	A	C	None

93E (40-60 KVA) POWER DISTRIBUTION OPTIONS: IAC-D

Catalog Number	Description	Input/Output Voltage	Subfeed #1 Rating	Subfeed #2 Rating	Subfeed #3 Rating	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZDB0000000000	93E 40-60 kVA IAC-D - W/42-pole Dist Panelboard and No Subfeed Breakers ^{5 7}	208/208 or 220/220	None	None	None	74.0 x 20.9 x 31.5	315	\$10,330
9EZDBA000000000	93E 40-60 kVA IAC-D - W/42-pole Dist Panelboard, 1-250A Subfeed BRKR ^{5 7}	208/208 or 220/220	250A	None	None	74.0 x 20.9 x 31.5	258	\$11,030
9EZDBAA000000000	93E 40-60 kVA IAC-D - W/42-pole Dist Panelboard, 2-250A Subfeed BRKR ^{5 7}	208/208 or 220/220	250A	250A	None	74.0 x 20.9 x 31.5	278	\$11,780
9EZDBAAA00000000	93E 40-60 kVA IAC-D - W/42-pole Dist Panelboard, 3-250A Subfeed BRKR ^{5 7}	208/208 or 220/220	250A	250A	250A	74.0 x 20.9 x 31.5	298	\$12,480

Subfeed Breaker Options	Breaker Trip Changes	Original	New	Pricing change
Subfeed breakers are also available in 125A and 80A ratings	From 250A to 125A	A	B	None
Subfeed #1 = Part number digit 6 (9EZDB"A"000000000): Subfeed #2 = Part number digit 7 (9EZDBA"A"000000000): Subfeed #3 = Part number digit 8 (9EZDBAA"A"000000000)	From 250A to 80A	A	C	None

93E (20-60 KVA) PARALLELING CABINET OPTIONS: INTEGRATED ACCESSORY CABINET - TIE & BYPASS IAC-TB or TIE ONLY - IAC-T and WALL MOUNT CABINETS

Catalog Number	Description	Input/Output Voltage	Output Rating	Breaker Ratings	Dimensions (H x W x D, in)	Weight (lb)	ListPrice
9EZCA0100000000	93E 20-30 kVA IAC-TB - Tie/Bypass for 1+1 Redundant with Maintenance Bypass	208/208 or 220/220	30kVA	See Drawings	53.5 x 20.9 x 31.5	326	\$11,900
9EZCA0200000000	93E 20-30 kVA IAC-TB - Tie/Bypass for 2+0 Capacity with Maintenance Bypass	208/208 or 220/220	60kVA	See Drawings	53.5 x 20.9 x 31.5	326	\$12,710
9ZECA0400000000	93E 20-30 kVA IAC-T - Tie for up to 3+1 Redundant system	208/208 or 220/220	90kVA	See Drawings	53.5 x 20.9 x 31.5	375	\$13,360
M1BIOX0X1XXXXXX	93E 20-30 90 kVA Wall Mount Maintenance Bypass Panel	208/208 or 220/220	90kVA	See Drawings	57.0 x 24.0 x 11.3	350	\$9,680
M9EZGA310000000	93E 20-30 90 kVA Wall Mount Maintenance Bypass Panel With 36 Pole Distribution ⁷	208/208 or 220/220	90kVA	See Drawings	73.5 x 24.0 x 11.3	350	\$10,910
9EZCB0100000000	93E 40-60 kVA IAC-TB - Tie/Bypass for 1+1 Redundant with Maintenance Bypass	208/208 or 220/220	60 kVA	See Drawings	74.0 x 20.9 x 31.5	350	\$15,750
9EZCB0200000000	93E 40-60 kVA IAC-TB - Tie/Bypass for 2+0 Capacity with Maintenance Bypass	208/208 or 220/220	120 kVA	See Drawings	74.0 x 20.9 x 31.5	456	\$18,190
9EZEB0400000000	93E 40-60 kVA IAC-T - Tie for up to 3+1 Redundant system	208/208 or 220/220	180kVA	See Drawings	74.0 x 20.9 x 31.5	404	\$19,360
M1BN0X0X1XXXXXX	93E 40-60 180 kVA Wall Mount Maintenance Bypass Panel	208/208 or 220/220	180kVA	See Drawings	73.5 x 24.0 x 11.3	350	\$18,780
M9EZGB310000000	93E 40-60 180 kVA Wall Mount Maintenance Bypass Panel With 36 Pole Distribution ⁷	208/208 or 220/220	180kVA	See Drawings	90.0 x 36.0 x 11.3	550	\$20,010

Notes:

1. Contact service for information on kVA upgrade kits
2. External battery cabinet (EBC) can be added at any time, however requires authorized service (Not available on reduced runtime units)
3. Eaton recommends you use a left side SAIC-B if Extended battery cabinets (EBC) are to be installed.
4. Wall mount bypass are three-breaker type, therefore for dual feed, separate feed will be required to be supplied by others to feed rectifier
5. Mount Transformer or IDC cabinets on the same side as SAIC-B cabinet.
6. Maximum of 2 Extended Battery Cabinets can be bought for a system. See runtime charts.
7. Distribution breakers for 36 pole panel are Eaton type BAB or QBH
8. External battery cabinet (EBC) cannot be added to reduced runtime 20KVA or 40kVA models

SERVICES

For detailed information on service plans, please contact your Eaton Service Sales Representative or use online service configurator

93E 20 kVA BATTERY RUNTIME CHART

IDC Part No.	oEA	IDC Part No.	oEA	oEA	oEA	oEA	oEA
--------------	-----	--------------	-----	-----	-----	-----	-----

EATON 93E UPS & ACCESSORIES

UPS Part No	9EF-----	UPS Part No	9EA-----	9EA-----	9EA-----	9EA-----	9EA-----
EBC		EBC		9EZAAB----	9EZAAC----	9EZAAB----	9EZAAC----
% Load on UPS	Internal Battery	% Load on UPS	Internal Battery	Qty 1	Qty 1	Qty 2	Qty 2
100%	12	100%	21	55	74	95	138
90%	14	90%	24	71	95	122	177
80%	17	80%	27	81	109	139	203
75%	18	75%	30	87	118	150	219
70%	19	70%	32	95	128	163	237
67%	21	67%	34	100	135	172	251
60%	23	60%	38	113	152	194	283
50%	28	50%	47	139	187	239	348
40%	37	40%	60	179	242	309	450
30%	51	30%	84	250	338	431	-
25%	63	25%	103	310	419	-	-
20%	81	20%	134	403	-	-	-
10%	185	10%	305	-	-	-	-

93E 30 kVA BATTERY RUNTIME CHART

UPS Part No	9EA-----	9EA-----	9EA-----	9EA-----	9EA-----
EBC		9EZAAB----	9EZAAC----	9EZAAB----	9EZAAC----
% Load on UPS	Internal Battery	Qty 1	Qty 1	Qty 2	Qty 2
100%	12	33	45	58	84
90%	14	38	51	68	95
80%	17	44	59	76	110
75%	18	48	64	82	119
70%	20	52	70	89	130
67%	21	55	74	95	138
60%	24	62	84	107	157
50%	30	77	104	133	194
40%	38	100	135	172	251
30%	53	139	187	239	348
25%	65	171	231	294	429
20%	84	221	299	381	-
10%	188	-	-	-	-

93E 40 kVA BATTERY RUNTIME CHART

UPS Part No	9EG-----	UPS Part No	9EB-----	9EB-----	9EB-----	9EB-----	9EB-----
EBC		EBC		9EZABB----	9EZABC----	9EZABB----	9EZABC----
% Load on UPS	Internal Battery	% Load on UPS	Internal Battery	Qty 1	Qty 1	Qty 2	Qty 2
100%	7	100%	12	46	65	85	128
90%	9	90%	14	52	73	96	146
80%	11	80%	17	60	85	111	168
75%	12	75%	18	65	92	120	181
70%	13	70%	19	70	99	130	197
67%	14	67%	21	74	105	138	209
60%	16	60%	23	84	119	156	236
50%	20	50%	29	104	147	193	291
40%	26	40%	37	134	190	249	376
30%	36	30%	52	186	263	345	-
25%	44	25%	64	228	324	425	-
20%	57	20%	82	295	418	-	-
10%	128	10%	183	-	-	-	-

93E 60 kVA BATTERY RUNTIME CHART

UPS Part No	9EB-----	9EB-----	9EB-----	9EB-----	9EB-----
EBC		9EZABB----	9EZABC----	9EZABB----	9EZABC----
% Load on UPS	Internal Battery	Qty 1	Qty 1	Qty 2	Qty 2
100%	6.6	27	39	51	77
90%	7.7	31	44	58	88
80%	9.0	36	51	67	102
75%	10.0	39	56	73	111
70%	11.0	43	61	80	121
67%	12.0	46	65	85	128
60%	14.0	52	73	96	146
50%	18.0	65	92	120	181
40%	23.0	84	119	156	236
30%	33.0	117	166	217	329
25%	40.0	144	204	268	404
20%	52.0	186	263	345	-
10%	114.0	412	-	-	-

Note: Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

EATON 93PM UPS

Double-conversion (20–400 kW)

The Eaton 93PM UPS combines unprecedented efficiency, reliability, and vertical or horizontal scalability with eye-catching design. A space-saving, flexible device that's as easy to deploy as it is to manage, it's the perfect three-phase white or grey space solution for today's mission critical applications.

- Industry-leading efficiency at up to 97% in double conversion and 99.1% in ESS
- Unity power factor provides 100% real power in a small footprint
- Internal battery options support up to 50 kW of load
- Internal redundancy option offers ultimate reliability in a compact footprint and low cost
- Fully detachable sidecar options for pre-wired, true external maintenance bypass in a slim footprint
- Easy to manage with LCD color touchscreen interface and status-indicating LED bars
- Flexible and innovative thermal management configurations to accommodate in-row, wall, or aisle installations
- Easy to deploy with line & match accessory cabinets and a wide range of distribution options
- Includes on-site 7x24 startup
- Includes one year of PredictPulse remote monitoring service (includes connectivity kit)



93PM (50 kW) BASE MODELS - 480V 3-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 50 kW UPS	9PA05D0000A00R2	50 kW	480/480	0	74.0 x 22.0 x 42.0	692	Call
93PM 50 kW UPS with internal batteries, 3 strings	9PA05D2000A00R2	50 kW	480/480	4.3	74.0 x 22.0 x 42.0	1,485	Call
93PM 50 kW UPS with internal batteries, 4 strings	9PA05D4000A00R2	50 kW	480/480	6.7	74.0 x 22.0 x 42.0	1,716	Call
93PM 50 kW UPS with internal batteries, 5 strings	9PA05D6000A00R2	50 kW	480/480	9.5	74.0 x 22.0 x 42.0	1,947	Call
93PM 50 kW UPS, N+1 internal redundancy	9PC05D0000A00R2	50 kW	480/480	0	74.0 x 22.0 x 42.0	867	Call
93PM 50 kW UPS, N+1 internal redundancy with internal batteries, 3 strings	9PC05D2000A00R2	50 kW	480/480	4.3	74.0 x 22.0 x 42.0	1,610	Call
Optional sidecar for top cable entry	(Change digit #11 in the UPS part number to "B")				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2")				74.0 x 8.0 x 42.0		Call
Optional internal rotary MBS	(Change digit #8 in the UPS part number to "1")						Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM (40 kW) BASE MODELS - 480V 3-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 40 kW UPS	9PA04D0000A00R2	40 kW	480/480	0	74.0 x 22.0 x 42.0	692	Call
93PM 40 kW UPS with internal batteries, 3 strings	9PA04D2000A00R2	40 kW	480/480	6.1	74.0 x 22.0 x 42.0	1,485	Call
93PM 40 kW UPS with internal batteries, 4 strings	9PA04D4000A00R2	40 kW	480/480	9.4	74.0 x 22.0 x 42.0	1,716	Call
93PM 40 kW UPS with internal batteries, 5 strings	9PA04D6000A00R2	40 kW	480/480	13.3	74.0 x 22.0 x 42.0	1,947	Call
93PM 40 kW UPS, N+1 internal redundancy	9PC04D0000A00R2	40 kW	480/480	0	74.0 x 22.0 x 42.0	867	Call
93PM 40 kW UPS, N+1 internal redundancy with internal batteries, 3 strings	9PC04D2000A00R2	40 kW	480/480	6.1	74.0 x 22.0 x 42.0	1,610	Call
Optional sidecar for top cable entry	(Change digit #11 in the UPS part number to "B")				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2")				74.0 x 8.0 x 42.0		Call
Optional internal rotary MBS	(Change digit #8 in the UPS part number to "1")						Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM (30 kW) BASE MODELS - 480V 3-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 30 kW UPS	9PA03D0000A00R2	30 kW	480/480	0	74.0 x 22.0 x 42.0	692	Call
93PM 30 kW UPS with internal batteries, 3 strings	9PA03D2000A00R2	30 kW	480/480	9.4	74.0 x 22.0 x 42.0	1,485	Call

Double-conversion (20–400 kW)

EATON 93PM UPS

93PM (30 kW) BASE MODELS - 480V 3-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 30 kW UPS with internal batteries, 4 strings	9PA03D4000A00R2	30 kW	480/480	14.6	74.0 x 22.0 x 42.0	1,716	Call
93PM 30 kW UPS with internal batteries, 5 strings	9PA03D6000A00R2	30 kW	480/480	19	74.0 x 22.0 x 42.0	1,947	Call
93PM 30 kW UPS, N+1 internal redundancy	9PC03D0000A00R2	30 kW	480/480	0	74.0 x 22.0 x 42.0	867	Call
93PM 30 kW UPS, N+1 internal redundancy with internal batteries, 3 strings	9PC03D2000A00R2	30 kW	480/480	9.4	74.0 x 22.0 x 42.0	1,610	Call
Optional sidecar for top cable entry	(Change digit #11 in the UPS part number to "B")				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2")				74.0 x 8.0 x 42.0		Call
Optional internal rotary MBS	(Change digit #8 in the UPS part number to "1")						Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM (20 kW) BASE MODELS - 480V 3-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 20 kW UPS	9PA02D0000A00R2	20 kW	480/480	0	74.0 x 22.0 x 42.0	692	Call
93PM 20 kW UPS with internal batteries, 3 strings	9PA02D2000A00R2	20 kW	480/480	17	74.0 x 22.0 x 42.0	1,485	Call
93PM 20 kW UPS with internal batteries, 4 strings	9PA02D4000A00R2	20 kW	480/480	24	74.0 x 22.0 x 42.0	1,716	Call
93PM 20 kW UPS with internal batteries, 5 strings	9PA02D6000A00R2	20 kW	480/480	32	74.0 x 22.0 x 42.0	1,947	Call
93PM 20 kW UPS, N+1 internal redundancy	9PC02D0000A00R2	20 kW	480/480	0	74.0 x 22.0 x 42.0	867	Call
93PM 20 kW UPS, N+1 internal redundancy with internal batteries, 3 strings	9PC02D2000A00R2	20 kW	480/480	17	74.0 x 22.0 x 42.0	1,610	Call
Optional sidecar for top cable entry	(Change digit #11 in the UPS part number to "B")				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2")				74.0 x 8.0 x 42.0		Call
Optional internal rotary MBS	(Change digit #8 in the UPS part number to "1")						Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

UPS Order Notes

1. Top cable entry requires a sidecar for wire routing space. A 3-breaker maintenance bypass sidecar can be used for top cable entry.
2. All weights are installed weight; add 65 lbs for shipping weight.
3. All units are parallel capable. Hot Sync is included in all models as standard.

93PM (50 kW) BASE MODELS - 480V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 50 kW UPS	9PA05C0000A00R2	50 kW	480/480	0	74.0 x 22.0 x 42.0	702	Call
93PM 50 kW UPS with internal batteries, 3 strings	9PA05C2000A00R2	50 kW	480/480	5.1	74.0 x 22.0 x 42.0	1,678	Call
93PM 50 kW UPS with internal batteries, 4 strings	9PA05C4000A00R2	50 kW	480/480	7.9	74.0 x 22.0 x 42.0	1,909	Call
93PM 50 kW UPS, N+1 internal redundancy	9PC05C0000A00R2	50 kW	480/480	0	74.0 x 22.0 x 42.0	929	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 8.0 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

Double-conversion (20–400 kW)

93PM (40 kW) BASE MODELS - 480V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 40 kW UPS	9PA04C0000A00R2	40 kW	480/480	0	74.0 x 22.0 x 42.0	702	Call
93PM 40 kW UPS with internal batteries, 3 strings	9PA04C2000A00R2	40 kW	480/480	7.1	74.0 x 22.0 x 42.0	1,678	Call
93PM 40 kW UPS with internal batteries, 4 strings	9PA04C4000A00R2	40 kW	480/480	11	74.0 x 22.0 x 42.0	1,909	Call

EATON 93PM UPS

93PM 40 kW UPS, N+1 internal redundancy	9PC04C0000A00R2	40 kW	480/480	0	74.0 x 22.0 x 42.0	929	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 8.0 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM (30 kW) BASE MODELS - 480V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 30 kW UPS	9PA03C0000A00R2	30 kW	480/480	0	74.0 x 22.0 x 42.0	702	Call
93PM 30 kW UPS with internal batteries, 3 strings	9PA03C2000A00R2	30 kW	480/480	10.9	74.0 x 22.0 x 42.0	1,678	Call
93PM 30 kW UPS with internal batteries, 4 strings	9PA03C4000A00R2	30 kW	480/480	16	74.0 x 22.0 x 42.0	1,909	Call
93PM 30 kW UPS, N+1 internal redundancy	9PC03C0000A00R2	30 kW	480/480	0	74.0 x 22.0 x 42.0	929	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 8.0 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM (20 kW) BASE MODELS - 480V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 20 kW UPS	9PA02C0000A00R2	20 kW	480/480	0	74.0 x 22.0 x 42.0	702	Call
93PM 20 kW UPS with internal batteries, 3 strings	9PA02C2000A00R2	20 kW	480/480	19	74.0 x 22.0 x 42.0	1,678	Call
93PM 20 kW UPS with internal batteries, 4 strings	9PA02C4000A00R2	20 kW	480/480	27	74.0 x 22.0 x 42.0	1,909	Call
93PM 20 kW UPS, N+1 internal redundancy	9PC02C0000A00R2	20 kW	480/480	0	74.0 x 22.0 x 42.0	929	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 8.0 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

UPS Order Notes

1. Top cable entry requires a sidecar for wire routing space. A 3-breaker maintenance bypass sidecar can be used for top cable entry.
2. All weights are installed weight; add 65 lbs for shipping weight.
3. All units are parallel capable. Hot Sync is included in all models as standard.

93PM (60 kW) BASE MODELS - 208V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 60 kW UPS	9GC312A000A00R0	60 kW	208/208	0	74.0 x 22.0 x 42.0	708	Call
93PM 60 kW UPS with internal batteries, 4 strings	9GC312A400A00R0	60 kW	208/208	3.2	74.0 x 22.0 x 42.0	1,593	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 12.5 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

Double-conversion (20–400 kW)

93PM (40 kW) BASE MODELS - 208V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 40 kW UPS	9GC208A000A00R0	40 kW	208/208	0	74.0 x 22.0 x 42.0	639	Call
93PM 40 kW UPS with internal batteries, 4 strings	9GC208A400A00R0	40 kW	208/208	6	74.0 x 22.0 x 42.0	1,524	Call
93PM 40 kW UPS, N+1 internal redundancy	9GC308A000A00R0	40 kW	208/208	0	74.0 x 22.0 x 42.0	708	Call
93PM 40 kW UPS, N+1 internal redundancy, with internal batteries, 4-strings	9GC308A400A00R0	40 kW	208/208	6	74.0 x 22.0 x 42.0	1,593	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 12.5 x 42.0		Call

EATON 93PM UPS

Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")	Call
------------------------------------	---	------

93PM (20 kW) BASE MODELS - 208V 4-Wire

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 20 kW UPS	9GC104A000A00R0	20 kW	208/208	0	74.0 x 22.0 x 42.0	570	Call
93PM 20 kW UPS with internal batteries, 4 strings	9GC104A400A00R0	20 kW	208/208	18	74.0 x 22.0 x 42.0	1,455	Call
93PM 20 kW UPS, N+1 internal redundancy	9GC204A000A00R0	20 kW	208/208	0	74.0 x 22.0 x 42.0	639	Call
93PM 20 kW UPS, N+1 internal redundancy, with internal batteries, 4-strings	9GC204A400A00R0	20 kW	208/208	18	74.0 x 22.0 x 42.0	1,524	Call
Optional sidecar for top cable entry	(Change digit 11 to "B" for left mount and "C" for right mount)				74.0 x 8.0 x 42.0		Call
Optional sidecar for 3-breaker maintenance bypass	(Change digits #11-12 in the UPS part number to "E2" for left mount and "H2" for right mount)				74.0 x 12.5 x 42.0		Call
Optional Energy Saver System (ESS)	(Change digit #9 in the UPS part number to "2")						Call

93PM 400kW FRAME (100 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 100 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P010D0000A00R2	100kW	480/480	0	74.0 x 63.9 x 42.0	1,785	Call
93PM 100 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P110D0000A00R2	100kW	480/480	0	74.0 x 63.9 x 42.0	1,925	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (1 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28010000			6.7	74.0 x 34.2 x 42.0	3,322	Call
External battery configuration 2 (1 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE39010000			10.8	74.0 x 34.2 x 42.0	3,795	Call

93PM 400kW FRAME (150 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 150 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P115D0000A00R2	150kW	480/480	0	74.0 x 63.9 x 42.0	1,925	Call
93PM 150 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P215D0000A00R2	150kW	480/480	0	74.0 x 63.9 x 42.0	2,066	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call

Double-conversion (20–400 kW)

93PM 400kW FRAME (150 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (1 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54010000			8.9	74.0 x 34.2 x 42.0	4,386	Call
External battery configuration 2 (2 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28020000			11.3	74.0 x 68.4 x 42.0	6,644	Call

EATON 93PM UPS

93PM 400kW FRAME (200 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 200 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P220D0000A00R2	200kW	480/480	0	74.0 x 63.9 x 42.0	2,066	Call
93PM 200 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P320D0000A00R2	200kW	480/480	0	74.0 x 63.9 x 42.0	2,206	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (2 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28020000			6.9	74.0 x 68.4 x 42.0	6,644	Call
External battery configuration 2 (2 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE39020000			11.2	74.0 x 68.4 x 42.0	7,590	Call

93PM 400kW FRAME (250 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 250 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P325D0000A00R2	250kW	480/480	0	74.0 x 63.9 x 42.0	2,206	Call
93PM 250 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P425D0000A00R2	250kW	480/480	0	74.0 x 63.9 x 42.0	2,347	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (2 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54020000			13	74.0 x 68.4 x 42.0	8,772	Call
External battery configuration 2 (3 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28030000			9.7	74.0 x 102.6 x 42.0	9,966	Call

Double-conversion (20–400 kW)

93PM 400kW FRAME (300 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 300 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P430D0000A00R2	300kW	480/480	0	74.0 x 63.9 x 42.0	2,347	Call
93PM 300 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P530D0000A00R2	300kW	480/480	0	74.0 x 63.9 x 42.0	2,487	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (2 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54020000			8.9	74.0 x 68.4 x 42.0	8,772	Call

EATON 93PM UPS

External battery configuration 2 (3 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54030000	19	74.0 x 102.6 x 42.0	13,158	Call
---	-----------------	----	---------------------	--------	------

93PM 400kW FRAME (350 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 350 kW Rating/400kW Frame UPS, upgradeable up to 400kW, Top Air Exhaust	9P535D0000A00R2	350kW	480/480	0	74.0 x 63.9 x 42.0	2,487	Call
93PM 350 kW Rating/400kW Frame UPS, N+1 internal redundancy	9P635D0000A00R2	350kW	480/480	0	74.0 x 63.9 x 42.0	2,628	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (3 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54030000			14.8	74.0 x 102.6 x 42.0	13,158	Call
External battery configuration 2 (4 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28040000			9	74.0 x 136.8 x 42.0	13,288	Call

93PM 400kW FRAME (400 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
93PM 400 kW Rating/400kW Frame UPS, Top Air Exhaust	9P640D0000A00R2	400kW	480/480	0	74.0 x 63.9 x 42.0	2,628	Call
Optional Energy Saver System (ESS)	Change digit #9 in the UPS part number to "2"						Call
2 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREA200000000						Call
3 breaker line and match maintenance bypass, 65 KAIC, interlock brackets	9PZREB200000000						Call
Optional Kirk Key and SKRU for bypass	Change digit #7 in the bypass part number to "1"						Call
External battery configuration 1 (3 cabinet) Integrated battery cabinet, 400A breaker, with tabs for battery monitoring	9PZVEAE54030000			11.4	74.0 x 102.6 x 42.0	13,158	Call

Double-conversion (20–400 kW)

93PM 400kW FRAME (400 kW) BASE MODELS

Description	Part Number	Rating (kW)	Input/Output Voltage	Base Runtime (min)	Dimensions (H x W x D, inches)	Weight (lb)	List Price
External battery configuration 2 (4 cabinet) Integrated battery cabinet, 300A breaker, with tabs for battery monitoring	9PZTEAE28040000			7	74.0 x 136.8 x 42.0	13,288	Call

93PM INTEGRATED ACCESSORY CABINETS

Description	Part Number	Input/Output Voltage	Dimensions (H x W x D, inches)	Weight (lb)	List Price
IAC-Distribution, K-13 iso output transformer with 250A adjustable distribution breaker	9PZD2S600000001	480/208	74.0 x 31.3 x 42.0	1,149	Call
IAC-Distribution, K-13 TP1 iso output transformer with 250A adjustable distribution breaker	9PZD4S600000001	480/208	74.0 x 31.3 x 42.0	1,149	Call
IAC-Distribution, K-13 iso output transformer with (2) 42-pole distribution panels	9PZD2SB80000001	480/208	74.0 x 31.3 x 42.0	1,149	Call
IAC-Distribution, K-13 TP1 iso output transformer with (2) 42-pole distribution panels	9PZD4SB80000001	480/208	74.0 x 31.3 x 42.0	1,149	Call

EATON 93PM UPS

IAC-Distribution, K-13 iso output transformer with (1) 42-pole distribution panel & (1) 250A adjustable distribution breaker	9PZD2SB40000001	480/208	74.0 x 31.3 x 42.0	1,149	Call
IAC-Distribution, K-13 TP1 iso output transformer with (1) 42-pole distribution panel & (1) 250A adjustable distribution breaker	9PZD4SB40000001	480/208	74.0 x 31.3 x 42.0	1,149	Call
IAC-Tie, (2) MOBs for 1+1 parallel redundant with 3-breaker maintenance bypass	9PZMBA200000000	480/480	74.0 x 19.7 x 42.0	458	Call
IAC-Tie, (2) MOBs for 2+0 parallel capacity with 3-breaker maintenance bypass	9PZMBB200000000	480/480	74.0 x 19.7 x 42.0	458	Call
IAC-Tie, (3) MOBs for 2+1 parallel redundant with 3-breaker maintenance bypass	9PZMBC200000000	480/480	74.0 x 19.7 x 42.0	458	Call
IAC-Tie, (3) MOBs for 3+0 parallel capacity with 3-breaker maintenance bypass	9PZMBD200000000	480/480	74.0 x 19.7 x 42.0	458	Call
IAC-Tie, (4) MOBs for 3+1 parallel redundant with 3-breaker maintenance bypass	9PZMBE200000000	480/480	74.0 x 19.7 x 42.0	458	Call
IAC-Tie, (4) MOBs for 4+0 parallel redundant with 3-breaker maintenance bypass	9PZMBF200000000	480/480	74.0 x 19.7 x 42.0	458	Call

IAC Order Notes

1. All weights are installed weight; add 65 lbs for shipping weight.
2. Panels are PRL1a; use BAB or QBHW bolt-on breakers.
3. Distribution breakers are JG3250 with trip settings of 250, 225, 200, 175, 160, 150, 125, 100A.
4. IAC-D 208/208V cabinet provides 3-wire 208V system input and 4-wire 208V system output. Single feed only.
For UPS metering to reflect 208V, change UPS digit #6 in UPS part number to "P".

93PM INTEGRATED BATTERY CABINETS - For Use with 480V 93PM Systems

Description	Part Number	Rating	Voltage ^{2,3}	Base Runtime (min) ⁴	Dimensions (H x W x D, inches)	Weight (lb)	List Price
IBC-S, one battery string	9PZBBAY08010000	216 cell	432V Link	2.3	74.0 x 19.7 x 42.0	2,395	Call
IBC-S, two battery strings	9PZBBAY08012000	432 cell	432V Link	6.5	74.0 x 19.7 x 42.0	3,580	Call
IBC-S, three battery strings	9PZBBAY08013000	648 cell	432V Link	12.1	74.0 x 19.7 x 42.0	2,405	Call
IBC-SW, 1 battery string/1 cabinet	9PZWBBE20010000	216 cell	480V Link	15	74.0 x 16.7 x 42.0	2,159	Call
IBC-SW, 2 battery string/2 cabinet	9PZWBBE20020000	432 cell	480V Link	36	74.0 x 33.4 x 42.0	4,318	Call
IBC-SW, 3 battery string/3 cabinet	9PZWDBE20030000	648 cell	480V Link	65	74.0 x 50.1 x 42.0	6,477	Call

IBC Order Notes

1. All weights are installed weight; add 48 lbs to determine shipping weight.
2. 432V batteries can **only** be used with 480V 3-Wire UPS's.
3. 480V batteries can **only** be used with both 480V 3W and 4W UPS models
4. Base runtime calculated at 50kW load.

Double-conversion (20–400 kW)

93PM INTEGRATED BATTERY CABINET - For Use with 208V 93PM Systems

Description	Part Number	Rating	Voltage	(min) ²	(H x W x D, inches)	(lb)	Price
IBC-SW, 1 battery string/1 cabinet	9PZWGBE20010000	216 cell	480V Link	11.6	74.0 x 16.7 x 42.0	2,159	Call

IBC Order Notes

1. All weights are installed weight; add 48 lbs to determine shipping weight.
2. Base runtime calculated at 60kW load.

MISCELLANEOUS PARTS

Part Number	Description	List Price
103006244	Wall-mount REPO switch	Call
P-116000035	Power Xpert Gateway Mini-slot communication card	Call
P-116000059	Industrial Relay Mini-slot card	Call

Order Notes

1. UPS EPO is selectable as N/O or N/C.

Power Xpert 9395 UPS

The energy-efficient Power Xpert 9395 UPS is designed to provide backup in a small footprint for large data centers, healthcare applications, and other uninterruptible power modules are purchased with the 9395, you can redundancy option. This means that any time the load is below 50 percent redundant.

- Delivers 99 percent UPS efficiency without sacrificing reliability using Energy Saver System
- Provides stronger power performance with double-conversion design and Eaton's exclusive Easy Capacity Test
- Offers the highest reliability and availability with Powerware Hot Sync paralleling, superior battery management, inherent redundancy and a scalable architecture that adapts to increasing power requirements
- Delivers robust manageability with a 7-inch color touchscreen display, superior control and connectivity
- Works with the Intelligent Power Software Suite, which offers free monitoring, management and shutdown software ideal for protecting physical and virtual machines
- Helps save money and protect the environment through energy efficient operation
- Provides room to grow in the future through on-site upgrades in 275 kVA increments
- Includes one year of PredictPulse remote monitoring service (includes connectivity kit)



Description	Part Number	Rating (kVA)	Input/Output Voltage	Base Runtime (min)	Dimensions Per cabinet (W x D x H, inches)	System Weight (lb)	List Price
9395 225 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CA22106060000R6	225	480 / 480	0	52.8 x 34.4 x 73.9	1900	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9A2213110000				41.1 x 34.5 x 74.0	374	Call
External battery configuration 1 (2 cabinets)	TL2253E28221201			8.5 at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (2 cabinets)	TL2253E33221201			11.5 full load	44.3 x 31.6 x 74.4	7190	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call
9395 250 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CA25106060000R6	250	480 / 480	0	52.8 x 34.4 x 73.9	1900	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9A2513110000				41.1 x 34.5 x 74.0	374	Call
External battery configuration 1 (2 cabinets)	TL2503E28221201			6.9 at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (2 cabinets)	TL2503E39221201			11.2 full load	44.3 x 31.6 x 74.4	7850	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call
Description	Part Number	Rating (kVA)	Input/Output Voltage	Base Runtime (min)	Dimensions Per cabinet (W x D x H, inches)	System Weight (lb)	List Price
9395 275 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CA27106060000R6	275	480 / 480	0	52.8 x 34.4 x 73.9	1900	Call

Power Xpert 9395 UPS

3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9A2713110000				41.1 x 34.5 x 74.0	374	Call
External battery configuration 1 (2 cabinets)	TL2753E28221201		5	at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (3 cabinets)	TL2753E28321201		11.9	full load	44.3 x 31.6 x 74.4	9750	Call
Optional Factory Witness Test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call
9395 450 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CC45106060000R6	450	480 / 480	0	76.6 x 34.4 x 73.9	3274	Call
3 breaker remote maintenance bypass, 65 KAIC, Electrical breaker interlock	MBM9B4513110000				41.1 x 34.5 x 74.0	435	Call
External Battery configuration 1 (3 cabinets)	TL4503E39321201		7	full load	44.3 x 31.6 x 74.4	11775	Call
External Battery configuration 2 (4 cabinets)	TL4503E33421201		11.5	full load	44.3 x 31.6 x 74.4	14380	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call
9395 500 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CC50106060000R6	500	480 / 480	0	76.6 x 34.4 x 73.9	3274	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9B5013110000				41.1 x 34.5 x 74.0	435	Call
External battery configuration 1 (4 cabinets)	TL5003E28421201		6.9	full load	44.3 x 31.6 x 74.4	13000	Call
External battery configuration 2 (4 cabinets)	(4 TL5003E39421201		11.2	full load	44.3 x 31.6 x 74.4	15700	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call
9395 550 kVA UPS, dual feed, monochrome display, no input breaker, common battery, reverse transfer, includes startup	CC55106060000R6	550	480 / 480	0	76.6 x 34.4 x 73.9	3274	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9B5513110000				41.1 x 34.5 x 74.0	435	Call
External battery configuration 1 (4 cabinets)	TL5503E28421201		5	full load	44.3 x 31.6 x 74.4	13000	Call
External battery configuration 2 (4 cabinets)	TL5503E54421201		14.2	full load	44.3 x 31.6 x 74.4	18712	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
Optional 7" color touchscreen	Change 12th digit from "0" to "1"						Call

Notes:

ESS (99% efficiency) & VMMS (Optimized efficiency in double conversion) come standard

Both ESS and VMMS cannot be used at the same time; VMMS can only be used when more than one UPM is installed

Power Xpert 9395P UPS - High Performance

The Power Xpert 9395P High Performance UPS models provide industry-leading efficiency and scalable battery runtimes in a small footprint. Large data centers, healthcare applications, multi-tenant data centers, light industry, and other critical systems can lower their total cost of ownership by leveraging the ground-breaking Energy Saver System.

Monitor and manage your 9395P UPS with the 7-inch color LCD touchscreen display.

The Power Xpert 9395P offers:

- 99% UPS efficiency without sacrificing reliability using Energy Saver System
- Up to 97% UPS efficiency in double conversion
- The highest reliability and availability with inherent redundancy and a scalable architecture that adapts to increasing power requirements
- 300kW Uninterruptible Power Module(s) (UPM), unity power factor rated
- Robust manageability with a 7-inch color touchscreen display, superior control and connectivity and with an extensive service offering



9395P HIGH PERFORMANCE BASE MODELS

Description	Part Number	Rating (kW/kVA)	Input/Output Voltage	Base Runtime (min)	Dimensions Per cabinet (W x D x H, inches)	System Weight (lb)	List Price
9395P high performance 200kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W320106060010R2	200	480 / 480	0	52.5 x 34.4 x 74.0	2150	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9A2013110000				41.1 x 34.5 x 74.0	374	Call
External battery configuration 1 (2 cabinets)	TL2003E28221201			9.6 at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (2 cabinets)	TL2003E33221201			12.9 full load	44.3 x 31.6 x 74.4	7190	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 250kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W325106060010R2	250	480 / 480	0	52.5 x 34.4 x 74.0	2150	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9A2513110000				41.1 x 34.5 x 74.0	374	Call
External battery configuration 1 (2 cabinets)	TL2503E28221201			5.1 at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (2 cabinets)	TL2503E39221201			8.4 full load	44.3 x 31.6 x 74.4	7190	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 275kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W327106060010R2	275	480 / 480	0	52.5 x 34.4 x 74.0	2150	Call
3 breaker remote maintenance bypass, 65 KAIC, Kirk Key interlocks, Solenoid Key Release Unit and "OK to Bypass" indicator lamp.	M1FJJXLX211XXXX				36.00 x 24.00 x 90.00	800	Call
External battery configuration 1 (2 cabinets)	TL2753E28221201			4.1 at full load	44.3 x 31.6 x 74.4	6500	Call
External battery configuration 2 (3 cabinets)	TL2753E28321201			11.2 full load	44.3 x 31.6 x 74.4	7190	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call

Description	Part Number	Rating (kW/kVA)	Input/Output Voltage	Base Runtime (min)	Dimensions Per cabinet (W x D x H, inches)	System Weight (lb)	List Price
-------------	-------------	--------------------	-------------------------	-----------------------	--	--------------------------	---------------

Power Xpert 9395P UPS - High Performance

9395P high performance 300kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W331106060010R2	300	480 / 480	0	52.5 x 34.4 x 74.0	2150	Call
3 breaker remote maintenance bypass, 65 KAIC, Kirk Key interlocks, Solenoid Key Release Unit and "OK to Bypass" indicator lamp.	M1FKKXLX211XXXX				36.00 x 24.00 x 90.00	800	Call
External battery configuration 1 (3 cabinets)	TL3003E39321201			14.9 at full load	44.3 x 31.6 x 74.4	11775	Call
External battery configuration 2 (4 cabinets)	TL3003E33421201			18.9 full load	44.3 x 31.6 x 74.4	14380	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 400kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W740106060010R2	400	480 / 480	0	73.8 x 34.4x 74	3184	Call
3 breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock	MBM9B4013110000				41.1 x 34.5 x 74.0	435	Call
External battery configuration 1 (4 cabinets)	TL4003E28421201			9.6 at full load	44.3 x 31.6 x 74.4	13000	Call
External battery configuration 2 (4 cabinets)	TL4003E39421201			15 full load	44.3 x 31.6 x 74.4	15700	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 500kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W750106060010R2	500	480 / 480	0	73.8 x 34.4x 74	3184	Call
3 breaker remote maintenance bypass, 65 KAIC,electrical breaker interlock	MBM9B4013110000				41.1 x 34.5 x 74.0	435	Call
External battery configuration 1 (4 cabinets)	TL5003E28421201			5.1 at full load	44.3 x 31.6 x 74.4	13000	Call
External battery configuration 2 (4 cabinets)	TL5003E39421201			8.5 full load	44.3 x 31.6 x 74.4	15700	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 550kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W755106060010R2	550	480 / 480	0	73.8 x 34.4x 74	3184	Call
'3 breaker remote maintenance bypass, 65 KAIC, Kirk Key interlocks, Solenoid Key Release Unit and "OK to Bypass" indicator lamp.	M1FNNXPX211XXXX				36.00 x 24.00 x 90.00	1200	Call
External battery configuration 1 (4 cabinets)	TL5503E28421201			4.1 at full load	44.3 x 31.6 x 74.4	13000	Call
External battery configuration 2 (4 cabinets)	TL5503E39421201			7 full load	44.3 x 31.6 x 74.4	18712	Call
Optional factory witness test	FWT9395-1						Call
Optional 100 KAIC input breaker	Change 8th digit from "0" to "4"						Call
9395P high performance 600kW UPS, dual feed, touchscreen display, no input breaker, common battery, reverse transfer, includes startup	W761106060010R2	600	480 / 480	0	73.8 x 34.4x 74	3184	Call
3 breaker remote maintenance bypass, 65 KAIC, Kirk Key interlocks, Solenoid Key Release Unit and "OK to Bypass" indicator lamp.	M1FPPXQX211XXXX				36.00 x 24.0 x 90.00	1200	Call

Power Xpert 9395P UPS - High Performance

External battery configuration 1 (5 cabinets)	TL6003E39521201	9 at full load	44.3 x 31.6 x 74.4	19645	Call
External battery configuration 2 (5 cabinets)	TL6003E54521201	19.1 at full load	44.3 x 31.6 x 74.4	23825	Call
Optional 100 kAIC input breaker	Change 8th digit from "0" to "4"				Call

Notes:

Touchscreen comes standard on high performance model

ESS (99% efficiency) & VMMS (Optimized efficiency in double conversion) come standard

Both ESS and VMMS cannot be used at the same time; VMMS can only be used when more than one UPM is installed

Power Xpert 9395C UPS

Eaton's Power Xpert 9395C is a unity power factor monolithic 1MW rated UPS designed with improved footprint in mind, saving customers valuable data center floor space. Based on the already proven 9395P High Performance hardware, the 9395C UPS provides equal capability in a package best suited for those not requiring modularity. Monitor and manage your 9395C UPS with the 7-inch color LCD touchscreen display. The Power Xpert 9395C offers:

- 99% UPS efficiency without sacrificing reliability using Energy Saver System
- Up to 97% UPS efficiency in double conversion
- 12% footprint reduction from the Power Xpert 9395P High Performance UPS
- 25% footprint reduction from the Power Xpert 9395P High Performance UPS when integrated in a connected system with a power distribution switchgear
- Robust manageability with a 7-inch color touchscreen display, superior control and connectivity and with an extensive service offering
- Includes 1-year subscription to Eaton's PredictPulse monitoring service to proactively identify component risks, reduce downtime, and expedite critical alarm response

9395C BASE MODELS



Description	Part Number	Rating (kVA/kW)	Input/Output Voltage	Base Runtime (min)	Dimensions Per System (W x D x H, inches)	System Weight (lb)	List Price
9395C 1000kVA/1000kW UPS, top entry, dual feed, touchscreen display, no input breaker, distributed bypass, Samsung Lithium battery, without ESS, includes startup	GA11109000020R2	1000/1000	480 / 480	0	146.9 x 34.5 x 77.3	2,402	Call
1600A rated, (2, 3, or 4) breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock, UL891 switchboard	M1FRRXSX21XXXXX				45.0 x 90.0 x 36.0	374	Call
External battery configuration 1 (128S model, 6 cabinets)	BS04866R00606100			8.7 at full load	153.5 x 23.6 x 88.9	38,268	Call
External battery configuration 2 (136S model, 6 cabinets)	BS05176R00606100			9.3 full load	153.5 x 23.6 x 88.9	39,672	Call
Optional factory witness test	FWT9395-2						Call
9395C 1100kVA/1000kW UPS, top entry, dual feed, touchscreen display, no input breaker, distributed bypass, Samsung Lithium battery, without ESS, includes startup	GC21109000020R2	1100/1000	480 / 480	0	146.9 x 34.5 x 77.3	2,402	Call
2000A rated, (2, 3, or 4) breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock, UL891 switchboard	M1FSSXSX21XXXXX				45.0 x 90.0 x 36.0	374	Call
External battery configuration 1 (128S model, 6 cabinets)	BS14866R00606100			8.7 at full load	153.5 x 23.6 x 88.9	38,268	Call
External battery configuration 2 (136S model, 6 cabinets)	BS15176R00606100			9.3 full load	153.5 x 23.6 x 88.9	39,672	Call
Optional factory witness test	FWT9395-2						Call
9395C 1100kVA/1100kW UPS, top entry, dual feed, touchscreen display, no input breaker, distributed bypass, Samsung Lithium battery, without ESS, includes startup	GE22109000020R2	1100/1100	480 / 480	0	146.9 x 34.5 x 77.3	2,402	Call
2000A rated, (2, 3, or 4) breaker remote maintenance bypass, 65 KAIC, electrical breaker interlock, UL891 switchboard	M1FSSXSX21XXXXX				45.0 x 90.0 x 36.0	374	Call
External battery configuration 1 (128S model, 6 cabinets)	BS14866R00606100			7.9 at full load	153.5 x 23.6 x 88.9	38,268	Call
External battery configuration 2 (136S model, 6 cabinets)	BS15176R00606100			8.4 full load	153.5 x 23.6 x 88.9	39,672	Call
Optional factory witness test	FWT9395-2						Call

Static Transfer Switch: STS

WaveStar® STS

Standard Features

- Front access for normal operation.
- NEMA 1 enclosure.
- ETL listed to UL 1008.
- Bottom or top entry/exit.
- System rated for 22 kAIC @ 480V.
- “Real time” waveform capture and monitor as a BCMS Hub.
- Fail safe dual redundant display.
- 10.4” diagonal LCD touch screen.
- 3-Pole Switching.
- Triple redundant logic & power supplies.
- Convection cooling for 250A and 400A units.
- Redundant fans provided for 600A and 800A units.
- Dual input power system with automatic sense and transfer option.
- Volt Second Synchronization algorithm limiting in-rush to 2.0 times.
- Standard password and pin code lockout protection (no key required).
- Five (5) or six (6) non-automatic circuit breakers; two (2) input, two (2) bypass, one (1) isolation (standard) or two (2) isolation (optional).
- Monitoring package communication protocols: Modbus RTU, SNMP or Web enabled (TCP/IP).
- Optional Sidecars with Distribution Options - 250A, 400A, 600A, 800A
- Optional Floor Stands - 18" to 48"



Amp Rating	5 molded case Switch STS	6 molded case Switch STS	22kAIC @480V	65kAIC @ 480V	100kAIC @ 480V	Type
150	See BidMan	See BidMan	STD	See BidMan	See BidMan	Molded Case Switch
250	See BidMan	See BidMan	STD	See BidMan	See BidMan	
400	See BidMan	See BidMan	STD	See BidMan	See BidMan	
600	See BidMan	See BidMan	STD	See BidMan	See BidMan	
800*	See BidMan	See BidMan	STD	See BidMan	See BidMan	
1000	N/A	See BidMan	N/A	STD	CF	
1200	N/A	See BidMan	N/A	STD	CF	
1600	N/A	See BidMan	N/A	STD	CF	
2000	N/A	See BidMan	N/A	STD	CF	

WaveStar® TFA Static Transfer Switch: STS

WaveStar TFA STS

Standard Features

- True Front Access (TFA) for Installation, Operation, Service, Maintenance and Infrared Scanning
- NEMA 1 enclosure.
- ETL listed to UL 1008S.
- Bottom or top entry/exit.
- System rated for 22 kAIC @ 480V.
- "Real time" waveform capture and monitor as a BCMS Hub.
- Fail safe dual redundant display.
- 10.4" diagonal LCD touch screen.
- 3-Pole Switching.
- Triple redundant logic & power supplies.
- Redundant fans.
- Dual input power system with automatic sense and transfer option.
- Volt Second Synchronization algorithm limiting in-rush to 2.0 times.
- Standard password and pin code lockout protection (no key required).
- Five (5) or six (6) non-automatic circuit breakers; two (2) input, two (2) bypass, one (1) isolation (standard) or two (2) isolation (optional).
- Monitoring package communication protocols: Modbus RTU, SNMP or Web enabled (TCP/IP).
- Source, Output and Ground Bus have 1.75-inch 2-hole NEMA Spacing for compression lugs.
- Optional Sidecars with Distribution Options - 250A, 400A, 600A, 800A, 1000A, 1200A
- Optional Floor Stands - 18" to 48"



3-Pole WaveStar TFA STS Front Access

Amp Rating	5 molded case Switch STS	6 molded case Switch STS	22kAIC @480V	65kAIC @ 480V	100kAIC @ 480V	Type
250	See BidMan	See BidMan	STD	See BidMan	See BidMan	Molded Case Switch
400	See BidMan	See BidMan	STD	See BidMan	See BidMan	
600	See BidMan	See BidMan	STD	See BidMan	See BidMan	
800	N/A	See BidMan	N/A	STD	See BidMan	
1000	N/A	See BidMan	N/A	STD	See BidMan	
1200	N/A	See BidMan	N/A	STD	See BidMan	

POWER-SUPPRESS 100: 500 to 7500 VA

Ultra-isolator Noise Suppressor and Isolation Provider

The Power-Suppress 100 offers the following advanced features:

- Traps unwanted harmonics
- Removes surge voltages and minimizes reflected THD
- Eliminates load generated feedback
- Available in both hardwired or line cord/receptacle models
- Fast and easy installation
- Long life operation
- Small footprint—saves valuable space
- Meets FCC Category A
- UL 1012, cUL, UL 1449

Catalog Number	Style Number	Description	Input/Output Voltage	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Line-cord/receptacle models						
T100R-0500	T100R-0500	PWR SUPPRESS T100 RCPT 500 VA	120V IN, 120V OUT	6.5 x 6.1 x 12.0	22	\$1,089
T100R-0750	T100R-0750	PWR SUPPRESS T100 RCPT 750 VA	120V IN, 120V OUT	6.5 x 6.1 x 12.0	28	\$1,163
T100R-1000	T100R-1000	PWR SUPPRESS T100 RCPT 1000 VA	120V IN, 120V OUT	6.5 x 6.1 x 12.0	31	\$1,179
T100R-1800	T100R-1800	PWR SUPPRESS T100 RCPT 1800 VA	120V IN, 120V OUT	10.5 x 11.1 x 17.0	54	\$1,560
T100R-2400	T100R-2400	PWR SUPPRESS T100 RCPT 2400 VA	120V IN, 120V OUT	10.5 x 11.1 x 17.0	58	\$1,771
Terminal style models						
T100H-0500	T100H-0500	PWR SUPPRESS T100 HW 500 VA	120/240V IN, 120/240V OUT	6.4 x 6.1 x 12.0	22	\$1,112
T100H-0750	T100H-0750	PWR SUPPRESS T100 HW 750 VA	120/240V IN, 120/240V OUT	6.4 x 6.1 x 12.0	28	\$1,172
T100H-1000	T100H-1000	PWR SUPPRESS T100 HW 1000 VA	120/240V IN, 120/240V OUT	6.4 x 6.1 x 12.0	31	\$1,195
T100H-1800	T100H-1800	PWR SUPPRESS T100 HW 1800 VA	120/240V IN, 120/240V OUT	10.3 x 11.1 x 17.0	54	\$1,401
T100H-2500	T100H-2500	PWR SUPPRESS T100 HW 2500 VA	120/240V IN, 120/240V OUT	10.3 x 11.1 x 17.0	58	\$1,728
T100H-5000	T100H-5000	PWR SUPPRESS T100 HW 5000 VA	120/240V IN, 120/240V OUT	10.3 x 11.1 x 17.0	86	\$2,517
T100H-5001*	T100H-5001	PWR SUPPRESS T100 HW V 5000 VA	240/480V IN, 120/240V OUT	10.3 x 11.1 x 17.0	92	\$3,043
T100H-7500	T100H-7500	PWR SUPPRESS T100 HW 7500 VA	120/240V IN, 120/240V OUT	10.3 x 11.1 x 17.0	116	\$3,053
T100H-7501*	T100H-7501	PWR SUPPRESS T100 HW 7500 VA	240/480V IN, 120/240V OUT	10.3 x 11.1 x 17.0	111	\$3,693

* Please note the higher input voltage on these models

Power-Suppress 600

The Power-Suppress 600 provides High Efficiency Isolation and Power Conditioning

- Traps unwanted harmonics
- Removes surge voltages and minimizes reflected THD
- Eliminates load generated feedback
- K Rated for high harmonic content Loads
- Triple shielded, computer grade transformer
- Highly efficient—97% typical
- IR Scanning Window for ease of maintenance and safety
- Transient protection and high frequency filter

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price adder for NEMA 3R Option	List price adder for 3rd Shield option	List price adder for Int Surge option	List price for IR Window option
208/208V									
T600BL-015N6	T600BL-015N6	PWRSURE 600 208/208V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600BL-030N6	T600BL-030N6	PWRSURE 600 208/208V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600BL-045N6	T600BL-045N6	PWRSURE 600 208/208V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600BL-075N6	T600BL-075N6	PWRSURE 600 208/208V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600BL-112N6	T600BL-112N6	PWRSURE 600 208/208V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600BL-150N6	T600BL-150N6	PWRSURE 600 208/208V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909

208/480V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price adder for	List price adder for	List price adder for	List price for IR Window
T600BN-015N6	T600BN-015N7	PWRSURE 600 208/480V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600BN-030N6	T600BN-030N7	PWRSURE 600 208/480V30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600BN-045N6	T600BN-045N7	PWRSURE 600 208/480V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600BN-075N6	T600BN-075N7	PWRSURE 600 208/480V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600BN-112N6	T600BN-112N6	PWRSURE 600 208/480V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600BN-150N6	T600BN-150N7	PWRSURE 600 208/480V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$1,745	\$3,909

240/208V

T600CL-015N6	T600CL-015N6	PWRSURE 600 240/208V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600CL-030N6	T600CL-030N6	PWRSURE 600 240/208V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600CL-045N6	T600CL-045N6	PWRSURE 600 240/208V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600CL-075N6	T600CL-075N6	PWRSURE 600 240/208V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600CL-112N6	T600CL-112N6	PWRSURE 600 240/208V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600CL-150N6	T600CL-150N6	PWRSURE 600 240/208V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909

240/480V

T600CN-015N6	T600CN-015N6	PWRSURE 600 240/480V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600CN-030N6	T600CN-030N6	PWRSURE 600 240/480V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600CN-045N6	T600CN-045N6	PWRSURE 600 240/480V 45 kVA	23 x 20 x 28	700	\$16,812	\$425	\$331	\$1,737	\$1,952
T600CN-075N6	T600CN-075N6	PWRSURE 600 240/480V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600CN-112N6	T600CN-112N6	PWRSURE 600 240/480V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600CN-150N6	T600CN-150N6	PWRSURE 600 240/480V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$1,745	\$3,909

480/208V

T600DL-015N6	T600DL-015N6	PWRSURE 600 480/208V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600DL-030N6	T600DL-030N6	PWRSURE 600 480/208V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600DL-045N6	T600DL-045N6	PWRSURE 600 480/208V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600DL-075N6	T600DL-075N6	PWRSURE 600 480/208V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600DL-112N6	T600DL-112N6	PWRSURE 600 480/208V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600DL-150N6	T600DL-150N6	PWRSURE 600 480/208V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909
T600DL-225N6	T600DL-225N6	PWRSURE 600 480/208V 225 kVA	38 x 32 x 57	1880	\$43,965	\$430	\$898	\$2,259	\$3,909

T600DL-300N6	T600DL-300N6	PWRSURE 600 480/208V 300 kVA	56 x 41.5 x 48	2656	\$73,415	STD	\$1,466	\$2,508	\$3,973
T600DL-500N6	T600DL-500N6	PWRSURE 600 480/208V 500 kVA	45 x 48 x 62.5	4820	\$119,227	STD	\$2,380	\$2,508	\$4,886
480/480V									
T600DN-015N6	T600DN-015N6	PWRSURE 600 480/480V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600DN-030N6	T600DN-030N6	PWRSURE 600 480/480V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600DN-045N6	T600DN-045N6	PWRSURE 600 480/480V 45 kVA	23 x 20 x 28	700	\$16,479	\$404	\$331	\$1,737	\$1,952
T600DN-075N6	T600DN-075N6	PWRSURE 600 480/480V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600DN-112N6	T600DN-112N6	PWRSURE 600 480/480V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600DN-150N6	T600DN-150N6	PWRSURE 600 480/480V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909
T600DN-225N6	T600DN-225N6	PWRSURE 600 480/480V 225 kVA	38 x 32 x 57	1880	\$43,965	\$430	\$898	\$2,259	\$3,909
T600DN-300N6	T600DN-300N6	PWRSURE 600 480/480V 300 kVA	56 x 41.5 x 48	2656	\$73,415	STD	\$1,466	\$2,508	\$3,973
T600DN-500N6	T600DN-500N6	PWRSURE 600 480/480V 500 kVA	45 x 48 x 62.5	4820	\$119,227	STD	\$2,380	\$2,508	\$4,886

600/208V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price adder for NEMA 3R Option	List price adder for 3rd Shield option	List price adder for Int Surge option	List price for IR Window option
T600EL-015N6	T600EL-015N6	PWRSURE 600 480/480V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600EL-030N6	T600EL-030N6	PWRSURE 600 480/480V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600EL-045N6	T600EL-045N6	PWRSURE 600 480/480V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600EL-075N6	T600EL-075N6	PWRSURE 600 480/480V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600EL-112N6	T600EL-112N6	PWRSURE 600 480/480V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600EL-150N6	T600EL-150N6	PWRSURE 600 480/480V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909
T600EL-225N6	T600EL-225N6	PWRSURE 600 480/480V 225 kVA	38 x 32 x 57	1880	\$43,965	\$430	\$898	\$2,259	\$3,909
T600EL-300N6	T600EL-300N6	PWRSURE 600 480/480V 300 kVA	56 x 41.5 x 48	2656	\$73,415	STD	\$1,466	\$2,508	\$3,973
T600EL-500N6	T600EL-500N6	PWRSURE 600 480/480V 500 kVA	45 x 48 x 62.5	4820	\$119,227	STD	\$2,380	\$2,508	\$4,886

600/480V

T600EN-015N6	T600EN-015N6	PWRSURE 600 600/480V 15 kVA	23 x 20 x 28	370	\$9,513	\$430	\$216	\$1,745	\$1,958
T600EN-030N6	T600EN-030N6	PWRSURE 600 600/480V 30 kVA	23 x 20 x 28	495	\$12,452	\$430	\$216	\$1,745	\$1,958
T600EN-045N6	T600EN-045N6	PWRSURE 600 600/480V 45 kVA	23 x 20 x 28	700	\$16,479	\$425	\$331	\$1,737	\$1,952
T600EN-075N6	T600EN-075N6	PWRSURE 600 600/480V 75 kVA	23 x 20 x 28	830	\$19,634	\$430	\$389	\$1,745	\$1,958
T600EN-112N6	T600EN-112N6	PWRSURE 600 600/480V 112 kVA	38 x 32 x 57	1210	\$29,340	\$430	\$598	\$1,745	\$3,909
T600EN-150N6	T600EN-150N6	PWRSURE 600 600/480V 150 kVA	38 x 32 x 57	1470	\$33,039	\$430	\$708	\$2,259	\$3,909
T600EN-225N6	T600EN-225N6	PWRSURE 600 600/480V 225 kVA	38 x 32 x 57	1880	\$43,965	\$430	\$898	\$2,259	\$3,909
T600EN-300N6	T600EN-300N6	PWRSURE 600 600/480V 300 kVA	56 x 41.5 x 48	2656	\$73,415	STD	\$1,466	\$2,508	\$3,973
T600EN-500N6	T600EN-500N6	PWRSURE 600 600/480V 500 kVA	45 x 48 x 62.5	4820	\$119,227	STD	\$2,380	\$2,508	\$4,886

Power-Suppress 600 OPTIONS

Suffix	Description
N	NEMA 1/2 Enclosure
R	NEMA 3R Enclosure
A	Third Shield
B	Surge Protector
C	IR Window
D	Third Shield, Surge Protector
E	Third Shield, IR Window
F	Surge Protector, IR Window
G	Third Shield, Surge Protector, IR Window

Power-Sure 700

The Power-Sure 700 provides intelligent protection for transmitters & industrial controls.

- Fast microprocessor controlled voltage regulation
- Tight output voltage regulation
- Zero-current switching
- Wide input regulation range
- Triple shielded, computer grade transformer
- Highly efficient—97% typical
- High inrush capability
- Transient protection and high frequency filter
- Includes input circuit breaker
- Manual bypass switch
- Optional 10-45 kVA
- Standard 50+ kVA

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ B option	List price w/ STD Meter option	Premium Meter option	List price w/ Int Surge option
208/208V									
TBL-010K-6	TBL-010K-6	PWRSURE 700 208/208V 10 kVA	30.2 x 22.2 x 29.0	440	\$22,176	\$23,981	\$27,657	\$29,388	\$24,196
TBL-015K-6	TBL-015K-6	PWRSURE 700 208/208V 15 kVA	30.2 x 22.2 x 29.0	520	\$23,999	\$25,787	\$29,457	\$31,194	\$26,008
TBL-025K-6	TBL-025K-6	PWRSURE 700 208/208V 25 kVA	44.2 x 22.2 x 29.0	700	\$34,605	\$36,293	\$39,969	\$41,705	\$36,507
TBL-030K-6	TBL-030K-6	PWRSURE 700 208/208V 30 kVA	44.2 x 22.2 x 29.0	720	\$29,964	\$31,697	\$35,373	\$37,109	\$31,917
TBL-045K-6	TBL-045K-6	PWRSURE 700 208/208V 45 kVA	44.3 x 45.9 x 29.0	950	\$37,340	\$40,333	\$42,671	\$44,414	\$39,216
TBL-050K-6	TBL-050K-6	PWRSURE 700 208/208V 50 kVA	66.0 x 29.0 x 35.5	970	\$45,532	STD	\$50,797	\$52,529	\$47,337
TBL-075K-6	TBL-075K-6	PWRSURE 700 208/208V 75 kVA	76.0 x 34.4 x 35.5	1100	\$51,427	STD	\$56,627	\$58,363	\$53,177
TBL-100K-6	TBL-100K-6	PWRSURE 700 208/208V 100 kVA	76.0 x 34.4 x 35.5	1660	\$69,472	STD	\$74,500	\$76,242	\$71,045
TBL-125K-6	TBL-125K-6	PWRSURE 700 208/208V 125 kVA	76.0 x 34.4 x 35.5	1980	\$78,498	STD	\$73,999	\$85,191	\$79,987
TBL-150K-6	TBL-150K-6	PWRSURE 700 208/208V 150 kVA	76.0 x 34.4 x 35.5	2200	\$93,406	STD	\$98,214	\$99,957	\$94,754
TBL-225K-6	TBL-225K-6	PWRSURE 700 208/208V 225 kVA	77.4 x 56.0 x 41.5	3300	\$144,365	STD	\$148,693	\$150,435	\$145,236
TBL-300K-6	TBL-300K-6	PWRSURE 700 208/208V 300 kVA	77.4 x 56.0 x 41.5	4000	\$210,352	STD	\$211,146	\$212,535	\$210,128

240/208V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ B option	List price w/ STD Meter option	Premium Meter option	List price w/ Int Surge option
TCL-010K-6	TCL-010K-6	PWRSURE 700 240/208V 10 kVA	30.2 x 22.2 x 29.0	440	\$22,305	\$24,115	\$27,522	\$29,533	\$24,341
TCL-015K-6	TCL-015K-6	PWRSURE 700 240/208V 15 kVA	30.2 x 22.2 x 29.0	520	\$23,999	\$25,787	\$28,054	\$30,144	\$26,008
TCL-030K-6	TCL-030K-6	PWRSURE 700 240/208V 30 kVA	44.2 x 22.2 x 29.0	720	\$29,042	\$30,789	\$32,817	\$36,195	\$30,996
TCL-045K-6	TCL-045K-6	PWRSURE 700 240/208V 45 kVA	44.3 x 45.9 x 29.0	950	\$43,942	\$46,879	\$46,874	\$50,954	\$45,757

240/208V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ B option	List price w/ STD Meter option	Premium Meter option	List price w/ Int Surge option
TCL-050K-6	TCL-050K-6	PWRSURE 700 240/208V 50 kVA	66.0 x 29.0 x 35.5	970	\$38,408	STD	\$43,742	\$45,484	\$40,286
TCL-075K-6	TCL-075K-6	PWRSURE 700 240/208V 75 kVA	76.0 x 34.4 x 35.5	1100	\$55,494	STD	\$60,655	\$62,391	\$57,200
TCL-100K-6	TCL-100K-6	PWRSURE 700 240/208V 100 kVA	76.0 x 34.4 x 35.5	1660	\$72,095	STD	\$77,111	\$78,842	\$73,650

480/208V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ B option	List price w/ STD Meter option	Premium Meter option	List price w/ Int Surge option
TDL-010K-6	TDL-010K-6	PWRSURE 700 480/208V 10 kVA	30.2 x 22.2 x 29.0	440	\$24,573	\$26,348	\$30,024	\$31,761	\$26,569
TDL-015K-6	TDL-015K-6	PWRSURE 700 480/208V 15 kVA	30.2 x 22.2 x 29.0	520	\$27,178	\$28,930	\$32,611	\$34,348	\$29,150
TDL-025K-6	TDL-025K-6	PWRSURE 700 480/208V 25 kVA	44.2 x 22.2 x 29.0	700	\$29,188	\$30,927	\$34,603	\$36,345	\$31,148
TDL-030K-6	TDL-030K-6	PWRSURE 700 480/208V 30 kVA	44.2 x 22.2 x 29.0	720	\$30,449	\$32,178	\$35,853	\$37,595	\$32,398
TDL-045K-6	TDL-045K-6	PWRSURE 700 480/208V 45 kVA	44.3 x 45.9 x 29.0	950	\$39,816	\$42,793	\$45,132	\$46,874	\$41,682
TDL-050K-6	TDL-050K-6	PWRSURE 700 480/208V 50 kVA	66.0 x 29.0 x 35.5	970	\$40,057	STD	\$45,369	\$47,106	\$41,907
TDL-075K-6	TDL-075K-6	PWRSURE 700 480/208V 75 kVA	76.0 x 34.4 x 35.5	1100	\$59,707	STD	\$64,835	\$66,577	\$61,373
TDL-100K-6	TDL-100K-6	PWRSURE 700 480/208V 100 kVA	76.0 x 34.4 x 35.5	1660	\$64,785	STD	\$69,864	\$71,601	\$66,402
TDL-125K-6	TDL-125K-6	PWRSURE 700 480/208V 125 kVA	76.0 x 34.4 x 35.5	1980	\$64,428	STD	\$69,512	\$71,253	\$66,050
TDL-150K-6	TDL-150K-6	PWRSURE 700 480/208V 150 kVA	76.0 x 34.4 x 35.5	2200	\$71,919	STD	\$76,931	\$78,673	\$73,470
TDL-225K-6	TDL-225K-6	PWRSURE 700 480/208V 225 kVA	77.4 x 56.0 x 41.5	3300	\$126,023	STD	\$130,529	\$132,271	\$127,074

TDL-300K-6	TDL-300K-6	PWRSURE 700 480/208V 300 kVA	77.4 x 56.0 x 41.5	4000	\$142,740	STD	\$144,172	\$145,567	\$143,160
480/480V									
TDN-010K-6	TDN-010K-6	PWRSURE 700 480/480V 10 kVA	30.2 x 22.2 x 29.0	440	\$22,696	\$24,491	\$28,167	\$29,909	\$29,909
TDN-025K-6	TDN-025K-6	PWRSURE 700 480/480V 25 kVA	44.2 x 22.2 x 29.0	700	\$31,987	\$33,700	\$37,375	\$39,106	\$39,106
TDN-030K-6	TDN-030K-6	PWRSURE 700 480/480V 30 kVA	44.2 x 22.2 x 29.0	720	\$31,905	\$33,613	\$37,294	\$39,031	\$39,031
TDN-045K-6	TDN-045K-6	PWRSURE 700 480/480V 45 kVA	44.3 x 45.9 x 29.0	950	\$41,003	\$43,962	\$46,305	\$48,042	\$48,042
TDN-075K-6	TDN-075K-6	PWRSURE 700 480/480V 75 kVA	76.0 x 34.4 x 35.5	1100	\$48,213	STD	\$53,455	\$55,185	\$55,185
TDN-100K-6	TDN-100K-6	PWRSURE 700 480/480V 100 kVA	76.0 x 34.4 x 35.5	1660	\$63,435	STD	\$68,532	\$70,269	\$70,269
TDN-125K-6	TDN-125K-6	PWRSURE 700 480/480V 125 kVA	76.0 x 34.4 x 35.5	1980	\$65,199	STD	\$70,276	\$72,012	\$72,012
TDN-150K-6	TDN-150K-6	PWRSURE 700 480/480V 150 kVA	76.0 x 34.4 x 35.5	2200	\$78,750	STD	\$83,697	\$85,434	\$85,434

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ w/ B option	List price w/ STD Meter option	List price w/ Premium Meter option	List price w/ Int Surge option
TDN-225K-6	TDN-225K-6	PWRSURE 700 480/480V 225 kVA	77.4 x 56.0 x 41.5	3300	\$115,580	STD	\$120,180	\$121,917	\$116,725
TDN-300K-6	TDN-300K-6	PWRSURE 700 480/480V 300 kVA	77.4 x 56.0 x 41.5	4000	\$141,887	STD	\$146,232	\$147,969	\$142,777
600/208V									
TEL-010K-6	TEL-010K-6	PWRSURE 700 600/208V 10 kVA	30.2 x 22.2 x 29.0	440	\$23,105	\$24,908	\$28,577	\$30,314	\$25,122
TEL-015K-6	TEL-015K-6	PWRSURE 700 600/208V 15 kVA	30.2 x 22.2 x 29.0	520	\$24,829	\$26,610	\$30,279	\$32,015	\$26,823
TEL-025K-6	TEL-025K-6	PWRSURE 700 600/208V 25 kVA	44.2 x 22.2 x 29.0	700	\$30,076	\$31,812	\$35,494	\$37,230	\$32,038
TEL-030K-6	TEL-030K-6	PWRSURE 700 600/208V 30 kVA	44.2 x 22.2 x 29.0	720	\$30,345	\$32,079	\$35,755	\$37,484	\$32,293
TEL-045K-6	TEL-045K-6	PWRSURE 700 600/208V 45 kVA	44.3 x 45.9 x 29.0	950	\$40,157	\$43,128	\$45,473	\$47,198	\$42,012
TEL-050K-6	TEL-050K-6	PWRSURE 700 600/208V 50 kVA	66.0 x 29.0 x 35.5	970	\$40,863	STD	\$46,167	\$47,904	\$42,706
TEL-075K-6	TEL-075K-6	PWRSURE 700 600/208V 75 kVA	76.0 x 34.4 x 35.5	1100	\$62,442	STD	\$67,536	\$69,273	\$64,087
TEL-100K-6	TEL-100K-6	PWRSURE 700 600/208V 100 kVA	76.0 x 34.4 x 35.5	1660	\$74,205	STD	\$79,200	\$80,937	\$75,739
TEL-125K-6	TEL-125K-6	PWRSURE 700 600/208V 125 kVA	76.0 x 34.4 x 35.5	1980	\$67,513	STD	\$72,561	\$74,304	\$69,111
TEL-150K-6	TEL-150K-6	PWRSURE 700 600/208V 150 kVA	76.0 x 34.4 x 35.5	2200	\$91,471	STD	\$96,310	\$98,046	\$92,849
TEL-225K-6	TEL-225K-6	PWRSURE 700 600/208V 225 kVA	77.4 x 56.0 x 41.5	3300	\$126,023	STD	\$130,529	\$132,271	\$127,074
TEL-300K-6	TEL-300K-6	PWRSURE 700 600/208V 300 kVA	77.4 x 56.0 x 41.5	4000	\$141,705	STD	\$146,053	\$147,795	\$142,604
600/480V									
TEN-010K-6	TEN-010K-6	PWRSURE 700 600/480V 10 kVA	30.2 x 22.2 x 29.0	440	\$22,696	\$24,491	\$28,167	\$29,909	\$24,711
TEN-015K-6	TEN-015K-6	PWRSURE 700 600/480V 15 kVA	30.2 x 22.2 x 29.0	520	\$25,524	\$27,305	\$30,973	\$32,715	\$27,518
TEN-025K-6	TEN-025K-6	PWRSURE 700 600/480V 25 kVA	44.2 x 22.2 x 29.0	700	\$28,130	\$29,886	\$33,555	\$35,297	\$30,099
TEN-030K-6	TEN-030K-6	PWRSURE 700 600/480V 30 kVA	44.2 x 22.2 x 29.0	720	\$31,567	\$33,289	\$36,965	\$38,701	\$33,503
TEN-045K-6	TEN-045K-6	PWRSURE 700 600/480V 45 kVA	44.3 x 45.9 x 29.0	950	\$36,077	\$39,083	\$41,427	\$43,158	\$37,965
TEN-075K-6	TEN-075K-6	PWRSURE 700 600/480V 75 kVA	76.0 x 34.4 x 35.5	1100	\$57,440	STD	\$62,583	\$64,326	\$59,132
TEN-100K-6	TEN-100K-6	PWRSURE 700 600/480V 100 kVA	76.0 x 34.4 x 35.5	1660	\$67,449	STD	\$72,504	\$74,240	\$69,042
TEN-125K-6	TEN-125K-6	PWRSURE 700	76.0 x 34.4 x 35.5	1980	\$69,757	STD	\$74,784	\$76,527	\$71,328
TEN-150K-6	TEN-150K-6	PWRSURE 700 600/480V 150 kVA	76.0 x 34.4 x 35.5	2200	\$82,776	STD	\$87,691	\$89,428	\$84,237

600/480V

Catalog Number	Style Number	Description	Dimensions* (H x W x D, inches)	Weight (lb)	List Price	List price w/ w/ B option	List price w/ STD Meter option	List price w/ Premium Meter option	List price w/ Int Surge option
TEN-225K-6	TEN-225K-6	PWRSURE 700 600/480V 225 kVA	77.4 x 56.0 x 41.5	3300	\$119,519	STD	\$124,082	\$125,811	\$120,620
TEN-300K-6	TEN-300K-6	PWRSURE 700 600/480V 300 kVA	77.4 x 56.0 x 41.5	4000	\$135,705	STD	\$140,115	\$141,845	\$136,654

** 10 & 15 KVA units utilize the next larger cabinet size when the meter option is included

Power-Sure 700 OPTIONS

Suffix	Description	List Price
W	Extended Regulation range (+10% to -40%)	Contact Factory for pricing

Power-Sure 800

Power Conditioners (500VA to 25 kVA)

Superior power conditioning for industrial, commercial and medical equipment. Power-Sure 800 power conditioners provide high quality power with inherent surge protection, noise and bi-directional harmonic filtering, as well as superior isolation. Power-Sure 800 units range from office models to floor or wall/panel mounted industrial models and provide an excellent solution for any application with noisy or poor power quality.

- Superior isolation
- Tight voltage regulation
- High immunity to distortion
- Lightning and surge protection
- Protection against power interruptions
- Power factor correction
- Bi-directional harmonic filtering
- Meets ANSI standards for computers with inputs as low as 50% of nominal
- UL 1012, UL 544 and cUL Listed
- K-30 rated design

Catalog Number	Style Number	Description	Dimensions (H x W x D, inches)	Weight (lb)	List Price
60 Hz Models—Receptacle Style (Plug-and-play)					
T800R-01000	T800R-01000	PWRSURE 800 OFC/RCPT 1 kVA	8.5 x 12.8 x 17.5	46	\$1,798
T800R-01600	T800R-01600	PWRSURE 800 OFC/RCPT 1.6 kVA	8.5 x 12.8 x 17.5	62	\$2,255
T800R-02100	T800R-02100	PWRSURE 800 OFC/RCPT 2.1 kVA	8.5 x 12.8 x 17.5	65	\$2,466
T800R-02500	T800R-02500	PWRSURE 800 OFC/RCPT 2.5 kVA	8.5 x 12.8 x 17.5	68	\$2,587
T800R-03500	T800R-03500	PWRSURE 800 OFC/RCPT 3.5 kVA	8.5 x 12.8 x 17.5	72	\$3,098
T800R-03501	T800R-03501	PWRSURE 800 OFC/RCPT 3.5 kVA	8.5 x 12.8 x 17.5	73	\$3,274
T800R-05000 *	T800R-05000	PWRSURE 800 OFC/RCPT 5 kVA	15.0 x 23.8 x 22.5	176	\$4,402
T800R-07500 *	T800R-07500	PWRSURE 800 OFC/RCPT 7.5 kVA	15.0 x 23.8 x 22.5	210	\$5,264
T800R-10000 *	T800R-10000	PWRSURE 800 OFC/RCPT 10 kVA	15.0 x 23.8 x 22.5	256	\$7,417
T800R-15000 *	T800R-15000	PWRSURE 800 OFC/RCPT 15 kVA	15.0 x 23.8 x 22.5	314	\$8,923
60 Hz Models—Hardwired Wall or Panel Mount					
T800P-00500	T800P-00500	PWRSURE 800 PNL/HW 500 VA	9.0 x 14.0 x 10.0	52	\$1,446
T800P-00750	T800P-00750	PWRSURE 800 PNL/HW 750 VA	9.0 x 14.0 x 10.0	60	\$1,869
T800P-01000	T800P-01000	PWRSURE 800 PNL/HW 1 kVA	9.0 x 14.0 x 10.0	82	\$1,855
T800P-01500	T800P-01500	PWRSURE 800 PNL/HW 1.5 kVA	13.0 x 16.5 x 14.8	106	\$2,671
T800P-02000	T800P-02000	PWRSURE 800 PNL/HW 2 kVA	13.0 x 16.5 x 14.8	125	\$2,583
T800P-03000	T800P-03000	PWRSURE 800 PNL/HW 3 kVA	13.0 x 16.5 x 14.8	142	\$4,001
T800P-05000	T800P-05000	PWRSURE 800 PNL/HW 5 kVA	27.0 x 22.5 x 28.5	437	\$7,194
T800P-08000	T800P-08000	PWRSURE 800 PNL/HW 8 kVA	27.0 x 22.5 x 28.5	495	\$8,848
T800P-10000	T800P-10000	PWRSURE 800 PNL/HW 10 kVA	27.0 x 22.5 x 28.5	535	\$10,799
60 Hz Models—Hardwired Floor Mount					
T800F-05000	T800F-05000	PWRSURE 800 FLR/HW 5 kVA	23.0 x 20.0 x 28.5	407	\$7,323
T800F-08000	T800F-08000	PWRSURE 800 FLR/HW 8 kVA	23.0 x 20.0 x 28.5	465	\$8,841
T800F-10000	T800F-10000	PWRSURE 800 FLR/HW 10 kVA	23.0 x 20.0 x 28.5	407	\$9,922
T800F-15000	T800F-15000	PWRSURE 800 FLR/HW 15 kVA	35.0 x 25.0 x 39.5	830	\$15,404
T800F-20000	T800F-20000	PWRSURE 800 FLR/HW 20 kVA	35.0 x 25.0 x 39.5	950	\$18,646
T800F-25000	T800F-25000	PWRSURE 800 FLR/HW 25 kVA	35.0 x 25.0 x 39.5	1070	\$21,283

POWER-SURE 800

CUSTOM OUTPUT RECEPTACLES

Suffix	NEMA	Volts	Amps	Output Panels used
A	(1) 5-15R	120	15	1
B	(2) 5-15R	120	15	1
C	(1) 5-20R	120	20	1
D	(2) 5-20R	120	20	1
E	(1) 5-30R	120	30	1.5
F	(1) 6-15R	208/240	15	1

Power-Sure 800

G	(2) 6-15R	208/240	15	1
H	(1) 6-20R	208/240	20	1
I	(2) 6-20R	208/240	20	1
J	(1) 6-30R	208/240	30	1.5
K	(1) 6-50R	208/240	50	1.5
L	(1) 14-20R	120/240	20	1
M	(1) 14-30R	120/240	20	1.5
N	(1) L5-15R	120	120	1
P	(2) L5-15R	120	15	1
R	(1) L5-20R	120	20	1
S	(1) L5-30R	120	30	1
T	(1) L6-15R	208/240	15	1
U	(2) L6-15R	208/240	15	1
V	(1) L6-20R	208/240	20	1
W	(1) L6-30R	208/240	30	1
X	(1) L14-30R	120/240	20	1
Y	(1) L14-20R	120/240	30	1

Example: T800R-100002B2Y Consists of 2 (2)5-15R receptacles and 2 (1)L14-30R receptacles

* Contact factory for pricing of custom receptacles

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE



Intelligent Power Manager (IPM) version 2.X (NEW)

See notes below regarding new node definition and maintenance support requirement

Description	Catalog Number	US List price	Discounting	
IPM MONITOR, Discounting available above 25 monitored nodes			node qty	Discount
IPM Monitor Perpetual, per node	IPM-MO-P	\$41	26-35	40%
IPM Monitor 1 Yr Maint., per node	IPM-MO-M1	\$9	36-50	50%
IPM Monitor 5 Yr Maint., per node	IPM-MO-M5	\$39	51-100	56%
IPM Monitor perpetual, and 1 Yr Maint bundle, per node	IPM-MO-P1	\$50	101-250	67%
IPM Monitor perpetual, and 5 Yr Maint bundle, per node	IPM-MO-P5	\$80	251-500	75%
IPM Monitor Subscription, 1 Yr, per node	IPM-MO-SUB1	\$20		
IPM MANAGE, Discounting available above 25 managed nodes			node qty	Discount
IPM Manage Perpetual, per node	IPM-MA-P	\$115	26-35	40%
IPM Manage 1 Yr Maint., per node	IPM-MA-M1	\$23	36-50	50%
IPM Manage 5 Yr Maint., per node	IPM-MA-M5	\$109	51-100	56%
IPM Manage perpetual, and 1 Yr Maint bundle, per node	IPM-MA-P1	\$138	101-250	67%
IPM Manage perpetual, and 5 Yr Maint bundle, per node	IPM-MA-P5	\$214	251-500	75%
IPM Manage Subs., 1 Yr, per node	IPM-MA-SUB1	\$56		
IPM OPTIMIZE, Discounting available above 5 managed/optimized nodes			node qty	Discount
IPM Optimize Perpetual, per node	IPM-OP-P	\$240	6-10	31%
IPM Optimize 1 Yr Maint., per node	IPM-OP-M1	\$48	11-15	38%
IPM Optimize 5 Yr Maint., per node	IPM-OP-M5	\$228	16-25	44%
IPM Optimize perpetual, and 1 Yr Maint bundle, per node	IPM-OP-P1	\$288	26-35	47%
IPM Optimize perpetual, and 5 Yr Maint bundle, per node	IPM-OP-P5	\$468	36-50	50%
IPM Optimize Subs., 1 Yr, per node	IPM-OP-SUB1	\$117	51-100	56%
			101-250	67%
			251-500	75%
IPM GRAPHITE / GRAFANA ADD-ON (Discounting available above 25 monitored nodes)				
IPM - Graphite / Grafana add-on, 1 Yr, per node	IPM-GRAPHITE	\$10	Same as IPM Monitor	

Notes - new for IPM version 2.X

A node equals a power device (UPS / rack PDU), a hypervisor, a non-virtualized server or a storage unit

A maintenance package must be purchased concurrently with a perpetual license

Customers buying/continuing use on IPM version 1.X will follow pricing shown below

Intelligent Power Manager (IPM) version 1.X

IPM MONITOR - free up to 10 nodes		
IPM Monitor - 11 to 15 nodes	IPM-MON-15	\$1,290
IPM Monitor - 16 to 25 nodes	IPM-MON-25	\$2,150
IPM Monitor - 26 to 35 nodes	IPM-MON-35	\$3,010
IPM Monitor - 36 to 50 nodes	IPM-MON-50	\$4,000
IPM Monitor - 51 to 100 nodes	IPM-MON-100	\$8,000
IPM Monitor - 101 to 250 nodes	IPM-MON-250	\$19,000
IPM Monitor - 251 to 500 nodes	IPM-MON-500	\$36,000
IPM BASIC - free up to 10 nodes		
IPM Basic - 11 to 15 nodes	IPM-BASIC-15	\$1,800
IPM Basic - 16 to 25 nodes	IPM-BASIC-25	\$2,850
IPM Basic - 26 to 35 nodes	IPM-BASIC-35	\$3,780
IPM Basic - 36 to 50 nodes	IPM-BASIC-50	\$5,200
IPM Basic - 51 to 100 nodes	IPM-BASIC-100	\$9,800
IPM Basic - 101 to 250 nodes	IPM-BASIC-250	\$24,500
IPM Basic - 251 to 500 nodes	IPM-BASIC-500	\$49,000
IPM GOLD - Trial License available - contact your sales rep		
IPM Gold - 1 to 5 nodes	IPM-GOLD-5	\$3,600
IPM Gold - 6 to 10 nodes	IPM-GOLD-10	\$5,000
IPM Gold - 11 to 15 nodes	IPM-GOLD-15	\$6,750
IPM Gold - 16 to 25 nodes	IPM-GOLD-25	\$10,000
IPM Gold - 26 to 35 nodes	IPM-GOLD-35	\$13,300
IPM Gold - 36 to 50 nodes	IPM-GOLD-50	\$18,000

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE



IPM Gold - 51 to 100 nodes	IPM-GOLD-100	\$32,000
IPM Gold - 101 to 250 nodes	IPM-GOLD-250	\$60,000
IPM Gold - 251 to 500 nodes	IPM-GOLD-500	\$90,000

IPM SUBSCRIPTIONS (for Version 1.X)

IPM Monitor subscription per node for 1 year	IPM-MON-SUB-1Y	\$48
IPM Monitor subscription per node for 2 years	IPM-MON-SUB-2Y	\$96
IPM Monitor subscription per node for 3 years	IPM-MON-SUB-3Y	\$144
IPM Monitor subscription per node for 4 years	IPM-MON-SUB-4Y	\$192
IPM Monitor subscription per node for 5 years	IPM-MON-SUB-5Y	\$240
IPM Basic subscription per node for 1 year	IPM-BASIC-SUB-1Y	\$96
IPM Basic subscription per node for 2 years	IPM-BASIC-SUB-2Y	\$192
IPM Basic subscription per node for 3 years	IPM-BASIC-SUB-3Y	\$288
IPM Basic subscription per node for 4 years	IPM-BASIC-SUB-4Y	\$384
IPM Basic subscription per node for 5 years	IPM-BASIC-SUB-5Y	\$480
IPM Gold subscription per node for 1 year	IPM-GOLD-SUB-1Y	\$180
IPM Gold subscription per node for 2 years	IPM-GOLD-SUB-2Y	\$342
IPM Gold subscription per node for 3 years	IPM-GOLD-SUB-3Y	\$513
IPM Gold subscription per node for 4 years	IPM-GOLD-SUB-4Y	\$684
IPM Gold subscription per node for 5 years	IPM-GOLD-SUB-5Y	\$855

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE



Visual Power Manager (VPM)

POWER INFRASTRUCTURE MONITORING SOFTWARE

VPM License Pricing (Rack Mounted Assets - RMAs)

Visual Power Manager (VPM)- 5 RMA License	VPM-5	\$562
Visual Power Manager (VPM)- 10 RMA License	VPM-10	\$1,123
Visual Power Manager (VPM)- 20 RMA License	VPM-20	\$2,246
Visual Power Manager (VPM)- 30 RMA License	VPM-30	\$3,370
Visual Power Manager (VPM)- 40 RMA License	VPM-40	\$4,493
Visual Power Manager (VPM)- 50 RMA License	VPM-50	\$5,616
Visual Power Manager (VPM)- 60 RMA License	VPM-60	\$6,739
Visual Power Manager (VPM)- 70 RMA License	VPM-70	\$7,862
Visual Power Manager (VPM)- 80 RMA License	VPM-80	\$8,986
Visual Power Manager (VPM)- 90 RMA License	VPM-90	\$10,109
Visual Power Manager (VPM)- 100 RMA License	VPM-100	\$10,368
Visual Power Manager (VPM)- 125 RMA License	VPM-125	\$12,960
Visual Power Manager (VPM)- 150 RMA License	VPM-150	\$15,552
Visual Power Manager (VPM)- 175 RMA License	VPM-175	\$18,144
Visual Power Manager (VPM)- 200 RMA License	VPM-200	\$20,736
Visual Power Manager (VPM)- 250 RMA License	VPM-250	\$24,120
Visual Power Manager (VPM)- 300 RMA License	VPM-300	\$28,944
Visual Power Manager (VPM)- 350 RMA License	VPM-350	\$33,768
Visual Power Manager (VPM)- 400 RMA License	VPM-400	\$38,592
Visual Power Manager (VPM)- 450 RMA License	VPM-450	\$43,416
Visual Power Manager (VPM)- 500 RMA License	VPM-500	\$43,920
Visual Power Manager (VPM)- 600 RMA License	VPM-600	\$52,704
Visual Power Manager (VPM)- 700 RMA License	VPM-700	\$61,488
Visual Power Manager (VPM)- 800 RMA License	VPM-800	\$70,272
Visual Power Manager (VPM)- 900 RMA License	VPM-900	\$79,056
Visual Power Manager (VPM)- 1000 RMA License	VPM-1000	\$80,640
Visual Power Manager (VPM)- 1500 RMA License	VPM-1500	\$120,960
Visual Power Manager (VPM)- 2000 RMA License	VPM-2000	\$161,280
Visual Power Manager (VPM)- 2500 RMA License	VPM-2500	\$190,800

This price does NOT include the first year's support. Please add the coordinating annual support part number to any quote.

Use these SKUs when quoting VPM for Single phase UPS and rack PDUs

VPM Annual Support Renewal (RMAs)

Visual Power Manager (VPM)- 5 RMA Annual Support	VPM-SUPPORT-5	\$112
Visual Power Manager (VPM)- 10 RMA Annual Support	VPM-SUPPORT-10	\$225
Visual Power Manager (VPM)- 20 RMA Annual Support	VPM-SUPPORT-20	\$449
Visual Power Manager (VPM)- 30 RMA Annual Support	VPM-SUPPORT-30	\$674
Visual Power Manager (VPM)- 40 RMA Annual Support	VPM-SUPPORT-40	\$899
Visual Power Manager (VPM)- 50 RMA Annual Support	VPM-SUPPORT-50	\$1,123
Visual Power Manager (VPM)- 60 RMA Annual Support	VPM-SUPPORT-60	\$1,348
Visual Power Manager (VPM)- 70 RMA Annual Support	VPM-SUPPORT-70	\$1,572
Visual Power Manager (VPM)- 80 RMA Annual Support	VPM-SUPPORT-80	\$1,797
Visual Power Manager (VPM)- 90 RMA Annual Support	VPM-SUPPORT-90	\$2,022
Visual Power Manager (VPM)- 100 RMA Annual Support	VPM-SUPPORT-100	\$2,074
Visual Power Manager (VPM)- 125 RMA Annual Support	VPM-SUPPORT-125	\$2,592
Visual Power Manager (VPM)- 150 RMA Annual Support	VPM-SUPPORT-150	\$3,110
Visual Power Manager (VPM)- 175 RMA Annual Support	VPM-SUPPORT-175	\$3,629
Visual Power Manager (VPM)- 200 RMA Annual Support	VPM-SUPPORT-200	\$4,147
Visual Power Manager (VPM)- 250 RMA Annual Support	VPM-SUPPORT-250	\$4,824
Visual Power Manager (VPM)- 300 RMA Annual Support	VPM-SUPPORT-300	\$5,789
Visual Power Manager (VPM)- 350 RMA Annual Support	VPM-SUPPORT-350	\$6,754
Visual Power Manager (VPM)- 400 RMA Annual Support	VPM-SUPPORT-400	\$7,718
Visual Power Manager (VPM)- 450 RMA Annual Support	VPM-SUPPORT-450	\$8,683
Visual Power Manager (VPM)- 500 RMA Annual Support	VPM-SUPPORT-500	\$8,784
Visual Power Manager (VPM)- 600 RMA Annual Support	VPM-SUPPORT-600	\$10,541
Visual Power Manager (VPM)- 700 RMA Annual Support	VPM-SUPPORT-700	\$12,298
Visual Power Manager (VPM)- 800 RMA Annual Support	VPM-SUPPORT-800	\$14,054
Visual Power Manager (VPM)- 900 RMA Annual Support	VPM-SUPPORT-900	\$15,811
Visual Power Manager (VPM)- 1000 RMA Annual Support	VPM-SUPPORT-1000	\$16,128
Visual Power Manager (VPM)- 1500 RMA Annual Support	VPM-SUPPORT-1500	\$24,192
Visual Power Manager (VPM)- 2000 RMA Annual Support	VPM-SUPPORT-2000	\$32,256
Visual Power Manager (VPM)- 2500 RMA Annual Support	VPM-SUPPORT-2500	\$38,160

VPM License Pricing (Floor Mounted Assets - FMAs)

Visual Power Manager (VPM)- 5 FMA License	VPMF-5	\$1,163
Visual Power Manager (VPM)- 10 FMA License	VPMF-10	\$2,325
Visual Power Manager (VPM)- 20 FMA License	VPMF-20	\$4,650

This price does NOT

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE

Visual Power Manager (VPM)- 30 FMA License	include the first year's support. Please add the coordinating annual support part number to any quote.	VPMF-30	\$6,975
Visual Power Manager (VPM)- 40 FMA License		VPMF-40	\$9,300
Visual Power Manager (VPM)- 50 FMA License		VPMF-50	\$11,550
Visual Power Manager (VPM)- 60 FMA License		VPMF-60	\$13,860
Visual Power Manager (VPM)- 70 FMA License		VPMF-70	\$16,170
Visual Power Manager (VPM)- 80 FMA License		VPMF-80	\$18,480
Visual Power Manager (VPM)- 90 FMA License		VPMF-90	\$20,790
Visual Power Manager (VPM)- 100 FMA License		VPMF-100	\$23,100
Visual Power Manager (VPM)- 125 FMA License		VPMF-125	\$27,375
Visual Power Manager (VPM)- 150 FMA License		VPMF-150	\$32,850
Visual Power Manager (VPM)- 175 FMA License	Use these SKUs when quoting VPM for 3 phase UPS and Floor mounted RPPs and PDUs	VPMF-175	\$38,325
Visual Power Manager (VPM)- 200 FMA License		VPMF-200	\$43,800
Visual Power Manager (VPM)- 250 FMA License		VPMF-250	\$52,125
Visual Power Manager (VPM)- 300 FMA License		VPMF-300	\$62,550
Visual Power Manager (VPM)- 350 FMA License		VPMF-350	\$72,975
Visual Power Manager (VPM)- 400 FMA License		VPMF-400	\$83,400
Visual Power Manager (VPM)- 450 FMA License		VPMF-450	\$93,825
Visual Power Manager (VPM)- 500 FMA License		VPMF-500	\$98,625
Visual Power Manager (VPM)- 600 FMA License		VPMF-600	\$118,350
Visual Power Manager (VPM)- 700 FMA License		VPMF-700	\$138,075
Visual Power Manager (VPM)- 800 FMA License		VPMF-800	\$157,800
Visual Power Manager (VPM)- 900 FMA License		VPMF-900	\$177,525
Visual Power Manager (VPM)- 1000 FMA License		VPMF-1000	\$188,250

VPM Annual Renewal (FMAs)		
Visual Power Manager (VPM)- 5 FMA Annual Support	VPMF-SUPPORT-5	\$233
Visual Power Manager (VPM)- 10 FMA Annual Support	VPMF-SUPPORT-10	\$465
Visual Power Manager (VPM)- 20 FMA Annual Support	VPMF-SUPPORT-20	\$930
Visual Power Manager (VPM)- 30 FMA Annual Support	VPMF-SUPPORT-30	\$1,395
Visual Power Manager (VPM)- 40 FMA Annual Support	VPMF-SUPPORT-40	\$1,860
Visual Power Manager (VPM)- 50 FMA Annual Support	VPMF-SUPPORT-50	\$2,310
Visual Power Manager (VPM)- 60 FMA Annual Support	VPMF-SUPPORT-60	\$2,772
Visual Power Manager (VPM)- 70 FMA Annual Support	VPMF-SUPPORT-70	\$3,234
Visual Power Manager (VPM)- 80 FMA Annual Support	VPMF-SUPPORT-80	\$3,696
Visual Power Manager (VPM)- 90 FMA Annual Support	VPMF-SUPPORT-90	\$4,158
Visual Power Manager (VPM)- 100 FMA Annual Support	VPMF-SUPPORT-100	\$4,620
Visual Power Manager (VPM)- 125 FMA Annual Support	VPMF-SUPPORT-125	\$5,475
Visual Power Manager (VPM)- 150 FMA Annual Support	VPMF-SUPPORT-150	\$6,570
Visual Power Manager (VPM)- 175 FMA Annual Support	VPMF-SUPPORT-175	\$7,665
Visual Power Manager (VPM)- 200 FMA Annual Support	VPMF-SUPPORT-200	\$8,760
Visual Power Manager (VPM)- 250 FMA Annual Support	VPMF-SUPPORT-250	\$10,425
Visual Power Manager (VPM)- 300 FMA Annual Support	VPMF-SUPPORT-300	\$12,510
Visual Power Manager (VPM)- 350 FMA Annual Support	VPMF-SUPPORT-350	\$14,595
Visual Power Manager (VPM)- 400 FMA Annual Support	VPMF-SUPPORT-400	\$16,680
Visual Power Manager (VPM)- 450 FMA Annual Support	VPMF-SUPPORT-450	\$18,765
Visual Power Manager (VPM)- 500 FMA Annual Support	VPMF-SUPPORT-500	\$19,725
Visual Power Manager (VPM)- 600 FMA Annual Support	VPMF-SUPPORT-600	\$23,670
Visual Power Manager (VPM)- 700 FMA Annual Support	VPMF-SUPPORT-700	\$27,615
Visual Power Manager (VPM)- 800 FMA Annual Support	VPMF-SUPPORT-800	\$31,560
Visual Power Manager (VPM)- 900 FMA Annual Support	VPMF-SUPPORT-900	\$35,505
Visual Power Manager (VPM)- 1000 FMA Annual Support	VPMF-SUPPORT-1000	\$37,650

VPM PROFESSIONAL SUBSCRIPTION (RMAs)		
Visual Power Manager (VPM) Professional -5 RMA Subscription	VPM-SUB-5	\$350
Visual Power Manager (VPM) Professional -10 RMA Subscription	VPM-SUB-10	\$700
Visual Power Manager (VPM) Professional -20 RMA Subscription	VPM-SUB-20	\$1,400
Visual Power Manager (VPM) Professional -30 RMA Subscription	VPM-SUB-30	\$2,100
Visual Power Manager (VPM) Professional -40 RMA Subscription	VPM-SUB-40	\$2,800
Visual Power Manager (VPM) Professional -50 RMA Subscription	VPM-SUB-50	\$3,500
Visual Power Manager (VPM) Professional -60 RMA Subscription	VPM-SUB-60	\$4,200
Visual Power Manager (VPM) Professional -70 RMA Subscription	VPM-SUB-70	\$4,900
Visual Power Manager (VPM) Professional -80 RMA Subscription	VPM-SUB-80	\$5,600
Visual Power Manager (VPM) Professional -90 RMA Subscription	VPM-SUB-90	\$6,300
Visual Power Manager (VPM) Professional -100 RMA Subscription	VPM-SUB-100	\$6,462
Visual Power Manager (VPM) Professional -125 RMA Subscription	VPM-SUB-125	\$8,077
Visual Power Manager (VPM) Professional -150 RMA Subscription	VPM-SUB-150	\$9,692
Visual Power Manager (VPM) Professional -175 RMA Subscription	VPM-SUB-175	\$11,308
Visual Power Manager (VPM) Professional -200 RMA Subscription	VPM-SUB-200	\$12,923
Visual Power Manager (VPM) Professional -250 RMA Subscription	VPM-SUB-250	\$15,032
Visual Power Manager (VPM) Professional -300 RMA Subscription	VPM-SUB-300	\$18,038

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE

Visual Power Manager (VPM) Professional -350 RMA Subscription	VPM-SUB-350	\$21,045
Visual Power Manager (VPM) Professional -400 RMA Subscription	VPM-SUB-400	\$24,051
Visual Power Manager (VPM) Professional -450 RMA Subscription	VPM-SUB-450	\$27,058
Visual Power Manager (VPM) Professional -500 RMA Subscription	VPM-SUB-500	\$27,372
Visual Power Manager (VPM) Professional -600 RMA Subscription	VPM-SUB-600	\$32,846
Visual Power Manager (VPM) Professional -700 RMA Subscription	VPM-SUB-700	\$38,321
Visual Power Manager (VPM) Professional -800 RMA Subscription	VPM-SUB-800	\$43,795
Visual Power Manager (VPM) Professional -900 RMA Subscription	VPM-SUB-900	\$49,269
Visual Power Manager (VPM) Professional -1000 RMA Subscription	VPM-SUB-1000	\$50,256
Visual Power Manager (VPM) Professional -1500 RMA Subscription	VPM-SUB-1500	\$75,385
Visual Power Manager (VPM) Professional -2000 RMA Subscription	VPM-SUB-2000	\$100,513
Visual Power Manager (VPM) Professional -2500 RMA Subscription	VPM-SUB-2500	\$118,910

VPM PROFESSIONAL SUBSCRIPTION (FMAs)

Visual Power Manager (VPM) Professional -5 FMA Subscription	VPMF-SUB-5	\$725
Visual Power Manager (VPM) Professional -10 FMA Subscription	VPMF-SUB-10	\$1,450
Visual Power Manager (VPM) Professional -20 FMA Subscription	VPMF-SUB-20	\$2,900
Visual Power Manager (VPM) Professional -30 FMA Subscription	VPMF-SUB-30	\$4,350
Visual Power Manager (VPM) Professional -40 FMA Subscription	VPMF-SUB-40	\$5,800
Visual Power Manager (VPM) Professional -50 FMA Subscription	VPMF-SUB-50	\$7,203
Visual Power Manager (VPM) Professional -60 FMA Subscription	VPMF-SUB-60	\$8,644
Visual Power Manager (VPM) Professional -70 FMA Subscription	VPMF-SUB-70	\$10,085
Visual Power Manager (VPM) Professional -80 FMA Subscription	VPMF-SUB-80	\$11,525
Visual Power Manager (VPM) Professional -90 FMA Subscription	VPMF-SUB-90	\$12,966
Visual Power Manager (VPM) Professional -100 FMA Subscription	VPMF-SUB-100	\$14,406
Visual Power Manager (VPM) Professional -125 FMA Subscription	VPMF-SUB-125	\$17,073
Visual Power Manager (VPM) Professional -150 FMA Subscription	VPMF-SUB-150	\$20,487
Visual Power Manager (VPM) Professional -175 FMA Subscription	VPMF-SUB-175	\$23,902
Visual Power Manager (VPM) Professional -200 FMA Subscription	VPMF-SUB-200	\$27,316
Visual Power Manager (VPM) Professional -250 FMA Subscription	VPMF-SUB-250	\$32,508
Visual Power Manager (VPM) Professional -300 FMA Subscription	VPMF-SUB-300	\$39,010
Visual Power Manager (VPM) Professional -350 FMA Subscription	VPMF-SUB-350	\$45,511
Visual Power Manager (VPM) Professional -400 FMA Subscription	VPMF-SUB-400	\$52,013
Visual Power Manager (VPM) Professional -450 FMA Subscription	VPMF-SUB-450	\$58,515
Visual Power Manager (VPM) Professional -500 FMA Subscription	VPMF-SUB-500	\$61,508
Visual Power Manager (VPM) Professional -600 FMA Subscription	VPMF-SUB-600	\$73,810
Visual Power Manager (VPM) Professional -700 FMA Subscription	VPMF-SUB-700	\$86,111
Visual Power Manager (VPM) Professional -800 FMA Subscription	VPMF-SUB-800	\$98,413
Visual Power Manager (VPM) Professional -900 FMA Subscription	VPMF-SUB-900	\$110,715
Visual Power Manager (VPM) Professional -1000 FMA Subscription	VPMF-SUB-1000	\$117,403

VPM Essential SUBSCRIPTION (RMAs Only)

Visual Power Manager (VPM) Essential -5 RMA Subscription	VPM-ESS-5	\$240
Visual Power Manager (VPM) Essential -10 RMA Subscription	VPM-ESS-10	\$480
Visual Power Manager (VPM) Essential -20 RMA Subscription	VPM-ESS-20	\$960
Visual Power Manager (VPM) Essential -30 RMA Subscription	VPM-ESS-30	\$1,440
Visual Power Manager (VPM) Essential -40 RMA Subscription	VPM-ESS-40	\$1,920
Visual Power Manager (VPM) Essential -50 RMA Subscription	VPM-ESS-50	\$2,385
Visual Power Manager (VPM) Essential -60 RMA Subscription	VPM-ESS-60	\$2,861
Visual Power Manager (VPM) Essential -70 RMA Subscription	VPM-ESS-70	\$3,338
Visual Power Manager (VPM) Essential -80 RMA Subscription	VPM-ESS-80	\$3,815
Visual Power Manager (VPM) Essential -90 RMA Subscription	VPM-ESS-90	\$4,292
Visual Power Manager (VPM) Essential -100 RMA Subscription	VPM-ESS-100	\$4,769
Visual Power Manager (VPM) Essential -125 RMA Subscription	VPM-ESS-125	\$5,652
Visual Power Manager (VPM) Essential -150 RMA Subscription	VPM-ESS-150	\$6,782
Visual Power Manager (VPM) Essential -175 RMA Subscription	VPM-ESS-175	\$7,912
Visual Power Manager (VPM) Essential -200 RMA Subscription	VPM-ESS-200	\$9,043
Visual Power Manager (VPM) Essential -250 RMA Subscription	VPM-ESS-250	\$10,761
Visual Power Manager (VPM) Essential -300 RMA Subscription	VPM-ESS-300	\$12,914
Visual Power Manager (VPM) Essential -350 RMA Subscription	VPM-ESS-350	\$15,066
Visual Power Manager (VPM) Essential -400 RMA Subscription	VPM-ESS-400	\$17,218
Visual Power Manager (VPM) Essential -450 RMA Subscription	VPM-ESS-450	\$19,370
Visual Power Manager (VPM) Essential -500 RMA Subscription	VPM-ESS-500	\$20,361
Visual Power Manager (VPM) Essential -600 RMA Subscription	VPM-ESS-600	\$24,434
Visual Power Manager (VPM) Essential -700 RMA Subscription	VPM-ESS-700	\$28,506
Visual Power Manager (VPM) Essential -800 RMA Subscription	VPM-ESS-800	\$32,578
Visual Power Manager (VPM) Essential -900 RMA Subscription	VPM-ESS-900	\$36,650
Visual Power Manager (VPM) Essential -1000 RMA Subscription	VPM-ESS-1000	\$38,865

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE

Software Installation Services for VCOM

INCLUDE SW-INSTALL-QS AT A MINIMUM WITH ALL SW DEALS

VPM Software install		
Software Remote Start- 8 hours of remote assistance deploying VPM	SW-INSTALL-RS	\$2,500
Software Quick Start - 3 day, on-site professional services deploying VPM + user training	SW-INSTALL-QS	\$9,500
Custom Professional services	SW-INSTALL-100	\$100
Custom Professional services	SW-INSTALL-1K	\$1,000
Custom Professional services	SW-INSTALL-10K	\$10,000

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE

VCOM

DATA CENTER INFRASTRUCTURE MANAGEMENT (DCIM) SOFTWARE



VCOM License Pricing (FMAs)

Visual Capacity Optimization Manager (VCOM)- 5 FMA License	VCOM-5	\$2,053
Visual Capacity Optimization Manager (VCOM)- 10 FMA License	VCOM-10	\$4,107
Visual Capacity Optimization Manager (VCOM)- 20 FMA License	VCOM-20	\$8,213
Visual Capacity Optimization Manager (VCOM)- 30 FMA License	VCOM-30	\$12,320
Visual Capacity Optimization Manager (VCOM)- 40 FMA License	VCOM-40	\$16,427
Visual Capacity Optimization Manager (VCOM)- 50 FMA License	VCOM-50	\$20,533
Visual Capacity Optimization Manager (VCOM)- 60 FMA License	VCOM-60	\$23,030
Visual Capacity Optimization Manager (VCOM)- 70 FMA License	VCOM-70	\$26,868
Visual Capacity Optimization Manager (VCOM)- 80 FMA License	VCOM-80	\$30,707
Visual Capacity Optimization Manager (VCOM)- 90 FMA License	VCOM-90	\$34,545
Visual Capacity Optimization Manager (VCOM)- 100 FMA License	VCOM-100	\$38,383
Visual Capacity Optimization Manager (VCOM)- 125 FMA License	VCOM-125	\$47,979
Visual Capacity Optimization Manager (VCOM)- 150 FMA License	VCOM-150	\$57,575
Visual Capacity Optimization Manager (VCOM)- 175 FMA License	VCOM-175	\$67,171
Visual Capacity Optimization Manager (VCOM)- 200 FMA License	VCOM-200	\$76,767
Visual Capacity Optimization Manager (VCOM)- 250 FMA License	VCOM-250	\$89,600
Visual Capacity Optimization Manager (VCOM)- 300 FMA License	VCOM-300	\$107,520
Visual Capacity Optimization Manager (VCOM)- 350 FMA License	VCOM-350	\$125,440
Visual Capacity Optimization Manager (VCOM)- 400 FMA License	VCOM-400	\$143,360
Visual Capacity Optimization Manager (VCOM)- 450 FMA License	VCOM-450	\$161,280
Visual Capacity Optimization Manager (VCOM)- 500 FMA License	VCOM-500	\$167,417
Visual Capacity Optimization Manager (VCOM)- 600 FMA License	VCOM-600	\$200,900
Visual Capacity Optimization Manager (VCOM)- 700 FMA License	VCOM-700	\$234,383
Visual Capacity Optimization Manager (VCOM)- 800 FMA License	VCOM-800	\$267,867
Visual Capacity Optimization Manager (VCOM)- 900 FMA License	VCOM-900	\$301,350
Visual Capacity Optimization Manager (VCOM)- 1000 FMA License	VCOM-1000	\$313,600
Visual Capacity Optimization Manager (VCOM)- 1500 FMA License	VCOM-1500	\$470,400
Visual Capacity Optimization Manager (VCOM)- 2000 FMA License	VCOM-2000	\$627,200
Visual Capacity Optimization Manager (VCOM)- 2500 FMA License	VCOM-2500	\$732,667

This price does NOT include the first year's support. Please add the coordinating annual support part number to any quote.

VCOM Annual Renewal (1 year) (FMA)

Visual Capacity Optimization Manager (VCOM)- 5 Annual Support	VCOM-SUPPORT-5	\$411
Visual Capacity Optimization Manager (VCOM)- 10 Annual Support	VCOM-SUPPORT-10	\$821
Visual Capacity Optimization Manager (VCOM)- 20 Annual Support	VCOM-SUPPORT-20	\$1,643
Visual Capacity Optimization Manager (VCOM)- 30 Annual Support	VCOM-SUPPORT-30	\$2,464
Visual Capacity Optimization Manager (VCOM)- 40 Annual Support	VCOM-SUPPORT-40	\$3,285
Visual Capacity Optimization Manager (VCOM)- 50 Annual Support	VCOM-SUPPORT-50	\$4,107
Visual Capacity Optimization Manager (VCOM)- 60 Annual Support	VCOM-SUPPORT-60	\$4,606
Visual Capacity Optimization Manager (VCOM)- 70 Annual Support	VCOM-SUPPORT-70	\$5,374
Visual Capacity Optimization Manager (VCOM)- 80 Annual Support	VCOM-SUPPORT-80	\$6,141
Visual Capacity Optimization Manager (VCOM)- 90 Annual Support	VCOM-SUPPORT-90	\$6,909
Visual Capacity Optimization Manager (VCOM)- 100 Annual Support	VCOM-SUPPORT-100	\$7,677
Visual Capacity Optimization Manager (VCOM)- 125 Annual Support	VCOM-SUPPORT-125	\$9,596
Visual Capacity Optimization Manager (VCOM)- 150 Annual Support	VCOM-SUPPORT-150	\$11,515
Visual Capacity Optimization Manager (VCOM)- 175 Annual Support	VCOM-SUPPORT-175	\$13,434
Visual Capacity Optimization Manager (VCOM)- 200 Annual Support	VCOM-SUPPORT-200	\$15,353
Visual Capacity Optimization Manager (VCOM)- 250 Annual Support	VCOM-SUPPORT-250	\$17,920
Visual Capacity Optimization Manager (VCOM)- 300 Annual Support	VCOM-SUPPORT-300	\$21,504
Visual Capacity Optimization Manager (VCOM)- 350 Annual Support	VCOM-SUPPORT-350	\$25,088
Visual Capacity Optimization Manager (VCOM)- 400 Annual Support	VCOM-SUPPORT-400	\$28,672
Visual Capacity Optimization Manager (VCOM)- 450 Annual Support	VCOM-SUPPORT-450	\$32,256
Visual Capacity Optimization Manager (VCOM)- 500 Annual Support	VCOM-SUPPORT-500	\$33,483
Visual Capacity Optimization Manager (VCOM)- 600 Annual Support	VCOM-SUPPORT-600	\$40,180
Visual Capacity Optimization Manager (VCOM)- 700 Annual Support	VCOM-SUPPORT-700	\$46,877
Visual Capacity Optimization Manager (VCOM)- 800 Annual Support	VCOM-SUPPORT-800	\$53,573
Visual Capacity Optimization Manager (VCOM)- 900 Annual Support	VCOM-SUPPORT-900	\$60,270
Visual Capacity Optimization Manager (VCOM)- 1000 Annual Support	VCOM-SUPPORT-1000	\$62,720
Visual Capacity Optimization Manager (VCOM)- 1500 Annual Support	VCOM-SUPPORT-1500	\$94,080

SOFTWARE

UPS MANAGEMENT/SUPERVISORY SOFTWARE

Visual Capacity Optimization Manager (VCOM)- 2000 Annual Support	VCOM-SUPPORT-2000	\$125,440
Visual Capacity Optimization Manager (VCOM)- 2500 Annual Support	VCOM-SUPPORT-2500	\$146,533

VCOM SUBSCRIPTION (FMAs)

Visual Capacity Optimization Manager (VCOM)- 5 FMA Annual Subscription	VCOM-SUB-5	\$1,312
Visual Capacity Optimization Manager (VCOM)- 10 FMA Annual Subscription	VCOM-SUB-10	\$2,624
Visual Capacity Optimization Manager (VCOM)- 20 FMA Annual Subscription	VCOM-SUB-20	\$5,248
Visual Capacity Optimization Manager (VCOM)- 30 FMA Annual Subscription	VCOM-SUB-30	\$7,872
Visual Capacity Optimization Manager (VCOM)- 40 FMA Annual Subscription	VCOM-SUB-40	\$10,496
Visual Capacity Optimization Manager (VCOM)- 50 FMA Annual Subscription	VCOM-SUB-50	\$13,120
Visual Capacity Optimization Manager (VCOM)- 60 FMA Annual Subscription	VCOM-SUB-60	\$14,736
Visual Capacity Optimization Manager (VCOM)- 70 FMA Annual Subscription	VCOM-SUB-70	\$17,192
Visual Capacity Optimization Manager (VCOM)- 80 FMA Annual Subscription	VCOM-SUB-80	\$19,648
Visual Capacity Optimization Manager (VCOM)- 90 FMA Annual Subscription	VCOM-SUB-90	\$22,104
Visual Capacity Optimization Manager (VCOM)- 100 FMA Annual Subscription	VCOM-SUB-100	\$24,560
Visual Capacity Optimization Manager (VCOM)- 125 FMA Annual Subscription	VCOM-SUB-125	\$30,700
Visual Capacity Optimization Manager (VCOM)- 150 FMA Annual Subscription	VCOM-SUB-150	\$36,840
Visual Capacity Optimization Manager (VCOM)- 175 FMA Annual Subscription	VCOM-SUB-175	\$42,980
Visual Capacity Optimization Manager (VCOM)- 200 FMA Annual Subscription	VCOM-SUB-200	\$49,120
Visual Capacity Optimization Manager (VCOM)- 250 FMA Annual Subscription	VCOM-SUB-250	\$57,200
Visual Capacity Optimization Manager (VCOM)- 300 FMA Annual Subscription	VCOM-SUB-300	\$68,640
Visual Capacity Optimization Manager (VCOM)- 350 FMA Annual Subscription	VCOM-SUB-350	\$80,080
Visual Capacity Optimization Manager (VCOM)- 400 FMA Annual Subscription	VCOM-SUB-400	\$91,520
Visual Capacity Optimization Manager (VCOM)- 450 FMA Annual Subscription	VCOM-SUB-450	\$102,960
Visual Capacity Optimization Manager (VCOM)- 500 FMA Annual Subscription	VCOM-SUB-500	\$106,800
Visual Capacity Optimization Manager (VCOM)- 600 FMA Annual Subscription	VCOM-SUB-600	\$128,160
Visual Capacity Optimization Manager (VCOM)- 700 FMA Annual Subscription	VCOM-SUB-700	\$149,520
Visual Capacity Optimization Manager (VCOM)- 800 FMA Annual Subscription	VCOM-SUB-800	\$170,880
Visual Capacity Optimization Manager (VCOM)- 900 FMA Annual Subscription	VCOM-SUB-900	\$192,240
Visual Capacity Optimization Manager (VCOM)- 1000 FMA Annual Subscription	VCOM-SUB-1000	\$200,000
Visual Capacity Optimization Manager (VCOM)- 1500 FMA Annual Subscription	VCOM-SUB-1500	\$300,000
Visual Capacity Optimization Manager (VCOM)- 2000 FMA Annual Subscription	VCOM-SUB-2000	\$400,000
Visual Capacity Optimization Manager (VCOM)- 2500 FMA Annual Subscription	VCOM-SUB-2500	\$442,080

Software Installation Services for VCOM

INCLUDE SW-INSTALL-QS AT A MINIMUM WITH ALL SW DEALS

VPM Software install

Software Remote Start- 8 hours of remote assistance deploying VPM	SW-INSTALL-RS	\$2,500
Software Quick Start - 3 day, on-site professional services deploying VPM + user training	SW-INSTALL-QS	\$9,500
Custom Professional services	SW-INSTALL-100	\$100
Custom Professional services	SW-INSTALL-1K	\$1,000
Custom Professional services	SW-INSTALL-10K	\$10,000

Connectivity Options

WEB/SNMP PRODUCTS

Description	Part Number	List Price
Eaton Gigabit Network Card (Replaces NETWORK-MS and ConnectUPS-BD)	NETWORK-M2	\$410
Industrial Gateway Card	INDGW-M2	\$464
Industrial Gateway Card (X-Slot)	INDGW-X2	\$524
Ethernet SNMP/HTTP Adapter	116750225-001	\$420
Power Xpert Mini-Slot UPS Card (Web/SNMP/Modbus TCP)	PXGMSUPS	\$709
Power Xpert Gateway PDP Card (Web/SNMP/Modbus TCP)	103008064-5591	\$1,142

CONNECTIVITY AND ENVIRONMENTAL ACCESSORIES

Description	Part Number	List Price
Environmental Monitoring Probe (Compatible with PXG cards)	116750224-001	\$266
Environmental Monitoring Probe Gen 2 (Compatible with M2 cards)	EMPDT1H1C2	\$291
Environmental Rack Monitor Water Leak Detector, 3ft	103005780	\$163
Environmental Rack Monitor Water Leak Detector, 12ft	103005894	\$282
Environmental Rack Monitor Door Contact Sensor	103005781	\$33
Environmental Rack Monitor Vibration Sensor	103005782	\$44
Environmental Rack Monitor Smoke Detector/Alarm (220V, IEC C-13)	103005779	\$163
Environmental Rack Monitor Smoke Detector/Alarm (110V, 5-15)	103005890	\$163

RELAY INTERFACE/REMOTE MONITORING PRODUCTS

Description	Part Number	List Price
Relay Card-MS	RELAY-MS	\$139
Industrial Relay Card MS	INDRELAY-MS	\$709
Industrial Relay and Display Drive Card X-Slot. Replaces 1014018 card	103003055	\$460
Provides (4) Form-C Relay contacts (5A @ 250V) for UPS integration into security and alarm systems. Also provides signal information for the Remote Monitor Display Panel (part number 103002687-001)		
Cable 10 ft DB9 - DB9 (compatible with AS/400 model 9406; for use with RELAY-MS)	66033	\$121

REMOTE MONITORING PANELS (FOR MONITORING OF UPS STATUS)

Description	Part Number	List Price
Remote Monitor Display Panel (Requires Industrial Relay and Display Drive Card Part # 103003055)	103002687-001	\$525

CONNECTIVITY PRODUCTS

					Eaton UPS models															
Class		Reference	Part number	List price	Environmental monitoring probe	5P	5PX UPS family	9SX	9PX	9PXM	FERRUPS FX	9130	FERRUPS	93E	93PM	BladeUPS	9x55	9305 UPS family		
IT		Gigabit Network Card	NETWORK-M2 744-A3983	\$410 (CAN\$720)		X	X	X	X	X	X	X								
		Industrial Gateway Card	INDGW-M2 744-07774	\$464 (CAN\$815)		X	X	X	X	X	X				X	X				
Industrial		Gigabit Industrial Gateway X2 Card	INDGW-X2 744-07538	\$524 (CAN\$920)													X	X	X	
		Power Xpert Gateway Minislot UPS Card	PXGXMSUPS P-116000035	\$709 (CAN\$1,245)												X				
		Power Xpert Gateway UPS X-Slot Card	PXGXUPS 103007974-5591	\$541 (CAN\$950)														X	X	X
		BestLink Web/SNMP Adapter	116750225-001	\$420 (CAN\$738)											X					
Relay		Relay Card — MS	RELAY-MS 744-98067-00P	\$139 (CAN\$244)		X	X	X	X	X	X				X	X				
		Industrial Relay Card — MS	INDRELAY-MS P-116000059	\$709 (CAN\$1,245)							X				X	X				
		X-Slot Industrial Relay Card	103003055	\$452 (CAN\$794)														X	X	X

SURGE PROTECTION

PSPD SERIES

Eaton's PSPD series of surge protection devices ensure that critical equipment is protected with the safest, most reliable and most advanced UL 1449 3rd Edition certified surge protectors. The array of features, options, and configurations ensures there is a unit for all electrical applications, including service entrances, data centers, critical distribution switchboards and panelboards, and PDU's and RPP's.

- Common voltages and configurations as well as a variety of surge current capacity ratings from 50 through 400 kA provide application flexibility.
- UL 1449 3rd Edition recognized component for the United States and Canada, covered by Underwriters Laboratories certification and follow-up service.
- Utilizes self-protected protected metal oxide varistor (MOV) technology, which provides both high energy capacity and fail-safe operation.
- Side mount units offer factory-sealed assembly, which prevents arc flash and shock hazards.
- Standard units include EMI/RFI filtering to provide effective protection for sensitive electronic loads.
- Side mount units contain no replaceable parts or items that require periodic maintenance thus reducing maintenance costs.



Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 050 (50 kA/phase surge rating)								
Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD050208Y3K	10.5 x 7.5 x 3.5	7.0	\$1,873	PSPD050208Y3M	11.0 x 11.5 x 6.0	14.0	\$2,319
120/240 Single Split-phase (3W + G)	PSPD050240S3K	10.5 x 7.5 x 3.5	7	\$1,732	PSPD050240S3M	11.0 x 11.5 x 6.0	14.0	\$2,463
240 Delta (3W + G)	PSPD050240D3K	10.5 x 7.5 x 3.5	7	\$1,873	PSPD050240D3M	11.0 x 11.5 x 6.0	14.0	\$2,590
480 Delta (3W + G)	PSPD050480D3K	10.5 x 7.5 x 3.5	7	\$1,873	PSPD050480D3M	11.0 x 11.5 x 6.0	14.0	\$2,590
400/230 Wye Three-phase (4W + G)	PSPD050400Y3K	10.5 x 7.5 x 3.5	7	\$1,873	PSPD050400Y3M	11.0 x 11.5 x 6.0	14.0	\$2,590
480/277 Wye Three-phase (4W + G)	PSPD050480Y3K	10.5 x 7.5 x 3.5	7	\$1,873	PSPD050480Y3M	11.0 x 11.5 x 6.0	14.0	\$2,590
Standard Diagnostics								
208/120 Wye Three-phase (4W + G)	PSPD050208Y2K	10.5 x 7.5 x 3.5	7.0	\$1,594	PSPD050208Y2M	11.0 x 11.5 x 6.0	14.0	\$2,611
120/240 Single Split-phase (3W + G)	PSPD050240S2K	10.5 x 7.5 x 3.5	7.0	\$1,473	PSPD050240S2M	11.0 x 11.5 x 6.0	14.0	\$2,466
240 Delta (3W + G)	PSPD050240D2K	10.5 x 7.5 x 3.5	7.0	\$1,594	PSPD050240D2M	11.0 x 11.5 x 6.0	14.0	\$2,611
480 Delta (3W + G)	PSPD050480D2K	10.5 x 7.5 x 3.5	7.0	\$1,594	PSPD050480D2M	11.0 x 11.5 x 6.0	14.0	\$2,611
400/230 Wye Three-phase (4W + G)	PSPD050400Y2K	10.5 x 7.5 x 3.5	7.0	\$1,594	PSPD050400Y2M	11.0 x 11.5 x 6.0	14.0	\$2,611
480/277 Wye Three-phase (4W + G)	PSPD050480Y2K	10.5 x 7.5 x 3.5	7.0	\$1,594	PSPD050480Y2M	11.0 x 11.5 x 6.0	14.0	\$2,611
Basic Diagnostics								
208/120 Wye Three-phase (4W + G)	PSPD050208Y1K	10.5 x 7.5 x 3.5	7.0	\$1,274	PSPD050208Y1M	11.0 x 11.5 x 6.0	14.0	\$1,995
120/240 Single Split-phase (3W + G)	PSPD050240S1K	10.5 x 7.5 x 3.5	7.0	\$1,394	PSPD050240S1M	11.0 x 11.5 x 6.0	14.0	\$2,120
240 Delta (3W + G)	PSPD050240D1K	10.5 x 7.5 x 3.5	7.0	\$1,533	PSPD050240D1M	11.0 x 11.5 x 6.0	14.0	\$2,253
480 Delta (3W + G)	PSPD050480D1K	10.5 x 7.5 x 3.5	7.0	\$1,533	PSPD050480D1M	11.0 x 11.5 x 6.0	14.0	\$2,253
400/230 Wye Three-phase (4W + G)	PSPD050400Y1K	10.5 x 7.5 x 3.5	7.0	\$1,533	PSPD050400Y1M	11.0 x 11.5 x 6.0	14.0	\$2,253
480/277 Wye Three-phase (4W + G)	PSPD050480Y1K	10.5 x 7.5 x 3.5	7.0	\$1,533	PSPD050480Y1M	11.0 x 11.5 x 6.0	14.0	\$2,253
PSPD 080 (80 kA/phase surge rating)								
Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD080208Y3K	10.5 x 7.5 x 3.5	7.0	\$2,002	PSPD080208Y3M	11.0 x 11.5 x 6.0	14	\$2,567
120/240 Single Split-phase (3W + G)	PSPD080240S3K	10.5 x 7.5 x 3.5	7.0	\$2,173	PSPD080240S3M	11.0 x 11.5 x 6.0	14	\$2,740
240 Delta (3W + G)	PSPD080240D3K	10.5 x 7.5 x 3.5	7.0	\$2,344	PSPD080240D3M	11.0 x 11.5 x 6.0	14	\$2,910
480 Delta (3W + G)	PSPD080480D3K	10.5 x 7.5 x 3.5	7.0	\$2,344	PSPD080480D3M	11.0 x 11.5 x 6.0	14	\$2,910
400/230 Wye Three-phase (4W + G)	PSPD080400Y3K	10.5 x 7.5 x 3.5	7.0	\$2,344	PSPD080400Y3M	11.0 x 11.5 x 6.0	14	\$2,910
480/277 Wye Three-phase (4W + G)	PSPD080480Y3K	10.5 x 7.5 x 3.5	7.0	\$2,344	PSPD080480Y3M	11.0 x 11.5 x 6.0	14	\$2,910
Standard Diagnostics								
208/120 Wye Three-phase (4W + G)	PSPD080208Y2K	10.5 x 7.5 x 3.5	7.0	\$1,659	PSPD080208Y2M	11.0 x 11.5 x 6.0	14.0	\$2,224
120/240 Single Split-phase (3W + G)	PSPD080240S2K	10.5 x 7.5 x 3.5	7.0	\$1,829	PSPD080240S2M	11.0 x 11.5 x 6.0	14.0	\$2,397
240 Delta (3W + G)	PSPD080240D2K	10.5 x 7.5 x 3.5	7.0	\$2,002	PSPD080240D2M	11.0 x 11.5 x 6.0	14.0	\$2,567
480 Delta (3W + G)	PSPD080480D2K	10.5 x 7.5 x 3.5	7.0	\$2,002	PSPD080480D2M	11.0 x 11.5 x 6.0	14.0	\$2,567
400/230 Wye Three-phase (4W + G)	PSPD080400Y2K	10.5 x 7.5 x 3.5	7.0	\$2,002	PSPD080400Y2M	11.0 x 11.5 x 6.0	14.0	\$2,567

SURGE PROTECTION

480/277 Wye Three-phase (4W + G)	PSPD080480Y2K	10.5 x 7.5 x 3.5	7.0	\$2,002	PSPD080480Y2M	11.0 x 11.5 x 6.0	14.0	\$2,567
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD080208Y1K	10.5 x 7.5 x 3.5	7.0	\$1,573	PSPD080208Y1M	11.0 x 11.5 x 6.0	14.0	\$2,139
120/240 Single Split-phase (3W + G)	PSPD080240S1K	10.5 x 7.5 x 3.5	7.0	\$1,736	PSPD080240S1M	11.0 x 11.5 x 6.0	14.0	\$2,303
240 Delta (3W + G)	PSPD080240D1K	10.5 x 7.5 x 3.5	7.0	\$1,906	PSPD080240D1M	11.0 x 11.5 x 6.0	14.0	\$2,473
480 Delta (3W + G)	PSPD080480D1K	10.5 x 7.5 x 3.5	7.0	\$1,906	PSPD080480D1M	11.0 x 11.5 x 6.0	14.0	\$2,473
400/230 Wye Three-phase (4W + G)	PSPD080400Y1K	10.5 x 7.5 x 3.5	7.0	\$1,906	PSPD080400Y1M	11.0 x 11.5 x 6.0	14.0	\$2,473
480/277 Wye Three-phase (4W + G)	PSPD080480Y1K	10.5 x 7.5 x 3.5	7.0	\$1,906	PSPD080480Y1M	11.0 x 11.5 x 6.0	14.0	\$2,473
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 100 (100 kA/phase surge rating) Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD100208Y3K	10.5 x 7.5 x 3.5	7.0	\$2,196	PSPD100208Y3M	11.0 x 11.5 x 6.0	14.0	\$2,727
120/240 Single Split-phase (3W + G)	PSPD100240S3K	10.5 x 7.5 x 3.5	7.0	\$2,382	PSPD100240S3M	11.0 x 11.5 x 6.0	14.0	\$2,913
240 Delta (3W + G)	PSPD100240D3K	10.5 x 7.5 x 3.5	7.0	\$2,564	PSPD100240D3M	11.0 x 11.5 x 6.0	14.0	\$3,095
480 Delta (3W + G)	PSPD100480D3K	10.5 x 7.5 x 3.5	7.0	\$2,564	PSPD100480D3M	11.0 x 11.5 x 6.0	14.0	\$3,095
400/230 Wye Three-phase (4W + G)	PSPD100400Y3K	10.5 x 7.5 x 3.5	7.0	\$2,564	PSPD100400Y3M	11.0 x 11.5 x 6.0	14.0	\$3,095
480/277 Wye Three-phase (4W + G)	PSPD100480Y3K	10.5 x 7.5 x 3.5	7.0	\$2,564	PSPD100480Y3M	11.0 x 11.5 x 6.0	14.0	\$3,095
PSPD SERIES								
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD100208Y2K	10.5 x 7.5 x 3.5	7.0	\$1,823	PSPD100208Y2M	11.0 x 11.5 x 6.0	14.0	\$2,355
120/240 Single Split-phase (3W + G)	PSPD100240S2K	10.5 x 7.5 x 3.5	7.0	\$2,010	PSPD100240S2M	11.0 x 11.5 x 6.0	14.0	\$2,534
240 Delta (3W + G)	PSPD100240D2K	10.5 x 7.5 x 3.5	7.0	\$2,190	PSPD100240D2M	11.0 x 11.5 x 6.0	14.0	\$2,717
480 Delta (3W + G)	PSPD100480D2K	10.5 x 7.5 x 3.5	7.0	\$2,190	PSPD100480D2M	11.0 x 11.5 x 6.0	14.0	\$2,717
400/230 Wye Three-phase (4W + G)	PSPD100400Y2K	10.5 x 7.5 x 3.5	7.0	\$2,190	PSPD100400Y2M	11.0 x 11.5 x 6.0	14.0	\$2,717
480/277 Wye Three-phase (4W + G)	PSPD100480Y2K	10.5 x 7.5 x 3.5	7.0	\$2,190	PSPD100480Y2M	11.0 x 11.5 x 6.0	14.0	\$2,717
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD100208Y1K	10.5 x 7.5 x 3.5	7.0	\$1,691	PSPD100208Y1M	11.0 x 11.5 x 6.0	14.0	\$2,223
120/240 Single Split-phase (3W + G)	PSPD100240S1K	10.5 x 7.5 x 3.5	7.0	\$1,858	PSPD100240S1M	11.0 x 11.5 x 6.0	14.0	\$2,389
240 Delta (3W + G)	PSPD100240D1K	10.5 x 7.5 x 3.5	7.0	\$2,023	PSPD100240D1M	11.0 x 11.5 x 6.0	14.0	\$2,554
480 Delta (3W + G)	PSPD100480D1K	10.5 x 7.5 x 3.5	7.0	\$2,023	PSPD100480D1M	11.0 x 11.5 x 6.0	14.0	\$2,554
400/230 Wye Three-phase (4W + G)	PSPD100400Y1K	10.5 x 7.5 x 3.5	7.0	\$2,023	PSPD100400Y1M	11.0 x 11.5 x 6.0	14.0	\$2,554
480/277 Wye Three-phase (4W + G)	PSPD100480Y1K	10.5 x 7.5 x 3.5	7.0	\$2,023	PSPD100480Y1M	11.0 x 11.5 x 6.0	14.0	\$2,554
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 120 (120 kA/phase surge rating) Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD120208Y3K	10.5 x 7.5 x 3.5	7.0	\$2,677	PSPD120208Y3M	11.0 x 11.5 x 6.0	14.0	\$3,369
120/240 Single Split-phase (3W + G)	PSPD120240S3K	10.5 x 7.5 x 3.5	7.0	\$2,904	PSPD120240S3M	11.0 x 11.5 x 6.0	14.0	\$3,595
240 Delta (3W + G)	PSPD120240D3K	10.5 x 7.5 x 3.5	7.0	\$3,137	PSPD120240D3M	11.0 x 11.5 x 6.0	14.0	\$3,831
480 Delta (3W + G)	PSPD120480D3K	10.5 x 7.5 x 3.5	7.0	\$3,137	PSPD120480D3M	11.0 x 11.5 x 6.0	14.0	\$3,831
400/230 Wye Three-phase (4W + G)	PSPD120400Y3K	10.5 x 7.5 x 3.5	7.0	\$3,137	PSPD120400Y3M	11.0 x 11.5 x 6.0	14.0	\$3,831
480/277 Wye Three-phase (4W + G)	PSPD120480Y3K	10.5 x 7.5 x 3.5	7.0	\$3,137	PSPD120480Y3M	11.0 x 11.5 x 6.0	14.0	\$3,831
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD120208Y2K	10.5 x 7.5 x 3.5	7.0	\$2,286	PSPD120208Y2M	11.0 x 11.5 x 6.0	14.0	\$2,980
120/240 Single Split-phase (3W + G)	PSPD120240S2K	10.5 x 7.5 x 3.5	7.0	\$2,511	PSPD120240S2M	11.0 x 11.5 x 6.0	14.0	\$3,207
240 Delta (3W + G)	PSPD120240D2K	10.5 x 7.5 x 3.5	7.0	\$2,744	PSPD120240D2M	11.0 x 11.5 x 6.0	14.0	\$3,439
480 Delta (3W + G)	PSPD120480D2K	10.5 x 7.5 x 3.5	7.0	\$2,744	PSPD120480D2M	11.0 x 11.5 x 6.0	14.0	\$3,439
400/230 Wye Three-phase (4W + G)	PSPD120400Y2K	10.5 x 7.5 x 3.5	7.0	\$2,744	PSPD120400Y2M	11.0 x 11.5 x 6.0	14.0	\$3,439
480/277 Wye Three-phase (4W + G)	PSPD120480Y2K	10.5 x 7.5 x 3.5	7.0	\$2,744	PSPD120480Y2M	11.0 x 11.5 x 6.0	14.0	\$3,439

SURGE PROTECTION

PSPD SERIES

Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD120208Y1K	10.5 x 7.5 x 3.5	7.0	\$2,114	PSPD120208Y1M	11.0 x 11.5 x 6.0	14.0	\$2,807
120/240 Single Split-phase (3W + G)	PSPD120240S1K	10.5 x 7.5 x 3.5	7.0	\$2,322	PSPD120240S1M	11.0 x 11.5 x 6.0	14.0	\$3,015
240 Delta (3W + G)	PSPD120240D1K	10.5 x 7.5 x 3.5	7.0	\$2,538	PSPD120240D1M	11.0 x 11.5 x 6.0	14.0	\$3,231
480 Delta (3W + G)	PSPD120480D1K	10.5 x 7.5 x 3.5	7.0	\$2,538	PSPD120480D1M	11.0 x 11.5 x 6.0	14.0	\$3,231
400/230 Wye Three-phase (4W + G)	PSPD120400Y1K	10.5 x 7.5 x 3.5	7.0	\$2,538	PSPD120400Y1M	11.0 x 11.5 x 6.0	14.0	\$3,231
480/277 Wye Three-phase (4W + G)	PSPD120480Y1K	10.5 x 7.5 x 3.5	7.0	\$2,538	PSPD120480Y1M	11.0 x 11.5 x 6.0	14.0	\$3,231
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 160 (160 kA/phase surge rating)								
Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD160208Y3K	10.5 x 7.5 x 3.5	7.0	\$3,217	PSPD160208Y3M	11.0 x 11.5 x 6.0	14.0	\$4,030
120/240 Single Split-phase (3W + G)	PSPD160240S3K	10.5 x 7.5 x 3.5	7.0	\$3,501	PSPD160240S3M	11.0 x 11.5 x 6.0	14.0	\$4,312
240 Delta (3W + G)	PSPD160240D3K	10.5 x 7.5 x 3.5	7.0	\$3,786	PSPD160240D3M	11.0 x 11.5 x 6.0	14.0	\$4,595
480 Delta (3W + G)	PSPD160480D3K	10.5 x 7.5 x 3.5	7.0	\$3,786	PSPD160480D3M	11.0 x 11.5 x 6.0	14.0	\$4,595
400/230 Wye Three-phase (4W + G)	PSPD160400Y3K	10.5 x 7.5 x 3.5	7.0	\$3,786	PSPD160400Y3M	11.0 x 11.5 x 6.0	14.0	\$4,595
480/277 Wye Three-phase (4W + G)	PSPD160480Y3K	10.5 x 7.5 x 3.5	7.0	\$3,786	PSPD160480Y3M	11.0 x 11.5 x 6.0	14.0	\$4,595
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD160208Y2K	10.5 x 7.5 x 3.5	7.0	\$2,852	PSPD160208Y2M	11.0 x 11.5 x 6.0	14.0	\$3,665
120/240 Single Split-phase (3W + G)	PSPD160240S2K	10.5 x 7.5 x 3.5	7.0	\$3,138	PSPD160240S2M	11.0 x 11.5 x 6.0	14.0	\$3,945
240 Delta (3W + G)	PSPD160240D2K	10.5 x 7.5 x 3.5	7.0	\$3,421	PSPD160240D2M	11.0 x 11.5 x 6.0	14.0	\$4,231
480 Delta (3W + G)	PSPD160480D2K	10.5 x 7.5 x 3.5	7.0	\$3,421	PSPD160480D2M	11.0 x 11.5 x 6.0	14.0	\$4,231
400/230 Wye Three-phase (4W + G)	PSPD160400Y2K	10.5 x 7.5 x 3.5	7.0	\$3,421	PSPD160400Y2M	11.0 x 11.5 x 6.0	14.0	\$4,231
480/277 Wye Three-phase (4W + G)	PSPD160480Y2K	10.5 x 7.5 x 3.5	7.0	\$3,421	PSPD160480Y2M	11.0 x 11.5 x 6.0	14.0	\$4,231
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD160208Y1K	10.5 x 7.5 x 3.5	7.0	\$2,642	PSPD160208Y1M	11.0 x 11.5 x 6.0	14.0	\$3,452
120/240 Single Split-phase (3W + G)	PSPD160240S1K	10.5 x 7.5 x 3.5	7.0	\$2,903	PSPD160240S1M	11.0 x 11.5 x 6.0	14.0	\$3,711
240 Delta (3W + G)	PSPD160240D1K	10.5 x 7.5 x 3.5	7.0	\$3,168	PSPD160240D1M	11.0 x 11.5 x 6.0	14.0	\$3,980
480 Delta (3W + G)	PSPD160480D1K	10.5 x 7.5 x 3.5	7.0	\$3,168	PSPD160480D1M	11.0 x 11.5 x 6.0	14.0	\$3,980
400/230 Wye Three-phase (4W + G)	PSPD160400Y1K	10.5 x 7.5 x 3.5	7.0	\$3,168	PSPD160400Y1M	11.0 x 11.5 x 6.0	14.0	\$3,980
480/277 Wye Three-phase (4W + G)	PSPD160480Y1K	10.5 x 7.5 x 3.5	7.0	\$3,168	PSPD160480Y1M	11.0 x 11.5 x 6.0	14.0	\$3,980
PSPD SERIES								
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 200 (200 kA/phase surge rating)								
Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD200208Y3K	10.5 x 7.5 x 3.5	7.0	\$3,741	PSPD200208Y3M	11.0 x 11.5 x 6.0	14.0	\$4,743
120/240 Single Split-phase (3W + G)	PSPD200240S3K	10.5 x 7.5 x 3.5	7.0	\$4,079	PSPD200240S3M	11.0 x 11.5 x 6.0	14.0	\$5,082
240 Delta (3W + G)	PSPD200240D3K	10.5 x 7.5 x 3.5	7.0	\$4,418	PSPD200240D3M	11.0 x 11.5 x 6.0	14.0	\$5,422
480 Delta (3W + G)	PSPD200480D3K	10.5 x 7.5 x 3.5	7.0	\$4,418	PSPD200480D3M	11.0 x 11.5 x 6.0	14.0	\$5,422
400/230 Wye Three-phase (4W + G)	PSPD200400Y3K	10.5 x 7.5 x 3.5	7.0	\$4,418	PSPD200400Y3M	11.0 x 11.5 x 6.0	14.0	\$5,422
480/277 Wye Three-phase (4W + G)	PSPD200480Y3K	10.5 x 7.5 x 3.5	7.0	\$4,418	PSPD200480Y3M	11.0 x 11.5 x 6.0	14.0	\$5,422
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD200208Y2K	10.5 x 7.5 x 3.5	7.0	\$3,392	PSPD200208Y2M	11.0 x 11.5 x 6.0	14.0	\$4,397
120/240 Single Split-phase (3W + G)	PSPD200240S2K	10.5 x 7.5 x 3.5	7.0	\$3,732	PSPD200240S2M	11.0 x 11.5 x 6.0	14.0	\$4,734
240 Delta (3W + G)	PSPD200240D2K	10.5 x 7.5 x 3.5	7.0	\$4,072	PSPD200240D2M	11.0 x 11.5 x 6.0	14.0	\$5,076
480 Delta (3W + G)	PSPD200480D2K	10.5 x 7.5 x 3.5	7.0	\$4,072	PSPD200480D2M	11.0 x 11.5 x 6.0	14.0	\$5,076
400/230 Wye Three-phase (4W + G)	PSPD200400Y2K	10.5 x 7.5 x 3.5	7.0	\$4,072	PSPD200400Y2M	11.0 x 11.5 x 6.0	14.0	\$5,076

SURGE PROTECTION

480/277 Wye Three-phase (4W + G)	PSPD200480Y2K	10.5 x 7.5 x 3.5	7.0	\$4,072	PSPD200480Y2M	11.0 x 11.5 x 6.0	14.0	\$5,076
Basic Diagnostics 208/120 Wye Three-phase (4W + G)	'K' Option - No Integral Disconnect PSPD200208Y1K	10.5 x 7.5 x 3.5	7.0	\$3,138	M' Option - Integral Disconnect PSPD200208Y1M	11.0 x 11.5 x 6.0	14.0	\$4,140
120/240 Single Split-phase (3W + G)	PSPD200240S1K	10.5 x 7.5 x 3.5	7.0	\$3,455	PSPD200240S1M	11.0 x 11.5 x 6.0	14.0	\$4,459
240 Delta (3W + G)	PSPD200240D1K	10.5 x 7.5 x 3.5	7.0	\$3,762	PSPD200240D1M	11.0 x 11.5 x 6.0	14.0	\$4,767
480 Delta (3W + G)	PSPD200480D1K	10.5 x 7.5 x 3.5	7.0	\$3,762	PSPD200480D1M	11.0 x 11.5 x 6.0	14.0	\$4,767
400/230 Wye Three-phase (4W + G)	PSPD200400Y1K	10.5 x 7.5 x 3.5	7.0	\$3,762	PSPD200400Y1M	11.0 x 11.5 x 6.0	14.0	\$4,767
480/277 Wye Three-phase (4W + G)	PSPD200480Y1K	10.5 x 7.5 x 3.5	7.0	\$3,762	PSPD200480Y1M	11.0 x 11.5 x 6.0	14.0	\$4,767
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 250 (250 kA/phase surge rating) Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD250208Y3K	10.5 x 7.5 x 6.0	11.5	\$4,697	PSPD250208Y3M	11.0 x 11.5 x 6.0	16.5	\$5,882
120/240 Single Split-phase (3W + G)	PSPD250240S3K	10.5 x 7.5 x 6.0	11.5	\$5,133	PSPD250240S3M	11.0 x 11.5 x 6.0	16.5	\$6,315
240 Delta (3W + G)	PSPD250240D3K	10.5 x 7.5 x 6.0	11.5	\$5,565	PSPD250240D3M	11.0 x 11.5 x 6.0	16.5	\$6,754
480 Delta (3W + G)	PSPD250480D3K	10.5 x 7.5 x 6.0	11.5	\$5,565	PSPD250480D3M	11.0 x 11.5 x 6.0	16.5	\$6,754
400/230 Wye Three-phase (4W + G)	PSPD250400Y3K	10.5 x 7.5 x 6.0	11.5	\$5,565	PSPD250400Y3M	11.0 x 11.5 x 6.0	16.5	\$6,754
480/277 Wye Three-phase (4W + G)	PSPD250480Y3K	10.5 x 7.5 x 6.0	11.5	\$5,565	PSPD250480Y3M	11.0 x 11.5 x 6.0	16.5	\$6,754
PSPD SERIES								
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD250208Y2K	10.5 x 7.5 x 6.0	11.5	\$4,343	PSPD250208Y2M	11.0 x 11.5 x 6.0	16.5	\$5,527
120/240 Single Split-phase (3W + G)	PSPD250240S2K	10.5 x 7.5 x 6.0	11.5	\$4,775	PSPD250240S2M	11.0 x 11.5 x 6.0	16.5	\$5,966
240 Delta (3W + G)	PSPD250240D2K	10.5 x 7.5 x 6.0	11.5	\$5,210	PSPD250240D2M	11.0 x 11.5 x 6.0	16.5	\$6,398
480 Delta (3W + G)	PSPD250480D2K	10.5 x 7.5 x 6.0	11.5	\$5,210	PSPD250480D2M	11.0 x 11.5 x 6.0	16.5	\$6,398
400/230 Wye Three-phase (4W + G)	PSPD250400Y2K	10.5 x 7.5 x 6.0	11.5	\$5,210	PSPD250400Y2M	11.0 x 11.5 x 6.0	16.5	\$6,398
480/277 Wye Three-phase (4W + G)	PSPD250480Y2K	10.5 x 7.5 x 6.0	11.5	\$5,210	PSPD250480Y2M	11.0 x 11.5 x 6.0	16.5	\$6,398
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD250208Y1K	10.5 x 7.5 x 6.0	11.5	\$4,018	PSPD250208Y1M	11.0 x 11.5 x 6.0	16.5	\$5,203
120/240 Single Split-phase (3W + G)	PSPD250240S1K	10.5 x 7.5 x 6.0	11.5	\$4,421	PSPD250240S1M	11.0 x 11.5 x 6.0	16.5	\$5,607
240 Delta (3W + G)	PSPD250240D1K	10.5 x 7.5 x 6.0	11.5	\$4,824	PSPD250240D1M	11.0 x 11.5 x 6.0	16.5	\$6,013
480 Delta (3W + G)	PSPD250480D1K	10.5 x 7.5 x 6.0	11.5	\$4,824	PSPD250480D1M	11.0 x 11.5 x 6.0	16.5	\$6,013
400/230 Wye Three-phase (4W + G)	PSPD250400Y1K	10.5 x 7.5 x 6.0	11.5	\$4,824	PSPD250400Y1M	11.0 x 11.5 x 6.0	16.5	\$6,013
480/277 Wye Three-phase (4W + G)	PSPD250480Y1K	10.5 x 7.5 x 6.0	11.5	\$4,824	PSPD250480Y1M	11.0 x 11.5 x 6.0	16.5	\$6,013
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 300 (300 kA/phase surge rating) Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD300208Y3K	10.5 x 7.5 x 6.0	11.5	\$5,638	PSPD300208Y3M	11.0 x 11.5 x 6.0	16.5	\$6,923
120/240 Single Split-phase (3W + G)	PSPD300240S3K	10.5 x 7.5 x 6.0	11.5	\$6,165	PSPD300240S3M	11.0 x 11.5 x 6.0	16.5	\$7,461
240 Delta (3W + G)	PSPD300240D3K	10.5 x 7.5 x 6.0	11.5	\$6,694	PSPD300240D3M	11.0 x 11.5 x 6.0	16.5	\$7,983
480 Delta (3W + G)	PSPD300480D3K	10.5 x 7.5 x 6.0	11.5	\$6,694	PSPD300480D3M	11.0 x 11.5 x 6.0	16.5	\$7,983
400/230 Wye Three-phase (4W + G)	PSPD300400Y3K	10.5 x 7.5 x 6.0	11.5	\$6,694	PSPD300400Y3M	11.0 x 11.5 x 6.0	16.5	\$7,983
480/277 Wye Three-phase (4W + G)	PSPD300480Y3K	10.5 x 7.5 x 6.0	11.5	\$6,694	PSPD300480Y3M	11.0 x 11.5 x 6.0	16.5	\$7,983
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD300208Y2K	10.5 x 7.5 x 6.0	11.5	\$5,278	PSPD300208Y2M	11.0 x 11.5 x 6.0	16.5	\$6,562
120/240 Single Split-phase (3W + G)	PSPD300240S2K	10.5 x 7.5 x 6.0	11.5	\$5,807	PSPD300240S2M	11.0 x 11.5 x 6.0	16.5	\$7,092
240 Delta (3W + G)	PSPD300240D2K	10.5 x 7.5 x 6.0	11.5	\$6,340	PSPD300240D2M	11.0 x 11.5 x 6.0	16.5	\$7,621
480 Delta (3W + G)	PSPD300480D2K	10.5 x 7.5 x 6.0	11.5	\$6,340	PSPD300480D2M	11.0 x 11.5 x 6.0	16.5	\$7,621
400/230 Wye Three-phase (4W + G)	PSPD300400Y2K	10.5 x 7.5 x 6.0	11.5	\$6,340	PSPD300400Y2M	11.0 x 11.5 x 6.0	16.5	\$7,621
480/277 Wye Three-phase (4W + G)	PSPD300480Y2K	10.5 x 7.5 x 6.0	11.5	\$6,340	PSPD300480Y2M	11.0 x 11.5 x 6.0	16.5	\$7,621

SURGE PROTECTION

PSPD SERIES

Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD300208Y1K	10.5 x 7.5 x 6.0	11.5	\$4,883	PSPD300208Y1M	11.0 x 11.5 x 6.0	16.5	\$6,164
120/240 Single Split-phase (3W + G)	PSPD300240S1K	10.5 x 7.5 x 6.0	11.5	\$5,372	PSPD300240S1M	11.0 x 11.5 x 6.0	16.5	\$6,657
240 Delta (3W + G)	PSPD300240D1K	10.5 x 7.5 x 6.0	11.5	\$5,862	PSPD300240D1M	11.0 x 11.5 x 6.0	16.5	\$7,147
480 Delta (3W + G)	PSPD300480D1K	10.5 x 7.5 x 6.0	11.5	\$5,862	PSPD300480D1M	11.0 x 11.5 x 6.0	16.5	\$7,147
400/230 Wye Three-phase (4W + G)	PSPD300400Y1K	10.5 x 7.5 x 6.0	11.5	\$5,862	PSPD300400Y1M	11.0 x 11.5 x 6.0	16.5	\$7,147
480/277 Wye Three-phase (4W + G)	PSPD300480Y1K	10.5 x 7.5 x 6.0	11.5	\$5,862	PSPD300480Y1M	11.0 x 11.5 x 6.0	16.5	\$7,147
Voltage	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price	Part Number	Dimensions (H x W x D, inches)	Weight (lb)	List Price
PSPD 400 (400 kA/phase surge rating) Standard with Surge Counter Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD400208Y3K	10.5 x 7.5 x 6.0	11.5	\$7,405	PSPD400208Y3M	11.0 x 11.5 x 6.0	16.5	\$8,776
120/240 Single Split-phase (3W + G)	PSPD400240S3K	10.5 x 7.5 x 6.0	11.5	\$8,117	PSPD400240S3M	11.0 x 11.5 x 6.0	16.5	\$9,481
240 Delta (3W + G)	PSPD400240D3K	10.5 x 7.5 x 6.0	11.5	\$8,818	PSPD400240D3M	11.0 x 11.5 x 6.0	16.5	\$10,185
480 Delta (3W + G)	PSPD400480D3K	10.5 x 7.5 x 6.0	11.5	\$8,818	PSPD400480D3M	11.0 x 11.5 x 6.0	16.5	\$10,185
400/230 Wye Three-phase (4W + G)	PSPD400400Y3K	10.5 x 7.5 x 6.0	11.5	\$8,818	PSPD400400Y3M	11.0 x 11.5 x 6.0	16.5	\$10,185
480/277 Wye Three-phase (4W + G)	PSPD400480Y3K	10.5 x 7.5 x 6.0	11.5	\$8,818	PSPD400480Y3M	11.0 x 11.5 x 6.0	16.5	\$10,185
Standard Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD400208Y2K	10.5 x 7.5 x 6.0	11.5	\$7,046	PSPD400208Y2M	11.0 x 11.5 x 6.0	16.5	\$8,416
120/240 Single Split-phase (3W + G)	PSPD400240S2K	10.5 x 7.5 x 6.0	11.5	\$7,756	PSPD400240S2M	11.0 x 11.5 x 6.0	16.5	\$9,114
240 Delta (3W + G)	PSPD400240D2K	10.5 x 7.5 x 6.0	11.5	\$8,465	PSPD400240D2M	11.0 x 11.5 x 6.0	16.5	\$9,824
480 Delta (3W + G)	PSPD400480D2K	10.5 x 7.5 x 6.0	11.5	\$8,465	PSPD400480D2M	11.0 x 11.5 x 6.0	16.5	\$9,824
400/230 Wye Three-phase (4W + G)	PSPD400400Y2K	10.5 x 7.5 x 6.0	11.5	\$8,465	PSPD400400Y2M	11.0 x 11.5 x 6.0	16.5	\$9,824
480/277 Wye Three-phase (4W + G)	PSPD400480Y2K	10.5 x 7.5 x 6.0	11.5	\$8,465	PSPD400480Y2M	11.0 x 11.5 x 6.0	16.5	\$9,824
Basic Diagnostics	'K' Option - No Integral Disconnect				M' Option - Integral Disconnect			
208/120 Wye Three-phase (4W + G)	PSPD400208Y1K	10.5 x 7.5 x 6.0	11.5	\$6,516	PSPD400208Y1M	11.0 x 11.5 x 6.0	16.5	\$7,886
120/240 Single Split-phase (3W + G)	PSPD400240S1K	10.5 x 7.5 x 6.0	11.5	\$7,165	PSPD400240S1M	11.0 x 11.5 x 6.0	16.5	\$8,530
240 Delta (3W + G)	PSPD400240D1K	10.5 x 7.5 x 6.0	11.5	\$7,825	PSPD400240D1M	11.0 x 11.5 x 6.0	16.5	\$9,192
480 Delta (3W + G)	PSPD400480D1K	10.5 x 7.5 x 6.0	11.5	\$7,825	PSPD400480D1M	11.0 x 11.5 x 6.0	16.5	\$9,192
400/230 Wye Three-phase (4W + G)	PSPD400400Y1K	10.5 x 7.5 x 6.0	11.5	\$7,825	PSPD400400Y1M	11.0 x 11.5 x 6.0	16.5	\$9,192
480/277 Wye Three-phase (4W + G)	PSPD400480Y1K	10.5 x 7.5 x 6.0	11.5	\$7,825	PSPD400480Y1M	11.0 x 11.5 x 6.0	16.5	\$9,192

SERVICES

Single-phase Service Plans

EATON PQ SINGLE-PHASE SERVICE RESPONSE TIME TOOL

Eaton offers world-class service for Eaton UPS products. Our factory-certified and trained service technicians deliver 7x24 support including on-site corrective and preventive maintenance. Next business day and faster response times are only available in certain zip codes. For the response times available in a given area, please check the Contract Service Response Time Tool found at the following link:

<http://powerquality.eaton.com/Products-services/services/responsetime/default.asp>

SELECTING A SERVICE PLAN

Eaton single-phase UPSs come with warranty coverage that typically includes parts and labor for electronics, 7x24 Customer Reliability Center triage and 7x24 technical support access. But to extend the term of the base factory warranty and expedite service delivery, you should recommend a service plan. The best service plans are essentially offered in two categories:

1. Extended Warranty (recommended for UPSs below 5 kVA or non-hardwired units - return to factory for exchange)

When your customer notifies Eaton about a defective unit, Eaton ships a replacement unit overnight. Upon receipt of the new UPS, the customer returns the defective unit to Eaton via ground shipment. The freight for both units is paid by Eaton. There is a 7 year cap on depot exchange units from date of shipment, this

2. Onsite service and repair (recommended for UPSs 5 kVA and above - upgrade 2 year factory warranty for 7x24 next day or 8-hour

Onsite service is a standard 7x24, next day or 8-hour (based on availability) response level of coverage – for detailed information, visit: www.eaton.com/upservices.

Note: 9155 service uses 3 Phase service pricing and can be found in the 3 Phase price book or service configurator

The following features can be added to onsite service to guarantee unparalleled UPS performance:

- Comprehensive coverage of the UPS and batteries; if external (EBM) batteries exist coverage for EBM's must be purchased.
- Telephone technical support (included in the warranty)
- PredictPulse remote monitoring: To learn more, activate or arrange a 90-day free trial of PredictPulse, visit Eaton.com/PredictPulse
- Connectivity support (included in the warranty)
- Expedited delivery of replacement parts, modules and batteries
- Onsite startup
- Onsite corrective maintenance
- Next-day 24-hour or 8-hour response(when available)
- Annual UPS and/or battery preventive maintenance

EXTENDED WARRANTIES - DEPOT EXCHANGE (CONCURRENT)

Style Number	Description	Range	Applicable UPS Models	Price
3 & 5 Series 5-Year UPS Extended Warranties				
3SW5Y-0750UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1 - 700	3S	\$22
3SW5Y-0949UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1 - 950	5S, 5SC	\$60
3SW5Y-1399UC	Ext Warranty-5YR UPS Adv Exchg, New Product	951 - 1400	5S, 5SC	\$120
3SW5Y-1749UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1401 - 1750	5S, 5SC	\$155
3SW5Y-0950UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1 - 950	5P, 5PX	\$61
3SW5Y-1400UC	Ext Warranty-5YR UPS Adv Exchg, New Product	951 - 1400	5P, 5PX	\$125
3SW5Y-1750UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1401 - 1750	5P, 5PX	\$159
3SW5Y-2500UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1751 - 2500	5P, 5PX	\$332
3SW5Y-3000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	2501 - 3000	5P, 5PX	\$381
5 Series 5-Year EBM Extended Warranties				
3SW5Y-1750BC	Ext Warranty-5YR EBM Adv Exchg, New Product	1 - 2200	EBM for 5PX	\$386
3SW5Y-3000BC	Ext Warranty-5YR EBM Adv Exchg, New Product	2201 - 3000	EBM for 5PX	\$603

Single-phase Service Plans

9 Series 3-Year & 5-Year UPS Extended Warranties

Style Number	Description	Range	Applicable UPS Models	List Price
9SW3Y-0700UC	Ext Warranty-3YR UPS Adv Exchg, New Product	1 - 700	9SX, 9PX, FERRUPS non hard-wired	\$155
9SW3Y-1000UC	Ext Warranty-3YR UPS Adv Exchg, New Product	701 - 1000	9SX, 9PX, FERRUPS non hard-wired	\$202
9SW3Y-1500UC	Ext Warranty-3YR UPS Adv Exchg, New Product	1001 - 1500	9SX, 9PX, FERRUPS non hard-wired	\$255
9SW3Y-2200UC	Ext Warranty-3YR UPS Adv Exchg, New Product	1501 - 2000	9SX, 9PX, FERRUPS non hard-wired	\$339
9SW3Y-2500UC	Ext Warranty-3YR UPS Adv Exchg, New Product	2001 - 2500	9SX, 9PX, FERRUPS non hard-wired	\$447
9SW3Y-3000UC	Ext Warranty-3YR UPS Adv Exchg, New Product	2501 - 3000	9SX, 9PX, FERRUPS non hard-wired, Ferrups FX	\$565
9SW3Y-6000UC	Ext Warranty-3YR UPS Adv Exchg, New Product	3001 - 6000	9PX, FERRUPS non hard-wired,	\$862
9SW3Y-11000UC	Ext Warranty-3YR UPS Adv Exchg, New Product	6001 - 11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$1,156
9SW3Y-18000UC	Ext Warranty-3YR UPS Adv Exchg, New Product	11001-20000	9PX, FERRUPS non hard-wired, 9PXM 12-slot	\$1,653
9SW5Y-0700UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1 - 700	9SX, 9PX, FERRUPS non hard-wired	\$371
9SW5Y-1000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	701 - 1000	9SX, 9PX, FERRUPS non hard-wired	\$475
9SW5Y-1500UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1001 - 1500	9SX, 9PX, FERRUPS non hard-wired	\$607
9SW5Y-2200UC	Ext Warranty-5YR UPS Adv Exchg, New Product	1501 - 2000	9SX, 9PX, FERRUPS non hard-wired	\$808
9SW5Y-2500UC	Ext Warranty-5YR UPS Adv Exchg, New Product	2001 - 2500	9SX, 9PX, FERRUPS non hard-wired	\$1,070
9SW5Y-3000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	2501 - 3000	9SX, 9PX, FERRUPS non hard-wired, Ferrups FX	\$1,349
9SW5Y-6000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	3001 - 6000	9SX, 9PX, FERRUPS non hard-wired	\$2,064

9SW5Y-11000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	6001 - 11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$2,779
9SW5Y-18000UC	Ext Warranty-5YR UPS Adv Exchg, New Product	11001-20000	9PX, FERRUPS non hard-wired, 9PXM 12-slot	\$3,528
9 Series 3-Year & 5-Year EBM Extended Warranties				
9SW3Y-3000BC	Ext Warranty-3YR EBM Adv Exchg, New Product	1 - 3000	EBMs for 9SX, 9PX, FERRUPS non hard-wired, Ferrups FX	\$276
9SW3Y-18000BC	Ext Warranty-3YR EBM Adv Exchg, New Product	3001-18000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM EBC-8-slot or EBC-12-slot	\$547
9SW5Y-3000BC	Ext Warranty-5YR EBM Adv Exchg, New Product	1 - 3000	EBMs for 9SX, 9PX, FERRUPS non hard-wired, Ferrups FX	\$684
9SW5Y-18000BC	Ext Warranty-5YR EBM Adv Exchg, New Product	3001-18000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$1,362
Rack PDU 5-Year Extended Warranties				
ESW5Y-0001-0400P	Rack PDU, 5-Year-Total Warranty (Rack PDU)	\$0 to \$400	All Rack PDU products based on list price	\$88
ESW5Y-0401-1000P	Rack PDU, 5-Year-Total Warranty (Rack PDU)	\$401 to \$1000	All Rack PDU products based on list price	\$214
ESW5Y-1001-2000P	Rack PDU, 5-Year-Total Warranty (Rack PDU)	\$1001 to \$2000	All Rack PDU products based on list price	\$422
ESW5Y-2001-5000P	Rack PDU, 5-Year-Total Warranty (Rack PDU)	\$2001 to \$5000	All Rack PDU products based on list price	\$1,054

Important Notes:

1) Extended Warranty extends term of Factory Warranty and adds Advanced Exchange Process

- Customer returns unit to Eaton (customer pays freight)
- Eaton ground ships replacement unit (on receipt of defective unit)
- Eaton covers freight to customer

3) Advanced Exchange - Return Process

- Eaton overnight ships replacement unit (on customer contact)
- Customer returns defective unit in overnight packaging
- Eaton covers freight in both directions

4) Advanced Exchange multiplier matches new product (hardware) multiplier

5) Prices apply to equipment installed in US 50 states

6) 9PXM uses the total KVA installed for service pricing (e. 4kVA N+1 = 8kVA)

7) Above prices are for concurrently sold services (with a new product sale); for non-concurrent service pricing and availability contact Eaton at 800-843-9433 opt. 4 or insideservicesales@eaton.com

8) Renewals beyond the initial warranty or extension must be purchased prior to any lapse in coverage or a new battery purchase is required (no grace period)

9) For on-site service plans on units that are 8kva and higher, a UPS PM is required every 4-Years (the fourth and fifth year on-site coverage must include one or more PMs).

UPS & EBM Next Day Warranty Upgrade to Onsite Service Plan 2 Years

WFLN72XX-2509UC	2YR warranty upgrade to onsite 7x24 Next Day Resp 1- 2500VA	1-2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$743
WFLN72XX-6009UC	2YR warranty upgrade to onsite 7x24 Next Day Resp 2.5-6kVA	2501-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,169
WFLN72XX-11000UC	2YR warranty upgrade to onsite 7x24 Next Day Resp 6- 11kVA	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$1,527
WFLN72XX-18000UC	2YR warranty upgrade to onsite 7x24 Next Day Resp 11-18kVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$1,812
WEBN72XX-7000BC	2YR warranty upgrade to onsite 7x24 Next Day Resp 1- 7000VA	1-7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$463
WEBN72XX-11000BC	2YR warranty upgrade to onsite 7x24 Next Day Resp 7- 11kVA	7001-11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$589
WEBN72XX-18000BC	2YR warranty upgrade to onsite 7x24 Next Day Resp 11-18kVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM EBC-12-slot	\$708

Single-phase Service Plans

UPS & EBM 8-Hour Warranty Upgrade to Onsite Service Plan 2 Years

WFL872XX-2509UC	2YR warranty upgrade to onsite 7x24 8hr Resp 1- 2500VA	1-2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,114
WFL872XX-6009UC	2YR warranty upgrade to onsite 7x24 8hr Resp 2.5-6kVA	2501-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,750
WFL872XX-11000UC	2YR warranty upgrade to onsite 7x24 8hr Resp 6- 11kVA	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$2,290
WFL872XX-18000UC	2YR warranty upgrade to onsite 7x24 8hr Resp 11- 18kVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$2,717
WEB872XX-7000BC	2YR EBM warranty upgrade to onsite 7x24 8hr Resp 1- 7000VA	1-7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$693
WEB872XX-11000BC	2YR EBM warranty upgrade to onsite 7x24 8hr Resp 7- 11kVA	7001-11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$883
WEB872XX-18000BC	2YR EBM warranty upgrade to onsite 8hr Resp 11- 18kVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM 12-slot, 9PXM EBC-12-slot	\$1,063

UPS & EBM Next Day Warranty Upgrade to Onsite Service Plan 3 Years

WFLN73XX-2509UC	3YR warranty upgrade to onsite 7x24 Next Day Response 2500VA	1 - 2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,340
WFLN73XX-6009UC	3YR warranty upgrade to onsite, 7x24 Next Day Response 2.5-6KVA	2501 - 6000	5P, 5PX, 9PX, 9SX, FERRUPS, Ferrups FX	\$2,105
WFLN73XX-11000UC	3YR warranty upgrade to onsite, 7x24 Next Day Response 6-11KVA	6001 - 11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$2,751
WFLN73XX-18000UC	3YR warranty upgrade to onsite, 7x24 Next Day Response 11-18KVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$3,261
WEBN73XX-7000BC	3YR EBM warranty upgrade to onsite, 7x24 Next Day Response 1-7KVA	1 - 7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$834
WEBN73XX-11000BC	3YR EBM warranty upgrade to onsite, 7x24 Next Day Response 7-11KVA	7001 - 11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$1,237
WEBN73XX-18000BC	3YR EBM warranty upgrade to onsite, 7x24 Next Day Response 11-18KVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM 12-slot, 9PXM EBC-12-slot	\$2,829
UPS & EBM 8-Hour Warranty Upgrade to Onsite Service Plan 3 Years				
WFL873XX-2509UC	3YR warranty upgrade to onsite, 7x24 8hr Response 2500VA	1-2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$2,008
WFL873XX-6009UC	3YR warranty upgrade to onsite, 7x24 8hr Response 2.5-6kVA	2501-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$3,152
WFL873XX-11000UC	3YR warranty upgrade to onsite, 7x24 8hr Response 6-11kVA	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$4,121

Single-phase Service Plans

UPS & EBM 8-Hour Warranty Upgrade to Onsite Service Plan 3 Years (Cont.)

Style Number	Description	Range	Applicable UPS Models	List Price
WFL873XX-18000UC	3YR warranty upgrade to onsite, 7x24 8hr Response 11-18kVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$4,890
WEB873XX-7000BC	3YR EBM warranty upgrade to onsite, 7x24 8hr Response 1-7000VA	1-7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,249
WEB873XX-11000BC	3YR EBM warranty upgrade to onsite, 7x24 8hr Response 7-11kVA	7001-11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$1,855
WEB873XX-18000BC	3YR EBM warranty upgrade to onsite, 7x24 8hr Response 11-18kVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM 12-slot, 9PXM EBC-12-slot	\$4,244

UPS & EBM Next Day Warranty Upgrade to Onsite Service Plan 5 Years

Style Number	Description	Range	Applicable UPS Models	List Price
WFLN75XX-2509UC	5YR warranty upgrade to onsite 7x24 Next Day Response 2500VA	1 - 2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$2,051
WFLN75XX-6009UC	5YR warranty upgrade to onsite, 7x24 Next Day Response 2.5-6KVA	2501 - 6000	5P, 5PX, 9PX, 9SX, FERRUPS, Ferrups FX	\$3,222
WFLN75XX-11000UC	5YR warranty upgrade to onsite, 7x24 Next Day Response 6-11KVA	6001 - 11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$4,214
WFLN75XX-18000UC	5YR warranty upgrade to onsite, 7x24 Next Day Response 11-18KVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$4,998
WEBN75XX-7000BC	5YR EBM warranty upgrade to onsite, 7x24 Next Day Response 1-7KVA	1 - 7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,383
WEBN75XX-11000BC	5YR EBM warranty upgrade to onsite, 7x24 Next Day Response 7-11KVA	7001 - 11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$2,398
WEBN75XX-18000BC	5YR EBM warranty upgrade to onsite, 7x24 Next Day Response 11-18KVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM 12-slot, 9PXM EBC-12-slot	\$6,641

UPS & EBM 8-Hour Warranty Upgrade to Onsite Service Plan 5 Years

WFL875XX-2509UC	5YR warranty upgrade to onsite, 7x24 8hr Response 2500VA	1-2500	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$3,076
WFL875XX-6009UC	5YR warranty upgrade to onsite, 7x24 8hr Response 2.5-6kVA	2501-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$4,828
WFL875XX-11000UC	5YR warranty upgrade to onsite, 7x24 8hr Response 6-11kVA	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$6,317
WFL875XX-18000UC	5YR warranty upgrade to onsite, 7x24 8hr Response 11-18kVA	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$7,494
WEB875XX-7000BC	5YR EBM warranty upgrade to onsite, 7x24 8hr Response 1-7000VA	1-7000	EBMs for 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$2,073
WEB875XX-11000BC	5YR EBM warranty upgrade to onsite, 7x24 8hr Response 7-11kVA	7001-11000	EBMs for 9PX, FERRUPS non hard-wired, 9PXM 8-slot, 9PXM EBC-8-slot	\$3,596
WEB875XX-18000BC	5YR EBM warranty upgrade to onsite, 7x24 8hr Response 11-18kVA	11001-20000	EBMs for 9PX, FERRUPS, 12 Slot, 9PXM 12-slot, 9PXM EBC-12-slot	\$9,961

UPS Preventive Maintenance

0005NXXX-6009UC	Onsite UPS PM 7x24, First Unit	1-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,376
0005NXXX-11000UC	Onsite UPS PM 7x24, First Unit	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$1,450
0005NXXX-18000UC	Onsite UPS PM 7x24, First Unit	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$1,595
0005N2XX-6009UC	Onsite UPS PM 7x24, Second Unit	1-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$961
0005N2XX-11000UC	Onsite UPS PM 7x24, Second Unit	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$1,018
0005N2XX-18000UC	Onsite UPS PM 7x24, Second Unit	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$1,117

Assembly, *Startup and Monitoring

AS00NXXX-6009UC	Scheduled UPS Assembly Service 7x24	1-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$667
AS00NXXX-11000UC	Scheduled UPS Assembly Service 7x24	6001-11000	9PX, FERRUPS non hard-wired,	\$1,092
AS00NXXX-18000UC	Scheduled UPS Assembly Service 7x24	11001-20000	9PX, FERRUPS FX	\$1,092
SR05NXXX-18000UC	Onsite 9PXM Rack Installation and Startup 7x24, First Unit	6001-20000	9PXM 8 and 12-slot	\$3,125
SR052XXX-18000UC	Onsite 9PXM Rack Installation and Startup 7x24, Second Unit	6001-20000	9PXM 8 and 12-slot	\$2,151
SR05NXXX-9PXMEBC	Onsite 9PXM EBC-8-slot or EBC-12-slot Rack Installation and Startup 7x24	6001-20000	9PXM EBC-8-slot or EBC-12-slot (requires 9PXM UPS rack install service)	\$777
SU05NXXX-6009UC	Onsite 1P UPS Startup 7x24, First Unit*	1-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$1,376
SU05NXXX-11000UC	Onsite 1P UPS Startup 7x24, First Unit*	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$1,702
SU05NXXX-18000UC	Onsite 1P UPS Startup 7x24, First Unit*	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$1,956
SU052XXX-6009UC	Onsite 1P UPS Startup 7x24, Second Unit*	1-6000	5P, 5PX, 9SX, 9PX, FERRUPS, Ferrups FX	\$690
SU052XXX-11000UC	Onsite 1P UPS Startup 7x24, Second Unit*	6001-11000	9PX, FERRUPS non hard-wired, 9PXM 8-slot	\$853
SU052XXX-18000UC	Onsite 1P UPS Startup 7x24, Second Unit*	11001-20000	9PX, FERRUPS, 9PXM 12-slot	\$981

Single-phase Service Plans

PredictPulse remote monitoring service

Style Number	Description	Range	Applicable UPS Models	List Price
XXXXNEXX-6009UC	PredictPulse monitoring 1YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM, Ferrups FX	\$297
XXXXNEXX-11000UC	PredictPulse monitoring 1YR	6001-11000	9PX, 9PXM	\$297
XXXXNEXX-18000UC	PredictPulse monitoring 1YR	11001-20000	9PX, 9PXM	\$526
XXXXWEXX-6009UC	PredictPulse Wireless 1YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM, Ferrups FX	\$616
XXXXWEXX-11000UC	PredictPulse Wireless 1YR	6001-11000	9PX, 9PXM	\$616
XXXXWEXX-18000UC	PredictPulse Wireless 1YR	11001-20000	9PX, 9PXM	\$844
XX3YNEXX-6009UC	PredictPulse monitoring 3YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM, Ferrups FX	\$819
XX3YNEXX-11000UC	PredictPulse monitoring 3YR	6001-11000	9PX, 9PXM	\$819
XX3YNEXX-18000UC	PredictPulse monitoring 3YR	11001-20000	9PX, 9PXM	\$1,449
XX3YWEXX-6009UC	PredictPulse Wireless 3YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM Ferrups FX	\$1,406
XX3YWEXX-11000UC	PredictPulse Wireless 3YR	6001-11000	9PX, 9PXM	\$1,406
XX3YWEXX-18000UC	PredictPulse Wireless 3YR	11001-20000	9PX, 9PXM	\$2,035
XX5YNEXX-6009UC	PredictPulse monitoring 5YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM Ferrups FX	\$1,261
XX5YNEXX-11000UC	PredictPulse monitoring 5YR	6001-11000	9PX, 9PXM	\$1,261
XX5YNEXX-18000UC	PredictPulse monitoring 5YR	11001-20000	9PX, 9PXM	\$2,231
XX5YWEXX-6009UC	PredictPulse Wireless 5YR	1-6000	5P, 5PX, 9SX, 9PX, 9PXM Ferrups FX	\$1,804
XX5YWEXX-11000UC	PredictPulse Wireless 5YR	6001-11000	9PX, 9PXM	\$1,804
XX5YWEXX-18000UC	PredictPulse Wireless 5YR	11001-20000	9PX, 9PXM	\$2,772

*To account for increased cost associated with a new law in WA State requiring a certified electrician to be present for onsite work performed on UPS's one year after startup, the following fees will apply for both 1 phase and 3 phase systems (effective January 1, 2018).

Electrician Required		WA State Electrician Fee	
Startups	No		
Warranties (UPS's < 1 yr. Old)	No		
Contracts (UPS's < 1 yr. Old)	Yes	\$282	per UPS & Per Year
Modifications	Yes	\$282	per UPS
Battery Replacements	Yes	\$282	per UPS
T&M	Yes	\$170	per Hour

Ferrups EBM Reference Table (EBM Battery Coverage)

Part Number	VA Range	Applicable UPS Model	Applicable EBM	List Price
EB871XXX-7000BC	1-7000	FERRUPS	EBPS12.5, EBPS18, 8FE, 2FE 9FE, 16FE 2re, 1rd, 8ME EBPS4.3R, 9ME EBPS10, 24ME 1FE, 25ME 1re	\$555
EB873XXX-7000BC	1-7000	FERRUPS	EBPS12.5, EBPS18, 8FE, 2FE 9FE, 16FE 2re, 1rd, 8ME EBPS4.3R, 9ME EBPS10, 24ME 1FE, 25ME 1re	\$1,380
EB871XXX-11000BC	7001-11000	FERRUPS	10ME 11ME, 12ME 3FE, 4FE 2rd, 13ME, 5FE, 3rd, 10FE, 17FE	\$972
EB873XXX-11000BC	7001-11000	FERRUPS	10ME 11ME, 12ME 3FE, 4FE 2rd, 13ME, 5FE, 3rd, 10FE, 17FE	\$2,714
EB871XXX-18000BC	11001-20000	FERRUPS	14ME, 6FE, 11FE, 12FE, 18FE, 19FE, 15ME, 7FE, 13FE, 20FE, 14FE, 21FE,	\$3,180
EB873XXX-18000BC	11001-20000	FERRUPS	14ME, 6FE, 11FE, 12FE, 18FE, 19FE, 15ME, 7FE, 13FE, 20FE, 14FE, 21FE,	\$8,899

RMA POLICY AND PRODUCT WARRANTIES

Sales Returned Merchandise Authorization (RMA) Policy

Written authority from Eaton must be obtained before any return or credit will be allowed.

Sales RMAs will be issued for new, unused equipment that is:

- A. Within 30 days of original shipment date
- B. Returned in original sealed packaging
- C. Returned in unmodified, untampered, original condition
- D. A current design

Cancellations and Erroneous Orders:

Any order for standard Eaton products may not be cancelled within thirty days of the date scheduled for shipment/delivery by Eaton.

Otherwise the order may be cancelled in accordance with the following:

- Sales RMAs issued for cancellations and erroneous orders will be subject to a minimum 15% restocking/cancellation fee
- Restocking/cancellation fee for standard product will be 15%
- Restocking/cancellation fee for special, custom or configured products will be a minimum of 50%
- The buyer is responsible for both inbound and outbound freight charges

Note: Charges may be waived by mutual agreement between buyer and seller. Proper approval and authorization must be obtained and documented in writing before the transaction is initiated.

Erroneous Shipments:

Sales RMAs necessary as a result of shipping/order entry errors will be issued and transacted with no charge to the buyer. Eaton will pay inbound freight, and outbound freight will be similar service level as original shipment.

RMA Expiration:

An RMA is valid for 60 calendar days from date of authorization by Eaton, after which it is subject to cancellation.

Sales Contracts:

An active Sales Contract with clauses relating to return of product for sales credits may supersede the Sales RMA policy statements above.

To request a Sales RMA please contact:

US Phone: 800.356.5794

Canadian Phone: 800.461.9166

US e-mail: salesrma@eaton.com

Canadian e-mail: epqcrma@eaton.com